(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/114095 A3

(51) International Patent Classification[7]: G06F 17/60, 19/00

(21) International Application Number: PCT/US2004/019860

(22) International Filing Date: 18 June 2004 (18.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/480,097 20 June 2003 (20.06.2003) US

(71) Applicant *(for all designated States except US)*: **STRATEGIC CAPITAL NETWORK LLC** [US/US]; 800 Boylston Street, 24th Floor, Boston, MA 02199 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **HUNTER, Brian, L.** [US/US]; 359 Beacon Street, Boston, MA 02116 (US). **KULKARNI, Ashish** [US/US]; 100 Memorial Drive, #11-1C, Cambridge, MA 02142 (US). **KACHANI, Soulaymane** [US/US]; S.W. Mudd Building, Room 334, New York, NY 10027 (US).


(74) Agent: **NELSON, Gordon, E.**; 57 Central St., P.O. Box 782, Rowley, MA 01969 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH,

[Continued on next page]

(54) Title: IMPROVED RESOURCE ALLOCATION TECHNIQUE



(57) Abstract: An improved resource allocation system comprising a reliability decision engine (323), which allocates the portfolio's assets as required for the desired reliability portfolio. The reliability decision engine including two reliability decision engines, a basic reliability decision engine (325) and a robust reliability decision engine (327). The use of robust optimization makes it possible to determine the sensitivity of the optimized portfolio. Scenarios can be specified directly by the user or automatically generated by the system in response to a selection by the user. Inputs (329, 331) are applied to basic the basic reliability decision engine (325) and inputs (311) are applied to robust reliability decision engine (327).

WO 2004/114095 A3

GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

(88) Date of publication of the international search report:
24 March 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.