[CLAIMS]

[Claim 1]

A jar container, comprising:

a container body that has an opening part at an upper end of a tubular member;

an annular member having a joint and a mouth edge part extending upward from the joint, ~~that~~ wherein the annular member is bonded to the upper end of the tubular member through the joint; and

a lid member that seals the opening part to be openable and closable,

wherein the container body has a bottom surface member that is bonded to the tubular member at a bottom surface part of the tubular member,

the tubular member is ~~constituted~~ formed by bonding difference surfaces in a thickness direction of a first flexible laminated body having a length corresponding to an outer circumference to face each other at both ends in the circumferential direction, or bonding inner surfaces to face each other so that both ends in the circumferential direction protrude outward in a radial direction, wherein ~~of~~ the flexible laminated body is constituted by three or more layers including a sealant layer, and

the lid member is coupled to the annular member by ~~any of~~ a hinge, ~~fitting, and a screw~~ to be openable and closable.

~~[Claim 2]~~

~~The container according to claim 1, wherein the lid member is constituted to be coupled to the annular member by a hinge.~~

~~[Claim 3]~~

~~The container according to claim 1 or 2, wherein the container is a jar container.~~

[Claim 42]

The jar container according to ~~any one of~~ claim~~s~~ 1 ~~to 3~~, wherein the ~~tubular~~

~~member is constituted by a~~ first flexible laminated body ~~having~~ has a total thickness of 100 to 500 μm and an outer diameter of the tubular member is 30 to 150 mm.

[Claim ~~5~~3]

The jar container according to ~~any one of~~ claim~~s~~ 1 ~~to~~ or ~~4~~2, wherein the bottom surface member is constituted by a second laminated body having a total thickness of 70 to 350 μm, and the second laminated body is a laminated body of three or more layers including at least one resin layer on each of both sides of aluminum foil having a thickness of 40 μm or more in a thickness direction thereof.

[Claim ~~6~~4]

The jar container according to any one of claims 1 to ~~5~~3, wherein a circumferential edge of the bottom surface member is bent with respect to the bottom surface part and is bonded to a lower end of the tubular member.

[Claim ~~7~~5]

The jar container according to any one of claims 1 to 4, wherein the bottom surface member is formed of a resin or aluminum molded item.

[Claim ~~8~~6]

The jar container according to any one of claims 1 to ~~7~~5, wherein the lid member is formed of a resin or aluminum molded item.