



- (51) **International Patent Classification:**
C10L 1/222 (2006.01) *C09K 8/584* (2006.01)
- (21) **International Application Number:**
PCT/US2014/038705
- (22) **International Filing Date:**
20 May 2014 (20.05.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/827,781 28 May 2013 (28.05.2013) US
- (71) **Applicant:** **THE LUBRIZOL CORPORATION**
[US/US]; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).
- (72) **Inventors:** **MASTRANGELO, Antonio**; P. O. Box 88, Belper Derby DE56 1QN (GB). **GREENFIELD, Hannah**; P. O. Box 88, Belper Derby DE56 1QN (GB). **DUNKERLEY, John W.**; P. O. Box 88, Belper Derby DE56 1QN (GB).
- (74) **Agents:** **DEMAS, Christopher P.** et al.; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) **Title:** ASPHALTENE INHIBITION

(57) **Abstract:** The technology disclosed herein provides compositions and methods for asphaltene control in a hydrocarbon fluid, such as crude oil, by employing a quaternary ammonium salt.

