

Description

The present invention relates to a button feeder for feeding buttons such as snap buttons, hook buttons, ornamental buttons, or the like to a button applicator for attaching such buttons to garment fabric pieces.

Description of the Prior Art:

Japanese Laid-Open Utility Model Publication No. 56-85407 published July 11, 1981 discloses an automatic button applicator having a lower die unit with a die and an upper die unit with a punch. The button applicator is equipped with a button feeder for feeding buttons one by one from a first hopper to the lower die unit. Button attachments are also fed one by one by another feeder from a second hopper to the upper die unit. With a garment fabric piece disposed between the upper and lower die units, the punch is moved toward the die to forcibly join the button and the button attachment together by staking on the garment fabric piece.

Where an ornamental button with characters and/or figures on its face is to be attached to a fabric piece, the button is required to be oriented in a desired direction at all times when it is fed to a button applicator. A known button feeder is designed to supply such a button to a lower die unit while the button is being directed as desired.

For example, as shown by Japanese Laid-Open Patent Publication No. 52-28453 published March 8, 1976, a guide member having a wedge-shaped groove and another guide member having a vertical wall are disposed in confronting relation on a base block, thus defining a button feed path receptive of the circular head of a button. When the button is fed along the button feed path by means of a pusher, the button is rotated about its own axis in one direction because the circular button head undergoes greater frictional resistance imposed by the wedge-shaped groove than by the vertical wall. The button has forks on its back which engage confronting edges of the guide members to orient the button while it is being fed along the button feed path.

When the button travels along the button feed path, the button tends to be subjected to more and more frictional resistance to its movement since the circular head thereof is progressively forced into the wedge-shaped groove due to rotation of the button about its own axis.

US-A-3 987 950, considered the closest prior art, discloses a button feeder for feeding a button having a circular head to a button applicator, comprising: a feed guide and a pusher unit, the feed guide including a base, a first side guide member mounted on said base and having a substantially wedge-shaped groove, and a second side guide member mounted on said base and having a vertical wall confronting said wedge-shaped groove, wherein said base, said wedge-shaped groove, and said vertical wall jointly define a button feed path; the pusher unit being coupled to said feed guide for delivering the button into said button feed path, whereby, in

use, the button is urged to rotate upon being pushed by the pusher unit along said button feed path, the pusher unit comprising a part which is adapted to engage a part of the button when the button is in, or is rotated to, a predetermined orientation, so that the button is held in the predetermined orientation against rotation by the pusher unit.

However, in US-A-3 987 950 the first side guide member is a unitary member so that the wedge-shaped groove is of fixed cross-section, liable to prevent sufficiently smooth feeding of the button.

EP-A-63 366 discloses an apparatus for orienting and placing a button for attachment to a garment comprises a guide having a button guide channel, and a spring-biased locking lever pivotable on a button pushing slide slidably mounted on the guide. The pushing slide has a stepped end portion engageable at its tip end with the button head on its peripheral edge. The locking lever has a flanged end portion extending beyond the stepped end portion and terminating in a pair of claws for catching therebetween a tab disposed on the reverse side of the button head. The guide channel is defined by a side wall and a friction member. The friction member has a friction surface tangentially engageable with the button head for causing the button to turn or roll, when the latter is pushed by the pushing lever in the guide channel, until the tab of the button is caught by the claws.

The present invention seeks to provide a button feeder capable of feeding buttons smoothly to a button applicator without increasing frictional resistance to movement of the buttons.

According to the invention there is provided a button feeder as claimed in each of claims 1 to 9 hereof, to which reference is directed.

Many other advantages and features of the present invention will become manifest to those versed in the art upon making reference to the detailed description and the accompanying sheets of drawings in which preferred structural embodiments incorporating the principles of the present invention are shown by way of illustrative example.

Figure 1 is a side elevational view of a button applicator;

Figure 2 is an exploded perspective view showing a button and a button attachment to be attached to a fabric piece;

Figure 3 is a perspective view of a button feeder embodying the present invention;

Figure 4 is an exploded perspective view of the feed guide shown in Figure 3;

Figure 5 is a transverse cross-sectional view of the feed guide shown in Figure 4;

Figure 6 is a plan view of a side guide member of a feed guide according to another embodiment of the present invention;

Figure 7 is a side elevational view of the side guide member illustrated in Figure 6;

Figure 8 is a front elevational view of the side guide member of Figure 6;

Figure 9 is a cross-sectional view taken along line IX - IX of Figure 6; and

Figure 10 is an exploded perspective view of the side guide member shown in Figure 6.

Figure 1 shows a button applicator, generally designated by the reference numeral 10, including a button attaching assembly 11 comprising an upper die unit 12 having a punch 13 which is vertically movable by a vertical actuator mechanism (not shown), and a lower die unit 14 having a die 15 disposed below the upper die unit 12 in vertical alignment therewith. A first hopper 16 which contains a number of button attachments A has an outlet connected by a first chute 17 to a feeder 18 coupled to the upper die unit 12. A number of buttons B are contained in a second hopper 19 with its outlet joined by a second chute 20 to a button feeder 21 which is connected to the lower die unit 14. The first and second hoppers 16, 19 are arranged to successively deliver the button attachments A and the buttons B, each one by one, to the first and second chutes 17, 20, respectively, as disclosed in Japanese Laid-Open Patent publication No. 56-85407, for example.

As shown in Figure 2, each of the buttons B has a circular head 27 bearing characters, figures, or the like on its face and a joint stud 22 projecting from the back thereof. The circular head 27 has a recess 23 defined in a peripheral edge of the back thereof. The joint stud 22 has a central hole 24 therein. Each of the button attachments A has a pin 25 projecting from a circular base 26. The button 21 can be attached to a garment fabric piece C by inserting the pin 25 through the garment fabric piece C into the central hole 24 of the joint stud 22, and pressing the button attachment A toward the button B. This can be effected by supplying one button attachment B into the upper die unit 12 beneath the punch 13, one button A into the lower die unit 14 on the die 15, placing the garment fabric piece C between the upper and lower die units 12, 14, and finally moving the upper die unit 12 toward the lower die unit 14 until the inserted pin 25 is deformed in the hole 24.

As shown in Figure 3, the button feeder 21 generally comprises a feed guide 30 positioned adjacent to the lower die unit 14 and a pusher unit 31 coupled to the feed guide 30. The feed guide 30 includes a side guide member 32 having a groove 33 of a substantially wedge-shaped cross section and disposed on an upper surface of a base 34 along one side thereof. The feed guide 30 also includes another side guide member 35 having a vertical wall 36 and disposed on the upper surface of the base 34 along an opposite side thereof. The groove 33 and the vertical wall 36 confront each other across a feed path 37 defined longitudinally between the side guide members 32, 35 over the upper surface of the base 34 for passage therethrough of the circular head 27 of the button B.

The pusher unit 31 includes a pusher body 38

having an upwardly opening guide channel 39 and an elongate pusher 40 longitudinally slidably disposed in the guide channel 39. The pusher 40 has a slot 41 defined in a rear portion thereof and terminating at a slanted edge 42, from which a thin lower plate 45 extends toward the feed guide 30. A finger 44 is pivotably mounted by a pin 45 on the pusher 40 for vertical swinging movement about the pin 45. The finger 44 has a rear portion disposed in the slot 41 and a front portion lying on the thin lower plate 43. The front end of the finger 44 has a downward projection 46 positioned beyond a frontal edge 47 of the thin lower plate 43. The finger 44 is normally urged to turn counterclockwise (Figure 3) about the pin 45 under the resiliency of a spring 48 disposed in the slot 41 and engaging the rear end of the finger 44, so that the projection 46 is biased downwardly in front of the frontal edge 47. The pusher 40 is coupled at its rear end to an actuator (not shown) such as a cylinder or a reciprocating link mechanism. The pusher body 38 has a side recess 49 defined in one side wall thereof. The second chute 20 is coupled transversely to the pusher body 38 at the side recess 49 to allow the button B to be fed from the second chute 20 through the side recess 49 into the guide channel 39.

As shown in Figures 4 and 5, the base 34 of the feed guide 30 comprises a base body 50 that is substantially in the form of a rectangular parallelepiped, the base body 50 having an integral attachment leg 51 on one side thereof and an upright member 52 on the opposite side thereof. The attachment leg 51 has a longitudinal through hole 53 of a circular cross section. The base body 50 also has a vertical opening 54 defined adjacent to the upright member 52, and a longitudinal through hole 55 of a circular cross section which extends through the opening 54. The side guide member 35 includes a downwardly extending arm 56 having a longitudinal through hole 57 of a circular cross section and disposed in the vertical opening 54. The side guide member 35 is swingably supported on the base body 50 by means of a pin 58 of a circular cross section extending through the holes 55, 57. A pair of bolts 59 is threaded through the upright member 52. The side guide member 35 is normally urged to turn counterclockwise (Figure 5) about the pin 58 under the resilient forces of two compression coil springs 60 acting between the side guide member 35 and the bolts 59.

The side guide member 32 comprises a first guide element 61 and a second guide element 62. The first guide element 61 is in the form of a thin plate having, on one side thereof, an upper vertical surface 63 and a lower slanted surface 64. The first guide element 61 is fixed by bolts 65 in flatwise face-to-face engagement with the upper surface 66 of the base body 50 along one side thereof near the leg 51.

The second guide element 62 is of a substantially L-shape composed of a vertical

portion 67 and a horizontal portion 68. The vertical portion 67 has a vertical recess 69 defined therethrough at a corner of the horizontal portion 68. The horizontal portion 68 has a pair of holes 70 through which the respective bolts 65 extend with clearance. The vertical portion 67 has a longitudinal through hole 71 extending through the vertical recess 69. With the leg 51 received in the vertical recess 69, the second guide element 62 is swingably mounted on the base body 50 by a pin 72 extending through the holes 53, 71. Two compression coil springs 73 act between the vertical portion 67 and a side surface 74 of the base body 50 for normally urging the second guide element 62 to turn clockwise (Figure 5) about the pin 72 for thereby bringing the lower surface 75 of the horizontal portion 68 into abutment against the upper surface 76 of the first guide element 61. Under this condition, the lower surface 75 of the horizontal portion 68 and the vertical and slanted surfaces 63, 64 of the first guide element 61 jointly define the wedge-shaped groove 33. The horizontal portion 68 has a side edge 77 facing the side guide member 35.

In operation, the button B passes down the second chute 20 through the side recess 49 into the guide channel 39 in the direction of the arrow D (Figure 3) with the joint stud 22 extending upwardly. Then, the pusher 40 is moved in the direction of the arrow E to cause the frontal edge 47 thereof to engage and push the circular head 27 of the button B in the direction of the arrow F into the feed path 37. At this time, the downward projection 46 of the finger 44 engages the back of the circular head 27, slightly turning the finger 44 clockwise about the pin 45 against the resiliency of the spring 48.

When the button B is pushed into the feed path 37, the circular head 27 is brought into contact with the surfaces 63, 64, 75 of the wedge-shaped groove 33 and the vertical wall 36, as shown in Figure 5 at diametrically opposite portions of the circular head 27. Since the circular head 27 undergoes greater frictional resistance imposed by the wedge-shaped groove 33 than by the vertical wall 36, the button B is rotated about its own axis in one direction by the pusher 40 while it is being fed along the feed path 37. The button B is rotated until the projection 46 on the finger 44 is fitted in the recess 23 defined in the back of the circular head 27. When the projection 46 engages in the recess 23, the button B is prevented from being rotated about its own axis and directed in a desired orientation. The button B which is thus oriented as desired is delivered by the pusher 40 into the lower die unit 14 and set on the die 15.

While the button B is being fed along the feed path 37, the circular head 27 as it rotates tends to be progressively forced into the wedge-shaped groove 33, which is then spread. More specifically, the horizontal portion 68 of the second guide element 62 is pushed upwardly by the circular head 27 to cause the second guide element 62 to turn counterclockwise (Figure 5)

about the pin 72 against the resilient forces of the springs 73. When the joint stud 22 engages the side edge 77 of the horizontal portion 68, the circular head 27 is prevented from farther entering the wedge-shaped groove 33 and hence from larger frictional resistance applied by the wedge-shaped groove 33. Therefore, the button B is fed smoothly along the feed path 37 without being stuck in the wedge-shaped groove 33.

Figures 6 through 10 illustrate a side guide member 80 according to another embodiment of the present invention. The side guide member comprises a first guide element 81 and a second guide element 82. The first guide element 81 has an upwardly opening recess 83 defined in an upper surface thereof at a longitudinally central area, the recess 83 having a depth which is about half the height of a vertical surface 84. The recess 83 has a bottom 85 through which bolts 86 extend threadedly into a base 87 to secure the first guide element 81 to the base 87. The first guide element 81 has a slanted surface 88 extending obliquely downwardly from the vertical surface 84. The second guide element 82 has a pair of recesses 89 defined vertically through opposite longitudinal end portions thereof. The upper portions of the first guide element 81 which are located one on each side of the recess 83 are snugly fitted respectively in the recesses 89 in the second guide element 82. The second guide element 82 thus has a longitudinal central portion 90 between the recesses 89 which is snugly fitted in the recess 83. The second guide element 82 combined with the first guide element 81 is prevented from moving longitudinally and transversely with respect to the first guide element 81, but is movable vertically relatively thereto. A leaf spring 91 has one end secured by a bolt 92 to one longitudinal end of the first guide element 81 and an opposite end resiliently held against the upper surface of the central portion 90 of the second guide element 82. The second guide element 82 has a lower surface 93 facing toward the base 87 and cooperating with the vertical and slanted surfaces 84, 88 in defining a substantially wedge-shaped groove 94 for receiving the circular head 27 (Figure 2) of the button B, the surface 95 slanting obliquely upwardly from surface 84.

When the circular head 27 is forced into the wedge-shaped groove 94, the second guide element 82 is moved upwardly against the resiliency of the leaf spring 91 thereby to spread the wedge-shaped groove 91.

Claims

1. A button feeder (21) for feeding a button (B) having a circular head (27) to a button applicator (10), comprising: a feed guide (30) and a pusher unit (31); the feed guide (30) including a base (34; 87), a first side guide member (32; 80) mounted on said base (34; 87) and having a substantially

portion 67 and a horizontal portion 68. The vertical portion 67 has a vertical recess 69 defined therethrough at a corner of the horizontal portion 68. The horizontal portion 68 has a pair of holes 70 through which the respective bolts 65 extend with clearance. The vertical portion 67 has a longitudinal through hole 71 extending through the vertical recess 69. With the leg 51 received in the vertical recess 69, the second guide element 62 is swingably mounted on the base body 50 by a pin 72 extending through the holes 53, 71. Two compression coil springs 73 act between the vertical portion 67 and a side surface 74 of the base body 50 for normally urging the second guide element 62 to turn clockwise (Figure 5) about the pin 72 for thereby bringing the lower surface 75 of the horizontal portion 68 into abutment against the upper surface 76 of the first guide element 61. Under this condition, the lower surface 75 of the horizontal portion 68 and the vertical and slanted surfaces 63, 64 of the first guide element 61 jointly define the wedge-shaped groove 33. The horizontal portion 68 has a side edge 77 facing the side guide member 35.

In operation, the button B passes down the second chute 20 through the side recess 49 into the guide channel 39 in the direction of the arrow D (Figure 3) with the joint stud 22 extending upwardly. Then, the pusher 40 is moved in the direction of the arrow E to cause the frontal edge 47 thereof to engage and push the circular head 27 of the button B in the direction of the arrow F into the feed path 37. At this time, the downward projection 46 of the finger 44 engages the back of the circular head 27, slightly turning the finger 44 clockwise about the pin 45 against the resiliency of the spring 48.

When the button B is pushed into the feed path 37, the circular head 27 is brought into contact with the surfaces 63, 64, 75 of the wedge-shaped groove 33 and the vertical wall 36, as shown in Figure 5 at diametrically opposite portions of the circular head 27. Since the circular head 27 undergoes greater frictional resistance imposed by the wedge-shaped groove 33 than by the vertical wall 36, the button B is rotated about its own axis in one direction by the pusher 40 while it is being fed along the feed path 37. The button B is rotated until the projection 46 on the finger 44 is fitted in the recess 23 defined in the back of the circular head 27. When the projection 46 engages in the recess 23, the button B is prevented from being rotated about its own axis and directed in a desired orientation. The button B which is thus oriented as desired is delivered by the pusher 40 into the lower die unit 14 and set on the die 15.

While the button B is being fed along the feed path 37, the circular head 27 as it rotates tends to be progressively forced into the wedge-shaped groove 33, which is then spread. More specifically, the horizontal portion 68 of the second guide element 62 is pushed upwardly by the circular head 27 to cause the second guide element 62 to turn counterclockwise (Figure 5)

about the pin 72 against the resilient forces of the springs 73. When the joint stud 22 engages the side edge 77 of the horizontal portion 68, the circular head 27 is prevented from farther entering the wedge-shaped groove 33 and hence from larger frictional resistance applied by the wedge-shaped groove 33. Therefore, the button B is fed smoothly along the feed path 37 without being stuck in the wedge-shaped groove 33.

Figures 6 through 10 illustrate a side guide member 80 according to another embodiment of the present invention. The side guide member comprises a first guide element 81 and a second guide element 82. The first guide element 81 has an upwardly opening recess 83 defined in an upper surface thereof at a longitudinally central area, the recess 83 having a depth which is about half the height of a vertical surface 84. The recess 83 has a bottom 85 through which bolts 86 extend threadedly into a base 87 to secure the first guide element 81 to the base 87. The first guide element 81 has a slanted surface 88 extending obliquely downwardly from the vertical surface 84. The second guide element 82 has a pair of recesses 89 defined vertically through opposite longitudinal end portions thereof. The upper portions of the first guide element 81 which are located one on each side of the recess 83 are snugly fitted respectively in the recesses 89 in the second guide element 82. The second guide element 82 thus has a longitudinal central portion 90 between the recesses 89 which is snugly fitted in the recess 83. The second guide element 82 combined with the first guide element 81 is prevented from moving longitudinally and transversely with respect to the first guide element 81, but is movable vertically relatively thereto. A leaf spring 91 has one end secured by a bolt 92 to one longitudinal end of the first guide element 81 and an opposite end resiliently held against the upper surface of the central portion 90 of the second guide element 82. The second guide element 82 has a lower surface 93 facing toward the base 87 and cooperating with the vertical and slanted surfaces 84, 88 in defining a substantially wedge-shaped groove 94 for receiving the circular head 27 (Figure 2) of the button B, the surface 95 slanting obliquely upwardly from surface 84.

When the circular head 27 is forced into the wedge-shaped groove 94, the second guide element 82 is moved upwardly against the resiliency of the leaf spring 91 thereby to spread the wedge-shaped groove 94.

Claims.

1. A button feeder (21) for feeding a button (B) having a circular head (27) to a button applicator (10), comprising: a feed guide (30) and a pusher unit (31); the feed guide (30) including a base (34; 87), a first side guide member (32; 80) mounted on said base (34; 87) and having a substantially



wedge-shaped groove (33; 94), and a second side guide member (35) mounted on said base (34) and having a vertical wall (36) confronting said wedge-shaped groove (33; 94) wherein said base (34; 87), said wedge-shaped groove (33; 94), and said vertical wall (36) jointly define a button feed path (37); the pusher unit (31) coupled to said feed guide (30) for delivering the button (B) into said button feed path (37), whereby, in use, the button (B) is urged to rotate upon being pushed by the pusher unit (31) along said button feed path (37), the pusher unit (31) comprising a part (46) which is adapted to engage a part (23) of the button (B) when the button (B) is in, or is rotated to, a predetermined orientation, so that the button (B) is held in the predetermined orientation against rotation by the pusher unit (31); characterised in that said first side guide member (32; 80) includes a first guide element (61; 81) fixed to said base (34; 87); a second guide element (62; 82) movably mounted on said first guide element (61; 81) for movement toward and away from said first guide element (61; 81), said wedge-shaped groove (33; 94) being defined between said first and second guide elements (61, 62; 81, 82); and resilient means (73; 91) for normally urging said second guide element (62; 82) resiliently toward said first guide element (61, 81).

2. A button feeder (21) according to claim 1, said second guide element (62) being angularly movably mounted on said base (34), said resilient means (73) acting between said second guide element (62) and said base (34).

3. A button feeder (21) according to claim 2, said second guide element (62) having a lower surface (75), said first guide element (61) having a vertical surface (63) and a slanted surface (64) extending obliquely downwardly from said vertical surface (63), said wedge-shaped groove (33) being jointly defined by said lower surface (75), said vertical surface (63), and said slanted surface (64).

4. A button feeder (21) according to claim 2 or 3, said resilient means (73) comprising a pair of compression coil springs (73).

5. A button feeder (21) according to claim 1, said second guide element (62) being linearly movably mounted on said base (87), said resilient means (91) acting between said second guide element (62) and said first guide element (81).

6. A button feeder (21) according to claim 5, said second guide element (62) having a lower surface (93), said first guide element (81) having a vertical surface (84) and a slanted surface (88) extending obliquely downwardly from said vertical surface (84), said wedge-shaped groove (94) being jointly defined by said lower surface (93), said vertical surface (84), and said slanted surface (88).

7. A button feeder (21) according to claim 5 or 6, said resilient means (91) comprising a leaf spring.

8. A button feeder (21) according to claim 7, said leaf spring (91) having one end secured to

said first guide element (81) and an opposite end resiliently held against said second guide element (82).

9. A button feeder (21) according to claim 1, said second side guide member (35) being angularly movably mounted on said base (50), further including second resilient means (60) for normally urging said second side guide member (35) toward said first side guide member (32).

Patentansprüche

1. Knopfzuführeinrichtung (21) zum Zuführen eines Knopfes (B) mit einem kreisrunden Kopf (27) zu einer Knopfansetzmaschine (10), umfassend eine Zuführführung (30) und eine Schubeinheit (31), wobei die Zuführführung (30) eine Basis (34; 87), ein erstes seitliches Führungsteil (32; 80), das an der Basis (34; 87) angebracht ist und eine im wesentlichen keilförmige Nut (33; 94) hat, und ein zweites seitliches Führungsteil (35) aufweist, das an der Basis (34) angebracht ist und eine der keilförmigen Nut (33; 94) zugekehrte vertikale Wand (36) hat, wobei die Basis (34; 87), die keilförmige Nut (33; 94) und die vertikale Wand (36) gemeinsam eine Knopfzuführbahn (37) begrenzen; wobei die Schubeinheit (31) mit der Zuführführung (30) verbunden ist, um den Knopf (B) in die Knopfzuführbahn (37) zuzuführen, wodurch im Gebrauch der Knopf (B) in Drehung versetzt wird, während er von der Schubeinheit (31) längs der Knopfzuführbahn (37) geschoben wird, wobei die Schubeinheit (31) ein Teil (46) umfaßt, das mit einem Teil (23) des Knopfes (B) in Eingriff gelangen kann, wenn der Knopf eine bestimmte Orientierung einnimmt oder in diese verdreht wird, so daß der Knopf (B) gegen eine Verdrehung durch die Schubeinheit (31) in der bestimmten Orientierung gehalten wird, dadurch gekennzeichnet, daß das erste seitliche Führungsteil (32; 80) ein an der Basis (34; 87) befestigtes erstes Führungselement (61; 81), ein an dem ersten Führungselement (61; 81) gegenüber diesem abstandsveränderlich beweglich gelagertes zweites Führungselement (62; 82), wobei die keilförmige Nut (33; 94) zwischen dem ersten und dem zweiten Führungselement (61, 62; 81, 82) begrenzt ist, und Federmittel (73; 91) aufweist, um das zweite Führungselement (62; 82) normalerweise elastisch gegen das erste Führungselement (61, 81) zu belasten.

2. Knopfzuführeinrichtung (21) nach Anspruch 1, wobei das zweite Führungselement (62) an der Basis (34) schwenkbar gelagert ist, wobei die Federmittel (73) zwischen dem zweiten Führungselement (62) und der Basis (34) wirksam sind.

3. Knopfzuführeinrichtung (21) nach Anspruch 2, wobei das zweite Führungselement (62) eine Unterseite (75) aufweist, wobei das erste Führungselement (61) eine vertikale Fläche (63)



und eine geneigte Fläche (64) aufweist, die sich von der vertikalen Fläche (63) schräg nach unten erstreckt, wobei die keilförmige Nut (33) gemeinsam von der Unterseite (75), der vertikalen Fläche (63) und der geneigten Fläche (64) begrenzt ist.

4. Knopfzuführeinrichtung (21) nach Anspruch 2 oder 3, wobei die Federmittel (73) zwei Druckfedern (73) umfassen.

5. Knopfzuführeinrichtung (21) nach Anspruch 1, wobei das zweite Führungselement (82) auf der Basis (87) linear beweglich gelagert ist, wobei die Federmittel (91) zwischen dem zweiten Führungselement (82) und dem ersten Führungselement (81) wirksam sind.

6. Knopfzuführeinrichtung (21) nach Anspruch 5, wobei das zweite Führungselement (82) eine Unterseite (93) hat, wobei das erste Führungselement (81) eine vertikale Fläche (84) und eine geneigte Fläche (88) hat, die sich von der vertikalen Fläche (84) schräg nach unten erstreckt, wobei die keilförmige Nut (94) gemeinsam von der Unterseite (93), der vertikalen Fläche (84) und der geneigten Fläche (88) begrenzt ist.

7. Knopfzuführeinrichtung (21) nach Anspruch 5 oder 6, wobei die Federmittel (91) eine Blattfeder (91) umfassen.

8. Knopfzuführeinrichtung (21) nach Anspruch 7, wobei ein Ende der Blattfeder (91) an dem ersten Führungselement (81) befestigt ist und ein gegenüberliegendes Ende an dem zweiten Führungselement (82) federnd anliegt.

9. Knopfzuführeinrichtung (21) nach Anspruch 1, wobei das zweite seitliche Führungsteil (35) an der Basis (50) schwenkbar gelagert ist und ferner zweite Federmittel (60) umfaßt, die das zweite seitliche Führungsteil (35) normalerweise gegen das erste seitliche Führungsteil (32) belasten.

Revendications

1. Dispositif (21) d'alimentation en boutons pour avancer un bouton (B) comportant une tête circulaire (27) jusqu'à un applicateur (10) de bouton, comprenant un guide d'avance (30) et un ensemble de poussée (31); le guide d'avance (30) comprenant une base (34; 87), un premier organe de guidage latéral (32; 80) monté sur ladite base (34; 87) et comportant une rainure (33; 94) sensiblement cunéiforme, et un second organe de guidage latéral (35) monté sur ladite base (34) et comportant une paroi verticale (36) située en regard de ladite rainure cunéiforme (33; 94), ladite base (34; 87), ladite rainure cunéiforme (33; 94), et ladite paroi verticale (36) définissant conjointement un trajet (37) d'avance de bouton; l'ensemble de poussée (31) étant couplé audit guide d'avance (30) pour fournir le bouton (B) au trajet (37) d'avance de bouton, ce qui fait que, pendant l'utilisation, le bouton (B) est sollicité de manière à tourner lorsqu'il est poussé par l'ensemble de poussée (31) le long dudit trajet

(37) d'avance de bouton, l'ensemble de poussée (31) comprenant une partie (46) qui est adaptée pour venir porter contre une partie (23) du bouton (B) lorsque le bouton (B) se trouve dans une orientation prédéterminée, ou a été amené par rotation dans cette orientation prédéterminée, de sorte que le bouton (B) est maintenu dans l'orientation prédéterminée à l'encontre de la rotation imprimée par l'ensemble de poussée (31), caractérisé en ce ledit premier organe de guidage latéral (32; 80) comprend un premier élément de guidage (61; 81) fixé à la base (34; 87); un second élément de guidage (62; 82) monté de façon mobile sur ledit premier élément de guidage (61; 81) en vue de se rapprocher et de s'éloigner du premier élément de guidage (61; 81), ladite rainure cunéiforme (33; 94) étant formée entre les premier et second éléments de guidage (61, 62; 81, 82); et un moyen élastique (73; 91) pour solliciter normalement ledit second élément de guidage (62; 82) élastiquement vers ledit premier élément de guidage (61; 81).

2. Dispositif (21) d'alimentation en boutons selon la revendication 1, ledit second élément de guidage (62) étant monté de façon mobile angulairement sur ladite base (34), ledit moyen élastique (73) agissant entre le second élément de guidage (62) et la base (34).

3. Dispositif (21) d'alimentation en boutons selon la revendication 2, ledit second élément de guidage (62) comportant une surface inférieure (75), ledit premier élément de guidage (61) comportant une surface verticale (63) et une surface inclinée (64) s'étendant obliquement vers le bas depuis ladite surface verticale (63), ladite rainure cunéiforme (33) étant définie conjointement par ladite surface inférieure (75), ladite surface verticale (63), et ladite surface inclinée (64).

4. Dispositif (21) d'alimentation en boutons selon la revendication 2 ou 3, ledit moyen élastique (73) comprenant une paire de ressorts hélicoïdaux (73) travaillant à la compression.

5. Dispositif (21) d'alimentation en boutons selon la revendication 1, ledit second élément de guidage (82) étant monté de façon mobile linéairement sur ladite base (87), ledit moyen élastique (91) agissant entre le second élément de guidage (82) et le premier élément de guidage (81).

6. Dispositif (21) d'alimentation en boutons selon la revendication 5, ledit second élément de guidage (82) comportant une surface inférieure (93), ledit premier élément de guidage (81) comportant une surface verticale (84) et une surface inclinée (88) s'étendant obliquement vers le bas depuis ladite surface verticale (84), ladite rainure cunéiforme (94) étant définie conjointement par la surface inférieure (93), la surface verticale (84) et la surface inclinée (88).

7. Dispositif (21) d'alimentation en boutons selon la revendication 5 ou 6, ledit moyen élastique (91) comprenant une lame de ressort (91).

8. Dispositif (21) d'alimentation en boutons

* C L N S *



selon la revendication 7, ladite lame de ressort (91) ayant une de ses extrémités fixée audit premier élément de guidage (81) et son extrémité opposée maintenue élastiquement contre ledit second élément de guidage (82).

9. Dispositif (21) d'alimentation en boutons selon la revendication 1, ledit second organe de guidage latéral (35) étant monté de façon mobile angulairement sur ladite base (50), le dispositif comprenant, en outre, un second moyen élastique (60) pour solliciter normalement ledit second organe de guidage latéral (35) en direction dudit premier organe de guidage latéral (32).

5

10

15

20

25

30

35

40

45

50

55

60

65

7

* C L H S *

