

-1-

ESTABLISHMENT OF TDM (AOTDM) OR IP (AOIP) BEARER ON THE A-INTERFACE IN A INTER-RNC HANDOVER

TECHNICAL FIELD

5 The present invention is related to assignment and handover in a radio communication network. (As used herein, references to the “present invention” or “invention” relate to exemplary embodiments and not necessarily to every embodiment encompassed by the appended claims.) More specifically, the present invention is related to assignment and handover in a radio communication network where a first
10 resource indicator and a second resource indicator are offered together in a message for selection.

BACKGROUND

 This section is intended to introduce the reader to various aspects of the art that
15 may be related to various aspects of the present invention. The following discussion is intended to provide information to facilitate a better understanding of the present invention. Accordingly, it should be understood that statements in the following discussion are to be read in this light, and not as admissions of prior art.

 The A-interface is defined in 3GPP as the terrestrial interface between the MSC
20 node and the BSS radio network. Today TDM is the only defined bearer technology for user plain connection defined in the A-interface. The A-interface is defined in 3GPP technical specification 48.001 (3GPP TS 48.001 Base Station System - Mobile-services Switching Centre (BSS - MSC) interface; General aspects) and the references specified therein.

25 Handover procedures are defined in 3GPP technical specification 23.009 (3GPP TS 23.009 Handover Procedures). The technical specification assumes an A-interface as defined in the 3GPP standard (3GPP TS 48.001 Base Station System - Mobile-services Switching Centre (BSS - MSC) interface; General aspects).

 Figure 1 shows the procedure for an intra MSC, inter BSC, GSM to GSM
30 handover procedure taken from 3GPP TS 23.009 Handover Procedures. This procedure is chosen as an example because it is used below to describe the concept of the new invention.

-2-

In regard to problems with existing solutions, currently the effort is taken to enhance the current standardized A-interface and to support the A-interface as well for IP used as bearer for the user plain. Although in the further disclosed, reference is made to IP technology as a further supported technology, the invention is not limited thereto but encompasses any differing bearer technology. It is assumed that during a network migration from the currently standardized A-interface (AoTDM) to the enhanced A-interface (AoIP) the two bearer technologies defined for the user plain are used in parallel. This may not be needed in all migration scenarios but it is seen as a likely scenario for many operators.

Applying the current 3GPP handover procedure (3GPP TS 23.009 Handover Procedures) in such a scenario - parallel use of TDM and IP as user plane bearer - results in the following issue: When the MSC request channel assignment from the target BSC then the MSC does not know if this BSC can establish the terrestrial interface using IP as bearer type. The BSC has the final decision on the bearer type because of the following rules:

- In the BSC the decision for a specific bearer on the terrestrial interface may depend on the selected speech coder version for the A-interface.
- The BSC has always the final decision regarding the radio codec and the same codec should be used on the terrestrial interface as on the radio link to avoid additional transcoding.

The MSC has to seize bearer resources for the A-interface user plain (terrestrial interface) before it sends BSSMAP Handover Request message to the target BSC. If the target BSC cannot support TDM bearer for the terrestrial interface then BSC has to reject the call. MSC could repeat the BSSMAP Handover Request message using in the new request IP bearer for the terrestrial interface. This handling would require additional signaling on the A-interface and would extend the handover time.

One simple solution to avoid the repetition of the handover request message would be to provide some configuration in MSC about the BSC capability. However, this solution has the following disadvantages:

-3-

- It is static and cannot provide BSC capability for a specific call
- It is error-prone due to manual interaction

5 Another sub-optimal solution would be that the BSC always accepts the bearer type offered from MSC in the handover request. If it cannot use the codec selected on the radio link on the terrestrial interface, then BSC should use another offered codec type. This solution has the following disadvantages:

- 10 • The operator has to provide transcoder resources in the BSC to cover the described scenario
- Inserting a transcoder in the BSC and using compressed speech codec on the terrestrial interface reduces speech quality and increases the delay in the speech path

15

BRIEF SUMMARY OF THE INVENTION

 The present invention pertains to a method for using a network entity of a radio communication network. The method comprises the steps of seizing a first resource and a second resource for a terrestrial interface of the network, where the first resource is distinct and different from the second resource. There is the step of sending a handover request message identifying the first resource and the second resource.

20

 The present invention pertains to a network entity for a radio communication network. The entity comprises a processing unit which causes a first resource and a second resource for a terrestrial interface of the radio network to be seized, where the first resource is distinct and different from the second resource. The entity comprises a network interface through which a handover request message identifying the first and the second resource is sent.

25

 The present invention pertains to a method for using a network entity of a radio communication network. The method comprises the steps of seizing a first resource and a second resource for a terrestrial interface of the network, where the first resource is distinct and different from the second resource. There is the step of sending an assignment request message identifying the first resource and the second resource.

30

The present invention pertains to a network entity for a radio communication network. The entity comprises a processing unit which causes a first resource and a second resource for a terrestrial interface of the radio network to be seized, where the first resource is distinct and different from the second resource. The entity comprises a network interface through which an assignment request message identifying the first and the second resource is sent.

The present invention pertains to a network entity for a radio communication network. The entity comprises a network interface which receives a handover request message identifying a first resource and a second resource, the first resource distinct and different from the second resource. The entity comprises a processing unit that selects one of the first and second resources, allocates a radio channel associated with the handover, selects a bearer for a terrestrial interface and seizes resources for the interface.

The present invention pertains to a method for a network entity of a radio communication network. The method comprises the steps of receiving a handover request message identifying a first resource and a second resource, the first resource distinct and different from the second resource. There is the step of selecting one of the first and second resources. There is the step of allocating a radio channel associated with the handover. There is the step of selecting a bearer for a terrestrial interface. There is the step of seizing resources for the interface.

The present invention pertains to a network entity for a radio communication network. The entity comprises a network interface which receives an assignment request message identifying a first resource and a second resource, the first resource distinct and different from the second resource. The entity comprises a processing unit that selects one of the first and second resources, allocates a radio channel associated with the assignment, selects a bearer for a terrestrial interface and seizes resources for the interface.

The present invention pertains to a method for a network entity of a radio communication network. Any method comprises the steps of receiving an assignment request message identifying a first resource and a second resource, the first resource distinct and different from the second resource. There is the step of selecting one of the first and second resources. There is the step of allocating a radio channel associated

with the assignment. There is the step of selecting a bearer for a terrestrial interface. There is the step of seizing resources for the interface.

BRIEF DESCRIPTION OF THE DRAWINGS

5 In the accompanying drawings, the preferred embodiment of the invention and preferred methods of practicing the invention are illustrated in which:

Figure 1 shows an intra MSC, inter BSC, GSM to GSM handover procedure.

Figure 2 shows inter BSC handover using AoTDM and AoIP of the present invention.

10 Figure 3 shows improved inter BSC HO; BSC selects IP bearer for the terrestrial interface of the present invention.

Figure 4 shows improved inter BSC HO; BSC selects TDM bearer for the terrestrial interface of the present invention.

15 Figure 5 shows the selection of the IP bearer at call setup of the present invention.

Figure 6 shows the selection of the TDM bearer at call setup of the present invention.

Figure 7 is a block diagram of a network entity of the present invention.

20 DETAILED DESCRIPTION

Referring now to the drawings wherein like reference numerals refer to similar or identical parts throughout the several views, and more specifically to figures 2 and 7 thereof, there is shown a network entity 10, such as an MSC, for a radio communication network. The entity comprises a processing unit 12 which causes a first resource and a
25 second resource for a terrestrial interface of the radio network to be seized, where the first resource is distinct and different from the second resource. The entity comprises a network interface 14 through which a handover request message identifying the first and the second resource is sent.

Preferably, the network interface 14 receives an acknowledgment of the
30 handover. The processing unit 12 preferably detects that one of the first and second resources is selected for a bearer. Preferably, the processing unit 12 causes an unselected one of the first and second resources to be released.

The network interface 14 preferably sends the handover request message with a circuit identifier code of a selected time division multiplexing (TDM) circuit with respect to a TDM bearer, and with a transport address of a media gateway (MGw) that will terminate an IP connection with respect to an IP bearer.

5 The present invention pertains to a method for using a network entity 10, such as an MSC, of a radio communication network. The method comprises the steps of seizing a first resource and a second resource for a terrestrial interface of the network, where the first resource is distinct and different from the second resource. There is the step of sending a handover request message identifying the first resource and the
10 second resource.

Preferably, there is the step of receiving an acknowledgment of the handover. There is preferably the step of detecting that one of the first and second resources is selected for a bearer. Preferably, there is the step of releasing an unselected one of the first and second resources.

15 The sending step preferably includes the step of sending the handover request message with a circuit identifier code of a selected time division multiplexing (TDM) circuit with respect to a TDM bearer, and with a transport address of a media gateway (MGw) that will terminate an internet protocol (IP) connection with respect to an IP bearer. The transport address can include an IP address and a port number.

20 The present invention pertains to a method for using a network entity 10, such as an MSC, of a radio communication network. The method comprises the steps of seizing a first resource and a second resource for a terrestrial interface of the network, where the first resource is distinct and different from the second resource. There is the step of sending an assignment request message identifying the first resource and the
25 second resource.

Preferably, there is the step of receiving an assignment complete message that indicates a bearer shall be used on an A-interface user plane connection.

The present invention pertains to a network entity 10 for a radio communication network. The entity comprises a processing unit 12 which causes a first resource and a
30 second resource for a terrestrial interface of the radio network to be seized, where the first resource is distinct and different from the second resource. The entity comprises a

network interface 14 through which an assignment request message identifying the first and the second resource is sent.

The present invention pertains to a network entity 10, such as a BSC, for a radio communication network. The entity comprises a network interface 14 which receives a
5 handover request message identifying a first resource and a second resource, the first resource distinct and different from the second resource. The entity comprises a processing unit 12 that selects one of the first and second resources, allocates a radio channel associated with the handover, selects a bearer for a terrestrial interface and seizes resources for the interface.

10 Preferably, the network interface 14 sends an acknowledgment of the handover request. The acknowledgment request preferably includes information that identifies which bearer is used on the terrestrial interface.

Preferably, the handover request message is a BSSMAP handover request with a circuit identifier code of a selected time division multiplexing (TDM) circuit with
15 respect to a TDM bearer, and with a transport address of a media gateway (MGW) that will terminate an IP connection with respect to an IP bearer.

The present invention pertains to a method for a network entity 10, such as a BSC, of a radio communication network. The method comprises the steps of receiving a handover request message identifying a first resource and a second resource, the first
20 resource distinct and different from the second resource. There is the step of selecting one of the first and second resources. There is the step of allocating a radio channel associated with the handover. There is the step of selecting a bearer for a terrestrial interface. There is the step of seizing resources for the interface.

Preferably, there is the step of sending an acknowledgment of the handover
25 request. The acknowledgment preferably includes information that identifies which bearer is used on the terrestrial interface.

Preferably, the receiving step includes the step of receiving a BSSMAP handover request with a circuit identifier code of a selected time division multiplexing (TDM) circuit with respect to a TDM bearer, and with a transport address of a media
30 gateway (MGW) that will terminate an IP connection with respect to an IP bearer.

The present invention pertains to a network entity 10, such as a BSC, for a radio communication network. The entity comprises a network interface 14 which receives

an assignment request message identifying a first resource and a second resource, the first resource distinct and different from the second resource. The entity comprises a processing unit 12 that selects one of the first and second resources, allocates a radio channel associated with the assignment, selects a bearer for a terrestrial interface and
5 seizes resources for the interface.

The present invention pertains to a method for a network entity 10, such as a BSC, of a radio communication network. The method comprises the steps of receiving an assignment request message identifying a first resource and a second resource, the first resource distinct and different from the second resource. There is the step of
10 selecting one of the first and second resources. There is the step of allocating a radio channel associated with the assignment. There is the step of selecting a bearer for a terrestrial interface. There is the step of seizing resources for the interface.

There is preferably the step of selecting the bearer to be used on an A-interface user plane connection. Preferably, there is the step of sending an assignment complete
15 message indicating the selected bearer.

Although this invention is explained with reference to 3GPP herein, the invention is not limited to 3GPP compliant networks but may encompass also other networks like the (W)iDEN compatible networks.

In the operation of the invention, to improve the inter BSC handover procedure
20 for intra MSC or inter MSC handover scenarios, the handover can be either GSM to GSM handover or WCDMA to GSM handover or any other HO from any radio technology to GSM such as LTE to GSM.

MSC automatically detects if BSC can support IP on the terrestrial interface. Therefore, MSC monitors mobile originating and mobile terminating calls. As soon as
25 BSC uses AoIP for any of those calls MSC marks the BSC as capable to support IP bearer. The call set-up procedure for AoIP supports that MSC and BSC are negotiating which bearer to use.

MSC seizes resources for the TDM bearer and the IP bearer before the handover request message is sent to BSC. Then BSC can choose any of the bearer types. In the
30 BSSMAP Handover Request Acknowledge message the BSC informs the MSC about the selected bearer type. Finally MSC can release the seized resources from the not selected bearer type.

Figure 2 shows the concept of the improved handover procedure. The numbers in the figure indicate the sequence of actions.

In a first step 1, a BSC (source BSC) detects a handover condition and indicates in a second step 2 towards a MSC that a Handover is required. In a next step 3, the MSC seizes TDM resources and resources for other bearer(s), e.g. IP for the terrestrial interface. Thereafter, in step 4, a handover request is sent towards a further BSC (target BSC) including an indication about the seized resources. The further BSC (target BSC) selects a bearer for the terrestrial interface and sends an acknowledgement of said handover request in a further step 6 towards the MSC. Either within the acknowledgement or within any other appropriate message information which bearer is used on the terrestrial interface is provided towards the MSC. Finally, the MSC uses the provided information which bearer is used on the terrestrial interface in a step 7 to continue handover procedure, e.g. as defined in 3GPP. In addition, the MSC may also use provided information which bearer is used on the terrestrial interface to release the unused but seized resources for the other bearers.

The improvement for the inter BSC handover procedure is based on the following scenario:

- Target BSC can support AoTDM and AoIP
- Note: the MSC sending the handover request to the target MSC does not know in advance, which bearer BSC will select.
- GSM to GSM or WCDMA to GSM handover is performed

MSC monitors the call set-up procedures for mobile originating and mobile terminating calls. Once BSC uses AoIP for any of those calls the MSC marks that BSC is capable using IP on the user plain.

The information whether a BSC supports AoIP may also be provided towards the MSC in a different manner, e.g. it might be administered via an O&M (Operations & Maintenance) tool.

During handover procedure, one MSC sends the BSSMAP Handover Request to the target BSC. This can be either the anchor MSC (intra MSC HO procedure or subsequent inter MSC HO back to anchor MSC), or in the non-anchor MSC (intra MSC in

-10-

non-anchor MSC, inter MSC handover or sub-subsequent inter MSC handover to another non-anchor MSC).

Figure 3 shows a possible message flow that can be used for the proposed handover procedure. In this example the BSC selects IP bearer for the terrestrial
5 interface.

The following steps are shown in figure 3:

- First the MSC detects a condition to request channel assignment from target BSC (step 1). This could be for example the reception of BSSMAP Handover
10 Required message from BSC (intra MSC HO) or the reception of MAP Prepare Handover Request message (inter MSC HO).
- Then seizes a TDM circuit and IP resources for the terrestrial interface towards the target BSC. This involves MSC internal processes and in case of layered
15 network architecture the MSC-S has to request MGW to seize a TDM termination and an IP termination (steps 2 - 5).
- Then MSC sends the BSSMAP Handover Request message to the target BSC (step 6). This message includes the CIC - in case MSC allocates the CIC - and a
20 container (AoIP Container) used to transport IP address information from the MGW to the BSC.
- BSC allocates the radio channel, selects the bearer for the terrestrial interface and seizes resources for this interface (step 7). Here, the BSC decides to use
25 IP bearer.
- In the acknowledgment message the BSC provides its user plain address information within the AoIP Container (step 8). MSC identifies that IP is selected for the bearer because it receives the AoIP Container.
30
- MSC is passing the contents of the AoIP Container to the MGW (steps 9, 10).

- MSC releases the seized TDM resources. In layered architecture MSC request MGW to release the TDM termination (steps 11, 12).

Figure 5 shows the selection of the IP bearer at call setup (assignment).

- 5 Figure 4 shows a second example for a possible message flow that can be used for the proposed handover procedure. In this example the BSC selects TDM as bearer for the terrestrial interface.

The steps 1 - 6 are equal to the case before, where BSC selected IP bearer for the terrestrial interface. The following steps are different:

10

- BSC allocates the radio channel, selects the bearer for the terrestrial interface and seizes resources for this interface (step 7). In opposite to the previous example, here, the BSC decides to use TDM bearer.

15

- BSC sends the acknowledgement message as defined in 3GPP for AoTDM (step 8). MSC identifies that TDM is selected for the bearer because it does not receive the AoIP Container.

- MSC releases the seized IP resources. In layered architecture MSC request MGW to release the IP termination (steps 9, 10).
- 20

Note, that in case BSC is responsible to allocate the CIC the following changes have to be applied to the examples above:

25

- MSC does not provide a CIC in the Handover Request message (both examples).

- If BSC select TDM bearer for the terrestrial interface it provides a CIC in the Handover Request Acknowledge message (first example).

30

Figure 6 shows the selection of the TDM bearer at call setup (assignment).

-12-

Handover (HO) and assignment request are two independent functions. Assignment request is at call setup. It is mandatory to establish the radio connection (mobile terminal to antenna and further to the BSC node) and to connect that part with the core network.

5 Handover is a process that is performed during the call when the terminal is moving around. Different handover types can be distinguished: while moving the terminal may reach the area of a new antenna, a new radio coverage cell, an area that is controlled by another BSC or even an area that is controlled by another MSC. Further intersystem handover is possible, that means a calling subscriber starts a call in the 2G
10 network and changes to the 3G network.

With respect to the invention herein, the relevant handover process is the inter BSC intra MSC (the BSC is changed, and both BSC nodes are controlled by the one MSC).

Not shown (but still possible) is inter BSC inter MSC HO. In this case BSC and
15 MSC are changed. Not shown but still possible is the inter system handover where the target system is a GSM system. The source system can be any technology for example WCDMA or LTE.

With reference to figures 5 and 6, the following are the steps for Assignment.

- 20 1. MSC detects a condition to perform call setup.
2. MSC seizes a TDM termination to be used in case BSC selects the TDM bearer for the A-interface user plane connection later. In the ADD Request MSC specifies the TDM termination identifier to be seized (not shown). The TDM termination identifier can be mapped uniquely to the CIC used in this call.
- 25 3. MGw replies on the ADD Request.
4. MSC seizes an IP termination to be used in case BSC selects the IP bearer for the A-interface user plane connection later.
5. MGw replies on the ADD Request.
6. MSC sends BSSMAP Assignment Request message to trigger the
30 channel assignment in the target BSC. MSC provides the CIC and the AoIP Container, where one of them is to be used for the call.

-13-

7. BSC establishes the radio channel. Further BSC selects the bearer to be used on the A-interface user plane connection. In this example (figure 5) BSC decided to use the TDM bearer.

8. BSC sends Assignment Complete message back to MSC as specified in standard.

9. From the received Assignment Complete message MSC deducts that TDM bearer (see figure 5). shall be used on A-interface user plane connection. MSC requests MGW to remove the previously seized IP termination (step 4)

10. MGW confirms the SUB Request.

The present invention includes, but is not limited to, the following inventive steps:

- MSC detects BSS capability to support IP on the terrestrial interface
- MSC seizes a TDM and IP bearer before it request channel assignment from the target BSC
- MSC releases unused resources after BSC selected a bearer and informed MSC about the decision

The invention has the following advantages:

- MSC automatically detects if BSC is capable to support IP bearer for the terrestrial interface
- The BSSMAP message defined for the 3GPP handover procedure and assignment procedure can be reused.
- BSC has full freedom to select the bearer for the terrestrial interface.
- No configuration in MSC or BSC is required

-14-

- The procedure is only applicable for the case that AoIP and AoTDM are used in parallel. The procedure can be removed and does not have any additional impact in case BSC supports on AoIP (proposed target solution for future networks).

5

- The procedure supports CIC selection in MSC and CIC selection in BSC (for AoTDM)

Abbreviations

10

(W)iDEN	(Wideband) Integrated Digital Enhanced Network
3GPP	3 rd generation Partnership Project
AoIP	A-Interface (user plane) over IP
AoTDM	A-Interface (user plane) over TDM
BSC	Base Station Controller
BSS	Base Station Subsystem
BSSMAP	Base Station System Management Application Part
CIC	Circuit Identity Code
GSM	Global System for Mobile communications
HO	Handover
iDEN	Integrated Digital Enhanced Network
IP	Internet Protocol
LTE	Long Term Evolution
MGw	Media Gateway
MSC	Mobile Switching Center
MSC-S	Mobile Switching Center Server
TDM	Time-division Multiplexing
WCDMA	Wideband Code Division Multiple Access

Although the invention has been described in detail in the foregoing embodiments for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that variations can be made therein by those skilled in the art

-15-

without departing from the spirit and scope of the invention except as it may be described by the following claims.

-16-

CLAIMS:

1. A method for using a network entity of a radio communication network comprising the steps of:
seizing a first resource and a second resource for a terrestrial interface of the
5 network, where the first resource is distinct and different from the second resource; and
sending a handover request message identifying the first resource and the
second resource.
2. The method as described in claim 1 including the step of receiving an
10 acknowledgment of the handover.
3. The method as described in claim 2 including the step of detecting that
one of the first and second resources is selected for a bearer.
- 15 4. The method as described in claim 3 including the step of releasing an
unselected one of the first and second resources.
5. The method as described in claim 4 wherein the sending step includes
the step of sending the handover request message with a circuit identifier code of a
20 selected time division multiplexing (TDM) circuit with respect to a TDM bearer, and
with a transport address of a media gateway (MGw) that will terminate an internet
protocol (IP) connection with respect to an IP bearer.
6. A network entity for a radio communication network comprising:
25 a processing unit which causes a first resource and a second resource for a
terrestrial interface of the radio network to be seized, where the first resource is distinct
and different from the second resource; and
a network interface through which a handover request message identifying the
first and the second resource is sent.
30
7. The apparatus as described in claim 6 wherein the network interface
receives an acknowledgment of the handover.

-17-

8. The apparatus as described in claim 7 wherein the processing unit detects that one of the first and second resources is selected for a bearer.

9. The apparatus as described in claim 8 wherein the processing unit causes
5 an unselected one of the first and second resources to be released.

10. The apparatus as described in claim 9 wherein the network interface sends the handover request message with a circuit identifier code of a selected time division multiplexing (TDM) circuit with respect to a TDM bearer, and with a transport
10 address of a media gateway (MGw) that will terminate an internet protocol (IP) connection with respect to an IP bearer.

11. A method for using a network entity of a radio communication network comprising the steps of:
15 seizing a first resource and a second resource for a terrestrial interface of the network, where the first resource is distinct and different from the second resource; and
sending an assignment request message identifying the first resource and the second resource.

20 12. The method as described in claim 11 including the step of receiving an assignment complete message that indicates a bearer shall be used on an A-interface user plane connection.

13. A network entity for a radio communication network comprising:
25 a processing unit which causes a first resource and a second resource for a terrestrial interface of the radio network to be seized, where the first resource is distinct and different from the second resource; and
a network interface through which an assignment request message identifying the first and the second resource is sent.

30

-18-

14. A network entity for a radio communication network comprising:
a network interface which receives a handover request message identifying a first resource and a second resource, the first resource distinct and different from the second resource; and
5 a processing unit that selects one of the first and second resources, allocates a radio channel associated with the handover, selects a bearer for a terrestrial interface and seizes resources for the interface.
15. The entity as described in claim 14 wherein the network interface sends
10 an acknowledgment of the handover request.
16. The entity as described in claim 15 wherein the acknowledgment request includes information that identifies which bearer is used on the terrestrial interface.
- 15 17. The entity as described in claim 16 wherein the handover request message is a base station system management application part (BSSMAP) handover request with a circuit identifier code of a selected time division multiplexing (TDM) circuit with respect to a TDM bearer, and with a transport address of a media gateway (MGw) that will terminate an IP connection with respect to an internet protocol (IP)
20 bearer.
18. A method for a network entity of a radio communication network comprising the steps of:
receiving a handover request message identifying a first resource and a second
25 resource, the first resource distinct and different from the second resource;
selecting one of the first and second resources;
allocating a radio channel associated with the handover;
selecting a bearer for a terrestrial interface; and
seizing resources for the interface.
30
19. The method as described in claim 18 including the step of sending an acknowledgment of the handover request.

-19-

20. The method as described in claim 19 wherein the acknowledgment includes information that identifies which bearer is used on the terrestrial interface.

21. The method as described in claim 20 wherein the receiving step includes
5 the step of receiving a base station system management application part (BSSMAP) handover request with a circuit identifier code of a selected time division multiplexing (TDM) circuit with respect to a TDM bearer, and with a transport address of a media gateway (MGW) that will terminate an IP connection with respect to an internet protocol (IP) bearer.

10

22. A network entity for a radio communication network comprising:
a network interface which receives an assignment request message identifying a first resource and a second resource, the first resource distinct and different from the second resource; and
15 a processing unit that selects one of the first and second resources, allocates a radio channel associated with the assignment, selects a bearer for a terrestrial interface and seizes resources for the interface.

23. A method for a network entity of a radio communication network
20 comprising the steps of:

receiving an assignment request message identifying a first resource and a second resource, the first resource distinct and different from the second resource;
selecting one of the first and second resources;
allocating a radio channel associated with the assignment;
25 selecting a bearer for a terrestrial interface; and
seizing resources for the interface.

24. The method as described in claim 23 including the step of selecting the bearer to be used on an A-interface user plane connection.

30

25. The method as described in claim 24 including the step of sending an assignment complete message indicating the selected bearer.