

Description

This invention relates generally to the field of optical scanning or reading and specifically to the structure of an optical system that is particularly suitable for use in hand-held probe for scanning bar codes.

6 The use of bar codes to provide information on product prices, identity, and inventory levels is a well-established practice in retail businesses and elsewhere because bar codes are convenient, inexpensive, and lend themselves well to semi or full automation reading techniques.

In bar codes, information is stored as alternating dark and light stripes, the width and spacing of which are used as a means of encoding. When properly illuminated with a small enough beam of light, they return
10 a modulated reflected beam of light which, if sufficiently intense, can be detected and converted to electrical form for decoding purposes. Usually, the bar code is scanned with a beam of illumination and the reflected beam simultaneously detected with an optical system of sufficient resolution. During scanning, the bar code is moved relative to the detection system, and relative motion is achieved by either moving the coded product relative to a fixed scanning head, most often seen in a supermarket, or by moving a hand-
15 held probe over the code on the product, more often seen in lower volume retail situations.

The performance of hand-held probes should be reasonably insensitive to their rotational and angular attitudes and, as well, to their proximity to a bar code because such positional variations are to be expected in hand operations. In addition, signal strength, resolution, noise level, and ease and cost of fabrication are important considerations in the design and manufacture of scanners, whether hand-held or fixed types.

20 Prior art hand-held probe devices have included fiber optic illumination systems along with a lens system that is structured to focus reflected light onto a sensing module as shown, for example, in U.S. Patent No. 3,916,184 issued to Thomas W. Turner on October 28, 1975 and entitled "Optical Scanner in Modular Form". In U.S. Patent No. 3,784,794 issued to David C. Allais on January 8, 1974 and entitled "Electro-Optical Reader for Bar Codes or the Like", a hand-held probe is disclosed which utilizes as an
25 optical system, for both the illumination and detection of reflected light from the bar code, a spherical lens on the rear surface of which is positioned either one or more detectors.

A dual focusing system for use in hand-held bar code probe is disclosed in U.S. Patent No. 4,143,809 issued to John J. Uebbing et al on March 13, 1979 and entitled "Optical Bar Code Reader". Here, a pair of discrete lenses are integrally molded aside of one another as part of a support with their optical axes
30 intersecting at a predetermined acute angle. The surfaces of the lenses are in the form of hyperbolic sections that are selectively shaped to eliminate spherical aberration.

In spite of the many innovations made in this art, improved hand-held bar code probes are still required and can be usefully employed for a variety of purposes. In particular, optical systems are required for use in hand-held probes to provide signals of high strength and low noise while at the same time being able to
35 resolve to levels required in a variety of positions and spacings from the bar code. Furthermore, ease and efficiency of manufacture and the use of simple structures are important considerations in the design of bar code scanners. Accordingly, it is the primary object of the present invention to provide an optical scanner for use for example in a hand-held bar code probe having the above beneficial characteristics and which overcomes the problems of US-A-4143809.

40 In accordance with the present invention, an optical scanner comprises a light source; a detector and lens means; the detector and light source being on the same side of the lens means; and the lens means having first and second opposed surfaces structured and arranged to distribute light from the source incident on the first opposed surface as a beam of illumination emerging from the second opposed surface, characterised in that one of the first and second surfaces is shaped to have overcorrected spherical
45 aberration whereby the beam of illumination is focussed over a range of focus by the opposed surfaces, the intensity of the beam being substantially uniform over an area including an image of the detector and throughout the range of focus.

This invention relates generally to the field of optical scanning and is for controlling light from a source and is suitable to provide a beam of light for reflection from a bar code located within a detector working
50 distance from the scanner to generate a modulated light beam for decoding purposes. The invention specifically relates to the structure of an optical element that is particularly suitable for use in a hand-held probe to conduct light to and from bar codes as they are scanned for their information content. The optical element or lens means may be integrally formed as a single piece fabricated of optical plastic by injection moulding.

55 The preferred form of the element has just three surfaces, two of which form a first coacting pair that are structured to jointly redistribute light from an offset divergent source as a beam of illumination having a uniform intensity over a detector image throughout a range of focus of the coacting pair corresponding to a predetermined working distance for the probe. This assures minimum signal strength when reading bar

codes anywhere in the working distance. To assist in accomplishing this, one of the pair of coating surfaces may be provided with a shape having overcorrected spherical aberration. A third surface, prismatic and converging or diverging as required, cooperates with part of one of the first coating pair of surfaces to collect and direct light reflected from a bar code anywhere in the working distance onto an offset photodetector located behind the element on the same side as the source and preferably in the same plane.

Other embodiments of the invention include four surfaces instead of three and some operate with source and detector located in tandem along a central axis instead of offset with respect to the central axis as in the preferred case. All embodiments, however, are rotationally symmetric and relatively insensitive to axial proximity and angular attitude to the bar code during scanning.

Some examples of hand-held probes including optical scanners according to the present invention will now be described with reference to the accompanying drawings, in which:-

Figure 1 is a diagrammatic perspective view of a first example of a hand-held probe;

Figure 2 is an enlarged cross-sectional view of the probe of Figure 1 taken generally along the line 2-2 of Figure 1;

Figure 3 is a section similar to Figure 2 and illustrates an alternative embodiment of the invention;

Figure 4 is a view similar to Figure 2 and illustrates yet another embodiment of the invention; and

Figure 5 is also similar to Figure 2, illustrating still another embodiment of the invention.

In Fig. 1, there is shown generally at 10 a probe or reader that is representative of the type with which the present invention is particularly suitable for use. As seen, probe 10 comprises a slender elongate housing 14 which has conical tapers at both ends. The top conical end terminates in a cable 17 that leads to a cash register or the like to which information from probe 10 is transmitted for further use. Probe 10 is pencil like in scale and, as such, is operated by manually passing its other conical end over a bar code, such as that designated at 12, to "read" the bar code. Consequently, the angular attitude of probe 10 with respect to the bar code 12 can be made to vary in three azimuths, i.e., pitch, roll and yaw as indicated in Fig. 1 by the curved double-headed arrows, where pitch is about the Z-axis, roll about the X-axis, and rotation about the Y-axis. In addition, the separation of the bottom conical end of probe 10 from the bar code 12 can also vary in the Y direction as well in the X and Z plane. Because of this inevitable variation in motion due to hand-held operation, it is important that the performance of such probes be relatively insensitive to expected positional changes. That is, the output of the probe 10 shouldn't, within reasonable limits, change as a function of the angular attitude or proximity of the probe to a bar code 12. In practical terms, this means that probe 10 must provide a minimum signal strength with adequate signal-to-noise ratio for pitch and roll angles over some reasonable range from, say 0 to approximately 50°, and this performance should not change with rotation of the probe 10 about the Y-axis or with displacement of the probe from the bar code 12 by some prescribed separation or working distance on the order of a few tenths of an inch or less.

The optical element of the invention satisfies these requirements with minimal structure easily fabricated using plastic injection molding techniques for high volume efficiency. To understand the present invention, reference is now made to Fig. 2 which is a section taken generally along line 2-2 of Fig. 1 and showing an optical element designated generally at 16, along with other components which reside in the interior of the probe body 14. The lower conical end of the probe body 14 terminates in an aperture 15 which may conveniently be closed over with a transparent dust cover to keep foreign matter out of the interior of the probe body 14. It is the general purpose of the optical element 16 to conduct light in a controllable way to and from the bar code 12 by way of the aperture 15. In doing so, the optical element 16 facilitates providing a beam of light for reflection from a nearby bar code to generate a modulated light beam and conducts the modulated light beam to a small photodetector for decoding purposes.

To perform its functions, the optical element 16 has a rear surface 18 which is aspheric and preferably hyperboloidal. The rear surface 18, as can be seen in Fig. 2, is rotationally symmetric about an axis, OA_0 , with in turn is offset by a distance, X_0 , with respect to the central axis of the probe 10, OA_c , coincident with the Y-axis. Consequently, the rear surface 18 is known as a decentered surface and thus has a well-known prism effect.

Facing rear surface 18 is a front surface 20 which is also aspheric, preferably strongly hyperboloidal in form. Front surface 20 is of stronger curvature, and therefore of stronger power than the rear surface 18 and is rotationally symmetric about the optical axis, OA_c .

In the center of the rear surface 18, there is a slight depression in which is found another surface, the third surface of the optical element 16, and this surface is designated generally at 22. As can be seen, the surface 22 is of diameter, X_r , is preferably rotationally symmetric and, although shown as a convex surface, may also be concave if required, and could conveniently be the same shape as that of the surface 18.

Surface 22 is superimposed on a prism that is at an angle, θ , with respect to the optical axis, OA_c .

Behind the optical element 16, there is an electronic subassembly 27 which includes a source of illumination 24 and a photodetector 28 along with its associated electronics 30, both of which are mounted on a board preferably perpendicular to the optical axis OA_c and each of which is aligned with an axis that is offset with respect to the optical axis OA_c .

The source 24 comprises an active radiation emitting area 23 over which is positioned a hemispherical lens 25 which accepts radiation from the active area 23 and generally converges it as indicated with the arrowed rays shown in Fig. 2. The central axis of the hemisphere 25 is preferably on the offset optical axis, OA_c , and therefore is centered with respect to the rear surface 18. The operational wavelength of the light source 24 is within the range including the visible as well as the IR portion of the spectrum and the overall integrated output intensity of the source 24 may be as high as several milliwatts.

Considering light travelling from the source 24 to the bar code 12, top to bottom in Fig. 2, it first encounters the rear surface 18 and, because of the shape of this surface, gets collimated, i.e., afterwards travels parallel within the optical element 16. As seen, the collimated bundle of rays provided by the rear surface 18, as well as travelling parallel to one another, also travel parallel to the optical axis, OA_c . Afterwards, this collimated light is refracted by the front surface 20 so that rays which are near the optical axis, OA_c , are focused on-axis near the center of the aperture 15 as designated generally by the point 32. Light rays further off of the optical axis, OA_c , are progressively focused further below the focus location for the near axial rays as shown, for example, at the focus points 34 and 36 for those rays displaced further off the optical axis, OA_c . Notice that, after rays are converged on-axis, they diverge beyond their focus points (32, 34 and 36) to become available downstream of their respective focus points as light useful for illuminating off-axis downstream points. Consequently, sections through the beam of illumination, taken perpendicular to the optical axis, within some working depth, say d_w , reveal a pattern, circular in overall shape, in which light intensity is more or less of one level because of the way in which the illumination from the source 24 is redistributed by the optical element 16. In addition, the illumination is also uniform over each circular section, which are generally not of the same size, but are made to coincide, or nearly so, with the detector image over the working distance as will be appreciated. This control of illumination in depth is brought about by the shape of the front surface 20 which, in its preferred form, is strongly hyperboloidal and of greater eccentricity than that of the rear surface 18. The shape of surface 20 is chosen so that it intentionally contributes overcorrected spherical aberration that produces the desired constant illumination level with depth, a property which allows one to have a constant signal strength wherever the bar code 12 is located within this distance, preferably about 0.15 inch.

The fact that the mechanical axis of the probe 10 and the optical axis, OA_c , of the front surface 20 are coincident is an important feature because this makes the system rotationally symmetric and therefore, the bar code 12 can be decoded the same regardless of the rotational attitude of the probe 10. This rotational symmetry is possible because the rear surface 18 collimates and has its axis of symmetry decentered with respect to the optical axis, OA_c . This, in turn, allows the light source 24 to be physically displaced to one side of the optical axis, OA_c .

For light travelling in the other direction, that is, bottom to top in Fig. 2, in the direction of light reflected from the bar code 12, such light is first collimated by the front surface 20 and can be considered to be composed of two segments, the first hitting the wedged surface 22 in the rear surface 18 and the second what goes on to hit the rear surface 18.

The first segment of this light, which is a light within the extreme bundle of rays intercepted by the diameter, x_r , is bent by the wedge surface 22 and afterwards, because of the net power of the surface 22 coacting with part of the front surface 20, is converged so that it passes through the aperture 26 located forward of the photodetector 28. This light is converted to electrical form by the photodetector 28 for decoding in a known manner by the electronics 30.

It will be understood that the image of the photodetector 28, as seen through the aperture 26, from the vantage of the bar code 12 has to be small enough to fit between alternate black and white pairs of the code 12 to be able to know when a black/white boundary has been crossed. If these conditions were not satisfied and the bar code 12 were fine enough, i.e., of high spatial frequency, the output would be relatively level since everything would look gray, the average of black and white, and therefore there would be no modulation present.

The final area of the photodetector image is preferably centered within the working distance, d_w , by placing the paraxial image midway, but the paraxial image can be placed at any other reasonable location throughout the working distance, d_w . It will be understood that wherever the photodetector paraxial image is, the photodetector image size on either side of this location will be larger due to defocus so that there exists some core, either converging or diverging, depending on the perspective in which the detector image

resides.

Because the photodetector image size in general changes throughout the working distance, one might think that the signal strength also changes. However, this is not the case because the illumination over the photodetector image throughout the working distance, d_w , is uniform and more or less of equal intensity.

5 Because of this property and the fact that the f-number to the photodetector 28 remains constant with defocus, the signal strength also remains constant or reasonably so.

An example of an optical element which has been found suitable for use in a bar code probe of about 3/10 of an inch (0.75cm) in diameter is the following. The rear surface 18 and the front surface 20 are both described by the general formula:

$$Y = \frac{CS^2}{1 + \sqrt{1 - (1+K)C^2S^2}} + \beta S^4 + \gamma S^6 + \delta S^8 + \epsilon S^{10}$$

15 where C is the reciprocal of the surface apex radius, K the conic constant, Y the distance of a point measured from the surface vertex and parallel to the Y-axis, taken to be the surface's optical axis, and S is the radial distance of the point measured perpendicular to the Y-axis and wherein the coefficients β through ϵ , are given in the following table:

Surface	18	20
C	5.683	16.0
K	-2.22	2.67
β	0.0	1.3
γ	0.0	56.0
δ	0.0	2.5×10^3
ϵ	0.0	1.1×10^5

For these values, the distance from the aperture 15 to the apex of the front surface 20 was 1.4 inches (3.56cm) and the separation between the apex of front surface 20 and the rear surface, measured along the optical axis, OA_o , was 0.3 inch (0.76cm) with the diameter of the element being approximately 0.32 inch.

40 The material was Plexiglas.

With this example, tests have indicated that as probe 10 is brought in towards the bar code from the working distance of 0.15 inch (0.38), the output signal does not vary from nominal by more than $\pm 15\%$ up to the point of contact with the bar code, and the output level is independent of the probe angle of rotation and does not vary over all operational angles or distances from the bar code by more than a factor of 2 to 1 for angles within the range from 0 to 40° . The distance to the offset axis, OA_o , i.e. X_o , was approximately 0.1 inch (0.25 cm) and slightly less on the photodetector offset. The paraxial image size of the photodetector was 0.0006 inch (0.0015cm) midway along the working distance the the f-number of the photodetection system was f/6.0 while that of the illumination system was f/0.6. Spatial frequencies of 0.357 line pairs/mm were easily resolved. It will be realized by those skilled in the art that for optimum resolution, the detector image size throughout the working distance, d_w , should be no more than one-half of the highest expected bar code frequency.

In Fig. 3 is shown an alternate embodiment for the optical element of the invention, and this embodiment is designated generally at 42. The element 42 in principle functions the same as the previous element 16, but differs in surface detail comprising a new rear surface 40 and a different front surface 44. Also, there is included in a depressed region in the rear surface 40 a rearwardly facing surface 48. All of the other parts shown in Fig. 3 retain the same numerical identification they had in Fig. 2 with the exception of the points of convergence which are now designated at 50, 52 and 54 because they may slightly differ from those shown previously.

The front surface 44 instead of being hyperboloidal as before, is now comprised of two intersecting sections, one of which is a straight conical section designated generally at 45 and the other of which is an aspheric section joined to the conical section 45 and designated generally at 46. Thus, the surface 44, while continuous, is comprised of two intersecting parts having different geometries. Because the surface 44 is different than previously, the surface 40, while still hyperboloidal will have slightly different characteristics than its correspondent before in order to collimate the bundle of diverging rays from the source 24.

A major difference between this element and the previous element is that in this element, the collecting system no longer uses part of the front surface to return light to the photodetector 28, but now rather is formed of a cooperative pair which includes the front surface segment 46 and the rear wedge segment 48. The wedge segment 48 is in shape aspheric and either positive or negative as required. In addition, the surface 48 is provided with a prismatic effect by virtue of its overall angular orientation with respect to the optical axis OA_c . This prismatic effect is responsible for diverting the bundle of rays emerging from the surface 48 through an angle, θ , appropriate to direct light to enter the aperture 26.

Again, the front surface conical segment 45 operates to provide overcorrected spherical aberration so that the energy from the source 24 is redistributed to provide a beam which is uniform over the image of the photodetector throughout the working distance, d_w .

In Fig. 4, there is shown yet another embodiment of the invention, and this optical element is designated generally at 60. In this figure, however, the light source, which is designated at 68, and the photodetector, which is designated at 82, are located in tandem, one behind the other, along the optical axis, OA_c . Again, the light source 68 is preferably an LED having an active area 72 from which radiation emanates and is thereafter converged by use of a hemispherical lens 70 which sits registered on top of the area 72. Diverging rays from the light source 68 are converged in a well-known manner through the use of a converging lens 76 which is structured to collimate or provide a collimated beam of radiation emerging from the element 76. This collimated beam of radiation emerging from the optical element 76 strikes the rear surface of the optical element 60 which is plano and generally designated at 62. Therefore, since the plano surface 62 does not deviate the collimated bundle of radiation, it continues on through the optical element 60 in a collimated state. Afterwards, the collimated radiation travelling through the element 60 encounters front surface 64 which is again made hyperboloidal in shape to converge the collimated bundle of radiation travelling along the optical axis, OA_c , and redistribute it as a beam afflicted with overcorrected spherical aberration so that the intensity and surface coverage of the beam is uniform over the image of the photodetector throughout the working length, d_w .

At the center of the rear plano surface 62, there is provided a converging surface 66 which cooperates with part of the front surface 64 having a diameter designated again by X_r to converge the reflected beam of radiation from the bar code 12 through an aperture 80. Afterwards, the beam strikes the photodetector 82 to provide an appropriate modulated signal for decoding. The major difference between this embodiment and those previously discussed is that in this embodiment the source and detector are located on-axis and tandemly spaced from one another and the optical element 60 operates on a collimated beam of radiation which is provided by an upstream optical element 76, rather than on a diverging source of radiation emanating directly from the light source 68. Consequently, the rear surface of the optical element 60 is not provided with any power to provide a collimated beam since this has already been done previously. Otherwise, the performance of this system is similar to that of those previously discussed, particularly with respect to rotational symmetry and consistency of signal output with changes in positional attitude.

Fig. 5 shows yet another embodiment of the optical element of the invention and here it is designated generally at 84. The optical element 84 is most similar to the optical element previously discussed at 60 in Fig. 4, differing only in the details of its front and rear surface with all other components shown in Fig. 4, retaining their same numerical designations in Fig. 5.

The optical element 84 again includes a planar rear surface 86 having a convex aspheric surface 92 centered with the optical axis, OA_c . The front surface of the element 84 consists of two segments of different power, one of which is an outer segment 88 that is aspheric and the other of which is an aspheric segment 90 centered on the optical axis, OA_c . Surface 88 as before is structured to introduce overcorrected spherical aberration into the collimated beam to distribute it in intensity in the manner required, and the surfaces 90 and 92 cooperate to collect and direct the reflected beam to the aperture 80 after which it proceeds to the photodetector 82 as before. The major difference between this embodiment and that of Fig. 4 is that here two surfaces are used to collect and direct radiation from the reflected beam onto the photodetector of the system.

Claims



1. An optical scanner comprising a light source (23) a detector (28) and lens means; the detector (28) and light source (23) being on the same side of the lens means; and the lens means (16) having first and second opposed surfaces (18,20) structured and arranged to distribute light from the source incident on the first opposed surface (18) as a beam of illumination emerging from the second opposed surface (20), characterised in that one of the first and second surfaces is shaped to have overcorrected spherical aberration whereby the beam of illumination is focussed over a range of focus by the opposed surfaces, the intensity of the beam being substantially uniform over an area including an image of the detector (28) and throughout the range of focus.
2. A scanner according to claim 1, wherein at least one of the first and second surfaces (18, 20) includes a third surface (22) to collect and direct light reflected from a surface within the range of focus towards the detector (28).
3. A scanner according to claim 1 or claim 2, wherein the lens means (16) is fabricated as a single piece of optical plastic.
4. An optical scanner according to any of the preceding claims, wherein the first opposed surface (18) is structured to collimate light incident thereon.
5. An optical scanner according to any of the preceding claims, wherein at least portions of one of the first and second opposed surfaces (18,20) is hyperboloidal in form.
6. An optical scanner according to any of the preceding claims, wherein the first opposed surface (18) is decentered with respect to the second opposed surface (20).
7. An optical scanner according to any of the preceding claims, wherein one or both of the first and second opposed surfaces (18,20) is aspheric in form.
8. An optical scanner according to any of the preceding claims, wherein the range of focus thereof is substantially 3.8mm.
9. An optical scanner according to any of the preceding claims, wherein the f/number thereof is substantially 0.6.
10. A probe comprising a cylindrical, tubular housing (14) supporting within it an optical scanner (10) according to any of the preceding claims, the optical axis (OA_c) of the lens means (16) being substantially coincident with the axis (Y) of the housing.

Revendications

1. Lecteur optique comprenant une source (23) de lumière, un détecteur (28) et un moyen formant lentille, le détecteur (28) et la source (23) de lumière étant du même côté du moyen formant lentille, et le moyen formant lentille (16) ayant une première et une seconde surfaces opposées (18, 20) dont la structure et l'agencement permettent que la lumière issue de la source et incidente sur la première surface opposée (18) soit transmise sous la forme d'un faisceau d'éclairage sortant de la seconde surface opposée (20), caractérisé en ce qu'une des première et seconde surfaces a une forme servant à avoir une aberration sphérique surcorrigée, grâce à quoi le faisceau d'éclairage est focalisé sur une plage de focalisation par les surfaces opposées, l'intensité du faisceau étant sensiblement uniforme sur une zone contenant une image du détecteur (28) et sur toute la plage de focalisation.
2. Lecteur selon la revendication 1, dans lequel au moins une des première et seconde surfaces (18, 20) comprend une troisième surface (22) pour recueillir et diriger vers le détecteur (28) la lumière réfléchie depuis une surface située sur la plage de focalisation.
3. Lecteur selon la revendication 1 ou la revendication 2, dans lequel le moyen formant lentille (16) est fabriqué d'une seule pièce en matière plastique de qualité optique.
4. Lecteur optique selon l'une quelconque des revendications précédentes, dans lequel la première



surface opposée (18) a une structure permettant de collimater la lumière incidente sur celle-ci.

- 5 5. Lecteur optique selon l'une quelconque des revendications précédentes, dans lequel au moins des parties de l'une des première et seconde surfaces opposées (18, 20) est en forme d'hyperboloïde.
6. Lecteur optique selon l'une quelconque des revendications précédentes, dans lequel la première surface opposée (18) est décentrée par rapport à la seconde surface opposée (20).
7. Lecteur optique selon l'une quelconque des revendications précédentes, dans lequel au moins l'une
10 des première et seconde surfaces opposées (18, 20) a une forme asphérique.
8. Lecteur optique selon l'une quelconque des revendications précédentes, dans lequel la plage de focalisation de celui-ci est de l'ordre de 3,8 mm.
- 15 9. Lecteur optique selon l'une quelconque des revendications précédentes, dans lequel la valeur de diaphragme de celui-ci est de l'ordre de 0,6.
10. Capteur comprenant un corps cylindrique tubulaire (14) supportant intérieurement un lecteur optique (10) selon l'une quelconque des revendications précédentes, l'axe optique (OA_c) du moyen formant
20 lentille (16) coïncidant sensiblement avec l'axe (Y) du corps.

Patentansprüche

- 25 1. Optischer Abtaster mit einer Lichtquelle (23), einem Detektor (28) und einer Linsenordnung; der Detektor (28) und die Lichtquelle (23) liegen auf der gleichen Seite der Linsenordnung; die Linsenordnung (16) besitzt eine erste und eine gegenüberliegende zweite Oberfläche (18, 20), die so ausgebildet und angeordnet sind, daß das von der Quelle auf die erste der gegenüberliegenden Oberflächen (18) einfallende Licht als Beleuchtungsstrahl verteilt wird, der aus der zweiten gegenüberliegenden Oberfläche (20) austritt, dadurch gekennzeichnet, daß eine der ersten und zweiten Oberflächen
30 so gestaltet ist, daß sie eine überkorrigierte sphärische Abberation liefert, wodurch der Beleuchtungsstrahl über einen Fokussierungsbereich durch die gegenüberliegenden Oberflächen fokussiert wird, wobei die Intensität des Strahles im wesentlichen gleichförmig über einen Bereich ist, der ein Bild des Detektors (28) und den Fokussierungsbereich einschließt.
- 35 2. Abtaster nach Anspruch 1, bei welcher wenigstens eine der ersten und zweiten Oberflächen (18, 20) eine dritte Oberfläche (22) aufweist, um das Licht, welches von einer Oberfläche innerhalb des Fokussierungsbereichs nach dem Detektor (28) reflektiert wird, zu sammeln und zu richten.
- 40 3. Abtaster nach den Ansprüchen 1 oder 2, bei welcher die Linsenordnung (16) einstückig aus optischem Plastikmaterial hergestellt ist.
4. Optischer Abtaster nach einem der vorhergehenden Ansprüche, bei welcher die erste gegenüberliegende Oberfläche (18) so strukturiert ist, daß das darauf auftreffende Licht parallelisiert wird.
- 45 5. Optischer Abtaster nach einem der vorhergehenden Ansprüche, bei welchem wenigstens Abschnitte der ersten und zweiten gegenüberliegenden Oberflächen (18, 20) von hyperboloidaler Form sind.
6. Optischer Abtaster nach einem der vorhergehenden Ansprüche, bei welchem die erste gegenüberliegende Oberfläche (18) gegenüber der zweiten gegenüberliegenden Oberfläche (20) außermittig angeordnet ist.
50
7. Optischer Abtaster nach einem der vorhergehenden Ansprüche, bei welchem eine oder beide der ersten und zweiten gegenüberliegenden Oberflächen (18, 20) eine asphärische Gestalt haben.
- 55 8. Optischer Abtaster nach einem der vorhergehenden Ansprüche, bei welchem der Fokussierungsbereich etwa 3,8 mm beträgt.
9. Optischer Abtaster nach einem der vorhergehenden Ansprüche, bei welchem die f/Zahl etwa 0,6



beträgt.

10. Sonde mit einem zylindrischen rohrförmigen Gehäuse (14), das im Inneren einen optischen Abtaster (10) nach einem der vorherigen Ansprüche aufweist, wobei die optische Achse (OA_c) der Linsenanordnung im wesentlichen mit der Achse (Y) des Gehäuses zusammenfällt.

10

15

20

25

30

35

40

45

50

55