SYSTEM AND METHOD FOR COMPUTING PRIVATE KEYS FOR SELF CERTIFIED IDENTITY BASED SIGNATURE SCHEMES

Field of the Invention

This invention relates to a system and method for generating private keys for devices participating in self-certified identity based signature schemes whereby the private keys are used by the devices to establish a common session key for encoding digital communications between devices. In particular, the private keys generated in accordance with the system and methods of the invention are only made known to the devices themselves and not by any other third parties.

Summary of the Prior Art

Due to a convergence of multiple technologies, an ever increasing number of devices are now able to seamlessly communicate wirelessly with the Internet or wirelessly exchange communications between themselves. This convergence has resulted in the vision of the Internet of Things (IoT) gaining more traction through recent years. In the Internet of Things, millions of entities or devices (i.e. Things) will be connected to one another. These devices, which comprise devices or entities such as smart chips, smart plugs, smart watches, smart phones, smart vehicles, smart buildings, and etc., either communicate directly with one another or via the Internet.

As the Internet of Things spreads into more areas, these devices become more prone to cyber-attacks from hackers or unauthorized users as a compromised device would grant a malicious user access to the network to which the device belongs. Hence, it is of utmost importance that a security protocol be set in place to allow one entity to verify the authenticity of a peer entity, with which it communicates with, before data is exchanged between these two entities. In addition to the above, once the authenticity of the entities have been verified, a secret key known to only these two entities, has to be established to facilitate the signing of data messages between these entities. This is to ensure that data communicated between these two entities will not be compromised even if the data were intercepted or redirected.

A common method of establishing a secret key for signing data communications between entities involves the pre-sharing of a common symmetric secret key between the relevant parties. For such a method, data messages that are to be transmitted between the entities will be signed using this pre-shared or pre-agreed-upon secret key. If the receiving entity is able to decrypt the received message using this pre-shared secret key, this implies

that the authenticity of the sender has been verified and the receiver may then proceed to process the decrypted message accordingly. Unfortunately, this method is not scalable and is quite inflexible as it requires the common secret to be pre-shared or communicated to all trusted entities or devices before the entities or devices may communicate with one another. In the IoT setting, the high mobility of devices is a norm and devices that are required to exchange data with one another may not have had the opportunity to establish a secret key beforehand.

Another approach that has been proposed utilizes public key infrastructure (PKI) based solutions whereby key-pairs allocated to each authorized entity are bound to its holders by means of a public key certificate. The key pair then utilizes a public key cryptosystem such as public-key encryption or digital signature methodologies to sign data messages or to verify the authenticity of a sender by validating the public key certificate of the sender. The setup and maintenance of such public key infrastructures are notoriously expensive and require entities to constantly maintain contact with a PKI server to validate the respective public key certificates.

Yet another approach that has been proposed utilizes identity based cryptography methodologies to authenticate entities and to sign data messages. Such identity based cryptosystems are special public key cryptosystems, which are based on bilinear pairing and utilize an entity's identity, such as user name, email address, telephone number, IP address, etc. as the public key and a corresponding private key is then derived from the entity's identity by a Key Generation Centre which contains a master secret key, which is utilized in the generation of private keys for entities. The downside of this approach is that bilinear pairing is an expensive and time consuming computation process.

Another inherent weakness of existing identity based cryptographic schemes is that users' private keys are usually generated by a Key Generation Centre. As the users' private keys are escrowed to the key generation centre, this means that the key generation centre will possess all the private keys of the users of the scheme. If the key generation centre were ever to become compromised, this would mean that all the users of the system would be compromised as well.

For the above reasons, those skilled in the art are constantly striving to come up with a system and method to generate private keys for users of an identity based signature scheme whereby the private keys are only made known to each respective user. The private keys are then utilized with the identity based signature scheme to verify the authenticity of users of the scheme and to generate a common session key that is to be used to encode data messages between verified users.

Summary of the Invention

The above and other problems are solved and an advance in the art is made by systems and methods provided by embodiments in accordance with the invention.

A first advantage of embodiments of systems and methods in accordance with the invention is that the private keys of devices or entities belonging to the self-certified identity based signature scheme are made known only to the devices themselves and are not escrowed out to any external third parties such as a Key Generating Centre.

A second advantage of embodiments of systems and methods in accordance with the invention is that the private keys generated in accordance with embodiments of the invention are of the same form as in existing self-certified identity based signature schemes and thus may be used in existing self-certified identity based signature schemes without changing the operation of existing self-certified identity based signature schemes.

A third advantage of embodiments of systems and methods in accordance with the invention is that the invention allows cross-domain authenticated key exchange to take place whereby users' or entities' respective private keys may be issued by different key generation centres whereby each centre has its own unique system parameters.

A fourth advantage of embodiments of systems and methods in accordance with the invention is that the invention may be utilized in Transport Layer Security (TLS) or Datagram Transport Layer Security (DTLS) protocols whereby a self-certified identity based signature scheme in accordance with embodiments of the invention may be used to sign messages for TLS protocol or DTLS protocol.

The above advantages are provided by embodiments of a method in accordance with the invention operating in the following manner. For brevity, in the subsequent description of the embodiments of the invention, although multiplicative notations are utilized for finite field arithmetic operations; it should be straightforward for a person skilled in the art to realize that the arithmetic operations should be described using additive notations when implemented over elliptic curves.

According to a first aspect of the invention, a system for computing a private key sk for a device participating in a self-certified identity based signature system comprises a secure server configured to: compute parameters for the device based on a second random number r_{i2} generated by the secure server, a first set of components received from the device, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components comprises a first random number r_{i1} generated by the

device, transmit the computed parameters to the device; and the device configured to compute the private key sk based on the received computed parameters and the random number r_{i1}.

With reference to the first aspect, in accordance with embodiments of the invention, the step of computing the parameters for the device comprises: retrieving an arbitrary first value R_{i1} and an identity of the device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1}; computing an arbitrary value of the device R_i and a first integer s_{i1}; and setting the computed arbitrary value of the device R_i and the first integer s_{i1} as the parameters for the device, whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the device R_i, the identity of the device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the first aspect, in accordance with embodiments of the invention, the step of computing the private key sk comprises: computing an integer s_i based on the first integer s_{i1} as retrieved from the computed parameters transmitted from the secure server, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and forming the private key sk based on the arbitrary value of the device R_i and the integer s_i.

With reference to the first aspect, in accordance with embodiments of the invention, the arbitrary value of the device R_i is defined by $R_i = R_{i1} \cdot g^{r_{i2}}$ or $R_i = {R_{i1}}/{g^{r_{i2}}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$ and the first integer s_{i1} is defined by $s_{i1} = r_{i2} + xH(R_i, id_i)(mod\ q)$ or $s_{i1} = -r_{i2} + xH(R_i, id_i)(mod\ q)$ where *H*( ) is a collision-resistant hash function.

With reference to the first aspect, in accordance with embodiments of the invention, the integer s_i is defined by $s_i = s_{i1} + r_{i1}(mod\ q)$.

With reference to the first aspect, in accordance with embodiments of the invention, the arbitrary value of the device R_i is defined by $R_i = {g^{r_{i2}}}/{R_{i1}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$ and the first integer s_{i1} is defined by $s_{i1} = r_{i2} + xH(R_i, id_i)(mod\ q)$ where *H*( ) is a collision-resistant hash function.

With reference to the first aspect, in accordance with embodiments of the invention, the integer s_i is defined by $s_i = s_{i1} - r_{i1}(mod\ q)$.

With reference to the first aspect, in accordance with embodiments of the invention, the step of computing the parameters for the device comprises: retrieving an arbitrary first value R_{i1}, an identity of the device id_i and a homomorphic encryption value *c* from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1} and the homomorphic encryption value *c* is generated by providing the first random number r_{i1} and a prime number q obtained from the parameters associated with the master public key *mpk* to an additive homomorphic encryption function *HEnc( )*; setting an arbitrary value of the device R_i and a first integer s_{i1} as the parameters for the device, whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed by providing the second random number r_{i2}, the homomorphic encryption value *c*, the master secret key *x*, the arbitrary value of the device R_i, the identity of the device id_i and the prime number q to the additive homomorphic encryption function *HEnc( )*.

With reference to the first aspect, in accordance with embodiments of the invention, the step of computing the private key sk comprises: computing an integer s_i by applying a complementary homomorphic decryption function to the first integer s_{i1} as retrieved from the computed parameters transmitted from the secure server; and forming the private key sk based on the arbitrary value of the device R_i and the integer s_i.

With reference to the first aspect, in accordance with embodiments of the invention, the arbitrary value of the device R_i is defined by $R_i = (R_{i1})^{r_{i2}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$, the homomorphic encryption value c is defined by $c = HEnc({r_{i1}}^{-1}\ mod\ q)$ and the first integer s_{i1} is defined by $s_{i1} = HEnc(r_{i2}) \cdot c^{xH(R_i, id_i)\ mod\ q}$ where HEnc( ) is the additive homomorphic encryption function.

With reference to the first aspect, in accordance with embodiments of the invention, the arbitrary value of the device R_i is defined by $R_i = (R_{i1})^{{r_{i2}}^{-1}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$ the homomorphic encryption value c is defined by $c = HEnc({r_{i1}}^{-1})$ and the first integer s_{i1} is defined by $s_{i1} = HEnc({r_{i2}}^{-1}) \cdot c^{xH(R_i, id_i)\ mod\ q}$ where HEnc( ) is the additive homomorphic encryption function.

With reference to the first aspect, in accordance with embodiments of the invention, the integer s_i is defined by $s_i = r_{i1} HDec(s_{i1})$; where HDec( ) is the complementary homomorphic decryption function.

With reference to the first aspect, in accordance with embodiments of the invention, the arbitrary value of the device R_i is defined by $R_i = (R_{i1})^{r_{i2}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}^{-1}}$, the homomorphic encryption value c is defined by $c = HEnc(r_{i1})$ and the first integer s_{i1} is defined by $s_{i1} = HEnc(r_{i2}) \cdot c^{xH(R_i, id_i) \, mod \, q}$ where HEnc( ) is the additive homomorphic encryption function.

With reference to the first aspect, in accordance with embodiments of the invention, the integer s_i is defined by $s_i = r_{i1}^{-1} HDec(s_{i1})$ where HDec( ) is the complementary homomorphic decryption function.

According to a second aspect of the invention, a system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme is disclosed, the system comprising: a secure server configured to instruct: the first device to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and the second device to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server; the first device configured to: sign a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G; transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device; upon receiving the transmission, the second device is configured to: verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i, sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where *b* is a random number generated by the first device, when the signed group element g^a is verified, and transmit the signed group elements (g^a || g^b) and a group element g^b to the first device; the first device is configured to: verify the signed group elements (g^a ||

g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j; compute a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified; generate the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; transmit the first authentication data Ad_i to the second device, such that upon receiving the first authentication data Ad_i, the second device is configured to: compute a second shared secret k_{ji} based on the group element g^a and the group element *b*, compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function, compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function, determine if the second authentication data Ad_j matches with the first authentication data $Ad_{i;}$ and generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

With reference to the second aspect, in accordance with embodiments of the invention, the step of generating the first set of parameters for the first device comprises: the secure server being configured to: retrieve an arbitrary first value R_{i1} and an identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1}; compute an arbitrary value of the first device R_i and a first integer s_{i1}; and set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device, whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the second aspect, in accordance with embodiments of the invention, the computing the private key sk_i comprises: the first device being configured to: compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*.; and form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

With reference to the second aspect, in accordance with embodiments of the invention, the generating the second set of parameters for the second device comprises: the

secure server being configured to: retrieve an arbitrary first value R_{j1} and an identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1}; compute an arbitrary value of the second device R_j and a first integer s_{j1}; and set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device, whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key *x*, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the second aspect, in accordance with embodiments of the invention, the computing the private key sk_j comprises: the second device being configured to: compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

According to a third aspect of the invention, a system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* participating in a self-certified identity based signature scheme is provided, the system comprising: a secure server configured to instruct: the first device to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and the second device to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server;the first device configured to: sign a cryptographic nonce N_i using a self-certified Identity Based Signature Scheme and the private key sk_i; transmit an identity of the first device id_i, the cryptographic nonce N_i and the signed cryptographic nonce N_i to the second device; upon receiving the transmission, the second

device is configured to: verify the signed cryptographic nonce N_i using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i, sign cryptographic nonces (N_i || N_j) using the self-certified Identity Based Signature Scheme and the private key sk_j, where N_j is a cryptographic nonce, when the signed cryptographic nonce N_i is verified, and transmit the signed cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j to the first device; the first device is configured to: verify the signed cryptographic nonces (N_i || N_j) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j, compute a first shared secret $k_{ij} = g^{sj \cdot si}$, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the cryptographic nonces N_i and N_j and the first key vk_i to an Authentication Data Deriving Function, when the signed cryptographic nonces (N_i || N_j) are verified; generate the common session key SK by providing the first shared secret k_{ij} and the cryptographic nonces N_i and N_j to the Key Deriving Function; transmit the first authentication data Ad_i to the second device; upon receiving the first authentication data Ad_i, the second device is configured to: compute a second shared secret $k_{ji} = g^{sj \cdot si}$, compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function, compute a second authentication data Ad_j by providing the key vk_j and the cryptographic nonces N_i and N_j to the Authentication Data Deriving Function, determine if the second authentication data Ad_j matches with the first authentication data Ad_i ;and generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

With reference to the third aspect, in accordance with embodiments of the invention, the generating the first set of parameters for the first device comprises: the secure server being configured to: retrieve an arbitrary first value R_{i1} and an identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1}; compute an arbitrary value of the first device R_i and a first integer s_{i1}; and set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device, whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the third aspect, in accordance with embodiments of the invention, the computing the private key sk_i comprises: the first device being configured to: compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first

random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

With reference to the third aspect, in accordance with embodiments of the invention, the generating the second set of parameters for the second device comprises: the secure server being configured to: retrieve an arbitrary first value R_{j1} and an identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1}; compute an arbitrary value of the second device R_j and a first integer s_{j1}; and set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device, whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key *x*, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the third aspect, in accordance with embodiments of the invention, the computing the private key sk_j comprises: the second device being configured to: compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

According a fourth aspect of the invention, a system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme is provided, the system comprising: a first secure server configured to instruct: the first device to compute a private key sk_i based on a first set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server; a second secure server configured to instruct: the second device to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second

random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, a master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted to the second secure server, wherein the first secure server is located in a different domain from the second secure server; the first device configured to: sign a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G; transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device; upon receiving the transmission, the second device is configured to: verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i, sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where *b* is a random number generated by the first device, when the signed group element g^a is verified, and transmit the signed group elements (g^a || g^b) and a group element g^b to the first device; the first device is configured to: verify the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j; compute a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified; generate the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; transmit the first authentication data Ad_i to the second device; upon receiving the first authentication data Ad_i, the second device is configured to: compute a second shared secret k_{ji} based on the group element g^a and the group element *b*, compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function, compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function, determine if the second authentication data Ad_j matches with the first authentication data Ad_i ; and generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

With reference to the fourth aspect, in accordance with embodiments of the invention, the generating the first set of parameters for the first device comprises: the first secure server being configured to: retrieve an arbitrary first value R_{i1} and an identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1}; compute an arbitrary value of the first device R_i and a

first integer s_{i1}; and set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device, whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key x_i, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key mpk_i.

With reference to the fourth aspect, in accordance with embodiments of the invention, the computing the private key sk_i comprises: the first device being configured to: compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key mpk_i; and form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

With reference to the fourth aspect, in accordance with embodiments of the invention, the generating the second set of parameters for the second device comprises: the second secure server being configured to: retrieve an arbitrary first value R_{j1} and an identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1}; compute an arbitrary value of the second device R_j and a first integer s_{j1}; and set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device, whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key x_j, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key mpk_j.

With reference to the fourth aspect, in accordance with embodiments of the invention, the computing the private key sk_j comprises: the second device being configured to: compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key mpk_j; and form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

According to a fifth aspect of the invention, a system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS) is provided, the system comprising: a secure server configured to instruct: the first device to compute a private key

sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and the second device to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server; the first and second devices configured to use a self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_i and sk_j.

With reference to the fifth aspect, in accordance with embodiments of the invention, the generating the first set of parameters for the first device comprises: the secure server being configured to: retrieve an arbitrary first value R_{i1} and the identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1}; compute an arbitrary value of the first device R_i and a first integer s_{i1}; and set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device, whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the fifth aspect, in accordance with embodiments of the invention, the computing the private key sk_i comprises: the first device being configured to: compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

With reference to the fifth aspect, in accordance with embodiments of the invention, the generating the second set of parameters for the second device comprises: the secure server being configured to: retrieve an arbitrary first value R_{j1} and the identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1}; compute an arbitrary value of the second device R_j and a first integer s_{j1}; and set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device, whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key *x*, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the fifth aspect, in accordance with embodiments of the invention, the computing the private key sk_j comprises: the second device being configured to: compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*.; and form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

According to a sixth aspect of the invention, a system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS) is provided, the system comprising: a first secure server configured to instruct: the first device to compute a private key sk_i based on a first set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server, a second secure server configured to instruct: the second device to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, the master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted

to the second secure server, wherein the first secure server is located in a different domain from the second secure server; the first and second devices configured to use a self-certified Identity Based Signature Scheme to generate the common session key SK_{ij} for the TLS protocol between the first device and the second device, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_i and sk_j.

With reference to the sixth aspect, in accordance with embodiments of the invention, the generating the first set of parameters for the first device comprises: the first secure server being configured to: retrieve an arbitrary first value R_{i1} and the identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1}; compute an arbitrary value of the first device R_i and a first integer s_{i1}; and set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device, whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key x_i, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key mpk_i.

With reference to the sixth aspect, in accordance with embodiments of the invention, the computing the private key sk_i comprises: the first device being configured to: compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key mpk_i.; and form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

With reference to the sixth aspect, in accordance with embodiments of the invention, the generating the second set of parameters for the second device comprises: the second secure server being configured to: retrieve an arbitrary first value R_{j1} and the identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1}; compute an arbitrary value of the second device R_j and a first integer s_{j1}; and set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device, whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key x_j, the arbitrary value of the second device R_j, the

identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key mpk_j.

With reference to the sixth aspect, in accordance with embodiments of the invention, the computing the private key sk_j comprises: the second device being configured to: compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key mpk_j; and form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

With reference to the sixth aspect, in accordance with embodiments of the invention, before the secure server is configured to compute parameters for the device based on the second random number r_{i2} generated by the secure server, the secure server is configured to: receive a zero-knowledge proof result from the device, whereby the zero-knowledge proof result is generated by the device using the first random number r_{i1} and a system parameter λ; determine from the zero-knowledge proof result if the first random number r_{i1} is equal or less than the system parameter λ; and compute parameters for the device based on the second random number r_{i2} generated by the secure server, when the first random number r_{i1} is equal or less than the system parameter λ.

According to a seventh aspect of the invention, a system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS) is provided, the system comprising: a secure server configured to: generate a private key sk_i for the first device based on an identity of the first device id_i and generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme; and transmit the private key sk_i to the first device and transmit the private key sk_j to the second device; the first and second devices configured to use the same self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is included in the Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_i and sk_j .

According to an eighth aspect of the invention, a system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an

extended Datagram Transport Layer Security protocol (DTLS) is provided, the system comprising: a first secure server configured to: generate a private key sk_i for the first device based on an identity of the first device id_i using a self-certified Identity Based Signature Scheme, and transmit the private key sk_i to the first device; a second secure server configured to: generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme, and transmit the private key sk_j to the second device; wherein the first secure server is located in a different domain from the second secure server, the first and second devices configured to use the same self-certified Identity Based Signature Scheme with different parameters or different self-certified Identity Based Signature Schemes to generate the common session key SK for the TLS or DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is included in the Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by sk_i and sk_j.

According to a ninth aspect of the invention, a secure server configured to compute a private key sk for a device participating in a self-certified identity based signature system comprising: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: compute parameters for the device based on a second random number r_{i2} generated by the secure server, a first set of components received from the device, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components comprises a first random number r_{i1} generated by the device, transmit the computed parameters to the device such that the device is configured to compute the private key sk based on the received computed parameters and the random number r_{i1}.

With reference to the ninth aspect, in accordance with embodiments of the invention, the instructions to compute the parameters for the device comprises: instructions for directing the processor to: retrieve an arbitrary first value R_{i1} and an identity of the device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1}; compute an arbitrary value of the device R_i and a first integer s_{i1}; and set the computed arbitrary value of the device R_i and the first integer s_{i1} as the parameters for the device, whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the ninth aspect, in accordance with embodiments of the invention, the instructions to compute the parameters for the device comprises: instructions for directing the processor to: retrieve an arbitrary first value R_{i1}, an identity of the device id_i and a homomorphic encryption value *c* from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1} and the homomorphic encryption value *c* is generated by providing the first random number r_{i1} and a prime number q obtained from the parameters associated with the master public key *mpk* to an additive homomorphic encryption function *HEnc( )*; set an arbitrary value of the device R_i and a first integer s_{i1} as the parameters for the device, whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed by providing the second random number r_{i2}, the homomorphic encryption value *c*, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and the prime number q to the additive homomorphic encryption function *HEnc( )*.

With reference to the ninth aspect, in accordance with embodiments of the invention, before the instructions to compute parameters for the device based on the second random number r_{i2} generated by the secure server, the secure server comprises: instructions for directing the processor to: receive a zero-knowledge proof result from the device, whereby the zero-knowledge proof result is generated by the device using the first random number r_{i1} and a system parameter λ; determine from the zero-knowledge proof result if the first random number r_{i1} is equal or less than the system parameter λ; and compute parameters for the device based on the second random number r_{i2} generated by the secure server, when the first random number r_{i1} is equal or less than the system parameter λ.

According to a tenth aspect of the invention, a method for computing a private key sk for a device participating in a self-certified identity based signature system comprises: computing, by a secure server, parameters for the device based on a second random number r_{i2} generated by the secure server, a first set of components received from the device, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components comprises a first random number r_{i1} generated by the device, transmitting the computed parameters to the device such that the device computes the private key sk based on the received computed parameters and the random number r_{i1}.

With reference to the tenth aspect, in accordance with embodiments of the invention, the computing the parameters for the device comprises: retrieving, by the secure server, an arbitrary first value R_{i1} and an identity of the device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

computing an arbitrary value of the device R_i and a first integer s_{i1}; and setting the computed arbitrary value of the device R_i and the first integer s_{i1} as the parameters for the device, whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

With reference to the tenth aspect, in accordance with embodiments of the invention, the computing the parameters for the device comprises: retrieving, by the secure server, an arbitrary first value R_{i1}, an identity of the device id_i and a homomorphic encryption value *c* from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1} and the homomorphic encryption value *c* is generated by providing the first random number r_{i1} and a prime number q obtained from the parameters associated with the master public key *mpk* to an additive homomorphic encryption function *HEnc( )*; setting an arbitrary value of the device R_i and a first integer s_{i1} as the parameters for the device, whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and whereby the first integer s_{i1} is computed by providing the second random number r_{i2}, the homomorphic encryption value *c*, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and the prime number q to the additive homomorphic encryption function *HEnc( )*.

According to an eleventh aspect of the invention, a method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme comprises: receiving, by the first device, instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and signing, by the first device, a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G; transmitting an identity of the first device id_i, the group element g^a and the signed group element g^a to the second.

With reference to the eleventh aspect, in accordance with embodiments of the invention, the method further comprises: receiving a signed group elements (ga || gb) and a group element gb from the second device; verifying the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j; computing a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified; generating the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; transmitting the first authentication data Ad_i to the second device.

According to a twelfth aspect of the invention, a first device for generating a common session key SK for encoding digital communications between the first device and a second device that are participating in a self-certified identity based signature scheme comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: receive instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and sign a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G; transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second.

With reference to the twelfth aspect, in accordance with embodiments of the invention, the instructions comprise instructions for directing the processor to: receive a signed group elements (ga || gb) and a group element gb from the second device; verify the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j; compute a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified; generate the common

session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; transmit the first authentication data Ad_i to the second device.

According to a thirteenth aspect of the invention, a method for generating a common session key SK for encoding digital communications between a first device i and a second device j that are participating in a self-certified identity based signature scheme comprises: receiving, by the second device, instructions from the secure server to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server; receiving an identity of the first device id_i, the group element g^a and the signed group element g^a from the first; verifying the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i; signing group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where b is a random number generated by the first device, when the signed group element g a is verified; and transmitting the signed group elements (g^a || g^b) and a group element g^b to the first device.

With reference to the thirteenth aspect, in accordance with embodiments of the invention, the method further comprises: receiving a first authentication data Ad_i from the first device; computing a second shared secret k_{ji} based on the group element g^a and the group element g^b; computing a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function; computing a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function; determining if the second authentication data Ad_j matches with the first authentication data Ad_i; and generating the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

According to a fourteenth aspect of the invention, a second device for generating a common session key SK for encoding digital communications between a first device and the second device that are participating in a self-certified identity based signature scheme comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: receive instructions from the secure server to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the

second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server; receive an identity of the first device id_i, the group element g^a and the signed group element g^a from the first; verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i; sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where b is a random number generated by the first device, when the signed group element g^a is verified; and transmit the signed group elements (g^a || g^b) and a group element g^b to the first device.

With reference to the fourteenth aspect, in accordance with embodiments of the invention, the instructions comprise instructions for directing the processor to: receive a first authentication data Ad_i from the first device; compute a second shared secret k_{ji} based on the group element g^a and the group element g^b; compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function; compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function; determine if the second authentication data Ad_j matches with the first authentication data Ad_i; and generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

According to a fifteenth aspect of the invention, a method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* participating in a self-certified identity based signature scheme comprises: receiving, by the first device, instructions from a secure server, to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and signing, by the first device, a cryptographic nonce N_i using a self-certified Identity Based Signature Scheme and the private key sk_i; transmitting an identity of the first device id_i, the cryptographic nonce N_i and the signed cryptographic nonce N_i to the second device. such that, upon receiving the transmission, the second device is configured to: verifying the signed cryptographic nonce N_i

using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i; signing cryptographic nonces (N_i || N_j) using the self-certified Identity Based Signature Scheme and the private key sk_j, where N_j is a cryptographic nonce, when the signed cryptographic nonce N_i is verified; and transmitting the signed cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j to the first device.

With reference to the fifteenth aspect, in accordance with embodiments of the invention, the method further comprises: receiving a cryptographic nonces (Ni || Nj) and the cryptographic nonce Nj from the second device; verifying the signed cryptographic nonces (N_i || N_j) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j, compute a first shared secret $k_{ij} = g^{sj \cdot si}$, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the cryptographic nonces N_i and N_j and the first key vk_i to an Authentication Data Deriving Function, when the signed cryptographic nonces (N_i || N_j) are verified; generating the common session key SK by providing the first shared secret k_{ij} and the cryptographic nonces N_i and N_j to the Key Deriving Function; transmitting the first authentication data Ad_i to the second device.

According to a sixteenth aspect of the invention, a first device for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* participating in a self-certified identity based signature scheme comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: receive instructions from a secure server, to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server; and sign a cryptographic nonce N_i using a self-certified Identity Based Signature Scheme and the private key sk_i; and transmit an identity of the first device id_i, the cryptographic nonce Ni and the signed cryptographic nonce Ni to the second device.

With reference to the sixteenth aspect, in accordance with embodiments of the invention, the instructions comprise instructions for directing the processor to: receive a cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j from the second device; verify the signed cryptographic nonces (N_i || N_j) using the verification function associated with the

self-certified Identity Based Signature Scheme and the identity of the second device id_j, compute a first shared secret $k_{ij} = g^{sj \cdot si}$, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the cryptographic nonces N_i and N_j and the first key vk_i to an Authentication Data Deriving Function, when the signed cryptographic nonces (N_i || N_j) are verified; generate the common session key SK by providing the first shared secret k_{ij} and the cryptographic nonces N_i and N_j to the Key Deriving Function; and transmit the first authentication data Ad_i to the second device.

According to a seventeenth aspect of the invention, a second device for generating a common session key SK for encoding digital communications between a first device and the second device participating in a self-certified identity based signature scheme comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: receive instructions from the secure server to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key x and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server; receive an identity of the first device id_i, the cryptographic nonce N_i and the signed cryptographic nonce N_i from the first device; verify the signed cryptographic nonce N_i using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i; sign cryptographic nonces (N_i || N_j) using the self-certified Identity Based Signature Scheme and the private key sk_j, where N_j is a cryptographic nonce, when the signed cryptographic nonce N_i is verified; and transmit the signed cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j to the first device.

With reference to the seventeenth aspect, in accordance with embodiments of the invention, the instructions comprise instructions for directing the processor to: receive a first authentication data Ad_i from the first device; compute a second shared secret $k_{ji} = g_{sj} \cdot s_i$; compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function; compute a second authentication data Ad_j by providing the key vk_j and the cryptographic nonces N_i and N_j to the Authentication Data Deriving Function; determine if the second authentication data Ad_j matches with the first authentication data Ad_i; and generate the common session key SK by providing the second shared secret k_{ji} to the Key

Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

According to an eighteenth aspect of the invention, a method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme, the method comprises: receiving, by the first device instructions from a first secure server to compute a private key sk_i based on a first set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server; wherein the first secure server is located in a different domain from the second secure server; signing, by the first device, a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G; transmitting an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device.

With reference to the eighteenth aspect, in accordance with embodiments of the invention, the method further comprises: receiving a signed group elements (g^a || g^b) and a group element g^b from the second device; verifying the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j; computing a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified; generating the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; and transmitting the first authentication data Ad_i to the second device.

According to a nineteenth aspect of the invention, a first device for generating a common session key SK for encoding digital communications between the first device and a second device that are participating in a self-certified identity based signature scheme, the first device comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: receive instructions from a first secure server to compute a private key sk_i based on a first

set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server; wherein the first secure server is located in a different domain from the second secure server; sign, by the first device, a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G; and transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device.

With reference to the nineteenth aspect, in accordance with embodiments of the invention, the instructions comprise instructions for directing the processor to: receive a signed group elements (g^a || g^b) and a group element gb from the second device; verify the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j; compute a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified; generate the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; and transmit the first authentication data Ad_i to the second device.

According to a twentieth aspect of the invention, a method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme, the method comprises: receiving, by the second device instructions from a second secure server to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, a master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted to the second secure server; receiving an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device; verifying the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i,

signing group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where *b* is a random number generated by the first device, when the signed group element g^a is verified, and transmitting the signed group elements (g^a || g^b) and a group element g^b to the first device.

With reference to the twentieth aspect, in accordance with embodiments of the invention, the method further comprises: receiving a first authentication data Ad_i to from the first device; computing a second shared secret k_{ji} based on the group element g^a and the group element b, computing a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function, computing a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function, determining if the second authentication data Ad_j matches with the first authentication data Ad_i; and generating the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

According to a twenty-first aspect of the invention, a second device for generating a common session key SK for encoding digital communications between a first device and the second device that are participating in a self-certified identity based signature scheme, the second device comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: receive instructions from a second secure server to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, a master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted to the second secure server; receive an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device; verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i, sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where b is a random number generated by the first device, when the signed group element g^a is verified, and transmit the signed group elements (g^a || g^b) and a group element g^b to the first device.

With reference to the twenty-first aspect, in accordance with embodiments of the invention, the instructions comprise instructions for directing the processor to: receive a first authentication data Ad_i from the first device; compute a second shared secret k_{ji} based on

the group element g^a and the group element g^b, compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function, compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function, determine if the second authentication data Ad_j matches with the first authentication data Ad_i; and generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

According to a twenty-second aspect of the invention, a method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the method comprises: receiving, by the first device instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server; and communicating, by the second device, to generate the common session key SK for the TLS protocol or the DTLS protocol by using a self-certified Identity Based Signature Scheme, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by a sk_j and the sk_i; wherein the sk_j is a private key computed by the second device.

According to a twenty-third aspect of the invention, a first device for generating a common session key SK for encoding digital communications between the first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the first device comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: receive instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first

device and transmitted to the secure server; and communicate with the second device to generate the common session key SK for the TLS protocol or the DTLS protocol by using a self-certified Identity Based Signature Scheme, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by a sk_j and the sk_i; wherein the sk_j is a private key computed by the second device.

According to a twenty-fourth aspect of the invention, a method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the method comprises: generating, by a secure server, a private key sk_i for the first device based on an identity of the first device id_i and generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme; and transmitting the private key sk_i to the first device and transmit the private key sk_j to the second device such that the first and second devices are configured to use the same self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is included in the Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_j and the sk_i.

According to a twenty-fifth aspect of the invention, a secure server for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the secure server comprises: a processor; and a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to: generate a private key sk_i for the first device based on an identity of the first device id_i and generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme; and transmit the private key sk_i to the first device and transmit the private key sk_j to the second device such that the first and second devices are configured to use the same self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is

included in the Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_j and the sk_i.

Brief Description of the Drawings

The above advantages and features in accordance with this invention are described in the following detailed description and are shown in the following drawings:

Figure 1 illustrating a block diagram representative of an entity-pair authentication and a common session key generation system for the authenticated entity-pair in accordance with embodiments of the invention;

Figure 2 illustrating a block diagram representative of components in an electronic device or server for implementing embodiments in accordance with embodiments of the invention;

Figure 3 illustrating a timing diagram for the generation of a private key sk for a device in a self-certified identity based signature scheme in accordance with embodiments of the invention;

Figure 4 illustrating a timing diagram for the authentication of an entity-pair and for the generation of a common session key for the authenticated entity-pair in accordance with embodiments of the invention;

Figure 5 illustrating a flow diagram of a process for verifying the authenticity of a second entity and for generating a common session key in accordance with embodiments of the invention.

Detailed Description

This invention relates to a system and method for generating private keys for devices participating in a self-certified identity based signature scheme whereby the private key is used by the devices to establish a common session key for encoding digital communications between devices. In particular, the private keys generated in accordance with the system and methods of the invention are only known to the devices themselves and not by any other third parties.

Further, before the common session key is calculated, an entity-pair or device-pair will first verify the veracity of each entity or device. Once each of these entities has been authenticated, the entity-pair will then proceed to generate a common session key that is then utilized to encode digital communications between these entities.

Figure 1 illustrates a block diagram of an entity-pair authentication and a common session key generation system in accordance with embodiments of the invention. One skilled in the art will recognize that the term entity and device may be used interchangeably throughout the description without departing from the invention.

The system illustrated in Figure 1 comprises devices or entities 105, 110, that are wirelessly connected to secure server 120. Entities 105 and 110 each may comprise, but is not limited to, any device that is able to carry out wireless communicative functions such as a smart phone, a tablet computer, a mobile computer, a netbook, a wearable electronic device such as smart watch, smart plugs, or transceivers that may be found in smart devices or Internet of Things (IoT) enabled devices, and etc.

As for secure server 120, this server may comprise a secure cloud server or a remotely located secure server which is able to communicate wirelessly with entities 105 and 110 either through Internet 115 or directly with entities 105 and 110. If server 120 is configured to communicate with entities 105 and 110 through Internet 115, server 120 may do so via wired networks or wireless networks 125 such as, but are not limited to, cellular networks, satellite networks, telecommunication networks, or Wide Area Networks (WAN). Alternatively, if server 120 is configured to communicate directly with entities 105 and 110, this may be accomplished through wireless networks 130 such as, but not limited to, Wireless-Fidelity (Wi-Fi), Bluetooth, or Near Field Communication (NFC). It should be noted that entities 105 and 110 may utilize either one of wireless network 125 (via the Internet) or wireless network 130 (direct communication) to exchange data messages with one another.

Figure 2 illustrates a block diagram representative of components of an electronic device 200 that is provided within entities 105, 110 and server 120 for implementing embodiments in accordance with embodiments of the invention. One skilled in the art will recognize that the exact configuration of each electronic device provided within the entities or the server may be different and the exact configuration of electronic device 200 may vary and Figure 2 is provided by way of example only.

In embodiments of the invention, device 200 comprises controller 201 and user interface 202. User interface 202 is arranged to enable manual interactions between a user and electronic device 200 and for this purpose includes the input/output components required for the user to enter instructions to control electronic device 200. A person skilled in the art will recognize that components of user interface 202 may vary from embodiment to embodiment but will typically include one or more of display 240, keyboard 235 and track-pad 236.

Controller 201 is in data communication with user interface 202 via bus 215 and includes memory 220, Central Processing Unit (CPU) 205 mounted on a circuit board that processes instructions and data for performing the method of this embodiment, an operating system 206, an input/output (I/O) interface 230 for communicating with user interface 202 and a communications interface, in this embodiment in the form of a network card 250. Network card 250 may, for example, be utilized to send data from electronic device 200 via a wired or wireless network to other processing devices or to receive data via the wired or wireless network. Wireless networks that may be utilized by network card 250 include, but are not limited to, Wireless-Fidelity (Wi-Fi), Bluetooth, Near Field Communication (NFC), cellular networks, satellite networks, telecommunication networks, Wide Area Networks (WAN) and etc.

Memory 220 and operating system 206 are in data communication with CPU 205 via bus 210. The memory components include both volatile and non-volatile memory and more than one of each type of memory, including Random Access Memory (RAM) 220, Read Only Memory (ROM) 225 and a mass storage device 245, the last comprising one or more solid-state drives (SSDs). Memory 220 also includes secure storage 246 for securely storing secret keys, or private keys. It should be noted that the contents within secure storage 246 are only accessible by a super-user or administrator of device 200 and may not be accessed by any user of device 200. One skilled in the art will recognize that the memory components described above comprise non-transitory computer-readable media and shall be taken to comprise all computer-readable media except for a transitory, propagating signal. Typically, the instructions are stored as program code in the memory components but can also be hardwired. Memory 220 may include a kernel and/or programming modules such as a software application that may be stored in either volatile or non-volatile memory.

Herein the term “CPU” is used to refer generically to any device or component that can process such instructions and may include: a microprocessor, microcontroller, programmable logic device or other computational device. That is, CPU 205 may be provided by any suitable logic circuitry for receiving inputs, processing them in accordance with instructions stored in memory and generating outputs (for example to the memory components or on display 240). In this embodiment, CPU 205 may be a single core or multi-core processor with memory addressable space. In one example, CPU 205 may be multi-core, comprising—for example—an 8 core CPU.

Generation of a Private Key

Referring back to Figure 1, prior to adding entities 105 and 110 to the entity-pair authentication and the common session key generation system in accordance with

embodiments of the invention, server 120, which is configured as a Key Generation Centre, will first initiate a setup procedure based on a discrete-logarithm type signature scheme to generate a master secret key “x” and a master public key “y”. In the setup procedure, server 120 will first determine an appropriate cyclic group, ***G***, with a prime order *q*, and a generator *g* of ***G***. In embodiments of the invention, the cyclic group, ***G***, will be based on finite fields or elliptic curves defined over a finite field.

Server 120 will then select a cryptographic collision-resistant hash function H: $\{0,1\}^* \rightarrow \{0,1\}^l$, whereby l is an appropriate integer known to a person skilled in the art. Server 120 will also select an Authentication Data Deriving Function and a Key Deriving Function that is to be adopted for use in the system. In embodiments of the invention, the Authentication Data Deriving Function (AdDF) may include any algorithm or scheme for verifying the authenticity of a message such as a message authentication code (MAC), a message integrity code or a keyed hash function while the Key Deriving Function (KDF) may include any scheme for deriving a secret key from a secret value such as a collision-resistant hash function.

Once that is done, server 120 then proceeds to select the master secret key “x” from an allowed set of integers ($x \in \mathbb{Z}_q$), sets $y = g^x$ and the master public key “*mpk*” is set as mpk = {***G***, g, *q*, y, H, AdDF, KDF}.

It should be noted that the setup procedure described above is similar to the initiation procedures for setting up a discrete-logarithmic type of self-certified identity based signature scheme such as, but not limited to, the lightweight identity based signature scheme as defined in ISO/IEC 29192-4 or elliptic curve-based certificate-less signature scheme as defined in IETF RFC 6507. In such self-certified Identity Based Signature Schemes, signatures generated by a particular user always contains a fixed component that is specific to that user’s private signing key or private key. Hence, the fixed component is termed key-specific data (KSD) in this invention whereby the KSD may be utilized to verify the generated signatures. For illustration purposes, the identity based signature scheme defined in ISO/IEC 29192-4 is adopted in all embodiments below, but for one skilled in the art, the system and method is easily applied to other self-certified identity based signature schemes such as the scheme specified in IETF RFC 6507, with due changes in a straightforward way.

When entity 105 or 110 joins the system, a private key unique to each of these entities will be issued by secure server 120, i.e. the Key Generation Centre. These unique private keys once generated will then be communicated to each of these entities whereby

the respective private keys will then be stored in the secure memory within each of entities 105 and 110.

The generation of a private key for entity 105 is illustrated in Figure 3. In particular, when entity 105 registers itself with server 120, at step 305, entity 105 will first generate a random number $r_{i1} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Entity 105 will then utilize the random number r_{i1} to compute an arbitrary value R_{i1} as $R_{i1} = g^{r_{i1}}$. At step 310, entity 105 then communicates the arbitrary value R_{i1} and its identity, id_i, to server 120. The identity, id_i, of entity 105 may comprise its user name, email address, telephone number, IP address, MAC address, or any alphanumeric combination that may be utilized to uniquely identify entity 105.

At step 315, server 120 will receive the arbitrary value R_{i1} and the identity of entity 105, id_i. Server 120 then selects a random number random number $r_{i2} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Based on the selected random number r_{i2} and the received information, server 120 then computes an arbitrary value R_i that is to be accorded to entity 105 as $R_i = R_{i1} g^{r_{i2}}$ or $R_i = {R_{i1}}/{g^{r_{i2}}}$ and also computes an integer s_{i1} as $s_{i1} = r_{i2} + xH(R_i, id_i)(mod\ q)$ or $s_{i1} = -r_{i2} + xH(R_i, id_i)(mod\ q)$ where x is the previously generated master secret key "x" and H( ) is the hash function as contained in the parameters of the *mpk*.

Server 120 then transmits the arbitrary value R_i and the integer s_{i1} to entity 105 at step 320. Upon receiving this information, entity 105, will at step 325 proceed to compute integer s_i as $s_i = s_{i1} + r_{i1}(mod\ q)$. Entity 105 then sets its private key sk_i as $sk_i = (R_i, s_i)$.

In another embodiment of the invention, at step 315, based on the selected random number r_{i2} and the information received at this step, server 120 will compute the arbitrary value R_i that is to be accorded to entity 105 as $R_i = {g^{r_{i2}}}/{R_{i1}}$ instead and also computes the integer s_{i1} as $s_{i1} = r_{i2} + xH(R_i, id_i)(mod\ q)$ where x is the previously generated master secret key "x" and H( ) is the hash function as contained in the parameters of the *mpk*.

Server 120 then transmits the arbitrary value R_i and the integer s_{i1} to entity 105 at step 320. Upon receiving this information, entity 105, will at step 325 proceed to compute integer s_i as $s_i = s_{i1} - r_{i1}(mod\ q)$. Entity 105 then sets its private key sk_i as $sk_i = (R_i, s_i)$.

In yet another embodiment of the invention, when entity 105 registers itself with server 120, at step 305, entity 105 will first generate a random number $r_{i1} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Entity 105 will then utilize the random number r_{i1} to

compute an arbitrary value R_{i1} as $R_{i1} = g^{r_{i1}}$. Further, entity 105 will also generate a homomorphic encryption value *c* defined by $c = HEnc({r_{i1}}^{-1} \, mod \, q)$ where HEnc( ) denotes an additive homomorphic encryption function and HDec( ) denotes a corresponding decryption function. In embodiments of the invention, the additive homomorphic encryption/decryption functions are based on Paillier's cryptosystem whereby $HEnc(m_1) \cdot HEnc(m_2) = HEnc(m_1 + m_2)$; and $HEnc(m_1)^{m_2} = HEnc(m_1 m_2)$.

At step 310, entity 105 then communicates the arbitrary value $R_{i1,}$ its identity, id_i, and the generated homomorphic encryption value *c* and the additive homomorphic encryption function to server 120. Similarly, the identity, $id_{i,}$ of entity 105 may comprise its user name, email address, telephone number, IP address, MAC address, or any alphanumeric combination that may be utilized to uniquely identify entity 105.

At step 315, server 120 will receive the homomorphic encryption value *c*, the arbitrary value R_{i1} and the identity of entity 105, id_i. Server 120 then selects a random number random number $r_{i2} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Based on the selected random number r_{i2} and the received information, server 120 then computes an arbitrary value R_i that is to be accorded to entity 105 as $R_i = (R_{i1})^{r_{i2}}$ and also computes an integer s_{i1} as $s_{i1} = HEnc(r_{i2}). \, c^{xH(R_i, id_i) \, mod \, q}$ where x is the previously generated master secret key "x" and H( ) is the hash function as contained in the parameters of the *mpk*. The integer s_{i1} may be further expanded to $s_{i1} = HEnc(r_{i2} + \, {r_{i1}}^{-1} xH(R_i, id_i) \, mod \, q)$.

Server 120 then transmits the arbitrary value R_i and the integer s_{i1} to entity 105 at step 320. Upon receiving this information, entity 105, will at step 325 proceed to compute integer s_i as $s_i = r_{i1} HDec(s_{i1}) = r_{i1} r_{i2} + xH(R_i, id_i) (mod \, q)$. Entity 105 then sets its private key sk_i as $sk_i = (R_i, s_i)$.

In still yet another embodiment of the invention, when entity 105 registers itself with server 120, at step 305, entity 105 will first generate a random number $r_{i1} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Entity 105 will then utilize the random number r_{i1} to compute an arbitrary value R_{i1} as $R_{i1} = g^{{r_{i1}}^{-1}}$. Further, entity 105 will generate the homomorphic encryption value *c* as defined by $c = HEnc(r_{i1})$ where HEnc( ) denotes an additive homomorphic encryption function and HDec( ) denotes a corresponding decryption function.

At step 310, entity 105 then communicates the arbitrary value $R_{i1,}$ its identity, id_i, and the generated homomorphic encryption value *c* to server 120.

At step 315, server 120 will receive the homomorphic encryption value *c*, the arbitrary value R_{i1} and the identity of entity 105, id_i. Server 120 then selects a random number random number $r_{i2} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Based on the selected random number r_{i2} and the received information, server 120 then computes an arbitrary value R_i that is to be accorded to entity 105 as $R_i = (R_{i1})^{r_{i2}}$ and also computes an integer s_{i1} as $s_{i1} = HEnc(r_{i2}).c^{xH(R_i,id_i)\ mod\ q}$ where x is the previously generated master secret key "x" and H( ) is the hash function as contained in the parameters of the *mpk*. The integer s_{i1} may be further expanded to $s_{i1} = HEnc(r_{i2} + r_{i1}\ .xH(R_i, id_i)\ mod\ q)$.

Server 120 then transmits the arbitrary value R_i and the integer s_{i1} to entity 105 at step 320. Upon receiving this information, entity 105, will at step 325 proceed to compute integer s_i as $s_i = {r_{i1}}^{-1} HDec(s_{i1}) = {}^{r_{i2}}/_{r_{i1}} + xH(R_i, id_i)(mod\ q)$. Entity 105 then sets its private key sk_i as $sk_i = (R_i, s_i)$.

In another embodiment of the invention, when entity 105 registers itself with server 120, at step 305, entity 105 will first generate a random number $r_{i1} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Entity 105 will then utilize the random number r_{i1} to compute an arbitrary value R_{i1} as $R_{i1} = g^{r_{i1}}$. Further, entity 105 will generate the homomorphic encryption value *c* as defined by $c = HEnc({r_{i1}}^{-1})$ where HEnc( ) denotes an additive homomorphic encryption function and HDec( ) denotes a corresponding decryption function.

At step 310, entity 105 then communicates the arbitrary value $R_{i1,}$ its identity, id_i, and the generated homomorphic encryption value *c* to server 120.

At step 315, server 120 will receive the homomorphic encryption value *c*, the arbitrary value R_{i1} and the identity of entity 105, id_i. Server 120 then selects a random number random number $r_{i2} \in \mathbb{Z}_q^*$ where $\mathbb{Z}_q^*$ are non-zero residuals of modular q. Based on the selected random number r_{i2} and the received information, server 120 then computes an arbitrary value R_i that is to be accorded to entity 105 as $R_i = (R_{i1})^{{r_{i2}}^{-1}}$ and also computes an integer s_{i1} as $s_{i1} = HEnc({r_{i2}}^{-1}).c^{xH(R_i,id_i)\ mod\ q}$ where x is the previously generated master secret key "x" and H( ) is the hash function as contained in the parameters of the *mpk*. The integer s_{i1} may be further expanded to $s_{i1} = HEnc({r_{i2}}^{-1} + {r_{i1}}^{-1}.xH(R_i, id_i)\ mod\ q)$.

Server 120 then transmits the arbitrary value R_i and the integer s_{i1} to entity 105 at step 320. Upon receiving this information, entity 105, will at step 325 proceed to compute integer s_i as $s_i = r_{i1}\ \ HDec(s_{i1}) = {}^{r_{i1}}/_{r_{i2}} + xH(R_i, id_i)(mod\ q)$. Entity 105 then sets its private key sk_i as $sk_i = (R_i, s_i)$.

It should be noted that private key sk_i generated in accordance with the embodiments set out above may only be computed by entity 105 alone. In other words, server 120 is not empowered to compute private keys for entities in this self-certified identity based signature scheme.

Generation of Private Key with Zero-Knowledge Proof

The above embodiments eliminate the escrow of devices' private keys to the Key Generation Centre. A more general embodiment may require the Key Generation Centre to be provided with adjustable difficulty levels of key escrow generation whereby the difficulty level is governed by a system parameter λ. In order to incorporate some form of adjustability into the system, a system parameter λ is introduced to set the length of random number r_{i1} that may be generated and utilized by entity 105. In this embodiment, which may be applied to any one of the previously described embodiments, a zero-knowledge proof function, ZKP( ) is applied to random number r_{i1} and the system parameter λ resulting in ZKP($|r_{i1}|$, λ) which shows in a zero-knowledge manner that the length of r_{i1}, $|r_{i1}| \leqslant \lambda$. The detailed workings of the function ZKP( ) are omitted for brevity as this function is known to those skilled in the art. In general, the function ZKP( ) will generate a zero-knowledge proof result using the random number r_{i1} and the system parameter λ. The zero-knowledge proof result is then transmitted together with id_i and arbitrary R_{i1} from entity 105 to server 120.

When server 120 receives the arbitrary value R_{i1}, server 120 will then check the validity of the zero-knowledge proof result before proceeding further. If server 120 determines from the zero-knowledge proof result that the length of r_{i1} is less or equal to the system parameter λ, system 120 will proceed as normal. Conversely, system 120 will abort the private key generation process.

It should be noted that steps 305 – 325 as described in the various embodiments above may also be repeated for other entities including entity 110 to generate private key sk_j for entity 110 as $sk_j = (R_j, s_j)$. Further, one skilled in the art will recognize that the embodiments above may be applied to any number of devices or entities to generate private keys for each of the entities in the system.

Generation of Private Key with Cross-Domain KGCs

In another embodiment of the invention, another secure server (not shown) may be utilized in place of server 120 to generate private key sk_j for entity 110 as $sk_j = (R_j, s_j)$. This means that steps 305-325 along with the various embodiments as described above may take place in the other secure server with entity 110 instead of with server 120. In this cross-

domain authenticated key exchange approach, the private signing key for entity 105 is generated using secure server 120 while the private signing key for entity 110 is generated using another separate secure server (not shown). In such an embodiment, each secure server would have its own set of master secret key "x" and a master public key "y".

Once the private keys have been stored in the secure memory of the respective entities, the entity-pair, i.e. entity 105 and 110, may then commence authentication procedures. Upon successfully authenticating each other, the entity-pair may then proceed to generate a common session key for encoding or signing digital communications sent between each other.

Static Diffie Hellman-based Authenticated Key Exchange Protocol

In embodiments of the invention, a static Diffie Hellman-based authenticated key exchange protocol is adopted to generate a common session key between participants 105 and 110. With reference to Figure 4, entity 105 initiates the authentication process with entity 110 by first selecting a cryptographic nonce, N_i. The selected cryptographic nonce may comprise any random or pseudo-random number. Entity 105 then computes a signed cryptographic nonce c_i whereby signed cryptographic nonce c_i is defined by c_i = SC-IBS.Sign(sk_i, N_i) where SC-IBS.Sign( ) is a signing function for a Self-Certified Identity Based Signature Scheme and sk_i is a private key of entity 105 that was generated using the steps set out in Figure 3. In other words, cryptographic nonce N_i is signed using the function SC-IBS.Sign( ) and private key sk_i.

Entity 105 then proceeds, at step 405, to transmit the identity of entity 105, id_i, the value of signed cryptographic nonce c_i, and the pseudo-random nonce, N_i, to entity 110.

Upon receiving the transmitted information, entity 110 will then proceed to verify c_i using a corresponding Verification function / algorithm associated with the Self-Certified Identity Based Signature Scheme, SC-IBS.Verify( ) and the identity of entity 105, id_i. This is done by entity 110 applying the verification function to c_i and the identity id_i thereby producing SC-IBS.Verify(id_i, c_i) and if the verification fails, entity 110 will abort the process. Else, upon successfully verifying the signed cryptographic nonce c_i, entity 110 will then proceed to select a random nonce N_j and will proceed to sign the cryptographic nonce N_j as c_j = SC-IBS.Sign(sk_j, N_i || N_j) where sk_j is a private key of entity 110 that was generated using the steps set out in Figure 3 .

Entity 110 then proceeds, at step 410, to transmit the value of signed cryptographic nonce c_j, and the pseudo-random nonce, N_j, to entity 105

Upon receiving the transmitted information, entity 105 will then proceed to verify c_j using a corresponding Verification function associated with the Self-Certified Identity Based Signature Scheme, SC-IBS.Verify( ) and the identity of entity 110, id_j. This is done by entity 105 applying the verification function to c_j together with the identity id_j thereby producing SC-IBS.Verify(id_j, c_j) and if the verification fails, entity 110 will abort the process. Else, entity 105 will calculate the shared secret k_{ij} where $k_{ij} = g^{s_j \cdot s_i}$ whereby $g^{s_j} = R_j y^{H(R_j, id_j)}$ and R_j is part of c_j, calculate a first key vk_i = KDF(k_{ij}) and calculate a first authentication data Ad_i = AdDF(vk_i, N_j). Once this is done entity 105 then calculates common session key SK as SK = KDF(k_{ij}, N_i, N_j).

Entity 105 then proceeds, at step 415, to transmit the first authentication data Ad_i to entity 105.

Upon receiving the first authentication data Ad_i, entity 110 will calculate the shared secret k_{ji} where $k_{ji} = g^{s_i \cdot s_j}$ whereby $g^{s_i} = R_i y^{H(R_i, id_i)}$ and R_i is part of c_i, calculate a second key vk_j = KDF(k_{ji}) and calculate a second authentication data Ad_j = AdDF(vk_j, N_j). Once this is done entity 105 then determines whether second authentication data Ad_j matches with the received first authentication data Ad_i. If a match is not found, the process aborts. Alternatively, if a match is found, entity 110 will calculate common session key SK as SK = KDF(k_{ji}, N_i, N_j).

In another embodiment of the static Diffie Hellman-based authenticated key exchange protocol, option fields op_f1, op_f2, op_f3, op_f4, op_f5, op_f6 and op_f7 are used and may comprise identities of entities of the system where applicable or any application specific data as determined by the entities themselves.

With reference to Figure 4, entity 105 initiates the authentication process with entity 110 by first selecting a cryptographic nonce, N_i. Entity 105 then computes a signed cryptographic nonce c_i whereby signed cryptographic nonce c_i is defined by c_i = SC-IBS.Sign(sk_i, N_i || op_f_1) where SC-IBS.Sign( ) is a signing function for a Self-Certified Identity Based Signature Scheme and sk_i is a private key of entity 105 that was generated using the steps set out in Figure 3. In other words, cryptographic nonce N_i is signed using the function SC-IBS.Sign( ) and private key sk_i.

Entity 105 then proceeds, at step 405, to transmit an option field op_f2, the identity of entity 105, id_i, the value of signed cryptographic nonce c_i, and the pseudo-random nonce, N_i, to entity 110.

Upon receiving the transmitted information, entity 110 will then proceed to verify c_i using a corresponding Verification function associates with the Self-Certified Identity Based

Signature Scheme, SC-IBS.Verify( ) and the identity of entity 105, id_i. This is done by entity 110 applying the verification function to c_i and the identity id_i thereby producing SC-IBS.Verify(id_i, c_i) and if the verification fails, entity 110 will abort the process. Else, upon successfully verifying the signed cryptographic nonce c_i, entity 110 will then proceed to select a random nonce N_j and will proceed to sign the cryptographic nonce N_j as c_j = SC-IBS.Sign(sk_j, N_i || N_j|| op_f3) where sk_j is a private key of entity 110 that was generated using the steps set out in Figure 3 .

Entity 110 then proceeds, at step 410, to transmit an option field op_f4, the value of signed cryptographic nonce c_j, and the pseudo-random nonce, N_j, to entity 105

Upon receiving the transmitted information, entity 105 will then proceed to verify c_j using a corresponding Verification function associated with the Self-Certified Identity Based Signature Scheme, SC-IBS.Verify( ) and the identity of entity 110, id_j. This is done by entity 105 applying the verification function to c_j together with the identity id_j thereby producing SC-IBS.Verify(id_j, c_j) and if the verification fails, entity 110 will abort the process. Else, entity 105 will calculate the shared secret k_{ji} where $k_{ji} = g^{s_j \cdot s_i}$, calculate a first key vk_i = KDF(k_{ji}, op_f5) and calculate a first authentication data Ad_i = AdDF(vk_i, N_j, op_f6). Once this is done entity 105 then calculates common session key SK as SK = KDF(k_{ji}, N_i, N_j, op_f7).

Entity 105 then proceeds, at step 415, to transmit the first authentication data Ad_i to entity 110.

Upon receiving the first authentication data Ad_i, entity 110 will calculate the shared secret k_{ji} where $k_{ji} = g^{s_i \cdot s_j}$, calculate a second key vk_j = KDF(k_{ji}, op_f5) and calculate a second authentication data Ad_j = AdDF(vk_j, N_j, op_f6). Once this is done entity 105 then determines whether second authentication data Ad_j matches with the received first authentication data Ad_i. If a match is not found, the process aborts. Alternatively, if a match is found, entity 110 will calculate common session key SK as SK = KDF(k_{ji}, N_i, N_j, op_f7).

In yet another embodiment of the invention, in the steps described above, the cryptographic nonces N_i and N_j may be replaced with ephemeral Diffie Hellman (DH) public values g^a and g^b, and k_{ij}, k_{ji} are derived from both $g^{si \cdot sj}$ and g^{ab}. Such an embodiment would inherit all the features of an ephemeral DH-based protocol and is more secure.

Static Diffie Hellman-based Authenticated Key Exchange Protocol Extended to TLS

In still yet another embodiment of the invention, the above idea of static Diffie-Hellman key exchange may be extended to Transport Layer Security (TLS) or Datagram Transport Layer Security (DTLS). In particular, the steps above in generating the shared

secret k_{ij} (as well as k_{ji}) between entity 105 and entity 110 are actually in the same spirit as the static DH-based cipher-suites contained in TLS v1.2. It is thus easy for those skilled in the art to extend conventional TLS such as TLS v1.2 to include a set of static DH-based cipher-suites based on self-certified IBS as above. In this embodiment of the invention, the Server Certificate message in the TLS protocol is set to be entity 110's id_j and its key specific data R_j; and the Client Message in the TLS protocols is set to be the entity 105's id_i and its key specific data R_i; other steps and operations of the TLS protocol follow the specification of TLS with the accommodation of the corresponding changes due to the use of self-certified Identity Based Signature in a straightforward way.

Ephemeral Diffie Hellman (DH) - based Authenticated Key Exchange Protocol

In yet still another embodiment of the invention, an ephemeral Diffie Hellman (DH) - based authenticated key exchange protocol is adopted to generate a common session key between participants 105 and 110. Entities 105 and 110 will each have private keys that correspond to a self-certified IBS scheme of either ISO/IEC 29192-4 or IETF RFC 6507.

With reference to Figure 4, entity 105 initiates the authentication process with entity 110 by first selecting a random value $a \in \mathbb{Z}_q^*$ and by computing a signed c_i whereby c_i is defined by c_i = SC-IBS.Sign(sk_i, g^a) where SC-IBS.Sign( ) is a signing function for a Self-Certified Identity Based Signature Scheme, sk_i is a private key of entity 105 that was generated using the steps set out in Figure 3 and g^a is the group element. In other words, group element g^a is signed using the function SC-IBS.Sign( ) and private key sk_i.

Entity 105 then proceeds, at step 405, to transmit the identity of entity 105, id_i, the value of signed c_i, and the group element g^a, to entity 110.

Upon receiving the transmitted information, entity 110 will then proceed to verify c_i using a corresponding Verification function associated with the Self-Certified Identity Based Signature Scheme, SC-IBS.Verify( ) and the identity of entity 105, id_i. This is done by entity 110 applying the verification function to c_i and the identity id_i thereby producing SC-IBS.Verify(id_i, c_i) and if the verification fails, entity 110 will abort the process. Else, upon successfully verifying c_i, entity 110 will then proceed to select a random value b, where $b \in \mathbb{Z}_q^*$ and will proceed to compute c_j = SC-IBS.Sign(sk_j, g^a || g^b) where sk_j is a private key of entity 110 that was generated using the steps set out in Figure 3 .

Entity 110 then proceeds, at step 410, to transmit the value of signed group element c_j, and the group element g^b to entity 105.

Upon receiving the transmitted information, entity 105 will then proceed to verify c_j using a corresponding Verification function associated with the Self-Certified Identity Based Signature Scheme, SC-IBS.Verify( ) and the identity of entity 110, id_j. This is done by entity 105 applying the verification function to c_j together with the identity id_j thereby producing SC-IBS.Verify(id_j, c_j) and if the verification fails, entity 105 will abort the process. Else, entity 105 will calculate the shared secret k_{ij} where $k_{ij} = g^{a \cdot b}$, calculate a first key vk_i = KDF(k_{ij}) and calculate a first authentication data Ad_i = AdDF(vk_i). Once this is done entity 105 then calculates common session key SK as SK = KDF(k_{ij}).

Entity 105 then proceeds, at step 415, to transmit the first authentication data Ad_i to entity 110.

Upon receiving the first authentication data Ad_i, entity 110 will calculate the shared secret k_{ji} where $k_{ji} = g^{a \cdot b}$, calculate a second key vk_j = KDF(k_{ji}) and calculate a second authentication data Ad_j = AdDF(vk_j). Once this is done entity 110 then determines whether second authentication data Ad_j matches with the received first authentication data Ad_i. If a match is not found, the process aborts. Alternatively, if a match is found, entity 110 will calculate common session key SK as SK = KDF(k_{ji}).

Ephemeral DH - based Authenticated Key Exchange Protocol for Cross-Domain KGCs

In another embodiment of the ephemeral Diffie Hellman-based authenticated key exchange protocol, the key generation centres of entities 105 and 110 are from different domains (i.e. the two key generation centres have their own respective master secret keys and master public keys). In this embodiment, prior to transmitting the identity of entity 105, id_i, the value of signed c_i, and the group element g^a, to entity 110 at step 405, entity 105 will share the master public key of its key generation centre with entity 110 and similarly, entity 110 will share the master public key of its key generation centre with entity 105. In addition, entity 105 may negotiate with entity 110 to determine a generator g of an appropriate finite field group that is to be used. Regardless, the master public keys to be adopted by both entities must be known to each other and g must be determined prior to step 405 so that entities 105 and 110 are able to subsequently verify each other's' signatures and carry out ephemeral Diffie Hellman key exchange. Steps 410-415 then proceeds as described above.

Ephemeral DH - based Authenticated Key Exchange Protocol extended to TLS Protocol

In still yet another embodiment of the invention, the idea above may be used to extend Transport Layer Security (TLS) or Datagram Transport Layer Security (DTLS). In

particular, the steps above may be fitted to the TLS protocol between entity 105 and entity 110, based on the use of a self-certified Identity Based Signature scheme. In this embodiment of the invention, a self-certified IBS scheme is used in place of the DSS/ECDSA or RSA digital signature schemes in the conventional TLS handshake protocol; besides, set the Server Certificate message and the Client Message in the TLS protocol to be the entity 110's id_j and the entity 105's id_i, respectively, while the key specific data (KSDs) of entity 110 and the entity 105 are part of the respective entity's signature; other steps and operations in the TLS protocol follow the TLS specification with the accommodation of the straightforward due changes because of the use of self-certified Identity Based Signature. In this embodiment of the invention, entity 105' private key sk_i and entity 110's private key sk_j may be generated as per any above embodiment of generation of a private key, or as per the key generation process of existing self-certified IBS schemes such as ISO/IEC 29192-4 and IETF RFC, or as per the above embodiment of generation of private key with cross-domain KGCs.

In another embodiment of the ephemeral Diffie Hellman-based authenticated key exchange protocol option fields op_f1, op_f2, op_f3, op_f4, op_f5, op_f6 and op_f7 are used and may comprise identities of entities of the system where applicable or any application specific data as determined by the entities themselves.

With reference to Figure 4, entity 105 initiates the authentication process with entity 110 by first selecting a random value $a \in \mathbb{Z}_q^*$ and by computing a signed group element c_i whereby signed group element c_i is defined by c_i = SC-IBS.Sign(sk_i, g^a || op_f_1)) where SC-IBS.Sign( ) is a signing function for a Self-Certified Identity Based Signature scheme, sk_i is a private key of entity 105 that was generated using the steps set out in Figure 3 and g^a is the group element. In other words, group element g^a is signed using the function SC-IBS.Sign( ) and private key sk_i.

Entity 105 then proceeds, at step 405, to transmit an option field op_f2, the identity of entity 105, id_i, the value of signed c_i, and the group element g^a, to entity 110.

Upon receiving the transmitted information, entity 110 will then proceed to verify c_i using a corresponding Verification function associated with the Self-Certified Identity Based Signature scheme, SC-IBS.Verify( ) and the identity of entity 105, id_i. This is done by entity 110 applying the verification function to c_i and the identity id_i thereby producing SC-IBS.Verify(id_i, c_i) and if the verification fails, entity 110 will abort the process. Else, upon successfully verifying the signed cryptographic nonce c_i, entity 110 will then proceed to select a random value b, where $b \in \mathbb{Z}_q^*$ and will proceed to compute c_j = SC-IBS.Sign(sk_j, g^a

|| g^b || op_f3) where sk_j is a private key of entity 110 that was generated using the steps set out in Figure 3 .

Entity 110 then proceeds, at step 410, to transmit an option field op_f4, the value of signed c_j, and the group element g^b to entity 105.

Upon receiving the transmitted information, entity 105 will then proceed to verify c_j using a corresponding Verification function associated with the Self-Certified Identity Based Signature Scheme, SC-IBS.Verify( ) and the identity of entity 110, id_j. This is done by entity 105 applying the verification function to c_j together with the identity id_j thereby producing SC-IBS.Verify(id_j, c_j) and if the verification fails, entity 110 will abort the process. Else, entity 105 will calculate the shared secret k_{ij} where $k_{ij} = g^{a \cdot b}$, calculate a first key vk_i = KDF(k_{ij}, op_f5) and calculate a first authentication data Ad_i = AdDF(vk_i, op_f6). Once this is done entity 105 then calculates common session key SK as SK = KDF(k_{ij}, op_f7).

Entity 105 then proceeds, at step 415, to transmit the first authentication data Ad_i to entity 110.

Upon receiving the first authentication data Ad_i, entity 110 will calculate the shared secret k_{ji} where $k_{ji} = g^{a \cdot b}$, calculate a second key vk_j = KDF(k_{ji}, op_f5) and calculate a second authentication data Ad_j = AdDF(vk_j, op_f6). Once this is done entity 110 then determines whether second authentication data Ad_j matches with the received first authentication data Ad_i. If a match is not found, the process aborts. Alternatively, if a match is found, entity 110 will calculate common session key SK as SK = KDF(k_{ij}, op_f7).

In accordance with an embodiment of the invention, a method for generating a private key sk for a device participating in a self-certified identity based signature system comprises the following three steps:

Step 1, computing, by a secure server, parameters for the device based on a second random number r_{i2} generated by the secure server, a first set of components received from the device, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components comprises a first random number r_{i1} generated by the device;

Step 2, transmitting, by the secure server, the computed parameters to the device; and

Step 3, computing, by the device, the private key sk based on the received computed parameters and the random number r_{i1}.

In order to provide such a system or method, a process is needed for generating secret private keys for entities of the system, and for authenticating an entity of an entity-pair before a common session key is generated for encoding or signing digital messages between the entity-pair. The following description and Figures 4-6 describe embodiments of processes that provide processes in accordance with this invention.

Figure 5 illustrates process 500 that is performed by a secure server configured as a Key Generation Centre, a first entity “i" and a second entity “j” for generating secret private keys for entities of the system, and for authenticating an entity of an entity-pair before a common session key is generated for encoding or signing digital messages between the entity-pair. Process 500 begins at step 505 with the secure server generating a master secret key “x” and a master public key “y”. When first entity, i, registers itself with the secure server, the secure server will carry out the steps as illustrated in Figure 3 and as described in the description above to generate a private key, sk_i, for the first entity using the first entity’s identity, id_i. All this takes place at step 510.

At step 515, when the next entity, that is when second entity, j, registers itself with the secure server, the secure server will carry out the steps as illustrated in Figure 3 and as described in the description above to generate a private key, sk_j, for the second entity using the second entity’s identity, id_j.

The first and second entities then verifies information sent between entities using signing functions and corresponding verification functions associated with self-certified identity based signature schemes at step 520.

Once both entities are verified, a secret is then shared between entities at step 523. The shared secret is then utilized to generate a common session key for the entities. The generated common session key may then be used to sign or encode any digital messages that are exchanged between the first and second entities. Process 500 then ends.

The above is a description of embodiments of a system and process in accordance with the present invention as set forth in the following claims. It is envisioned that others may and will design alternatives that fall within the scope of the following claims.

CLAIMS:

1. A system for computing a private key sk for a device participating in a self-certified identity based signature system comprising:

a secure server configured to:

compute parameters for the device based on a second random number r_{i2} generated by the secure server, a first set of components received from the device, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components comprises a first random number r_{i1} generated by the device,

transmit the computed parameters to the device; and

the device configured to compute the private key sk based on the received computed parameters and the random number r_{i1}.

2. The system according to claim 1 wherein the step of computing the parameters for the device comprises:

retrieving an arbitrary first value R_{i1} and an identity of the device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

computing an arbitrary value of the device R_i and a first integer s_{i1}; and

setting the computed arbitrary value of the device R_i and the first integer s_{i1} as the parameters for the device,

whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the device R_i, the identity of the device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

3. The system according to claim 2 wherein the step of computing the private key sk comprises:

computing an integer s_i based on the first integer s_{i1} as retrieved from the computed parameters transmitted from the secure server, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and

forming the private key sk based on the arbitrary value of the device R_i and the integer s_i.

4. The system according to claims 2 or 3 wherein the arbitrary value of the device R_i is defined by $R_i = R_{i1} \cdot g^{r_{i2}}$ or $R_i = {R_{i1}}/{g^{r_{i2}}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$ and the first integer s_{i1} is defined by $s_{i1} = r_{i2} + xH(R_i, id_i)(mod\ q)$ or $s_{i1} = -r_{i2} + xH(R_i, id_i)(mod\ q)$ where *H*( ) is a collision-resistant hash function.

5. The system according to claim 4 wherein the integer s_i is defined by $s_i = s_{i1} + r_{i1}(mod\ q)$.

6. The system according to claims 2 or 3 wherein the arbitrary value of the device R_i is defined by $R_i = {g^{r_{i2}}}/{R_{i1}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$ and the first integer s_{i1} is defined by $s_{i1} = r_{i2} + xH(R_i, id_i)(mod\ q)$ where *H*( ) is a collision-resistant hash function.

7. The system according to claim 6 wherein the integer s_i is defined by $s_i = s_{i1} - r_{i1}(mod\ q)$.

8. The system according to claim 1 wherein the step of computing the parameters for the device comprises:

retrieving an arbitrary first value R_{i1}, an identity of the device id_i and a homomorphic encryption value *c* from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1} and the homomorphic encryption value *c* is generated by providing the first random number r_{i1} and a prime number q obtained from the parameters associated with the master public key *mpk* to an additive homomorphic encryption function *HEnc( )*;

setting an arbitrary value of the device R_i and a first integer s_{i1} as the parameters for the device,

whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed by providing the second random number r_{i2}, the homomorphic encryption value *c*, the master secret key *x*, the arbitrary value of the device R_i, the identity of the device id_i and the prime number q to the additive homomorphic encryption function *HEnc( )*.

9. The system according to claim 8 wherein the step of computing the private key sk comprises:

computing an integer s_i by applying a complementary homomorphic decryption function to the first integer s_{i1} as retrieved from the computed parameters transmitted from the secure server; and

forming the private key sk based on the arbitrary value of the device R_i and the integer s_i.

10. The system according to claims 8 or 9 wherein the arbitrary value of the device R_i is defined by $R_i = (R_{i1})^{r_{i2}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$, the homomorphic encryption value c is defined by $c = HEnc({r_{i1}}^{-1} \, mod \, q)$ and the first integer s_{i1} is defined by $s_{i1} = HEnc(r_{i2}) \cdot c^{xH(R_i, id_i) \, mod \, q}$ where HEnc( ) is the additive homomorphic encryption function.

11. The system according to claims 8 or 9 wherein the arbitrary value of the device R_i is defined by $R_i = (R_{i1})^{{r_{i2}}^{-1}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{r_{i1}}$ the homomorphic encryption value c is defined by $c = HEnc({r_{i1}}^{-1})$ and the first integer s_{i1} is defined by $s_{i1} = HEnc({r_{i2}}^{-1}) \cdot c^{xH(R_i, id_i) \, mod \, q}$ where HEnc( ) is the additive homomorphic encryption function.

12. The system according to claims 10 or 11 wherein the integer s_i is defined by $s_i = r_{i1} HDec(s_{i1})$; where HDec( ) is the complementary homomorphic decryption function.

13. The system according to claims 8 or 9 wherein the arbitrary value of the device R_i is defined by $R_i = (R_{i1})^{r_{i2}}$, the arbitrary first value R_{i1} is defined by $R_{i1} = g^{{r_{i1}}^{-1}}$, the homomorphic encryption value c is defined by $c = HEnc(r_{i1})$ and the first integer s_{i1} is defined by $s_{i1} = HEnc(r_{i2}) \cdot c^{xH(R_i, id_i) \, mod \, q}$ where HEnc( ) is the additive homomorphic encryption function.

14. The system according to claim 13 wherein the integer s_i is defined by $s_i = {r_{i1}}^{-1} HDec(s_{i1})$ where HDec( ) is the complementary homomorphic decryption function.

15. A system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme, the system comprising:

a secure server configured to instruct:

the first device to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and

the second device to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server;

the first device configured to:

sign a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G;

transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device;

upon receiving the transmission, the second device is configured to:

verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i,

sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where *b* is a random number generated by the first device, when the signed group element g^a is verified, and

transmit the signed group elements (g^a || g^b) and a group element g^b to the first device;

the first device is configured to:

verify the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j;

compute a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key

vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified;

generate the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function;

transmit the first authentication data Ad_i to the second device, such that upon receiving the first authentication data Ad_i, the second device is configured to:

compute a second shared secret k_{ji} based on the group element g^a and the group element *b*,

compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function,

compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function,

determine if the second authentication data Ad_j matches with the first authentication data $Ad_{i;}$ and

generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

16. The system according to claim 15 wherein the step of generating the first set of parameters for the first device comprises:

the secure server being configured to:

retrieve an arbitrary first value R_{i1} and an identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

compute an arbitrary value of the first device R_i and a first integer s_{i1}; and

set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device,

whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

17. The system according to claim 16 wherein the computing the private key sk_i comprises:

the first device being configured to:

compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*.; and

form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

18. The system according to claim 15 wherein the generating the second set of parameters for the second device comprises:

the secure server being configured to:

retrieve an arbitrary first value R_{j1} and an identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1};

compute an arbitrary value of the second device R_j and a first integer s_{j1}; and

set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device,

whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and

whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key *x*, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key *mpk*.

19. The system according to claim 18 wherein the computing the private key sk_j comprises:

the second device being configured to:

compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and

form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

20. A system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* participating in a self-certified identity based signature scheme, the system comprising:

a secure server configured to instruct:

the first device to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device,

wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and

the second device to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server;

the first device configured to:

sign a cryptographic nonce N_i using a self-certified Identity Based Signature Scheme and the private key sk_i;

transmit an identity of the first device id_i, the cryptographic nonce N_i and the signed cryptographic nonce N_i to the second device ;

upon receiving the transmission, the second device is configured to:

verify the signed cryptographic nonce N_i using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i,

sign cryptographic nonces (N_i || N_j) using the self-certified Identity Based Signature Scheme and the private key sk_j, where N_j is a cryptographic nonce, when the signed cryptographic nonce N_i is verified, and

transmit the signed cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j to the first device;

the first device is configured to :

verify the signed cryptographic nonces (N_i || N_j) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j, compute a first shared secret $k_{ij} = g^{sj \cdot si}$, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the cryptographic nonces N_i and N_j and the first key vk_i to an Authentication Data Deriving Function, when the signed cryptographic nonces (N_i || N_j) are verified;

generate the common session key SK by providing the first shared secret k_{ij} and the cryptographic nonces N_i and N_j to the Key Deriving Function;

transmit the first authentication data Ad_i to the second device;

upon receiving the first authentication data Ad_i, the second device is configured to:

compute a second shared secret $k_{ji} = g^{sj \cdot si}$,

compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function,

compute a second authentication data Ad_j by providing the key vk_j and the cryptographic nonces N_i and N_j to the Authentication Data Deriving Function,

determine if the second authentication data Ad_j matches with the first authentication data Ad_i ;and

generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

21. The system according to claim 20 wherein the generating the first set of parameters for the first device comprises:

the secure server being configured to:

retrieve an arbitrary first value R_{i1} and an identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

compute an arbitrary value of the first device R_i and a first integer s_{i1}; and

set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device,

whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

22. The system according to claim 21 wherein the computing the private key sk_i comprises:

the first device being configured to:

compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and

form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

23. The system according to claim 20 wherein the generating the second set of parameters for the second device comprises:

the secure server being configured to:

retrieve an arbitrary first value R_{j1} and an identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1};

compute an arbitrary value of the second device R_j and a first integer s_{j1}; and

set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device,

whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and

whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key *x*, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key *mpk*.

24. The system according to claim 23 wherein the computing the private key sk_j comprises:

the second device being configured to:

compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and

form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

25. A system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme, the system comprising:

a first secure server configured to instruct:

the first device to compute a private key sk_i based on a first set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server;

a second secure server configured to instruct:

the second device to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, a master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted to the second secure server,

wherein the first secure server is located in a different domain from the second secure server;

the first device configured to:

sign a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where a is a random number generated by the first device and g is a generator of a cyclic group G;

transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device ;

upon receiving the transmission, the second device is configured to:

verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i,

sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where b is a random number generated by the first device, when the signed group element g^a is verified, and

transmit the signed group elements (g^a || g^b) and a group element g^b to the first device;

the first device is configured to :

verify the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j;

compute a first shared secret k_{ij} based on the group element a and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified;

generate the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function;

transmit the first authentication data Ad_i to the second device;

upon receiving the first authentication data Ad_i, the second device is configured to:

compute a second shared secret k_{ji} based on the group element g^a and the group element *b*,

compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function,

compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function,

determine if the second authentication data Ad_j matches with the first authentication data Ad_i ; and

generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

26. The system according to claim 25 wherein the generating the first set of parameters for the first device comprises:

the first secure server being configured to:

retrieve an arbitrary first value R_{i1} and an identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

compute an arbitrary value of the first device R_i and a first integer s_{i1}; and

set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device,

whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key x_i, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key mpk_i.

27. The system according to claim 26 wherein the computing the private key sk_i comprises:

the first device being configured to:

compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key mpk_i; and

form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

28. The system according to claim 25 wherein the generating the second set of parameters for the second device comprises:

the second secure server being configured to:

retrieve an arbitrary first value R_{j1} and an identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1};

compute an arbitrary value of the second device R_j and a first integer s_{j1}; and

set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device,

whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and

whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key x_j, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key mpk_j.

29. The system according to claim 28 wherein the computing the private key sk_j comprises:

the second device being configured to:

compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key mpk_j; and

form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

30. A system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the system comprising:

a secure server configured to instruct:

the first device to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second

random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and

the second device to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server;

the first and second devices configured to use a self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_i and sk_j.

31. The system according to claim 30 wherein the generating the first set of parameters for the first device comprises:

the secure server being configured to:

retrieve an arbitrary first value R_{i1} and the identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

compute an arbitrary value of the first device R_i and a first integer s_{i1}; and

set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device,

whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

32. The system according to claim 31 wherein the computing the private key sk_i comprises:

the first device being configured to:

compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*; and

form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

33. The system according to claim 30 wherein the generating the second set of parameters for the second device comprises:

the secure server being configured to:

retrieve an arbitrary first value R_{j1} and the identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1};

compute an arbitrary value of the second device R_j and a first integer s_{j1}; and

set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device,

whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and

whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key *x*, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key *mpk*.

34. The system according to claim 33 wherein the computing the private key sk_j comprises:

the second device being configured to:

compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key *mpk*.; and

form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

35. A system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the system comprising:

a first secure server configured to instruct:

the first device to compute a private key sk_i based on a first set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server,

a second secure server configured to instruct:

the second device to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, the master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted to the second secure server,

wherein the first secure server is located in a different domain from the second secure server;

the first and second devices configured to use a self-certified Identity Based Signature Scheme to generate the common session key SK_{ij} for the TLS protocol between the first device and the second device, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_i and sk_j.

36. The system according to claim 35 wherein the generating the first set of parameters for the first device comprises:

the first secure server being configured to:

retrieve an arbitrary first value R_{i1} and the identity of the first device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

compute an arbitrary value of the first device R_i and a first integer s_{i1}; and

set the computed arbitrary value of the first device R_i and the first integer s_{i1} as the parameters for the first device,

whereby the arbitrary value of the first device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key x_i, the arbitrary value of the first device R_i, the identity of the first device id_i and a prime number q obtained from the parameters associated with the master public key mpk_i.

37. The system according to claim 36 wherein the computing the private key sk_i comprises:

the first device being configured to:

compute an integer s_i based on the first integer s_{i1} as retrieved from the first set of parameters, the first random number r_{i1}, and a prime number q as obtained from the parameters associated with the master public key mpk_i.; and

form the private key sk_i based on the arbitrary value of the first device R_i and the integer s_i.

38. The system according to claim 35 wherein the generating the second set of parameters for the second device comprises:

the second secure server being configured to:

retrieve an arbitrary first value R_{j1} and the identity of the second device id_j from the second set of components, wherein the arbitrary first value R_{j1} is generated based on the first random number r_{j1};

compute an arbitrary value of the second device R_j and a first integer s_{j1}; and

set the computed arbitrary value of the second device R_j and the first integer s_{j1} as the parameters for the second device,

whereby the arbitrary value of the second device R_j is computed based on the arbitrary first value R_{j1} and the second random number r_{j2}; and

whereby the first integer s_{j1} is computed based on the second random number r_{j2}, the master secret key x_j, the arbitrary value of the second device R_j, the identity of the second device id_j and a prime number q obtained from the parameters associated with the master public key mpk_j.

39. The system according to claim 38 wherein the computing the private key sk_j comprises:

the second device being configured to:

compute an integer s_j based on the first integer s_{j1} as retrieved from the second set of parameters, the first random number r_{j1}, and a prime number q as obtained from the parameters associated with the master public key mpk_j; and

form the private key sk_j based on the arbitrary value of the second device R_j and the integer s_j.

40. The system according to claim 35 wherein before the secure server is configured to compute parameters for the device based on the second random number r_{i2} generated by the secure server, the secure server is configured to:

receive a zero-knowledge proof result from the device, whereby the zero-knowledge proof result is generated by the device using the first random number r_{i1} and a system parameter λ;

determine from the zero-knowledge proof result if the first random number r_{i1} is equal or less than the system parameter λ; and

compute parameters for the device based on the second random number r_{i2} generated by the secure server, when the first random number r_{i1} is equal or less than the system parameter λ.

41. A system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the system comprising:

a secure server configured to:

generate a private key sk_i for the first device based on an identity of the first device id_i and generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme; and

transmit the private key sk_i to the first device and transmit the private key sk_j to the second device;

the first and second devices configured to use the same self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is included in the Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_i and sk_j.

42. A system for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the system comprising:

a first secure server configured to:

generate a private key sk_i for the first device based on an identity of the first device id_i using a self-certified Identity Based Signature Scheme, and transmit the private key sk_i to the first device;

a second secure server configured to:

generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme, and transmit the private key sk_j to the second device;

wherein the first secure server is located in a different domain from the second secure server,

the first and second devices configured to use the same self-certified Identity Based Signature Scheme with different parameters or different self-certified Identity Based Signature Schemes to generate the common session key SK for the TLS or DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is included in the Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by sk_i and sk_j.

43. A secure server configured to compute a private key sk for a device participating in a self-certified identity based signature system comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

compute parameters for the device based on a second random number r_{i2} generated by the secure server, a first set of components received from the device, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components comprises a first random number r_{i1} generated by the device,

transmit the computed parameters to the device such that the device is configured to compute the private key sk based on the received computed parameters and the random number r_{i1}.

44. The secure server according to claim 43 wherein the instructions to compute the parameters for the device comprises:

instructions for directing the processor to:

retrieve an arbitrary first value R_{i1} and an identity of the device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

compute an arbitrary value of the device R_i and a first integer s_{i1}; and

set the computed arbitrary value of the device R_i and the first integer s_{i1} as the parameters for the device,

whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

45. The secure server according to claim 43 wherein the instructions to compute the parameters for the device comprises:

instructions for directing the processor to:

retrieve an arbitrary first value R_{i1}, an identity of the device id_i and a homomorphic encryption value *c* from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1} and the homomorphic encryption value *c* is generated by providing the first random number r_{i1} and a prime number q obtained from the parameters associated with the master public key *mpk* to an additive homomorphic encryption function *HEnc( )*;

set an arbitrary value of the device R_i and a first integer s_{i1} as the parameters for the device,

whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed by providing the second random number r_{i2}, the homomorphic encryption value *c*, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and the prime number q to the additive homomorphic encryption function *HEnc( )*.

46. The secure server according to anyone of claims 43-45 wherein before the instructions to compute parameters for the device based on the second random number r_{i2} generated by the secure server, the secure server comprises:

instructions for directing the processor to:

receive a zero-knowledge proof result from the device, whereby the zero-knowledge proof result is generated by the device using the first random number r_{i1} and a system parameter λ;

determine from the zero-knowledge proof result if the first random number r_{i1} is equal or less than the system parameter λ; and

compute parameters for the device based on the second random number r_{i2} generated by the secure server, when the first random number r_{i1} is equal or less than the system parameter λ.

47. A method for computing a private key sk for a device participating in a self-certified identity based signature system comprising:

computing, by a secure server, parameters for the device based on a second random number r_{i2} generated by the secure server, a first set of components received from the device, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components comprises a first random number r_{i1} generated by the device,

transmitting the computed parameters to the device such that the device computes the private key sk based on the received computed parameters and the random number r_{i1}.

48. The method according to claim 47 wherein the computing the parameters for the device comprises:

retrieving, by the secure server, an arbitrary first value R_{i1} and an identity of the device id_i from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1};

computing an arbitrary value of the device R_i and a first integer s_{i1}; and

setting the computed arbitrary value of the device R_i and the first integer s_{i1} as the parameters for the device,

whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed based on the second random number r_{i2}, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and a prime number q obtained from the parameters associated with the master public key *mpk*.

49. The method according to claim 47 wherein the computing the parameters for the device comprises:

retrieving, by the secure server, an arbitrary first value R_{i1}, an identity of the device id_i and a homomorphic encryption value *c* from the first set of components, wherein the arbitrary first value R_{i1} is generated based on the first random number r_{i1} and the homomorphic encryption value *c* is generated by providing the first random number r_{i1} and a prime number q obtained from the parameters associated with the master public key *mpk* to an additive homomorphic encryption function *HEnc( )*;

setting an arbitrary value of the device R_i and a first integer s_{i1} as the parameters for the device,

whereby the arbitrary value of the device R_i is computed based on the arbitrary first value R_{i1} and the second random number r_{i2}; and

whereby the first integer s_{i1} is computed by providing the second random number r_{i2}, the homomorphic encryption value *c*, the master secret key *x*, the arbitrary value of the first device R_i, the identity of the device id_i and the prime number q to the additive homomorphic encryption function *HEnc( )*.

50. A method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme comprising:

receiving, by the first device, instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and

signing, by the first device, a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G;

transmitting an identity of the first device id_i, the group element g^a and the signed group element g^a to the second.

51. The method according to claim 50, wherein the method further comprises:

receiving a signed group elements (g^a || g^b) and a group element g^b from the second device;

verifying the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j;

computing a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified;

generating the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function;

transmitting the first authentication data Ad_i to the second device.

52. A first device for generating a common session key SK for encoding digital communications between the first device and a second device that are participating in a self-certified identity based signature scheme comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

receive instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and

sign a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G;

transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second.

53. The first device according to claim 52, wherein the instructions comprises

instructions for directing the processor to:

receive a signed group elements (g^a || g^b) and a group element g^b from the second device;

verify the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j;

compute a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified;

generate the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function;

transmit the first authentication data Ad_i to the second device.

54. A method for generating a common session key SK for encoding digital communications between a first device i and a second device j that are participating in a self-certified identity based signature scheme comprising:

receiving, by the second device, instructions from the secure server to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server;

receiving an identity of the first device id_i, the group element g^a and the signed group element g^a from the first ;

verifying the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device idi;

signing group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where b is a random number generated by the first device, when the signed group element g^a is verified; and

transmitting the signed group elements (g^a || g^b) and a group element g^b to the first device.

55. The method according to claim 54, wherein the method further comprises:

receiving a first authentication data Ad_i from the first device;

computing a second shared secret k_{ji} based on the group element g^a and the group element g^b;

computing a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function;

computing a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function;

determining if the second authentication data Ad_j matches with the first authentication data Ad_i; and

generating the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

56. A second device for generating a common session key SK for encoding digital communications between a first device and the second device that are participating in a self-certified identity based signature scheme comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

receive instructions from the secure server to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key *x* and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server;

receive an identity of the first device id_i, the group element g^a and the signed group element g^a from the first ;

verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i;

sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where b is a random number generated by the first device, when the signed group element g^a is verified; and

transmit the signed group elements (g^a || g^b) and a group element g^b to the first device.

57. The second device according to claim 56, wherein the instructions comprises

instructions for directing the processor to:

receive a first authentication data Ad_i from the first device;

compute a second shared secret k_{ji} based on the group element g^a and the group element g^b;

compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function;

compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function;

determine if the second authentication data Ad_j matches with the first authentication data Ad_i; and

generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

58. A method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* participating in a self-certified identity based signature scheme comprising:

receiving, by the first device, instructions from a secure server, to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server, and

signing, by the first device, a cryptographic nonce N_i using a self-certified Identity Based Signature Scheme and the private key sk_i;

transmitting an identity of the first device id_i, the cryptographic nonce N_i and the signed cryptographic nonce N_i to the second device. such that, upon receiving the transmission, the second device is configured to:

verifying the signed cryptographic nonce N_i using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i;

signing cryptographic nonces (N_i || N_j) using the self-certified Identity Based Signature Scheme and the private key sk_j, where N_j is a cryptographic nonce, when the signed cryptographic nonce N_i is verified; and

transmitting the signed cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j to the first device.

59. The method according to claim 58, wherein the method further comprises:

receiving a cryptographic nonces (Ni || Nj) and the cryptographic nonce Nj from the second device;

verifying the signed cryptographic nonces (N_i || N_j) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j, compute a first shared secret $k_{ij} = g^{sj \cdot si}$, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the cryptographic nonces N_i and N_j and the first key vk_i to an Authentication Data Deriving Function, when the signed cryptographic nonces (N_i || N_j) are verified;

generating the common session key SK by providing the first shared secret k_{ij} and the cryptographic nonces N_i and N_j to the Key Deriving Function;

transmitting the first authentication data Ad_i to the second device.

60. A first device for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* participating in a self-certified identity based signature scheme comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

receive instructions from a secure server, to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server; and

sign a cryptographic nonce N_i using a self-certified Identity Based Signature Scheme and the private key sk_i; and

transmit an identity of the first device id_i, the cryptographic nonce Ni and the signed cryptographic nonce Ni to the second device.

61. The first device according to claim 60, wherein the instructions comprises

instructions for directing the processor to:

receive a cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j from the second device;

verify the signed cryptographic nonces (N_i || N_j) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j, compute a first shared secret $k_{ij} = g^{sj \cdot si}$, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the cryptographic nonces N_i and N_j and the first key vk_i to an Authentication Data Deriving Function, when the signed cryptographic nonces (N_i || N_j) are verified;

generate the common session key SK by providing the first shared secret k_{ij} and the cryptographic nonces N_i and N_j to the Key Deriving Function; and

transmit the first authentication data Ad_i to the second device.

62. A second device for generating a common session key SK for encoding digital communications between a first device and the second device participating in a self-certified identity based signature scheme comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

receive instructions from the secure server to compute a private key sk_j based on a second set of parameters received from the secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the secure server based on a second random number r_{j2} generated by the secure server, a second set of components comprising the first random number r_{j1}, the master secret key x and the parameters associated with a master public key *mpk*, wherein the second set of components is generated by the second device and transmitted to the secure server;

receive an identity of the first device id_i, the cryptographic nonce N_i and the signed cryptographic nonce N_i from the first device;

verify the signed cryptographic nonce N_i using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device idi;

sign cryptographic nonces (N_i || N_j) using the self-certified Identity Based Signature Scheme and the private key sk_j, where N_j is a cryptographic nonce, when the signed cryptographic nonce N_i is verified; and

transmit the signed cryptographic nonces (N_i || N_j) and the cryptographic nonce N_j to the first device.

63. The second device according to claim 62, wherein the instructions comprises instructions for directing the processor to:

receive a first authentication data Ad_i from the first device;

compute a second shared secret $k_{ji} = g_{sj} \cdot s_i$;

compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function;

compute a second authentication data Ad_j by providing the key vk_j and the cryptographic nonces N_i and N_j to the Authentication Data Deriving Function;

determine if the second authentication data Ad_j matches with the first authentication data Ad_i; and

generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

63. A method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme, the system comprising:

receiving, by the first device instructions from a first secure server to compute a private key sk_i based on a first set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server;

wherein the first secure server is located in a different domain from the second secure server;

signing, by the first device, a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G;

transmitting an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device.

64. The method according to claim 63, wherein the method further comprises:

receiving a signed group elements (g^a || g^b) and a group element g^b from the second device;

verifying the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j;

computing a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified;

generating the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; and

transmitting the first authentication data Ad_i to the second device.

65. A first device for generating a common session key SK for encoding digital communications between the first device and a second device that are participating in a self-certified identity based signature scheme, the first device comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

receive instructions from a first secure server to compute a private key sk_i based on a first set of parameters received from the first secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the first secure server based on a second random number r_{i2} generated by the first secure server, a first set of components comprising the first random number r_{i1}, a master secret key x_i and parameters associated with a master public key mpk_i, wherein the first set of components is generated by the first device and transmitted to the first secure server;

wherein the first secure server is located in a different domain from the second secure server;

sign, by the first device, a group element g^a using a self-certified Identity Based Signature Scheme and the private key sk_i, where *a* is a random number generated by the first device and *g* is a generator of a cyclic group G; and

transmit an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device.

66. The first device according to claim 65, wherein the instructions comprises instructions for directing the processor to:

receive a signed group elements (g^a || g^b) and a group element gb from the second device;

verify the signed group elements (g^a || g^b) using the verification function associated with the self-certified Identity Based Signature Scheme and the identity of the second device id_j;

compute a first shared secret k_{ij} based on the group element *a* and the group element g^b, compute a first key vk_i by providing the first shared secret k_{ij} to a Key Deriving Function, and compute a first authentication data Ad_i by providing the first key vk_i to an Authentication Data Deriving Function, when the signed group elements (g^a || g^b) are verified;

generate the common session key SK by providing the first shared secret k_{ij} to the Key Deriving Function; and

transmit the first authentication data Ad_i to the second device.

67. A method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in a self-certified identity based signature scheme, the method comprising:

receiving, by the second device instructions from a second secure server to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, a master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted to the second secure server;

receiving an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device ;

verifying the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i,

signing group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where *b* is a random number generated by the first device, when the signed group element g^a is verified, and

transmitting the signed group elements (g^a || g^b) and a group element g^b to the first device.

68. The method according to claim 67, wherein the method further comprises:

receiving a first authentication data Ad_i to from the first device;

computing a second shared secret k_{ji} based on the group element g^a and the group element b,

computing a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function,

computing a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function,

determining if the second authentication data Ad_j matches with the first authentication data Ad_i; and

generating the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

69. A second device for generating a common session key SK for encoding digital communications between a first device and the second device that are participating in a self-certified identity based signature scheme, the second device comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

receive instructions from a second secure server to compute a private key sk_j based on a second set of parameters received from the second secure server, and a random number r_{j1} generated by the second device, wherein the second set of parameters is generated by the second secure server based on a second random number r_{j2} generated by the second secure server, a second set of components comprising the first random number r_{j1}, a master secret key x_j and the parameters associated with a master public key mpk_j, wherein the second set of components is generated by the second device and transmitted to the second secure server;

receive an identity of the first device id_i, the group element g^a and the signed group element g^a to the second device;

verify the signed group element g^a using a verification function associated with the self-certified Identity Based Signature Scheme and the identity of the first device id_i,

sign group elements (g^a || g^b) using the self-certified Identity Based Signature Scheme and the private key sk_j, where b is a random number generated by the first device, when the signed group element g^a is verified, and

transmit the signed group elements (g^a || g^b) and a group element g^b to the first device.

70. The second device according to claim 69, wherein the instructions comprises instructions for directing the processor to:

receive a first authentication data Ad_i from the first device;

compute a second shared secret k_{ji} based on the group element g^a and the group element g^b,

compute a second key vk_j by providing the second shared secret k_{ji} to the Key Deriving Function,

compute a second authentication data Ad_j by providing the key vk_j to the Authentication Data Deriving Function,

determine if the second authentication data Ad_j matches with the first authentication data Ad_i; and

generate the common session key SK by providing the second shared secret k_{ji} to the Key Deriving Function, when the second authentication data Ad_j matches with the first authentication data Ad_i.

71. A method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the method comprising:

receiving, by the first device instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server; and

communicating, by the second device, to generate the common session key SK for the TLS protocol or the DTLS protocol by using a self-certified Identity Based Signature Scheme, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by a sk_j and the sk_i; wherein the sk_j is a private key computed by the second device.

72. A first device for generating a common session key SK for encoding digital communications between the first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the first device comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

receive instructions from a secure server to compute a private key sk_i based on a first set of parameters received from the secure server, and a random number r_{i1} generated by the first device, wherein the first set of parameters is generated by the secure server based on a second random number r_{i2} generated by the secure server, a first set of components comprising the first random number r_{i1}, a master secret key *x* and parameters associated with a master public key *mpk*, wherein the first set of components is generated by the first device and transmitted to the secure server; and

communicate with the second device to generate the common session key SK for the TLS protocol or the DTLS protocol by using a self-certified Identity Based Signature Scheme, wherein an identity of the first device id_i is included in the first device's Certificate message and the identity of the second device id_j is included in the second device's Certificate message; wherein the self-certified Identity Based Signature Scheme are dictated by a sk_j and the sk_i; wherein the sk_j is a private key computed by the second device.

73. A method for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the method comprising:

generating, by a secure server, a private key sk_i for the first device based on an identity of the first device id_i and generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme; and

transmitting the private key sk_i to the first device and transmit the private key sk_j to the second device such that the first and second devices are configured to use the same self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is included in the

Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_j and the sk_i.

74. A secure server for generating a common session key SK for encoding digital communications between a first device *i* and a second device *j* that are participating in an extended Transport Layer Security (TLS) protocol or an extended Datagram Transport Layer Security protocol (DTLS), the secure server comprising:

a processor; and

a non-transitory media readable by the processor, the media storing instructions that when executed by the processor, cause the processor to:

generate a private key sk_i for the first device based on an identity of the first device id_i and generate a private key sk_j for the second device based on an identity of the second device id_j, using a self-certified Identity Based Signature Scheme; and

transmit the private key sk_i to the first device and transmit the private key sk_j to the second device such that the first and second devices are configured to use the same self-certified Identity Based Signature Scheme to generate the common session key SK for the TLS protocol or the DTLS protocol between the first device and the second device, wherein the identity of the first device id_i is included in the Certificate message of the first device and the identity of the second device id_j is included in the Certificate message of the second device; wherein the self-certified Identity Based Signature Scheme are dictated by the sk_j and the sk_i.