

ANTI-EROSION SYSTEM OF GRATE IN STOCKER TYPE INCINERATOR

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to, in general, a fire grate assembly for stoker incinerators, and more particularly, to a fire grate assembly capable of preventing stationary and movable grate members from coming into direct contact with each other resulting in deteriorating wear, thus allowing the
10 grate members to be free from being changed with new ones.

Description of the Prior Art

As well known to those skilled in the art, conventional incinerators for burning refuse are typically classified into
15 three types: stoker incinerators, rotary kiln incinerators and fluidized bed incinerators. The three types of incinerators are selectively used according to the kind of refuse and desired refuse treatment capacity.

Generally, stoker incinerators are preferably used for
20 burning large amounts of municipal refuse, while fluidized bed incinerators are in the early stages of being used practically.

Such stoker incinerators are classified into various types according to both the types of fire grate assemblies and the

construction of combustion furnaces. When such fire grate assemblies are designed, it is necessary to consider the installation area of a stoker incinerator, calorific power of refuse, the circulation type of combustion gas, and
5 configuration and expected loaded conditions of the grate assembly, such as the weight of the load, because the operational functions and characteristics of such fire grate assemblies are different from each other.

Fig. 1 is a schematic view showing the construction of
10 a conventional stoker incinerator.

As shown in Fig. 1, refuse, piled up in a refuse pit 2, is primarily measured prior to being fed into a hopper 4 by a traveling crane 3. Thereafter, the refuse of the hopper 4 are moved to the top portion of a fire grate assembly 6.
15 The refuse is mixed with the previously burnt refuse of the grate assembly 6, thereby being dried and burnt simultaneously. In addition, the refuse, disposed at the top portion of the grate assembly 6, is gradually moved to the bottom portion of the fire grate assembly 6. Ashes,
20 produced from the refuse completely burnt during the movement of the refuse along the grate assembly 6, are dropped into a re-treatment facility by a clinker roller 33 of Fig. 2 and are fed into an ash bunker 8.

Primary combustion air or atmospheric air, necessary
25 for the incineration of the refuse, is forcibly intaken into the grate assembly 6 through the refuse pit 2 by a force draft

fan 7, thereby preventing noxious odor from being exhausted into the atmosphere. In such a case, the intaken primary combustion air is heated by an air heater prior to being introduced into a combustion chamber of the incinerator through the fire grate assembly. The intaken air is divided into four to six sections capable of being separately controlled.

In addition, secondary combustion air, which is about 20 to 40% of the supplied air, is discharged from the side
10 portion of the incinerator into the combustion chamber, thereby completely incinerating the incompletely burnt refuse.

Combustion gas, having a high temperature and being produced from the burnt refuse, passes into a combustion
15 gas cooling facility and an exhaust gas treatment facility through first and second combustion chambers.

The incinerator also comprises a boiler facility 11 and an antipollution facility, including both a dust collector 13 and a stack 15. The boiler facility 11 is used for recovering
20 heat from the combustion gas and cooling the gas, while the antipollution facility is used for removing pollutants from the combustion gas. Also, the incinerator further comprises subsidiary facilities, such as conveyer equipment for feeding, piling up and discharging dusts and ashes, a sewage
25 treatment facility for biologically or chemically treating sewage from the incinerator, plumbing equipment for

supplying water into the incinerator and draining sanitary sewage, and supply equipment for feeding compressed air and fuels, etc.

Thus, it is necessary to maintain the temperature of the
5 combustion gas, introduced from a cooling device, lower than 300C so as to prevent the above equipment and facilities from being corroded.

Fig. 2 is a view illustrating the fire grate assembly 6 for feeding and agitating the refuse.

10 The grate assembly 6 comprises a plurality of uniformly-spaced stationary and movable grate members 31 and 32, which are alternately and inclinedly arranged in the assembly 6.

The movable grate members 32 push upwardly the
15 lower portion of the refuse. However, the refuse, disposed at the top portion of the grate assembly 6, is also moved downwardly along the assembly 6 due to gravity. Therefore, the refuse is moved upwardly and downwardly, thus being effectively agitated.

20 The stationary grate members 31 are fixedly mounted to the incinerator, while the movable grate members 32 are movably mounted to the incinerator in such a manner that they reciprocate linearly while being in contact with the stationary grate members 31, respectively. Due to such a
25 linear reciprocating motion of the movable grate members 32, the refuse on the fire grate assembly 6 is continuously

agitated, thereby effectively improving the refuse combustion efficiency.

However, the stationary and movable grate members 31 and 32 are brought into frictional contact with each other and the movable members 32 are moved on the top surfaces of the stationary members 31. Thus, each surface of the stationary and movable grate members 31 and 31 is irregularly abraded.

Therefore, the above fire grate assembly is problematic in that the combustion pressure of the incinerator is reduced because the primary burning air, supplied to the grate assembly 6 upwardly, leaks through the gaps defined between the abraded surfaces of the grate members 31 and 32. Also, the movable grate members 32 may fail to effectively perform their linear reciprocating motion and fail to mix the refuse because the refuse is introduced into the gaps between the abraded surfaces of the grate members 31 and 32. In such a case, the refuse is incompletely burnt. As a result, poisonous gas may be generated, which is harmful to the human body.

Such abraded grate members 31 and 32 require frequent changing with new ones, thus shortening the life span of the fire grate assembly and forcing the owner to replace an existing grate assembly with a new one at excessive costs.

SUMMARY OF THE INVENTION

Accordingly, the present invention has been made with the above problems occurring in the prior art in mind, and an object of the present invention is to provide a fire grate assembly for stoker incinerators, which replaces the abraded
5 portion of the fire grate assembly without changing the assembly with a new fire grate assembly, thereby decreasing the cost of repairs.

In order to accomplish the above object, the present
10 invention provides a fire grate assembly for stoker incinerators, comprising a plurality of stationary and movable grate members alternately arranged in the fire grate assembly, further comprising: means for spacing the stationary grate members from the movable grate members
15 while allowing the movable grate members to be linearly movable relative to the stationary grate members, the spacing means being detachably mounted to each of the movable grate members, thus being replaceable with a new one.

20 In the preferred embodiment, the spacing means comprises: a liner plate detachably mounted to an end of each of the movable grate members.

The liner plate has a countersunk hole, thus being bolted to the end of each of the movable grate members.

BRIEF DESCRIPTION OF THE DRAWINGS

The above object, and other features and advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

Fig. 1 is a view illustrating the construction of a conventional stoker incinerator;

Fig. 2 is a side view of a typical fire grate assembly included in such an incinerator; and

Fig. 3 is an exploded perspective view of a movable grate member of the fire grate assembly, showing the structure for selectively replacing an abraded liner plate with a new one in accordance with the preferred embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

In the present invention, the general shape and operation of the stoker incinerator remains the same as in the prior art incinerator and further explanation is thus not deemed necessary, but the construction of a fire grate assembly included in such an incinerator is altered to easily replace an abraded liner plate of the assembly with a new one as follows.

Fig. 3 is a view illustrating the construction of a movable grate member according to the present invention.

In Fig. 3, the movable grate member 32 of this invention is turned over for easy description. Such a
5 movable grate member 32 includes a liner plate 22 and a plurality of bolts 23. That is, the liner plate 22 is detachably mounted to the end portion 21 of the grate member 32 being in contact with a stationary grate member.

In addition, a plurality of countersunk holes are
10 formed on the liner plate 22 so as to be bolted to the end of each of the movable grate member 32 by the bolts 23.

Thus, even when both the plate 22 and the stationary grate members are excessively abraded during the linear reciprocating motion of the movable grate member 23, the
15 bolts 23 and movable grate 32 are free from being abraded.

As mentioned above, the fire grate assembly for stoker incinerators in accordance with the present invention is provided with a liner plate capable of preventing stationary and movable grate members from coming into direct contact
20 with each other resulting in deteriorating wear, thereby allowing the fire grate members to be free from being changed with new ones.

Although the preferred embodiments of the present invention have been disclosed for illustrative purposes, those
25 skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing

from the scope and spirit of the invention as disclosed in the accompanying claims.



WHAT IS CLAIMED IS:

1. A fire grate assembly for stoker incinerators, comprising a plurality of stationary and movable grate members alternately arranged in the fire grate assembly,
5 further comprising:

means for spacing said stationary grate members from said movable grate members while allowing said movable grate members to be linearly movable relative to said stationary grate members, said spacing means being
10 detachably mounted to each of said movable grate members, thus being replaceable with a new one.

2. The fire grate assembly according to Claim 1, wherein said spacing means comprises:

a liner plate detachably mounted to an end of each of
15 said movable grate members.

3. The fire grate assembly according to Claim 2, wherein said liner plate has a countersunk hole, thus being bolted to the end of each of said movable grate members.