20011022-L

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
28 December 2000 (28.12.2000)

PCT

(10) International Publication Number
WO 00/79521 A1

(51) International Patent Classification⁷: G11B 5/02, H03K 17/66

(21) International Application Number: PCT/EP00/05107

(22) International Filing Date: 2 June 2000 (02.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
99401547.7 22 June 1999 (22.06.1999) EP

(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors: VEENSTRA, Hugo; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LE, Luan; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: VAN DER KRUK, Willem, L.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(81) Designated States *(national)*: JP, KR, SG.

(84) Designated States *(regional)*: European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published:
— *With international search report.*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WRITE DRIVE APPARATUS



(57) Abstract: The invention provides a write driver circuit for writing an information signal on a magnetic record carrier. The write driver circuit comprises a first and a second input terminal (20,22) for receiving the information signal. A first current sink (24) is available, having a first transistor (T3) of a first type, having a first main electrode coupled to the first point of constant potential (+), having a second main electrode coupled to the first input (34) of a write head combination (32) via a first impedance (38), and a control electrode coupled to the first input terminal (20). A second current sink (28) is available having a second transistor (T4) of the first type, having a first main electrode coupled to the first point of constant potential (+), having a second main electrode coupled to the second input (36) of the write head combination via a second impedance (42), and a control electrode coupled to the second input terminal (22). A first current source (26) is available having a third transistor (T1) of the first type, having a first main electrode coupled to the first input (34) of the write head combination, having a second main electrode coupled to a second point of constant potential (-), and a control electrode coupled to the first input terminal (20). Further, a second current source (30) is available having a fourth transistor (T2) of the first type, having a first main electrode coupled to the second input (36) of the write head combination, having a second main electrode coupled to the second point of constant potential (-), and a control electrode coupled to the second input terminal (22).

WO 00/79521 A1

162162

G00002