

Description

Method and arrangement for designing the control of a complete process

5

The invention relates to a method and an arrangement for designing the control of a complete process which comprises a number of individual processes.

10

The control of a complex technical installation or, respectively, of a system (complete process) comprises a number of smaller control units which are provided for certain parts (individual processes) of the installation or, respectively, of the system. A first control unit for a first individual process is restricted in this case to this individual process. The same applies to a second control for a second individual process. Even if an interplay of the first control with the second control functions largely without errors, this does not guarantee that an error-free operation of the complete installation is still guaranteed with a slight modification of the first or of the second individual process. Thus, a small change in a process or the addition of a third process can lead to conflicts and blocking between the processes which can only be empirically verified. In this context, it is possible that a faulty state of the complete process overcomes an empirical test and thus remains undetected. This is not acceptable especially with regard to a critical installation with respect to safety since it must be guaranteed in every case that no unpredicted event occurs in the interplay of the processes.

35 Apart from the unauthorized states to be avoided, there are in the sequence of a process so-called authorized states which should occur exclusively for the process if it is functioning correctly.

It is the object of the invention to specify a method and an arrangement for designing the control of a complete process in which it is (formally) ensured that there is no impediment to the individual processes
5 and only authorized states are occupied.

This object is achieved in accordance with the features of the independent claims.

Within the context of the invention, a method for designing the control of a complete process which
10 comprises a number of individual processes is specified. In the method, functionalities of the individual processes are identified. Furthermore, a validation is performed by automatically verifying an interplay of the functionalities in accordance with an
15 input to the complete process, to the effect that each individual process is not disturbed during the operation. From the result of the validation, data for controlling the complete process are determined.

An advantage of the method consists in that it
20 is ensured in the step of validation that each individual process can run undisturbed. A further advantage consists in the automatic generation of data for controlling the complete process. Thus, data for controlling the complete process are systematically
25 generated with the aid of the method.

An embodiment consists in that a sequence optimization is performed after the validation. Thus, it is certainly an advantage that individual processes can run undisturbed and another advantage consists in
30 that the several individual processes run time-optimized if possible. It is the aim of the sequence optimization to carry out the performance of predetermined actions of the several individual processes in parallel and in the shortest possible time
35 without disturbances.

A further development consists in that the data for controlling the complete process are determined in the form of an executable code. This ensures that the result of the validation and possibly of the sequence optimization flows completely automatically into the control of the complete process. For example, a program code written in the programming language C or the programming language C++ is generated which initiates or ensures the control of the complete process.

In particular, the advantage becomes noticeable in the generation of executable code if functionalities of the individual processes are also provided in the form of respective program units. If a number of functionalities of a number of individual processes in each correspond to at least one program unit, the data which were generated in the form of executable codes are used for controlling the coordination of the individual program units or, respectively, the executable code uses the interfaces, e.g. function calls or method calls, provided by the program units.

It is also a further development that an individual process is disturbed if one of the following conditions is met:

- a) The individual process is blocked by another individual process. In the case of the blocking, two individual processes wish to use one physical resource in different ways. In such a case, blocking occurs since the resource cannot meet the requirements of both individual processes at the same time.
- b) The individual process reaches an unauthorized state or a state endangering the operation of the complete system. It is an essential requirement for a critical application with respect to safety that no hazardous states are assumed.

In the context of the invention, an arrangement for controlling a complete process is also specified, which complete process comprises a number of individual processes, a processor unit being provided which is set
5 up in such a manner that functionalities of the individual processes can be identified. Furthermore, a validation can be performed by automatically verifying an interplay of the functionalities in accordance with an input to the complete process to the effect that
10 each individual process is not impeded during the operation. Finally, the data resulting from the result of the validation can be used for controlling the complete process.

This arrangement is suitable, in particular,
15 for carrying out the method according to the invention or one of its further developments explained above.

Further developments of the invention are also obtained from the dependent claims.

In the text which follows, exemplary
20 embodiments of the invention are shown and explained with reference to the drawing, in which:

Fig. 1 shows a turret head of an automatic placement machine;

Fig. 2 shows steps of a method for generating the
25 control of a complete process;

Fig. 3 shows a state machine which represents the system behavior of the "scan" operation;

Fig. 4 shows a state machine which represents the specific system behavior of the scan test;

Fig. 5 shows a state machine which represents a sequential processing of the vacuum test and of the scan test;

5 Fig. 6 shows two state machines which represent a parallel processing of the vacuum test and of the scan test;

Fig. 7 shows a number of state machines which represent a system behavior;

10 Fig. 8 shows a state machine which represents a specific system behavior;

Fig. 9 shows two state machines which in each case represent specific system behavior for the vacuum test and the scan test;

Fig. 10 shows a state machine for the complete process.

15 Figure 1 shows a turret head 101 of an automatic placement machine. The turret head 101 accepts components and places them at a predetermined target position. The turret head contains 12 vacuum pipettes 102 which are used as receptacle and placement
20 tool. If the turret head 101 is used for a prolonged period, wear occurs, the vacuum pipettes become dirty and worn. Accordingly, it is necessary to perform periodic tests in order to determine the state of the vacuum pipettes 102 and to exchange them, if necessary.
25 Two different tests are performed by two different C programs. A vacuum test 103 is used for finding out whether the respective vacuum pipette 102 can still generate the intended vacuum; a scan test 104 indicates the extent to which the individual vacuum pipette 102
30 is subject to physical wear and whether it needs to be exchanged. For the subsequent observations, the scan test 104 and the

vacuum test 103 access one and the same resource: the rotation of the turret head 101.

The text which follows explains how the control of a complete process is determined, guaranteeing freedom from conflict and providing for the execution of vacuum test 103 and scan test 104 at the same time without the complete process being able to assume unpredicted states. For this purpose, the function calls of the abovementioned C programs must be coordinated.

Figure 2 shows steps of a method for generating the control of a complete process.

In a step 201, functionalities of the individual processes are identified (structuring). Furthermore, controllable and uncontrollable events are identified. Controllable events are events which can be avoided by the control. Uncontrollable events are events which cannot be avoided, e.g. output values of sensors or results of actions. Furthermore, sequences of events are identified which represent a possible physical system behavior. In addition, sequences of events are identified which represent a specific system behavior (task-related system behavior) under the influence of the control.

The step of structuring 201 also comprises the representation of a state machine as shown in figure 3 for the "scan behavior".

From an initial state 301, a "scan" command places the machine into a state 302 in which the vacuum pipette 102 is examined for wear. If the "scanning" is concluded, the machine returns to state 301. Similarly, the machine returns to

state 301 from state 302 when an error occurs (error: the process of scanning indicates that the vacuum pipette 102 must be replaced). A "recover" command changes state 301 to a state 303 in which the machine
5 returns to the starting conditions (recovering). If the "recovering" process is ended, the machine jumps back into state 301 ("done recover").

The specific system behavior is also shown in the form of a state machine. For this purpose, figure 4
10 shows a state machine which corresponds to the specific system behavior for the coordination of the events "turn", "done turn", "error turn", "scan", "done scan", "error scan", "counter".

Figure 4 shows a state machine which represents
15 the specific system behavior of the scan test 104. An initial state 401 is changed to a state 402 by a "turn" command. If the turning of the turret head 101 is ended, the machine changes from state 402 to a state 403. If an error occurs during the turn ("error turn"),
20 state 402 changes to a state 407. From state 403, the "scan" command initiates a change to a state 404; when the scan test 104 is concluded, the machine changes from state 404 to a state 405. Incrementing a counter changes state 405 to a state 406. A check is then made
25 to determine whether the counter has already reached a value 12. If this is so, state 406 is changed to state 407; if the counter exhibits a smaller value than 12, state 406 changes to state 401. Various commands ensure that state 407 is kept: "recover", "done recover",
30 "operator input", "stop". A "repeat" command causes the process to be repeated in that state 407 is changed to state 401.

A next step 202 in figure 2 ensures a validation of the control of the complete process by automatically verifying characteristics of the complete process. Such characteristics are, in particular, a blocking or non-blocking characteristic and a controllability characteristic. If various individual processes are operating in parallel with one another and if these individual processes share one or more resources (in this case the turning of the turret head 101), freedom from blocking is ensured if the individual processes can perform their tasks right to the end without impeding each other by accessing common resources. In the exemplary embodiment shown, the individual process scan test 104 and the individual process vacuum test 103 jointly use the resource "turning of the turret head 101". This could lead to mutual blocking if the control of the complete process does not prevent this preventatively.

Furthermore, the validation 202 is carried out in that a plausibility check of the structuring 201 of the complete process to be controlled is effected by observation or simulation of the system and of the specific system behavior in the form of a state machine. Finally, predetermined characteristics are automatically verified. One of these characteristics is "after an error has occurred in scan test 104 (the event "error scan" was indicated), the "recovery" operation (the event "recover") always starts".

The validation 202, if it is not done completely and which formally verifies the undisturbed sequence of the individual processes, is repeated by branching back to step 201, the structuring of the functionalities of the individual processes. If the validation 202 is successful, code for controlling the complete process is automatically generated (compare change to step 203 in figure 2).

During this process, during the automatic generation of the control of the complete process, controllable events are allocated, in particular, to the linked function calls within the individual processes and thus to the associated program code fragments. Uncontrollable events are allocated to corresponding return values of function calls or output values of sensors. An example is represented by the function call of the event "scan" which relates to the corresponding program code fragment (C program routine "scan test") which comprises "scan error" or "scan done" as return values.

The automatic generation of the C code for controlling the complete process is determined from various state machines, allocations and/or program code fragments. The individual functionalities structured in step 201 correspond in this case to the corresponding state machines or, respectively, program code fragments.

As already mentioned, the vacuum test 103 and the scan test 104 are carried out in parallel, each test being performed at different physical locations (compare figure 1, oppositely located performance of the two tests).

Figures 5 and 6 show the desired behavior of the individual processes for the vacuum test 103 and the scan test 104, figure 5 showing a sequential processing of the two tests and figure 6 showing a parallel processing of the two tests. In the parallel processing in figure 6, blocking of the two individual processes can occur due to the fact that after the event "recovery vacuum", one of the two events "turn" or "counter" will not occur. As a result, a turning ("turn" command) of the cylinder head, which is needed by both individual processes running in parallel, is not guaranteed. Whereas one machine wants to turn the cylinder head, the other machine

wants to increment the counter, resulting in blocking. In contrast, sequential processing as indicated in figure 5 is possible, the tests for 12 vacuum pipettes 102 each being performed in succession and thus the cylinder head 101 having to be turned twice completely. The time expenditure for the sequential processing is far greater than for (almost) parallel processing.

On the basis of figure 4, figure 5 to figure 10 can be analogously understood per se. Thus, figure 5 comprises states 501 to 517, figure 6 comprises states 601 to 618, states 501 to 509 and 509 to 517 characterizing the in each case independent machines according to figure 6 which can run in parallel. The event which is in each case decisive for a state changing to another one is in each case indicated along the transition arrows in the figures.

Events having the same name occur synchronously in machines in which the respective event is defined. In the present exemplary embodiment, the event "scan" occurs if the state machine of the system behavior (compare figure 7) is in state "0" or, respectively, the state machine of the specific system behavior according to figure 8 is in state 0 or in state 1 and if the state machine of the specific system behavior according to figure 9 is in state 2.

Controllable events are:

"turn", "scan", "vacuum", "recover", "recovery turn", "recovery scan", "recovery vacuum", "counter", "operator input", "reset".

Uncontrollable events are:

"done turn", "error turn", "done scan", "error scan", "done vacuum", "error vacuum", "done recover", "counter=12?", "counter<12?", "stop", "repeat".

The respective state machine indicates the state in which the corresponding system behavior can be terminated, i.e. the state with a dark background defines a termination condition.

5 Figure 7 shows the system behavior. As already mentioned above, the system behavior shows sequences of events which represent physically possible system states. Such physically possible behaviors are the turning of the cylinder head, the performance of the vacuum test, the performance of the scan test, the
10 incrementing and interrogating of the counter and the inputting of a command which triggers a predetermined action. The state 0 in figure 7 characterizes both the initial state and the end state of the respective
15 system behavior.

 After the system behavior has been identified, the specific system behavior is determined which relates to a behavior of the complete process with regard to the task to be controlled. The associated
20 state machine for the specific system behavior of the error recovery is shown in figure 8. In figure 8, there are two marked states 801 and 807, state 801 being simultaneously the start and an end state of the state machine. The specific system behavior "error recovery"
25 can be terminated in each case in states 801 and 807.

 According to the above statements, the validation is then performed. To this end, a number of iterations which, finally, lead to the solution according to figure 7 to figure 9 are shown according
30 to figure 2 (compare transition from validation 202 to structuring 201: iteration).

 Figures 8 and 9 show the controlled specific system behavior corresponding to the predetermined functionality of the complete process. For this
35 purpose, three tasks have been identified

which are executed in parallel: error recovery, scan test and vacuum test. The error recovery, in particular, is only activated if both the scan test 104 and the vacuum test 103 [lacuna] in a marked state
5 (compare state 6 or, respectively states 907, 917 in figure 9). The scan test 104 and the vacuum test 103 are only activated if the error recovery is in the initial state (compare state 0 or 801 in figure 8).

The system behavior and the specific system
10 behavior according to figures 7-9 are non-blocking. Furthermore, the specific system behavior according to figures 8 and 9 is controllable with respect to the system behavior from figure 7.

In figure 10, the complete process is assembled
15 from the state machines according to figures 7-9. Figure 10 represents the product state machine of the state machines described and is comprehensible per se. In particular, the product state machine according to figure 10 is not used for structuring and solving the
20 control task for the complete process since the easily traceable procedure, as described, guarantees a structured and clear approach to determining the data which are necessary for controlling the complete process.

25 The executable program code for controlling the complete process is automatically generated in that first function calls are assigned to the controllable events, the return values of the function calls or output values of sensors being assigned the
30 corresponding uncontrollable events. The program code for controlling the complete process is generated from the state machine assignments and associated program code fragments.

Patent claims

1. A method for designing the control of a complete process which comprises a number of individual processes,
 - a) in which functionalities of the individual processes are identified,
 - b) in which a validation is performed by automatically verifying an interplay of the functionalities in accordance with an input to the complete process, to the effect that each individual process is not impeded during the operation,
 - c) in which data for controlling the complete process are determined from a result of the validation.
2. The method as claimed in claim 1, in which a sequence optimization is performed in addition to step 1c).
3. The method as claimed in claim 1 or 2, in which the data for the control are determined in the form of an executable code.
4. The method as claimed in one of claims 1 to 3, in which one of the functionalities of the individual processes is a software unit for controlling the individual process affected.
5. The method as claimed in one of the preceding claims, in which an individual process is impeded if one of the following conditions is met:
 - a) the individual process is blocked by another individual process;
 - b) the individual process reaches an unauthorized state or a state endangering the operation of the complete system.



6. The method as claimed in one of the preceding claims, in which the control of individual processes of an automatic placement machine is designed.

7. The method as claimed in one of the preceding
5 claims, in which the data determined for controlling the complete process are used for controlling a technical installation.

8. An arrangement for designing the control of a complete process which comprises a number of individual
10 processes, comprising a processor unit which is set up in such a manner that

- a) functionalities of the individual processes can be identified;
- b) a validation can be performed by automatically
15 verifying an interplay of the functionalities in accordance with an input to the complete process, to the effect that each individual process is not impeded during the operation;
- c) data from a result of the validation can be used
20 for controlling the complete process.