

Description**BACKGROUND OF THE INVENTION****5 Field of the Invention:**

10 This invention relates to a detergent composition for removing stains of oils and fats, machine oils, cutting oils, grease, liquid crystals, rosin-type fluxes, and the like attached to the solid surfaces of articles such as electronic and precision parts, and tools used for the assembly or fabrication of these parts (such parts and tools herein collectively called "electronic and precision parts"), and to a process for cleaning the electronic and precision parts using said detergent composition, which is characterized by the ease in treating the waste water discharged therefrom.

Description of the Background Art:

15 Conventionally, hydrocarbon solvents, e.g. kerosene, benzene, xylene, etc.; chlorine-containing solvents, e.g. trichloroethylene, tetrachloroethylene, etc.; Freon-type solvents, e.g. trichlorotrifluoroethane, etc.; aqueous type detergents comprising surface active agents, builders, etc.; and the like have been used for removing stains, of which the major components are oils and fats, machine oils, cutting oils, greases, liquid
20 crystals, rosin-type fluxes, and the like, attached to the solid surfaces of precision parts and tools. In particular, Freon-type solvents and chlorine-containing solvents are used for removing stains on electronic, electrical, and machinery parts owing to their high detergency and flame retardance.

25 The detergent compositions containing a chlorine-containing solvent or a Freon-type solvent, however, have crucial problems in terms of the safety, toxicity, environmental pollution, and the like. Among hydrocarbon solvents, benzene and xylene are both specified as hazardous compounds under the Law Concerning Industrial Hygiene and Workmen's Safety because of their high toxicity, and are therefore undesirable solvents for use in a detergent composition. Special consideration must be given to avoid risks involved in handling these solvents.

30 Aqueous type detergents, on the other hand, are less hazardous and toxic than solvent type detergents. High detergency can be provided by properly selecting detergent components such as surface active agents, builders, and the like.

35 Aqueous type detergents containing various types of surface active agents are usually abundantly soluble in water. This is the cause of the drawback of these aqueous type detergents; i.e. difficulty in the treatment of waste water. The treatment of a detergent liquid after removing stains and the treatment of the waste water used to rinse the detergent liquid from the parts to be cleaned (such waste water herein called "rinse waste water") have conventionally been carried out by coagulation and sedimentation, pressure
40 flotation, activated sludge treatment, or activated carbon treatment, or by the combination of two or more of these. These treatment processes, however, require large facilities involving enormous investment and operating costs.

45 The object of the present invention is therefore, with due consideration to the above problems and drawbacks in aqueous-type detergent compositions or the detergent composition of the type in which water is used for the rinse after washing, to provide a detergent composition of which the rinse waste water can easily be treated and which can effectively remove stains of oils and fats, machine oils, cutting oils, greases, liquid crystals, rosin-type fluxes, and the like from the solid surfaces of electronic and precision parts. Another object of the present invention is to provide an industrially advantageous process for cleaning electronic and precision parts without requiring large facilities involving huge investment cost and high operating costs.

50 The present inventors have undertaken extensive studies and have found that the above objects can be achieved by a detergent composition comprising, as a detergent ingredient, one or more nonionic surface active agents, of which a 5% by weight aqueous solution has a cloud point of 5-100 °C.

55 The present inventors have further found that the rinse waste water after cleaning the electronic and precision parts with the detergent composition and after rinsing at a temperature of 5-100 °C can easily separate out the oil components contained therein, such as oil stains and detergent components, if heated to a temperature above the cloud point, thereby remarkably improving the waste water treatment process and ensuring recycling of the rinse water from which the oil components have been eliminated.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide a detergent composition for cleaning electronic and precision parts, comprising one or more nonionic surface active agents and wherein a 5% by weight (hereinafter referred to simply as %) of aqueous solution of said detergent composition has a cloud point of 5-100 °C.

Another object of the present invention is to provide a process for cleaning electronic and precision parts, which comprises the steps 1) to 3):

- 1) cleaning the electronic and precision parts with a detergent composition comprising one or more nonionic surface active agents and wherein a 5% by weight of aqueous solution of said detergent composition has a cloud point of 5-100 °C, or with an aqueous solution of this detergent composition, at a temperature below said cloud point (herein called "cleaning step"),
- 2) rinsing the electronic and precision parts with a rinse water resulted in step 1) at a temperature of 5-100 °C (herein called "rinse step"), and
- 3) heating the rinse waste water to a temperature above its cloud point (herein called "separation step"); thereby separating the oil components contained therein.

Other objects, features and advantages of the invention will hereinafter become more readily apparent from the following description.

20 DETAILED DESCRIPTION OF THE INVENTION AND PREFERRED EMBODIMENTS

"Cloud point" used here is defined as a temperature at which a 5% solution of the detergent composition of the present invention in ion-exchanged water began to become turbid when the solution in a 10-30 ml test tube is first cooled to 0 °C and then allowed to raise its temperature at a rate of 1 °C per minute.

Nonionic surface active agents used in the present invention may be those classified under the nonionic surface active agents in "Handbook of Surface Active Agent" (pages 37-45, published by Sangyo Tosho Publishing Co.). They include, for example, ether-type surface active agents, e.g. alkyl ether-type, alkylaryl ether-type, alkylthio ether-type; ester-type surface active agents, e.g. alkylester-type, sorbitan alkylester-type; condensed aminopolyoxyalkylene-type surface active agents, e.g. polyoxyalkylenealkylamine; condensed amide-polyoxyalkylene-type surface active agents, e.g. polyoxyalkylenealkylamide; Pluronic or Tetric-type surface active agents which are random or block condensation products of polyoxyethylene and polyoxypropylene; polyethyleneimine-type surface active agents; and the like. Of these, particularly preferable are nonionic surface active agents having a hydrocarbon residue having 4-22 carbon atoms. Such nonionic surface active agents provide a detergent composition with increased affinity toward oil stains, thus promoting the detergency of the composition. In addition, they give a distinct cloud point to the rinse waste water into which they are mingled.

The amount of the nonionic surface active agents to be incorporated into the detergent composition of the present invention is preferably 2-100% by weight, and particularly preferably 2-90% by weight. An amount less than 2% by weight decreases the detergency of the composition, while the detergency proportionate to the amount cannot be obtained by the incorporation exceeding 90% by weight.

The above-mentioned nonionic surface active agents lose their solubility in water at temperatures above the cloud point of the detergent composition, and are expelled from water. This forces oil stains and the like held in the water to deposit as precipitating or floating materials depending on their specific gravity, thus ensuring the removal of oil stains by a simple procedure such as scoop-up or the like.

A detergent composition having a cloud point within a specific temperature range can expel oil stains as well as nonionic surface active agents contained in water by simply heating it to a temperature above the cloud point, making the removal of oil stains possible with simple sewage treatment facilities, in a short period of time, and at a low cost.

It is essential that the 5% aqueous solution of the detergent composition of the present invention have a cloud point of 5-100 °C. A more preferable cloud point range is 20-90 °C. If the cloud point is lower than 5 °C, the efficiency of rinsing with water to be carried out after cleaning decreases. This is because a rinse operation using water is usually carried out above normal water temperature (5 °C) for a better rinse efficiency. If the cloud point is lower than the temperature at which the rinse is performed, the detergent liquid attached to the surfaces to be cleaned can be removed only with difficulty. If the cloud point is higher than 100 °C, on the other hand, the waste water treatment facilities must have special devices, e.g. a device for pressurizing, to rinse at a temperature above the cloud point, resulting in an increase in the treatment cost.

It is desirable that a 5% aqueous solution of the detergent composition of the present invention, when maintained at a temperature above the cloud point for 30 minutes or more, separates 30% by weight or more, preferably 50% by weight or more, of organic components contained in the detergent from the water. The degree of separation of organic components can readily be determined by comparing CODs (chemical oxygen demand) of the aqueous solution before and after heating to the cloud point. The greater the separation degree, the larger is the amount of nonionic surface active agents which have lost their activity, thus indicating a better waste water treatment effect. Beside the nonionic surface active agents, various other components may be added to the detergent composition of the present invention inasmuch as the effect of the present invention is not impaired. Such components include other surface active agents which are used in common detergent compositions, organic or inorganic compounds having a chelating activity, antiseptics, rust preventives, antifoaming agents, antioxidant, hydrocarbon solvents, amine-type additives, alcohols, water, and the like.

The cleaning process of the present invention is hereinafter illustrated.

A method used in the cleaning step may be the dipping method, ultrasonic cleaning method, shaking method, spray method, or the like, or the combination of two or more of these. The cleaning is performed at a temperature below the cloud point. If the cleaning temperature is above the cloud point, the detergent composition becomes turbid, resulting in insufficient cleaning.

The rinse liquid is used to rinse the detergent liquid containing oil stains and the detergent composition in the rinsing step. Although pure water is preferable for use as a rinse liquid, rinse waste water after removal of oil components is preferably used in practice.

Rinse may be performed by the dipping method, ultrasonic method, shaking method, spray method, or the like, using a rinse liquid at a temperature of 5-100°C. A temperature outside the 5-100°C range is not only uneconomical but also undesirable from the aspect of facilities required for the rinsing at such a temperature. An especially preferable rinse temperature range is below the cloud point of the detergent composition.

In the separation step, the rinse waste water is heated above its cloud point. Here, the cloud point of a rinse waste water is determined in the same manner as that of the detergent composition without diluting the rinse waste water. The cloud point of a rinse waste water is almost the same as the cloud point of the detergent composition used for the cleaning.

The rinse waste water is kept in the separation step by heating above its cloud point, preferably a temperature higher than the cloud point by 5°C or more. As mentioned above, nonionic surface active agents contained in the rinse waste water become insoluble, causing oil stains, such as fluxes, emulsified or dissolved therein to separate from the rinse waste water.

Removal of the separated nonionic surface active agents and oil components floating on the surface of the waste water or precipitated in the bottom is carried out by scooping them in the effluent receiving tank or separation tank, by continuously extracting them, or by using auxiliary equipment such as filters.

The rinse effluent can be cleaned by an efficient separation procedure and circulated for reuse as rinse water.

If necessary, an ion-exchange treatment, an absorption treatment, a treatment by activated carbon or by filter, or the like may further be used in order to remove organic materials such as water soluble nonionic surface active agents and the like.

The detergent composition of the present invention exhibits an exceptionally excellent effect when applied to cleaning of solid surfaces of articles such as electronic and precision parts, and tools used for the assembly or fabrication of these parts. Electronic and precision parts herein include any parts of electronic appliances, electric machines, precision equipment, resin processing machines, optical instruments, and the like. Parts of electronic appliances include, for example, print circuit boards used in computers and their peripheral equipment, electronic appliances for household use, communication equipment, OA equipment, and other electronic-related articles; hoops used as connection parts for IC lead frames, resistors, condensers, relays, etc.; liquid crystal image displays used for OA equipment, watches, computers, toys, etc.; semiconductor materials such as silicon or ceramic wafers; parts used in crystal oscillators; parts for photoelectric transfer used in CD, FD, copying machine, optical resistors, etc.; and the like. Parts for electric machines include, for example, motor parts such as brushes, rotors, stators, housing, etc.; parts of dispensers such as ticket dispensers, soft drink dispensers, etc.; parts for bill inspection machines used for cash dispensers, etc.; and the like. Parts for precision equipment include, for example, bearings used in minute motors, video recorders, etc.; ultra-hard tips; and the like. Resin processing parts include, for example, lenses used in cameras, glasses, optical equipment, etc., glass frames, watch cases, watch belts, etc.; and the like.

Assembly or fabrication parts herein include any tools, instruments, and devices used for the manufacture, processing, assembly, fabrication, and finishing of various parts mentioned above, as well as various instruments, their parts, and the like for handling the above precision parts.

5 The detergent composition of the present invention exhibits particularly outstanding capability when applied to the removal of fluxes remaining on the surfaces of printed circuit boards or the cleansing of liquid crystals attached to glass substrates. The objects to be cleaned by the application of the detergent composition of the present invention are not limited to the above-mentioned electronic or precision parts, tools, or instruments. It can be applied to any and all electronic or precision parts, tools, or instruments having a solid surface of any configuration, to which is attached any contaminant or substance which may
10 interfere the subsequent assembling or processing operations, e.g. oils, fluxes, etc.

The detergent composition of the present invention can exhibit a particularly good performance, when such a contaminating substance is stains of which the major component is organic oils such as oils and fats, machine oils, cutting oils, grease, liquid crystals, rosin-type fluxes, and the like. Inclusion of metallic powders, inorganic powders, and the like in the oil stains does not inhibit the effect of the detergent
15 composition of the present invention.

Other features of the invention will become apparent in the course of the following description of the exemplary embodiments which are given for illustration of the invention and are not intended to be limiting thereof.

20 EXAMPLES

Examples 1-15 and Comparative Examples 1-5

Detergent compositions with formulations shown in Table 1 were prepared and the cloud point of a 5%
25 aqueous solution of each composition was determined. The results are shown in Table 1.

Ten (10) sheets of (i) print circuit boards treated with flux, (ii) copper boards to which naphthenic mineral oil was applied, and (iii) glass plates to which nematic liquid crystal was applied were respectively dipped into the detergent compositions of (i) Examples 1-5 and Comparative Examples 1 and 4; (ii) Examples 6-10 and Comparative Example 2; and (iii) Examples 11-15 and Comparative Examples 3 and 5,
30 and cleansed at 40°C for 3 minutes while ultrasonic wave was applied. They were rinsed with ion-exchanged water at 20°C in order to evaluate their rinsability. The results are shown in Table 1.

The rinse was further continued until the concentration of the detergent composition in the rinse waste water became 5% by weight. COD of the water layer when the rinse waste water was kept above the cloud point within the 5-100°C range and COD of the water layer below the cloud point were compared to
35 evaluate the separability of organic components according to the following criterion. The results are given in Table 1.

(Criterion of Rinsability)

40 AAA: Excellent
BBB: Good
CCC: A slight amount of detergent composition remained attached
DDD: A large amount of detergent composition remained attached

45 (Criterion of Separability)

AAA: Excellent; The degree of the separation was 80% by weight or more.
BBB: Good; The degree of the separation was 30% by weight or more.
CCC: The degree of the separation was insufficient.
50 DDD: Organic components hardly separated.

TABLE 1

Component	Example															Comparative Example				
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	1	2	3	4	5
(POE) ₅ (POP) ₂ ethyl ether	20	-	-	-	-	-	-	-	-	-	50	-	-	-	-	-	-	-	-	-
(POE) ₃ hexyl ether	-	30	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(POE) ₁₀ lauryl ether	-	-	-	20	-	-	10	-	-	-	-	25	-	-	-	-	-	5	-	-
(POE) ₂₀ stearyl ether	-	-	15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(POE) ₁₀ oleylamine	-	-	-	-	30	-	-	-	-	-	-	-	-	30	-	-	-	-	-	-
(POE) ₂₀ dibutyl ester	-	-	-	-	-	15	-	-	-	-	20	-	-	-	-	-	-	-	-	-
(POE) ₃₀ (POP) ₁₅	-	-	5	-	-	-	10	-	-	-	-	-	-	-	-	-	-	-	-	-
(POE) ₁₅ nonyl phenyl ether	-	-	-	-	-	10	-	-	-	-	-	-	20	-	5	-	-	-	-	-
(POE) ₁₆ sorbitan oleate	-	-	-	-	-	-	-	15	-	-	-	-	-	-	-	-	-	-	-	-
(POE) ₅ (POP) ₂ adduct of furfuryl alcohol	-	60	-	-	-	-	-	-	70	-	-	-	-	-	-	-	-	-	-	-
(POE) ₅ (POB) ₃ laurylamine	-	-	-	-	-	-	5	-	-	20	-	-	-	-	-	-	-	-	-	-
(POE) ₁₀ dodecyl ether-methyl ether	-	-	-	-	10	-	-	-	-	-	-	-	-	70	-	-	-	-	-	-
(POE) ₃ decyl ester	-	-	-	5	-	-	-	-	10	-	-	-	45	-	-	-	-	-	-	100
(POE) ₉₀ nonylphenol ether	-	-	-	-	-	-	-	-	-	5	-	-	-	-	-	15	-	-	10	-
Sodium dodecylbenzene sulfonate	-	-	5	-	-	-	-	4	-	-	-	5	-	-	-	-	30	15	5	-
Triethanolamine	-	-	-	-	-	1	-	-	1	-	-	-	-	-	-	-	-	-	-	-
Water	80	10	75	75	60	74	75	81	19	75	30	70	35	0	95	85	70	80	85	-

TABLE 1 (Continued)

Component	Example															Comparative Example					
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	1	2	3	4	5	
Cloud point (°C)	58	35	85	28	34	26	75	68	41	65	30	47	8	15	85	>100	>100	>100	>100	0<	
Soil components																					
Flux	0	0	0	0	0	-	-	-	-	-	-	-	-	-	-	0	-	-	0	-	
Naphthenic oil	-	-	-	-	-	0	0	0	0	0	-	-	-	-	-	-	0	-	-	-	
Liquid crystals	-	-	-	-	-	-	-	-	-	-	0	0	0	0	0	-	-	0	-	0	
Evaluation results																					
Rinsability	B-A	B-A	A	B-A	B-A	B-A	A	A	B-A	A	B-A	B-A	B	B	A	B	A	B	B	D	
Separability	B	A	A	A	A	B	A	A	B	A	A	A	A	A	B	D	D	D	D	A	

* (POE)_n: Polyoxyethylene, (POP)_n: Polyoxypropylene, (POB)_n: Polyoxybutylene, ni: average addition mol

The results in Table 1 shows superior detergency and rinsability of the detergent compositions of the present invention in cleansing and rinsing of precision parts.

Examples 16-24, Comparative Examples 6-8

Detergent compositions with formulations shown in Table 2 were prepared and diluted to 20-fold with ion-exchanged water to measure their cloud points. The detergent compositions were used to ultrasonically cleanse the following test pieces.

Test piece 1: Print circuit boards (10 cm x 15 cm) treated with flux.

Test piece 2: Steel test piece (10 cm x 15 cm) to which naphthenic oil (40 °C, 350 cSt) was applied (1 g/m²)

Test piece 3: Glass plate (10 cm x 10 cm) to which liquid crystals were applied (5 g/m²)

After cleansing, test pieces were dipped into ion-exchanged water at 25 °C and ultrasonically rinsed for 1 minute. All test pieces after the rinse had good outward appearance.

The rinse waste water was allowed to stand still for 30 minutes at a temperature (maximum temperature: below 100 °C) 10-20 °C higher than above its cloud point. All rinse waste waters according to the present invention separated oil components in either upper or lower layer. COD of the water layer was measured (A value) and was compared with the COD before the rinse was performed (B value), to determine the oil component separation rate: $[(B-A)/B] \times 100$. The results are shown in Table 2.

TABLE 2

	Example											Comparative Example		
	16	17	18	19	20	21	22	23	24	6	7	8		
Subject to be cleansed														
Test piece 1	0	0	0	-	-	-	-	-	-	0	-	-	-	-
Test piece 2	-	-	-	0	0	0	-	-	-	-	0	-	-	-
Test piece 3	-	-	-	-	-	-	0	0	0	-	-	-	-	0
Formulation of detergent composition														
(POE) ₅ nonylphenol ether	80	10	10	30	-	-	10	5	-	-	5	-	-	-
(POE) ₁₀ lauryl ether	-	20	-	-	-	15	20	35	-	-	-	5	-	5
(POE) ₃₅ oleyl ether	-	-	-	10	-	-	-	-	10	20	-	35	-	35
(POE) ₁₅ (POP) ₂ decyl ether	20	-	35	-	30	-	70	-	65	-	-	-	-	-
Sodium dodecylbenzene sulfonate	-	-	-	-	2	-	-	2	-	10	20	-	-	-
Sodium oleate	-	-	5	-	-	-	-	-	-	-	-	-	-	-
Triethanolamine	-	2	1	-	-	-	-	-	-	2	-	-	-	-
Water	0	68	49	60	68	85	0	58	25	68	75	60	-	-

TABLE 2 (Continued)

	Example												Comparative Example
	16	17	18	19	20	21	22	23	24	25	26	27	28
Cloud point of the detergent composition (20-fold dilution; °C)	6	65	32	35	45	87	28	90	35	100<	100<	100<	100<
COD of rinse water (Mn method, g/l)													
Before rinse (A)	9	11	19	1	3	2	2	2	2	2	47	23	3
After rinse (B)	75	45	50	25	24	21	15	10	12	12	50	26	11
Rate of oil component separation	88	75	61	95	87	90	85	80	83	5	10	7	

* (POE)_n: Polyoxyethylene, (POP)_n: Polyoxypropylene

The results of Table 2 show that the compositions of Examples 16-24 can separate oil components at a higher rate and that the rinse water from which the oil components have been separated have a low COD value evidencing that the water contains very little oil components.

All rinse waters from which at least 50% of oil components have been eliminated (all example compositions meet this criterion) were confirmed to be reusable as a rinse water in the rinse step of the

claimed process. Especially, water layers from which 70% or more of oil components have been eliminated exhibited excellent rinsability.

As illustrated above, the detergent composition herein disclosed exhibits excellent detergency and the rinse waste water can be treated with ease. It can be applied with advantage to the cleansing of electronic and precision parts, and tools used for the assembly or fabrication of these parts. Especially, the process of the present invention can afford an industrially advantageous cleansing process of these parts, since it can greatly decrease oil components contained in the rinse waste water, thus simplifying the subsequent effluent treatment. Furthermore, the process brings about an economic advantage by ensuring the reclamation and reuse of the rinse waste water after separation of oil components.

Claims

1. A detergent composition for cleaning electronic and precision parts, comprising one or more nonionic surface active agents and wherein a 5% by weight of aqueous solution of said detergent composition has a cloud point of 5-100 °C.
2. The detergent composition according to Claim 1, wherein a 5% by weight of aqueous solution of said detergent composition separates 30% by weight or more of organic components contained therein when said solution is maintained above its cloud point for at least 30 minutes.
3. The detergent composition according to Claim 1, wherein said nonionic surface active agents are those having a hydrocarbon residue having 4-22 carbon atoms.
4. A process for cleaning electronic and precision parts, which comprises the steps 1) to 3):
 - 1) cleaning the electronic and precision parts with a detergent composition comprising one or more nonionic surface active agents and wherein a 5% by weight of aqueous solution of said detergent composition has a cloud point of 5-100 °C, or with an aqueous solution of this detergent composition, at a temperature below said cloud point,
 - 2) rinsing the electronic and precision parts with a rinse water resulted in step 1) at a temperature of 5-100 °C, and
 - 3) heating the rinse waste water to a temperature above its cloud point; thereby separating the oil components contained therein.

Patentansprüche

1. Zusammensetzung zum Reinigen von elektronischen und Präzisionsteilen, umfassend ein oder mehrere nichtionische oberflächenaktive Mittel und wobei eine 5 gew.-%-ige wässrige Lösung der Reinigungsmittel-Zusammensetzung einen Trübungspunkt von 5 bis 100 °C hat.
2. Reinigungsmittel-Zusammensetzung nach Anspruch 1, worin eine 5 gew.-%-ige wässrige Lösung der Reinigungsmittel-Zusammensetzung 30 Gew.-% oder mehr der darin enthaltenen organischen Komponenten abscheidet, wenn die Lösung für mindestens 30 min oberhalb ihres Trübungspunktes gehalten wird.
3. Reinigungsmittel-Zusammensetzung nach Anspruch 1, worin die nichtionischen oberflächenaktiven Mittel solche mit einem Kohlenwasserstoffrest von 4 bis 22 Kohlenstoffatomen sind.
4. Verfahren zum Reinigen von elektronischen und Präzisionsteilen, umfassend die Stufen 1) bis 3):
 - 1) Reinigen der elektronischen und Präzisionsteile mit einer Reinigungsmittel-Zusammensetzung umfassend ein oder mehrere nichtionische oberflächenaktive Mittel und wobei eine 5 gew.-%-ige wässrige Lösung der Reinigungsmittel-Zusammensetzung einen Trübungspunkt von 5 bis 100 °C hat oder mit einer wässrigen Lösung dieser Reinigungsmittel-Zusammensetzung bei einer Temperatur unterhalb des Trübungspunktes,
 - 2) Spülen der elektronischen und Präzisionsteile mit einem in Stufe 1) resultierenden Spülwasser bei einer Temperatur von 5 bis 100 °C und
 - 3) Erhitzen des Spül-Abwassers auf eine Temperatur oberhalb seines Trübungspunktes, wodurch die darin enthaltenen Öl-Komponenten abgeschieden werden.



claimed process. Especially, water layers from which 70% or more of oil components have been eliminated exhibited excellent rinsability.

As illustrated above, the detergent composition herein disclosed exhibits excellent detergency and the rinse waste water can be treated with ease. It can be applied with advantage to the cleansing of electronic and precision parts, and tools used for the assembly or fabrication of these parts. Especially, the process of the present invention can afford an industrially advantageous cleansing process of these parts, since it can greatly decrease oil components contained in the rinse waste water, thus simplifying the subsequent effluent treatment. Furthermore, the process brings about an economic advantage by ensuring the reclamation and reuse of the rinse waste water after separation of oil components.

Claims

1. A detergent composition for cleaning electronic and precision parts, comprising one or more nonionic surface active agents and wherein a 5% by weight of aqueous solution of said detergent composition has a cloud point of 5-100 °C.
2. The detergent composition according to Claim 1, wherein a 5% by weight of aqueous solution of said detergent composition separates 30% by weight or more of organic components contained therein when said solution is maintained above its cloud point for at least 30 minutes.
3. The detergent composition according to Claim 1, wherein said nonionic surface active agents are those having a hydrocarbon residue having 4-22 carbon atoms.
4. A process for cleaning electronic and precision parts, which comprises the steps 1) to 3):
 - 1) cleaning the electronic and precision parts with a detergent composition comprising one or more nonionic surface active agents and wherein a 5% by weight of aqueous solution of said detergent composition has a cloud point of 5-100 °C, or with an aqueous solution of this detergent composition, at a temperature below said cloud point,
 - 2) rinsing the electronic and precision parts with a rinse water resulted in step 1) at a temperature of 5-100 °C, and
 - 3) heating the rinse waste water to a temperature above its cloud point; thereby separating the oil components contained therein.

Patentansprüche

1. Zusammensetzung zum Reinigen von elektronischen und Präzisionsteilen, umfassend ein oder mehrere nichtionische oberflächenaktive Mittel und wobei eine 5 gew.-%-ige wässrige Lösung der Reinigungsmittel-Zusammensetzung einen Trübungspunkt von 5 bis 100 °C hat.
2. Reinigungsmittel-Zusammensetzung nach Anspruch 1, worin eine 5 gew.-%-ige wässrige Lösung der Reinigungsmittel-Zusammensetzung 30 Gew.-% oder mehr der darin enthaltenen organischen Komponenten abscheidet, wenn die Lösung für mindestens 30 min oberhalb ihres Trübungspunktes gehalten wird.
3. Reinigungsmittel-Zusammensetzung nach Anspruch 1, worin die nichtionischen oberflächenaktiven Mittel solche mit einem Kohlenwasserstoffrest von 4 bis 22 Kohlenstoffatomen sind.
4. Verfahren zum Reinigen von elektronischen und Präzisionsteilen, umfassend die Stufen 1) bis 3):
 - 1) Reinigen der elektronischen und Präzisionsteile mit einer Reinigungsmittel-Zusammensetzung umfassend ein oder mehrere nichtionische oberflächenaktive Mittel und wobei eine 5 gew.-%-ige wässrige Lösung der Reinigungsmittel-Zusammensetzung einen Trübungspunkt von 5 bis 100 °C hat oder mit einer wässrigen Lösung dieser Reinigungsmittel-Zusammensetzung bei einer Temperatur unterhalb des Trübungspunktes,
 - 2) Spülen der elektronischen und Präzisionsteile mit einem in Stufe 1) resultierenden Spülwasser bei einer Temperatur von 5 bis 100 °C und
 - 3) Erhitzen des Spül-Abwassers auf eine Temperatur oberhalb seines Trübungspunktes, wodurch die darin enthaltenen Öl-Komponenten abgeschieden werden.

**Revendications**

1. Composition détergente pour nettoyer des pièces électroniques et de précision, comprenant un ou plusieurs agents tensio-actifs non-ioniques, une solution aqueuse à 5% en poids de ladite composition détergente présentant un point de trouble de 5 - 100 °C.
2. Composition détergente selon la revendication 1, dont une solution aqueuse à 5% en poids est le siège d'une séparation de 30% en poids, ou davantage, des composants organiques qui y sont contenus lorsque ladite solution est maintenue au-dessus de son point de trouble pendant un laps de temps d'au moins 30 minutes.
3. Composition détergente selon la revendication 1, dans laquelle lesdits agents tensio-actifs non-ioniques sont ceux ayant un reste hydrocarboné ayant 4 - 22 atomes de carbone.
4. Procédé de nettoyage de pièces électroniques et de précision, qui comprend les étapes (1) à (3) :
 - (1) nettoyage des pièces électroniques et de précision avec une composition détergente comprenant un ou plusieurs agents tensio-actifs non-ioniques, et dont une solution aqueuse à 5% en poids présente un point de trouble de 5 - 100 °C, ou avec une solution aqueuse de cette composition détergente, à une température inférieure audit point de trouble ;
 - (2) rinçage des pièces électroniques et de précision avec une eau de rinçage, résultant de l'étape (1), à une température de 5 - 100 °C ; et
 - (3) chauffage de l'eau résiduaire de rinçage à une température dépassant son point de trouble, permettant ainsi de séparer les composants huileux qui y sont contenus.