



(51) International Patent Classification:

H05H 1/36 (2006.01) *H02M 7/48* (2007.01)
H01L 21/3065 (2006.01)

(21) International Application Number:

PCT/US2010/053263

(22) International Filing Date:

19 October 2010 (19.10.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

12/603,326 21 October 2009 (21.10.2009) US

(71) Applicant (for all designated States except US): **LAM RESEARCH CORPORATION** [US/US]; 4650 Cushing Parkway, Fremont, California 94538 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BENJAMIN, Neil Martin Paul** [GB/US]; c/o Lam Research Corporation, Legal Department, 4650 Cushing Parkway, Fremont, California 94538 (US).

(74) Agent: **NGUYEN, Joseph A.**; PO Box 700640, San Jose, California 95170 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: RF ISOLATION FOR POWER CIRCUITRY




FIG. 2

(57) Abstract: System and method for providing isolated power to a component that is also subject to a set of RF signals that includes at least a first RF signal having a first RF frequency is provided. There is included providing a DC voltage signal and modulating the DC voltage signal into an isolated power signal using an isolation transformer. The isolated power signal has an intermediate frequency that is higher than 60 Hz and lower than the first RF frequency. There is included supplying the DC voltage signal to the primary winding and obtaining the isolated power signal from the secondary winding; and delivering the isolated power to the component using the isolated power signal.