



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E21B 15/00, 19/08	A1	(11) International Publication Number: WO 97/28347 (43) International Publication Date: 7 August 1997 (07.08.97)
(21) International Application Number: PCT/NO97/00025 (22) International Filing Date: 31 January 1997 (31.01.97) (30) Priority Data: 960412 31 January 1996 (31.01.96) NO (71) Applicant (for all designated States except US): MARITIME HYDRAULICS A/S [NO/NO]; Dvergsnes, N-4639 Kristiansand (NO). (72) Inventor; and (75) Inventor/Applicant (for US only): VATNE, Per [NO/NO]; Rabbersvik, N-4639 Kristiansand (NO). (74) Agent: TOFTING, Arild; Bryns Patentkontor A/S, P.O. Box 765, Sentrum, N-0106 Oslo (NO).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. In English translation (filed in Norwegian).	

(54) Title: ARRANGEMENT FOR FASTENING A PISTON-CYLINDER ARRANGEMENT AND METHOD FOR REPLACING SEALINGS THEREIN

(57) Abstract

There is described a mounting means for a piston-cylinder arrangement (10, 11) in a derrick (1) placed on a drill floor (2), which hydraulic piston-cylinder arrangement (10, 11) is adapted to raise and lower a yoke (8) which travels on guide rails (7) in the derrick (1) itself, where the cylinder (20) is firmly held by means of a mounting apparatus (31) in relation to the drill floor (2). For the changing of gaskets (27) on the piston (21) and the cylinder (20), the cylinder is arranged so as to be lowerable in relation to the mounting thereof. The mounting apparatus (31) is designed to be releasable and comprises a flange (32) permanently mounted on the cylinder (20), a fixing device (37) in fixed position in relation to the drill floor (2), a dividable locking ring (34), and a locking means (38), said locking ring (34) being adapted for engagement between the flange (32) and the fixing device (37) and being firmly held in said engagement with the aid of the locking means (38). A method of changing gaskets on a piston and cylinder is also described.

