

CORRECTED VERSION

(19) World Intellectual Property  
Organization  
International Bureau

(43) International Publication Date  
8 May 2014 (08.05.2014)



(10) International Publication Number  
**WO 2014/070685 A8**

(51) International Patent Classification:  
*H02G 3/18* (2006.01) *G02B 6/44* (2006.01)  
*H02G 9/10* (2006.01)

(74) Agent: MAXWELL, Walter, G.; Christie, Parker & Hale, LLP, P.O. Box 29001, Glendale, California 91209-9001 (US).

(21) International Application Number:  
PCT/US2013/067148

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:  
28 October 2013 (28.10.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
61/720,297 30 October 2012 (30.10.2012) US  
13/830,670 14 March 2013 (14.03.2013) US

(71) Applicant: CHANNELL COMMERCIAL CORPORATION [US/US]; 26040 Ynez Road, Temecula, California 92589 (US).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

(72) Inventor: BURKE, Edward, J.; 26040 Ynez Road, Temecula, California 92589 (US).

[Continued on next page]

(54) Title: ENHANCED STRENGTH GRADE LEVEL UTILITIES ENCLOSURE

FIG. 3



(57) Abstract: An enhanced strength grade level utility enclosure comprises a vertical wall structure having an upright inner wall panel (46) extending from an upper edge to a bottom edge of the structure. The inner wall panel (46) has an inside face spanning the enclosure's interior. One or more narrow, vertically extending slotted regions (58) are recessed in the inside face of the wall panel. Upright rigid support bars (60), optionally adapted for use as cable racks, are positioned in and rigidly affixed to separate slotted regions on the wall panel. The support bars (60) provide a continuous means of rigid vertical support from the upper edge down to the bottom edge of the enclosure's wall structure. The recessed support bars, in combination with the vertical wall structure, provide enhanced wall strength in excess of industrial vertical side wall and center load test standards.



EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,  
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,  
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, KM, ML, MR, NE, SN, TD, TG).

**(48) Date of publication of this corrected version:**

21 May 2015

**(15) Information about Correction:**

see Notice of 21 May 2015

**Published:**

— *with international search report (Art. 21(3))*