

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 February 2006 (23.02.2006)

PCT

(10) International Publication Number
WO 2006/020610 A2

(51) International Patent Classification:
G02F 1/1335 (2006.01)

(21) International Application Number:
PCT/US2005/028217

(22) International Filing Date: 9 August 2005 (09.08.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/600,272 10 August 2004 (10.08.2004) US
11/194,360 1 August 2005 (01.08.2005) US

(71) Applicant (for all designated States except US): **TRIVIUM TECHNOLOGIES, INC.** [US/US]; 1301 East Ninth Street, 37th Floor, Cleveland, OH 44114 (US).

(71) Applicants and


(72) Inventors (for all designated States except US): **LUBART, Neil, D.** [US/US]; 10707 Cooper Hill Drive, Austin, TX 75758 (US). **WOJCIECHOWSKI, Timothy, J.** [US/US]; 30370 Hilliard Boulevard, Westlake, OH 44145 (US). **LASH, Thomas, E.** [US/US]; 16310 S. Woodland Road, Shaker Heights, OH 44120 (US).

(74) Agent: **KOLOCOURIS, Gregory, S.**; 2300 BP Tower, 200 Public Square, Cleveland, OH 44114 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: LIGHT COLLIMATING DEVICE



(57) Abstract: A collimating device and a translector for use in a system having a backlight is disclosed herein. In one embodiment of the application, the collimating device and the translector each include an immersing layer, a reflecting layer, and an optical element layer formed from a plurality of three-dimensional, optical elements. Each optical element is tapered such that a small area end has a horizontal plane cross sectional area that is less than that of a wide area end. The optical elements of the collimating device are tapered towards the backlight and the optical elements of the translector are tapered away from the backlight. The reflecting layer has apertures which correspond to the position and shape of the light input ends of the optical elements.

WO 2006/020610 A2



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.