



WEIGHTED OPEN LOOP POWER CONTROL IN A TIME DIVISION DUPLEX COMMUNICATION SYSTEM

BACKGROUND



G00001

This invention generally relates to spread spectrum time division duplex (TDD) communication systems. More particularly, the present invention relates to a system and method for controlling transmission power within TDD communication systems.

Figure 1 depicts a wireless spread spectrum time division duplex (TDD) communication system. The system has a plurality of base stations 30_1 - 30_7 . Each base station 30_1 communicates with user equipments (UEs) 32_1 - 32_3 in its operating area. Communications transmitted from a base station 30_1 to a UE 32_1 are referred to as downlink communications and communications transmitted from a UE 32_1 to a base station 30_1 are referred to as uplink communications.

In addition to communicating over different frequency spectrums, spread spectrum TDD systems carry multiple communications over the same spectrum. The multiple signals are distinguished by their respective chip code sequences (codes). Also, to more efficiently use the spread spectrum, TDD systems as illustrated in **Figure 2** use repeating frames 34 divided into a number of time slots 36_1 - 36_n , such as fifteen time slots. In such systems, a communication is sent in selected time slots 36_1 - 36_n using selected codes. Accordingly, one frame 34 is capable of carrying multiple communications distinguished by both time slot 36_1 - 36_n and code. The use

of a single code in a single time slot is referred to as a resource unit. Based on the bandwidth required to support a communication, one or multiple resource units are assigned to that communication.

Most TDD systems adaptively control transmission power levels. In a TDD system, many communications may share the same time slot and spectrum. When a UE 32₁ or base station 30₁ is receiving a specific communication, all the other communications using the same time slot and spectrum cause interference to the specific communication. Increasing the transmission power level of one communication degrades the signal quality of all other communications within that time slot and spectrum. However, reducing the transmission power level too far results in undesirable signal to noise ratios (SNRs) and bit error rates (BERs) at the receivers. To maintain both the signal quality of communications and low transmission power levels, transmission power control is used.

One approach using transmission power control in a code division multiple access (CDMA) communication system is described in U.S. Patent No. 5,056,109 (Gilhousen et al.). A transmitter sends a communication to a particular receiver. Upon reception, the received signal power is measured. The received signal power is compared to a desired received signal power. Based on the comparison, a control bit is sent to the transmitter either increasing or decreasing transmission power by a fixed amount. Since the receiver sends a control signal to the transmitter to control the transmitter's power level, such power control techniques are commonly referred to as closed loop.

Under certain conditions, the performance of closed loop systems degrades. For instance, if communications sent between a UE **32₁** and a base station **30₁** are in a highly dynamic environment, such as due to the UE **32₁** moving, such systems may not be able to adapt fast enough to compensate for the changes. The update rate of closed loop power control in a typical TDD system is 100 cycles per second which is not sufficient for fast fading channels. Accordingly, there is a need for alternate approaches to maintain signal quality and low transmission power levels.

SUMMARY

The invention controls transmission power levels in a spread spectrum time division duplex communication station. A first communication station transmits a communication to a second communication station. The second station receives the communication and measures its received power level. Based on, in part, the received communication's power level and the communication's transmission power level, a path loss estimate is determined. The transmission power level for a communication from the second station to the first station is set based on, in part, weighting the path loss estimate and a long term pathloss estimate.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a prior art TDD system.

Figure 2 illustrates time slots in repeating frames of a TDD system.

Figure 3 is a flow chart of weighted open loop power control.

Figure 4 is a diagram of components of two communication stations using weighted open loop power control.

Figure 5 depicts a graph of the performance of a weighted open loop, open loop and closed loop power control system for a UE moving at 30 kilometers per hour (km/h).

Figure 6 depicts a graph of the three systems' performance for a UE moving at 60 km/h.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The preferred embodiments will be described with reference to the drawing figures where like numerals represent like elements throughout. Weighted open loop power control will be explained using the flow chart of **Figure 3** and the components of two simplified communication stations **110**, **112** as shown in **Figure 4**. For the following discussion, the communication station having its transmitter's power controlled is referred to as the transmitting station **112** and the communication station receiving power controlled communications is referred to as the receiving station **110**. Since weighted open loop power control may be used for uplink, downlink or both types of communications, the transmitter having its power controlled may be located at a base station **30₁**, UE **32₁** or both. Accordingly, if both uplink and downlink power control are used, the receiving and transmitting station's components are located at both the base station **30₁** and UE **32₁**. For use in estimating the path loss between the receiving and transmitting stations **110**, **112**, the

receiving station **110** sends a communication to the transmitting station **112**. The communication may be sent on any one of various channels. Typically, in a TDD system, the channels used for estimating path loss are referred to as reference channels, although other channels may be used. If the receiving station **110** is a base station **30₁**, the communication is preferably sent over a downlink common channel or a Common Control Physical Channel (CCPCH).

Data to be communicated to the transmitting station **112** over the reference channel is referred to as reference channel data. The reference channel data is generated by a reference channel data generator **56**. The reference data is assigned one or multiple resource units based on the communication's bandwidth requirements. A spreading and training sequence insertion device **58** spreads the reference channel data and makes the spread reference data time-multiplexed with a training sequence in the appropriate time slots and codes of the assigned resource units. The resulting sequence is referred to as a communication burst. The communication burst is subsequently amplified by an amplifier **60**. The amplified communication burst may be summed by a sum device **62** with any other communication burst created through devices, such as a data generator **50**, spreading and training sequence insertion device **52** and amplifier **54**. The summed communication bursts are modulated by a modulator **64**. The modulated signal is passed through an isolator **66** and radiated by an antenna **78** as shown or, alternately, through an antenna array, step **38**. The radiated signal is passed through a wireless radio channel **80** to an antenna **82** of the transmitting station **112**. The type of

modulation used for the transmitted communication can be any of the those known to those skilled in the art, such as direct phase shift keying (DPSK) or quadrature phase shift keying (QPSK).

The antenna **82** or, alternately, antenna array of the transmitting station **112** receives various radio frequency signals. The received signals are passed through an isolator **84** to a demodulator **86** to produce a baseband signal. The baseband signal is processed, such as by a channel estimation device **88** and a data estimation device **90**, in the time slots and with the appropriate codes assigned to the communication's burst. The channel estimation device **88** commonly uses the training sequence component in the baseband signal to provide channel information, such as channel impulse responses. The channel information is used by the data estimation device **90** and a power measurement device **92**. The power level of the processed communication corresponding to the reference channel, R_{TS} , is measured by the power measurement device **92** and sent to a pathloss estimation device **94**, **step 40**. The channel estimation device **88** is capable of separating the reference channel from all other channels. If an automatic gain control device or amplifier is used for processing the received signals, the measured power level is adjusted to correct for the gain of these devices at either the power measurement device **92** or the pathloss estimation device **94**.

To determine the path loss, L , the transmitting station **112** also requires the communication's transmitted power level, T_{RS} . The transmitted power level, T_{RS} , may be sent along with the communication's data or in a signaling channel. If the

power level, T_{RS} , is sent along with the communication's data, the data estimation device **90** interprets the power level and sends the interpreted power level to the pathloss estimation device **94**. If the receiving station **110** is a base station **30₁**, preferably the transmitted power level, T_{RS} , is sent via the broadcast channel (BCH) from the base station **30₁**. By subtracting the received communication's power level, R_{TS} in dB, from the sent communication's transmitted power level, T_{RS} in dB, the pathloss estimation device **94** estimates the path loss, L , between the two stations **110**, **112**, **step 42**. Additionally, a long term average of the pathloss, L_0 , is updated, **step 44**. In certain situations, instead of transmitting the transmitted power level, T_{RS} , the receiving station **110** may transmit a reference for the transmitted power level. In that case, the pathloss estimation device **94** provides reference levels for the path loss, L , and the long term average of the path loss, L_0 .

Since TDD systems transmit downlink and uplink communications in the same frequency spectrum, the conditions these communications experience are similar. This phenomenon is referred to as reciprocity. Due to reciprocity, the path loss experienced for the downlink will also be experienced for the uplink and vice versa. By adding the estimated path loss to a desired received power level, a transmission power level for a communication from the transmitting station **112** to the receiving station **110** is determined. This power control technique is referred to as open loop power control.

Open loop systems have drawbacks. If a time delay exists between the estimated path loss and the transmitted communication, the path loss experienced by

the transmitted communication may differ from the calculated loss. In TDD where communications are sent in differing time slots **36₁-36_n**, the time slot delay between received and transmitted communications may degrade the performance of an open loop power control system. To overcome these drawbacks, a quality measurement device **96** in a weighted open loop power controller **100** determines the quality of the estimated path loss, **step 46**. The quality measurement device **96** also weights the estimated path loss, L , and long term average of the pathloss, L_0 , to set the transmit power level by transmit power calculation device **98**, **step 48**. As illustrated in **Figure 4**, the weighted open loop power controller **100** consists of the power measurement device **92**, pathloss estimation device **94**, quality measurement device **96**, and transmit power calculation device **98**.

The following is one of the preferred weighted open loop power control algorithms. The transmitting station's power level in decibels, P_{TS} , is determined using **Equation 1**.

$$P_{TS} = P_{RS} + \alpha(L - L_0) + L_0 + \text{CONSTANT VALUE} \quad \text{Equation 1}$$

P_{RS} is the power level that the receiving station **110** desires to receive the transmitting station's communication in dB. P_{RS} is determined by the desired SIR, SIR_{TARGET} , at the receiving station **110** and the interference level, I_{RS} , at the receiving station **110**.

To determine the interference level, I_{RS} , at the receiving station, received communications from the transmitting station **112** are demodulated by a demodulator **68**. The resulting baseband signal is processed, such as by a channel estimation

device **70** and a data estimator device **72** in the time slots and with the appropriate codes assigned the transmitting station's communications. The channel information produced by the channel estimation device **70** is used by an interference measurement device **74** to determine the interference level, I_{RS} . The channel information may also be used to control the transmit power level of the receiving station **110**. The channel information is input to a data estimation device **72** and a transmit power calculation device **76**. The data estimation produced by the data estimation device **72** is used with the channel information by the transmit power calculation device **76** to control the amplifier **54** which controls the receiving station's transmit power level.

P_{RS} is determined using **Equation 2**.

$$P_{RS} = SIR_{TARGET} + I_{RS} \quad \text{Equation 2}$$

I_{RS} is either signaled or broadcasted from the receiving station **110** to the transmitting station **112**. For downlink power control, SIR_{TARGET} is known at the transmitting station **112**. For uplink power control, SIR_{TARGET} is signaled from the receiving station **110** to the transmitting station **112**. Using **Equation 2**, **Equation 1** is rewritten as either **Equations 3** or **4**.

$$P_{TS} = SIR_{TARGET} + I_{RS} + \alpha(L - L_0) + L_0 + \text{CONSTANT VALUE} \quad \text{Equation 3}$$

$$P_{TS} = \alpha L + (1 - \alpha)L_0 + I_{RS} + SIR_{TARGET} + \text{CONSTANT VALUE} \quad \text{Equation 4}$$

L is the path loss estimate in decibels, $T_{RS} - R_{TS}$, for the most recent time slot **36₁-36_n** that the path loss was estimated. The long term average of the pathloss, L_0 , is a running average of the path loss estimates L . The **CONSTANT VALUE** is a

correction term. The CONSTANT VALUE corrects for differences in the uplink and downlink channels, such as to compensate for differences in uplink and downlink gain. Additionally, the CONSTANT VALUE may provide correction if the transmit power reference level of the receiving station is transmitted, instead of the actual transmit power, T_{RS} . If the receiving station is a base station **30₁**, the CONSTANT VALUE is preferably sent via Layer 3 signaling. If the receiving station is a base station **30₁**, the CONSTANT VALUE is preferably sent via Layer 3 signaling.

The weighting value, α , determined by the quality measurement device **94**, is a measure of the quality of the estimated path loss and is, preferably, based on the number of time slots **36₁-36_n** between the time slot, n , of the last path loss estimate and the first time slot of the communication transmitted by the transmitting station **112**. The value of α is from zero to one. Generally, if the time difference between the time slots is small, the recent path loss estimate will be fairly accurate and α is set at a value close to one. By contrast, if the time difference is large, the path loss estimate may not be accurate and the long term average path loss measurement is most likely a better estimate for the path loss. Accordingly, α is set at a value closer to zero.

Equation 5 is one equation for determining α , although others may be used.

$$\alpha = 1 - (D - 1)/D_{\max}$$

Equation 5

The value, D , is the number of time slots **36₁-36_n** between the time slot of the last path loss estimate and the first time slot of the transmitted communication which will

be referred to as the time slot delay. If the delay is one time slot, α is one. $D_{\max}$ is the maximal possible delay. A typical value for a frame having fifteen time slots is six. If the delay is $D_{\max}$ or greater, α approaches zero. Using the transmit power level, P_{TS} , determined by a transmit power calculation device **98**, the weighted open loop power controller **100** sets the transmit power of the transmitted communication, **step 48**.

Data to be transmitted in a communication from the transmitting station **112** is produced by a data generator **102**. The communication data is spread and time-multiplexed with a training sequence by the spreading and training sequence insertion device **104** in the appropriate time slots and codes of the assigned resource units. The spread signal is amplified by the amplifier **106** and modulated by the modulator **108** to radio frequency.

The weighted open loop power controller **100** controls the gain of the amplifier **106** to achieve the determined transmit power level, P_{TS} , for the communication. The communication is passed through the isolator **84** and radiated by the antenna **82**.

Figures 5 and 6 depict graphs **82, 84** illustrating the performance of a weighted open loop system using **Equation 4**. **Equation 5** is used to calculate α . These graphs **82, 84** depict the results of simulations comparing the performance of a weighted open loop, an open loop and a closed loop system controlling the transmission power level of the transmitting station **112**. The simulations address the performance of these systems in a fast fading channel under steady-state

conditions. In this example, the receiving station is a base station **30₁** and the transmitting station is a UE **32₁**. For the simulation, the UE **32₁** was a mobile station. The simulated base station **30₁** used two antenna diversity for reception with each antenna having a three finger RAKE receiver. The simulation approximated a realistic channel and SIR estimation based on a midamble sequence of burst type 1 field in the presence of additive white Gaussian noise (AWGN). The simulation used an International Telecommunication Union (ITU) Pedestrian B type channel and QPSK modulation. Interference levels were assumed to be accurately known with no uncertainty. Channel coding schemes were not considered. The CONSTANT VALUE and L_0 were set at 0 db.

For each of the power control techniques, **Figure 5**, graph **82** shows the energy for a transmitted complex symbol in decibels (E_s/N_0) required to maintain a BER of 1% for various time slot delays, D , with the UE **32₁** moving at 30 kilometers per hour (km/h). As shown, at lower time slot delays, both weighted open loop and open loop outperform closed loop. For higher time slot delays, weighted open loop outperforms both open loop and closed loop. As shown in **Figure 6**, graph **84**, similar results occur if the UE **32₁** is traveling at 60 km/h.

*

*

*

CLAIMS

What is claimed is:

1. A method for controlling transmission power levels in a spread spectrum time division duplex communication system having frames with time slots for communication, the method comprising:

transmitting a first communication having a transmission power level in a first time slot from a first communication station;

receiving at a second communication station the first communication and measuring a power level of the first communication as received;

determining a path loss estimate based on in part the measured received first communication power level and the first communication transmission power level; and

setting a transmission power level for a second communication in a second time slot from the second station to the first station based on in part combining the path loss estimate weighted by a first factor with a long term path loss estimate weighted by a second factor, wherein the first and second factors are a function of a time separation of the first and second time slots.

2. The method of claim 1 further comprising:

determining the long term path loss estimate based at least in part upon an average of path loss estimates of communications sent from the first station to the second station.

3. The method of claim 1 further comprising:
determining a quality, α , of the pathloss estimate based on in part a number of time slots, D , between the first and second time slot; and
wherein the first factor is α and the second factor is $1-\alpha$.

4. The method of claim 3 wherein a maximum time slot delay is $D_{\max}$ and the determined quality, α , is determined by

$$\alpha = 1 - (D-1) / D_{\max}.$$

5. The method of claim 1 wherein the set transmission power level compensates for differences in the uplink and downlink gains.

6. The method of claim 1 wherein the first station is a base station and the second station is a user equipment.

7. The method of claim 1 wherein the first station is a user equipment and the second station is a base station.

8. A spread spectrum time division duplex communication system having a first and second communication station, the system using frames with time slots for communication, the system comprising:

the first station comprising:

5 means for transmitting a first communication having a transmit power level in a first time slot; and

the second station comprising:

means for receiving the first communication and measuring a power level of the first communication as received;

10 means for determining a path loss estimate based on in part the measured received first communication power level and the first communication transmission power level;

means for setting a transmission power level for a second communication in a second time slot based on in part combining the path loss estimate weighted by a first factor with a long term path loss estimate weighted by
15 estimate weighted by a first factor with a long term path loss estimate weighted by a second factor, wherein the first and second factors are a function of a time separation of the first and second time slots; and

means for transmitting the second communication in the second time slot at the set transmission power level.

9. The system of claim 8 wherein the second station further comprises:

means for determining the long term path loss estimate based at least in part upon an average of path loss estimates of communications sent from the first station to the second station.

10. The system of claim 8 wherein the first station further comprises:
means for determining a quality, α , of the pathloss estimate based on in part
a number of time slots, D , between the first and second time slot; and
wherein the first factor is α and the second factor is $1-\alpha$.

11. The system of claim 10 wherein a maximum time slot delay is $D_{\max}$ and
the determined quality, α , is determined by

$$\alpha = 1 - (D-1) / D_{\max}.$$

12. The system of claim 8 wherein the setting means sets the transmission
power level to compensate for differences in the uplink and downlink gains.

13. The system of claim 8 wherein the first station is a base station and the
second station is a user equipment.

14. The system of claim 8 wherein the first station is a user equipment and
the second station is a base station.

15. A communication station having its transmission power level
controlled in a spread spectrum time division duplex communication system, the
system using frames with time slots for communication and having a second
communication station transmitting a first communication in a first time slot, the

5 communication station comprising:

at least one antenna for receiving the first communication and transmitting an amplified second communication in a second time slot;

a channel estimation device having an input configured to receive the received first communication for producing channel information;

10 a data estimation device having inputs configured to receive the received first communication and the channel information for producing interpreted data;

a power measurement device having an input configured to receive the channel information for producing a measurement of a received power level of the first communication;

15 a pathloss estimation device having an input configured to receive the measured received power level for producing a pathloss estimate for the first communication;

a quality measurement device for producing a quality measurement based at least in part upon a time separation of the first time slot and a second time slot;

20 a transmit power calculation device having inputs configured to receive the pathloss estimation and the quality measurement for producing a power control signal based at least in part upon combining the path loss estimate weighted by a first factor and a long term pathloss estimate weighted by a second factor, wherein the first and second factors are based on in part the quality measurement; and

25 an amplifier having inputs configured to receive the power control signal and a second communication to be transmitted in the second time slot for amplifying the

second communication in response to the power control signal to produce the amplified second communication.

16. The communication station of claim 15 further comprising:

a data generator for producing communication data;

a spreading and training sequence insertion device having an input configured to receive the communication data for producing the second communication in the second time slot; and

a modulator having an input configured to receive the amplified second communication for modulating the amplified second communication to radio frequency prior to transmission.

17. The communication station of claim 15 further comprising:

a demodulator having an input configured to receive the received first communication for producing a baseband signal; and

wherein both the channel estimation device and the data estimation device have an input configured to receive the baseband signal.

18. The communication station of claim 15 wherein the quality measurement is in the range of zero to one and the first factor is the quality measurement and the second factor is one minus the quality measurement.

19. The communication station of claim 15 wherein the first station is a base station and the second station is a user equipment.

20. The communication station of claim 15 wherein the first station is a user equipment and the second station is a base station.