

MOTORIZED SHAVING APPARATUS HEAD AND SHAVING APPARATUS IMPLEMENTING THE SAME

Cross-Reference to Related Patent Applications

[0001] The present application claims the benefit to United States Provisional Patent Application No. 61/295,783, filed January 18, 2010, the entirety of which is hereby incorporated by reference.

Field of the Invention

[0002] The present invention relates generally to motorized shaving apparatus that utilize a shearing technique to cut hair bristles, and specifically to a motorized shaving apparatus that shears hairs between a rotary cutter and a fixed blade.

Background of the Invention

[0003] The current methods for removing hair from the human body, by shaving, as opposed to epilation, involve two basic approaches: the razor approach, wherein a very sharp blade is pushed against the skin at an angle, thereby cutting hair; and the screen approach, wherein a thin fenestrated metal screen is moved across the skin, exposing hair through the holes and cutting them by a mechanized, typically motorized, cutting element.

[0004] In the sharp razor blade approach, the energy for cutting is provided by the hand driving the razor across the skin of the user, typically by the hand of the user him/herself, and the hair is cut by the impact force applied thereon and by virtue of its stiffness. The conditions of cutting hair are a compromise between the ease of cutting a soft (or softened) hair (or hair bristle) and having the necessary counter-force against the blade's impact which can only come from the hardness of the hair bristle. Apart from being a compromise difficult to optimize daily on a variety of hair bristles, the sharpness of the blade and its angle pose a constant risk of nicks and cuts, as the blade is driven forcefully across the skin.

[0005] In the screen approach of most motorized shaving apparatus, the problem of safety is mitigated since the skin and the cutting elements are separated by the screen. Moreover, the hair bristles which penetrate the screen through its holes are given a prop to be cut against; hence, the lack of a counter-force for cutting is also mitigated to some extent. However, in order to arrive at an efficient cutting condition, the hair bristle must enter a hole and be perpendicular to the skin, requirements which are not always met

unless the screen is constantly moved across the skin. Still, when the hair bristle is eventually cut at the optimal angle, it cannot be cut close to the skin due to the separating screen.

[0006] One cutting technique which requires minimal force for cutting hair can be effected by scissors. Scissors cut hair at the crossing point of two blades which do not have to be very sharp in order to cut the hair due to the fact that the blades contact the hair from substantially opposite directions in the plane of cutting, mutually providing each other with a counter-force for cutting. While it is impractical to use scissors for daily shaving, which requires maximal closeness of the cutting point to the skin, the scissors cutting technique was implemented in the form of rotary cutter units cutting hair against a flat and straight stationary blade. This hair cutting technique is capable of providing a very close shave since the cutting blades are positioned flush against the skin at the time of cutting. This also renders this cutting approach relatively safe from accidental cuts.

[0007] However, the presently known configurations which have attempted to implement this technique have suffered, among other drawbacks, from improperly positioned driving mechanisms, which were placed outside of the shaving head, moving the rotary cutter unit by means of a direct shaft, or indirectly by means of external gears, bevel gears, worm gears, sprockets, belt and pulley mechanisms and the like. Essentially, these external driving mechanisms suffer from loss of kinetic energy, leading to limited rotation speed of the rotary cutter unit, and therefore provide poor shaving results. Moreover, all these external driving mechanisms lead to cumbersome designs, large size and substantial weight of the resulting shaving device since they house the drive mechanism alongside or perpendicularly to the shaving head. In addition, they require large powerful motors with or without portable power sources.

[0008] For example, one rotary razor exists that comprises a casing provided with a slot, a cutting edge formed along one edge of the slot, guards projecting from the opposite side of the slot to a point immediately adjacent the cutting edge, the cutting edge and the guards being rigid with respect to the casing, and a rotary cutter within the casing arranged to co-act with such cutting edge. The rotary cutter in this rotary razor is provided with an adjustment means whereby it may be set at a point in close proximity to the first named cutting edge but not in frictional contact therewith, such means

comprising bearings within the casing. The bearings each have a pair of projecting arms and the casing is provided with a slot adjacent each arm. Set screws project through the slots and into the arms while another arm projects from each pair of arms at right angles thereto. The set screws project through the casing and into the last named arms. This rotary razor provides a rotary cutter shaving device wherein the rotary cutter unit is pressed and held against the stationary blade in order to effect a close and effective shave. However, in this rotary razor, the drive mechanism is not part of the shaving head or hair-cutting head.

[0009] A shearing tool also exists with a tapered cylindrical cutter held by bearings inside a housing. The housing is formed with a slot, wherein one of the edges of the slot constitutes a cutting edge cooperating with the cutting edges of the tapered cylindrical cutter. In this shearing tool, a shaft extends out of the hair-cutting head and the drive mechanism is not part of the hair-cutting head.

[0010] Another rotary razor exists having a casing formed with a longitudinal slot, a rotary shaft, a series of filler blocks encircling the shaft, a series of razor blades engaged between the filler blocks and having their edges projecting spirally beyond the outer face of the filler blocks. Upon rotation of the shaft, the razor blades pass across the slot opening of the casing. A plate on the casing is arranged along one edge of the slot in a position to contact the cutting edge of the spirally positioned blades on the shaft. While this rotary razor provides a solution to the production of the rotary cutter unit, the drive mechanism is outside the hair-cutting head.

[0011] Another shaver exists comprising a tubular casing formed with a longitudinally extending slot and with comb teeth or fingers extending transversely to the slot. A rotor is located within and extends longitudinally in the casing, and is rotatable therein. The rotor is formed with radial ridges extending helically and longitudinally of the rotor and have edge faces confronting the annular wall of the casing. The blades have their outer surfaces contacting the inner surface of the annular wall of the casing and are thereby pressed inwardly and cut hair against the comb's teeth. This shaver has a motor casing of usual construction, serving as a handle, and positioned outside of the hair-cutting head.

[0012] Still another rotary safety razor exists comprising a shaving head having a rotary cutter unit (with helical blades) mounted to rotate about an axis. The head of this rotary

safety razor comprises, in combination, a tubular casing adapted to contain the cutter and split along a longitudinal line so as to present a slot with two edges. One of these edges is formed along a major portion of its length with the cutting edge of a stationary straight blade while the other of these edges is formed with a comb opposite the cutting edge. This rotary safety razor addresses the issue of the drive mechanism by placing it outside the shaving head and transferring the rotational motion of the external motor via a shaft formed at one end with a worm engaging worm teeth on a rotatable cutter unit.

[0013] Additional motorized shaving apparatus exist that utilize a screen wherein the cutting elements do not come in direct contact with the skin but rather are located behind the screen.

Brief Summary of the Invention

[0014] The invention is directed to a shaving apparatus in which the drive mechanism, which may be in the form of an electric motor, is positioned within a rotary cutter, and hairs are sheared between the cutting edges of the rotary cutter and a fixed blade in a scissor-like action during operation of the inventive shaving apparatus. As a result of positioning the drive mechanism within the rotary cutter, the head of the inventive shaving apparatus achieves a very compact and efficient construction.

[0015] In one embodiment, the invention can be a shaving apparatus head comprising: a rotary cutter comprising a cylindrical body having an outer surface and an inner surface forming a cavity, and a plurality of spaced-apart cutting edges extending from the outer surface of the cylindrical body; an electric motor located within the cavity and operably coupled to the rotary cutter to rotate the rotary cutter about an axis; and a fixed blade having a cutting edge, the fixed blade mounted adjacent the rotary cutter so that a user's hairs are sheared between the cutting edge of the fixed blade and the cutting edges of the rotary cutter when the rotary cutter is rotating.

[0016] In another embodiment, the invention can be a shaving apparatus comprising: an elongated handle portion; a power source; and a head portion coupled to a distal end of the elongated handle portion, the head portion comprising: a cylindrical rotary cutter comprising a cavity and a plurality of spaced-apart cutting edges; an electric motor located within the cavity and operably coupled to the rotary cutter to rotate the rotary cutter about an axis, the electric motor electrically coupled to the power source; and a

fixed blade having a cutting edge, the fixed blade mounted adjacent the rotary cutter so that a user's hairs are sheared between the cutting edge of the fixed blade and the cutting edges of the rotary cutter when the rotary cutter is rotating.

[0017] In still another aspect, the invention can be a shaving apparatus head comprising: a rotary cutter comprising a body having an outer surface and an inner surface forming a cavity, and a plurality of spaced-apart cutting edges extending from the outer surface of the cylindrical body; a drive mechanism located within the cavity and operably coupled to the rotary cutter to rotate the rotary cutter about an axis; and a blade having a cutting edge, the blade mounted adjacent the rotary cutter so that a user's hairs are sheared between the cutting edge of the blade and the cutting edges of the rotary cutter when the rotary cutter is rotating.

[0018] In an even further aspect, the invention can be a motorized shaving head for removing hair bristles from the skin of a user, including: a rotary cutter unit of cylindrical configuration having an outer surface formed with a plurality of spaced, outwardly-projecting cutter edges arrayed along the length of the rotary cutter unit; a cutter blade having a cutter edge extending along the length of the rotary cutter unit and proximal to the cutter edges thereof; and an electrical motor located within the rotary cutter unit for rotating the rotary cutter unit with respect to the cutter blade to cut hair bristles between the cutter edges of the rotary cutter unit and the cutter edge of the cutter blade during a cutting operation when the shaving head is pressed against and moved along the user's skin.

[0019] Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating some embodiments of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

Brief Description of the Drawings

[0020] The features of the exemplified embodiments will be described with reference to the following drawings in which like elements are labeled similarly. The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

[0021] Figure 1 is a front perspective view of a shaving apparatus according to an embodiment of the present invention;

[0022] Figure 2 is a rear perspective view of the shaving apparatus of FIG. 1;

[0023] Figure 3 is a top perspective view of a shaving apparatus head according to one embodiment of the present invention;

[0024] Figure 4 is an exploded view of the shaving apparatus head of FIG. 3;

[0025] Figure 5A is a schematic of the rotary cutter and fixed blade of the shaving apparatus head of FIG. 3 in which the rotary cutter and fixed blade are operably positioned to achieve the shearing of hairs therebetween in accordance with an embodiment of the present invention;

[0026] Figure 5B is a close-up view of area V-V of FIG. 5A;

[0027] Figure 6 is a cross-sectional view of the shaving apparatus head of FIG. 3 taken along the axis B-B;

[0028] Figure 7 is a perspective view of one embodiment of a bearing that can be used to rotatably mount the rotary cutter within the shaving apparatus head of FIG. 3; and

[0029] Figure 8 is a cross-sectional view of a shaving apparatus head in accordance with an alternate embodiment of the present invention, wherein the motor extends through one of the annular bearings.

Detailed Description of the Invention

[0030] The following description of some embodiment(s) is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

[0031] The description of illustrative embodiments according to principles of the present invention is intended to be read in connection with the accompanying drawings, which are to be considered part of the entire written description. In the description of embodiments of the invention disclosed herein, any reference to direction or orientation is merely intended for convenience of description and is not intended in any way to limit the scope of the present invention. Relative terms such as “lower,” “upper,” “horizontal,” “vertical,” “above,” “below,” “up,” “down,” “left,” “right,” “top” and “bottom” as well as derivatives thereof (e.g., “horizontally,” “downwardly,” “upwardly,” etc.) should be construed to refer to the orientation as then described or as shown in the drawing under discussion. These relative terms are for convenience of description only and do not

require that the apparatus be constructed or operated in a particular orientation unless explicitly indicated as such. Terms such as "attached," "affixed," "connected," "coupled," "interconnected," "mounted" and similar refer to a relationship wherein structures are secured or attached to one another either directly or indirectly through intervening structures, as well as both movable or rigid attachments or relationships, unless expressly described otherwise. Moreover, the features and benefits of the invention are illustrated by reference to the exemplified embodiments. Accordingly, the invention expressly should not be limited to such exemplary embodiments illustrating some possible non-limiting combination of features that may exist alone or in other combinations of features; the scope of the invention being defined by the claims appended hereto.

[0032] As discussed hereinabove, shaving aims to achieve safe hair cutting as close as possible to the level of the skin. In the context of human grooming activity, shaving is performed using two basic paradigms, cutting the hair bristle by a single sharp element impacting the hair from one side (e.g., razor), which can be referred to as "scraping", or by two cutting elements snipping the hair from two opposite sides (e.g. scissors and shaving machines), which can be referred to as "shearing", "clipping" or "snipping". In terms of industrial applications, these two paradigms have split early on and evolved separately.

[0033] Attempts at mechanizing the razor have resulted in two basic types of motorized razors, the vibrating razor which is directed at affording a sawing motion perpendicular to the movement of the blade across the skin, and the rotating blade, directed at mechanizing and speeding-up the scraping action. Nevertheless, shaving by the scraping paradigm has always presented a peril, either from scratching and lacerating the skin by blunt and/or rough (used) blades, or from nicks and cuts from very sharp and even fresh (unused) blades.

[0034] Compared to scraping (razor) shaving, using scissors for shaving (shearing) presents an entirely different set of problems to be solved. One problem associated with using scissors for close and safe facial shaving is the point of shear, namely the hair is less likely to be snipped at the level of the skin, leaving a substantial bristle. Another problem is speed, since a hair is cut only at the crossing of the blade-pair, an event that is

less frequent when compared to the frequency of hair-blade encounters in the case of the single scraping blade (razor).

[0035] Screen-based shaving machines mitigated some of the problems of shaving by shearing, mainly closeness and speed. Still, the need for a narrow shaving head which can be placed or passed across the human face without obstructions posed a limit on the size of the shaving head to be narrow and slim, and the need for a powerful motor (and thus a large enough power supply unit) imposed limits to the size of the contemporary shaving machine from the other side of the range. Hence, a shaving machine having the requirements of a small and accessible shaving head and sufficiently powered motor is typically bulky.

[0036] While searching for an optimal solution to all the aforementioned problems associated with a mechanized scissors action shaving (shearing) apparatus, the present inventor has now accomplished a light-weight and compact shearing shaving apparatus which provides a fast, safe and close shave.

[0037] Hence, according to some embodiments of the present invention, the problem of an accessible shaving head is solved with a narrow and slim shaving head having the moving parts confined within the rotary cutter. Furthermore, according to some embodiments of the present invention, the compact drive mechanism, which can be in the form of an electric motor, can be powered effectively using a relatively compact power source placed in a narrow tube-like handle. Because the shaving apparatus will not have external gears, shafts or belts in some embodiments, far less energy is wasted on eccentric moving parts and friction. Put together, the provisions of the present invention solve the problem of cumbersome motorized shaving apparatus by using a shaving head as described hereinbelow, which is implemented in a shaving apparatus that has, for example, the size and shape of a contemporary non-motorized razor as described below.

[0038] Referring first to FIGS. 1 and 2 concurrently, a shaving apparatus **1000** according to an embodiment of the present invention is illustrated. The shaving apparatus **1000** generally comprises a handle portion **100** (hereinafter referred to as the “handle”) and a head portion **200** (hereinafter referred to as the “head”). The handle **100** provides the user of the shaving apparatus **1000** with the necessary structure to comfortably and firmly grip and maneuver the shaving apparatus **1000** in the manner necessary to shave a desired

area of skin. In the exemplified embodiment, the handle **100** is an elongated structure that comprises a generally cylindrical portion **104** for gripping and a mounting member **106** for coupling of the head **200** to the handle **100**. In one embodiment, the handle **100** has a length between 70 mm to 140 mm.

[0039] The cylindrical portion **104** extends along the longitudinal axis **A-A**. In one embodiment, the cylindrical portion **104** of the handle **100** has a diameter of between 10 mm to 25 mm. The mounting member **106** is coupled to a distal end of the cylindrical portion **104** and extends radially away from the longitudinal axis **A-A** in an inclined manner. The distal end of the mounting member **106** is configured so that the head **200** can be coupled thereto. The head **200** can be coupled to the mounting member **106** in a permanent, semi-permanent, or detachable manner. For example, the head **200** could be integrally formed with the mounting member **106**, thereby creating a permanent coupling. Alternatively, the head **200** could be coupled to the mounting member **106** via ultrasonic welding, thermal welding, soldering, adhesion or combinations thereof, thereby creating a semi-permanent coupling. In still other embodiments, the head **200** could be coupled to the mounting member **106** via a snap-fit connection, a mechanical interlock, an interference fit, a threaded connection, a tab/slot interlock, a latch, or combinations thereof, thereby creating a detachable coupling. Of course, other connection techniques are contemplated and are considered to be within the scope of the invention. Moreover, in certain other embodiments of the invention, the mounting member **106** can be less prominent or omitted all together so that the head **200** is directly coupled to the cylindrical portion **104**.

[0040] As will be appreciated by the skilled artisan, an attempt to arrive at a minimal size and weight of a battery-powered motorized shaving apparatus may end at the size limitation of the battery which can power the motor effectively so as to deliver the required effect for the required time period. When achieving a reduction of the workload of the motorized element and making its action more efficient, one can then reduce the overall size limitations imposed also of the power source, namely the battery or batteries. As presented hereinbelow, the shaving head according to some embodiments of the present invention is designed such that its scissors-like shaving action can be effected by a small motor, which can therefore be powered by a correspondingly small

power source, compared to presently known configurations. Hence, the shaving head design, according to embodiments of the present invention, can afford a significant reduction of power consumption, leading to a significant reduction in size of the motor assembly, leading in turn to a significant reduction in size and weight of the entire shaving apparatus.

[0041] In the exemplified embodiment, the handle **100** also acts as a water-tight housing for a power source **105** (shown in dotted lines) that powers the motor **400** that rotates the rotary cutter **300** of the head **200** (the details of which will be discussed in greater detail below with respect to FIG. 6). Of course, in other embodiments, the power source **105** may be housed elsewhere in the shaving apparatus **1000**. For example, in certain alternate embodiments, the power source **105** may be housed entirely or at least partially within the head **200**. The power source **105** can be in the form of one or more batteries as is known in the art. In the exemplified embodiment, the batteries are disposed on and extend along the longitudinal axis **A-A** of the handle **100**. Of course, alternative types of power sources can be utilized to power the motor **400** as desired. The exact type of power source **105** utilized in the shaving apparatus **1000** will depend on the power requirements of the motor **400** and, thus, is not to be considered limiting of the present invention unless specifically stated otherwise in the claims.

[0042] The power source **105** could be replaceable or permanent. In embodiments in which a removable power source **105** is used, the power source **105** may be one or more batteries that could be removed from the handle **100** for replacement or recharging. In such an embodiment, the handle **100** will further comprise the necessary structure to access the chamber of the handle **100** in which the power source **105** is located. In the exemplified embodiment, a removable cap **107** is provided at the proximal end **101** of the handle **100**. The removable cap **107** can be coupled to the cylindrical portion **104** of the handle **100** via a threaded connection, a tight-fit assembly, or other connection technique that would create a fluid tight boundary so that water could not enter the chamber in which the power source **105** is located. In alternate embodiments, access to the internal chamber of the handle **100** in which the power source **105** is disposed can be accomplished via a hinged panel, a latch, a removable panel or any other structure as would be known to one of skill in the art.

[0043] In embodiments where a permanent (or non-removable) battery is used, the handle **100** may further comprise an electrical port to which a power cord could be electrically coupled to recharge the power source **105**. To prevent water or other fluids from entering the electrical port, the electrical port may be provided behind a removable access panel or be provided with a cap/plug that seals the electrical port.

[0044] A switch **108** is provided on the handle **100** for manually controlling the energization of the motor **400**. While the switch **108** is exemplified as a manual slide switch, the switch could be any type of manual or automatic switch as would be known by those of skill in the art. In addition to the switch **108**, control circuitry for controlling the performance characteristics of the motor **400** may also be located within the chamber of the handle **100** as desired.

[0045] As mentioned above, the head **200** is coupled to the distal end of the mounting member **106** of the handle **100**. The head **200** has a generally elongated shape and extends along the longitudinal axis **B-B**. As discussed in detail below, the longitudinal axis **B-B** of the head **200** also serves as the axis of rotation of the rotary cutter **300**. In the exemplified embodiment, when the head **200** is coupled to the handle **100**, the head **200** is substantially perpendicular to the handle **100**. More specifically, when the head **200** is coupled to the handle **100**, the longitudinal axis **B-B** of the head **200** is substantially perpendicular to the longitudinal axis **A-A** of the handle **100**. Moreover, the handle **200** is coupled to the center of the head **200** so that the shaving apparatus **1000** has a generally T-shape.

[0046] In the exemplified embodiment, the head **200** is fixedly coupled to the handle **100** through the use of fastener elements **201** that extend from a tubular housing **202** of the head **200**. The fastener elements **201** are plates that extend from a rear face **203** of the head **200** opposite the front face **204** of the head **200**, wherein the front face **204** can be considered the working/cutting face of the head **200** as described below. The fastener elements **201** matingly engage corresponding structure on the mounting member **106** of the handle **100**. Of course, the fastener elements **201** can take on a wide variety of structures, including pins, tangs, sockets, or other coupling or mating structures.

[0047] While the head **200** is fixedly coupled to the handle **100** in the exemplified embodiment, the head **200** may be pivotally connected to the handle **100** so that the

orientation of the head **200** can be pivoted with respect to the handle **100**. Thought of another way, in such an arrangement, the head **200** can be pivoted so that the longitudinal axis **B-B** of the head **200** can be rotated relative to the longitudinal axis **A-A** of the handle **100**. Such pivotal movement can be accomplished in a variety of manners. In one embodiment, the fastener elements **201** of the head **200** pivotally couples the head **200** to the mounting member **106**. In another embodiment, the mounting member **106** is pivotally coupled to the cylindrical portion **104** of the handle **100**. Pivotally coupling the head **200** to the handle **100** enables the front face **204** of the head **200** to be pivoted to any desired position with respect to the handle **100** during use of the shaving apparatus **1000**, thereby allowing the user a greater degree of flexibility and the ability to shave complex contours and/or hard to reach places.

[0048] The pivotal coupling of the head **200** to the handle **100** allows the head **200** to swivel (i.e., rock) within a limited angle range about the longitudinal axis **A-A** of the handle. Such pivotal rotation allows the head **200** to adjust its position relative to the plane of motion and the skin of a user during use of the shaving apparatus **1000**. Such pivotal motion can be limited, by mechanical means in the attachment mechanism and/or the handle **100** and/or the head **200**, to a desired angle of rotation. In certain embodiments, the angle of rotation may be 180 degrees, 90 degrees, 60 degrees, 30 degrees or less than 30 degrees.

[0049] As mentioned above, in certain alternate embodiments, the head **200** will be detachably coupled to the handle **100**. In such embodiments, the head **200** can be sold as a “refill” head for the handle **100**. As discussed below with respect to FIG. 6, the motor **400** is located within the rotary cutter **300** of the head **200**. Moreover, as discussed above, the power source **105** is located within the handle **100**. Thus, a continuous electrical connection extends from the power source **105** in the handle **100** to the motor **400** in the head **200** in order to power the motor **400** during use. Therefore, in embodiments where the head **200** is detachably coupled to the handle **100**, electrical interface connectors (i.e., contacts) will be provided at appropriate positions on both the handle **100** and the head **200** that come into electrical coupling with one another when the head **200** is coupled to the handle **100**, thereby completing the electrical circuit.

[0050] Referring now to FIGS. 3-4 concurrently, the head 100 generally comprises a tubular housing 202, a first end cap 205, a second end cap 206, a fixed blade 350, the motor 400, the rotary cutter 300, a first annular bearing 250, and a second annular bearing 251. When the head is assembled (discussed below with respect to FIG. 6), as shown in FIG. 3, the head 200 is a compact, elongated and generally cylindrical structure, extending along longitudinal axis B-B.

[0051] The head 100 extends from a first end 207 to a second end 208 along the longitudinal axis B-B, thereby defining a maximum longitudinal width W_L of the head 200. In an exemplary embodiment, the maximum longitudinal width W_L of the head 200 is less than or equal to 60 mm. In another exemplary embodiment, the maximum longitudinal width W_L of the head 200 is between 40 mm to 60 mm. In yet another embodiment, the maximum longitudinal width W_L of the head 200 is between 45 mm to 55 mm. The head further comprises a maximum transverse width W_T , extending from a lead face 209 of the head 200 to a trail face 210 of the head 200. In an exemplary embodiment, the maximum transverse width W_T of the head 200 is less than or equal to 25 mm. In another embodiment, the maximum transverse width W_T of the head 200 is between 10 mm to 25 mm. In yet another embodiment, the maximum transverse width W_T of the head 200 is between 10 mm to 20 mm. In still another embodiment, the maximum transverse width W_T of the head 200 is between 10 mm to 15 mm.

[0052] In the exemplified embodiment, both the maximum longitudinal width W_L of the head 200 and the maximum transverse width W_T of the head 200 are measured on the front face 204 of the head 200. The front face 204 of the head 200 is the working face of the head 200 in that it is the face of the head 200 that is put into contact with the user's skin so that the shaving apparatus 1000 can shear hairs between the rotary cutter 300 and the fixed blade 350. In alternate embodiments, the maximum longitudinal width W_L of the head 200 and/or the maximum transverse width W_T of the head 200 may be dictated by other components of (or at other locations on) the head 200.

[0053] The tubular housing 202 is an elongated hollow tubular structure extending from a first end 212 of the tubular housing 202 to a second end 213 of the tubular housing 202 along longitudinal axis B-B. The tubular housing 202 comprises an internal cavity 211 for accommodating the rotary cutter 300 and the motor 400. The internal cavity 211 of

the tubular housing **202** is dimensioned so as to be capable of receiving and enclosing both the rotary cutter **300** and the motor **400** therein.

[0054] The tubular housing **202** also comprises an elongated slot **214** that forms a passageway into the internal cavity **211** of the tubular housing **202**. The elongated slot **214** allows hair bristles to enter the tubular housing **202** and be sheared between the rotary cutter **300** and the fixed blade **350** as discussed in greater detail with respect to FIGS. 5A-B. In the exemplified embodiment, the elongated slot **214** extends the entire longitudinal length of the tubular housing **202** in a continuous and uninterrupted manner. However, in certain alternate embodiments, the elongated slot **214** may not extend the entire longitudinal length of the tubular housing **202** and may instead be segmented and/or discontinuous in nature.

[0055] The elongated slot **214** is defined by a cutting edge **351** of the fixed blade **350** and an opposing edge **215** of the tubular housing **202**. In the exemplified embodiment, the opposing edge **215** of the tubular housing is formed by a plurality of axially-spaced fingers **216** that collectively form a comb guard **217**. The comb guard **217** is part of the tubular housing **202** and can be pressed against the user's skin during a cutting operation to more effectively feed the hair bristles to the rotary cutter **300** and fixed blade **350** for shearing, while at the same time protecting the user from nicking or cutting the skin. In order to further achieve this purpose, the outer surfaces **218** of the fingers **216** of the comb guard **217** are optionally flat or rounded to facilitate the movement of the head **200** over the user's skin.

[0056] In certain embodiments, the tubular housing **202** may also comprise an optional opening (short slot) in the rear face **203** of the head **200** for allowing removal of sheared hair bristle debris from the internal cavity **211**. Such a feature may be especially useful in embodiments in which a bi-directional helical rotary cutter **300** is utilized (described in greater detail below). Finally, as can be seen in FIG. 3, the fastener elements **201** are also part of the tubular housing **202**.

[0057] Referring now to FIGS. 4 and 5A-B, the rotary cutter **300** is of a hollow cylindrical configuration. The rotary cutter **300** comprises a cylindrical body **301** having an outer surface **302** and an inner surface **303**. The inner surface **303** forms a cavity **304** about the longitudinal axis **B-B** (which is also both the central axis and rotational axis of

the rotary cutter 300). The cavity 304 of the rotary cutter 300 is dimensioned so as to receive the motor 400 therein. When the head 200 is assembled, the motor 400 is mounted within the cavity 304 of the rotary cutter 300 (discussed in detail with respect to FIG. 6). In an exemplary embodiment, the cavity 304 has a diameter D_1 between 3 mm to 18 mm.

[0058] The rotary cutter 300 further comprises a plurality of spaced-apart ridges 305 protruding from the outer surface 302 of the cylindrical body 301. The ridges 305 extend radially outward from the outer surface 302 of the cylindrical body 301 and terminate in convex outer surfaces 306 that collectively define a reference cylinder (delineated by dotted circle C-C of FIG. 5A) that is concentric to the longitudinal axis B-B and has a diameter D_2 . In an exemplary embodiment, the diameter D_2 is less than or equal to 20 mm. In another embodiment, the diameter D_2 is between 6 mm to 20 mm.

[0059] Each of the ridges 305 includes a sharpened cutting edge 307. In the exemplified embodiment, each of the cutting edges 307 is formed by the sharp intersection of the convex outer surfaces 306 of the ridges 305 and concave sidewall surfaces 308 of the ridges 305. As a result of the aforementioned structure, the rotary cutter 300 comprises a plurality of spaced-apart cutting edges 307 extending from the outer surface 302 of the cylindrical body 301.

[0060] In the exemplified embodiment, the spaced-apart ridges 305 (and thus the spaced-apart cutting edges 307) are in a helical configuration about the cylindrical body 301. In an alternative embodiment, the spaced-apart ridges 305 (and thus the spaced-apart cutting edges 307) can have a helical configuration twisted in one direction (hand) from a first end 309 of the rotary cutter 300 to a mid-point of the rotary cutter 300, and then twisted in the opposite direction (opposite hand) from that mid-point of the rotary cutter 300 to the second end 310 of the rotary cutter 300. Such a bi-directional helical rotary cutter 300 may be used to impel the hair bristle debris to a mid-point along the head 200 or away therefrom, thereby facilitating removal of the debris.

[0061] In further embodiments, the rotary cutter 300 can be of a segmental configuration, namely the rotary cutter 300 can be collectively formed by a plurality of cylindrical segments, or hollow cylinder slices, wherein each segment is formed with a plurality of evenly-spaced, outwardly-projecting ribs 305 and cutting edges 306 on its outer surface,

and each slice is shifted by a small angle with respect to its adjacent neighboring slice. In an even further embodiment, the rotary cutter **300** can be (or form part of) the outer housing of the motor **400**, which also acts as the rotor component of the motor while the stator of the motor **400** would be the core.

[0062] Referring now to FIGS. 3 and 5A-B, when the head **200** is assembled for operation, the fixed blade **350** is mounted adjacent the rotary cutter **300**. In one embodiment, the fixed blade **350** is mounted adjacent the rotary cutter **300** so that the cutting edge **351** of the fixed blade **350** extends substantially parallel to the axis of rotation of the rotary cutter **300**, which in the exemplified embodiment is the longitudinal axis **B-B**. In the exemplified embodiment, such adjacent positioning is achieved by mounting the fixed blade **350** to the tubular housing **202** so that the cutting edge **351** of the fixed blade **350** extends into the slot **314** and adjacent the cutting edges **307** of the rotary cutter **300**.

[0063] In one embodiment, the fixed blade **350** is “fixed” with respect to its radial distance from the axis of rotation **B-B** of the rotary cutter **300**. As used herein, the term “fixed” is intended to cover embodiments where small vibrations may be imparted to the fixed blade **350** and/or wherein the fixed blade **350** may axially translate slightly in a manner that maintains the cutting edge **351** substantially parallel to axis of rotation **B-B** and its radial distance therefrom. In certain other embodiments, the fixed blade **350** may be completely stationary and immovable with respect to both the axis of rotation **B-B** and the tubular housing **202**.

[0064] When the exemplified embodiment is assembled, the cutting edge **351** of the fixed blade **350** extends along the entire length of the rotary cutter **300**. The cutting edge **351** of the fixed blade **350** is sufficiently proximate the cutting edges **307** of the rotary cutter **300** so as to be effective in cooperating with the cutting edges **307** of the rotary cutter **300** to shear hair bristles therebetween during a cutting operation when the motor **400** is activated and the front face **204** of the head **200** is pressed against and moved along the skin. In one embodiment, a tolerance, in the form of a cutting gap **325** is designed to exist between the cutting edge **351** of the fixed blade **350** and the cutting edges **307** of the rotary cutter **300** during a cutting operation. In one embodiment, the cutting gap **325** is no greater than 0.5 mm, and optionally no greater than 2.5 mm. In one embodiment, the

cutting gap 325 has a fixed size and thus can not be varied and/or adjusted. As shown in FIG. 5B, the cutting edges 307 of the rotary cutter 300 oppose the cutting edge 351 of the fixed blade 350 during shearing of the user's hair between the cutting edge 351 of the fixed blade 351 and the cutting edges 307 of the rotary cutter 300.

[0065] Referring now to FIGS. 3-4 and 6, the structural cooperation of the various components of the head 200 in the assembled state will be further discussed. When the head 200 is assembled for use, the motor 400 is positioned in the cavity 304 of the rotary cutter 300 and operably coupled thereto so as to be capable of rotating the rotary cutter 300 about the longitudinal axis B-B.

[0066] According to some embodiments of the present invention, the motor 400 is an electric motor and is electrically coupled to the power source 105 housed in the handle 100 as described below. When the motor 400 is electric, the motor 400 can be powered by alternating or direct current. In certain embodiments, the motor 400 may be a brushless type motor or a brushed motor type; and/or may be a cored or coreless type motor. For example, a brushless DC electric motor is a synchronous electric motor which is powered by direct-current electricity and has an electronically controlled commutation system (a "controller") instead of a mechanical commutation system based on brushes, as present in the brushed motors.

[0067] The motor 400 is dimensioned so as to be locatable within the cavity 304 of the rotary cutter 300. In one embodiment, the motor 400 has an outer diameter that is equal to or less than 12 mm. In another embodiment, the motor 400 has an outer diameter between 3 mm to 12 mm. In yet another embodiment, the motor 400 has an outer diameter between 3 mm to 10 mm. In a yet further embodiments, the motor 400 has an outer diameter between 3 mm to 8 mm.

[0068] It is noted herein that the term "motor", which is used herein interchangeably with the phrase "electric motor assembly", is intended to encompass the assembly of parts which transform electrical power to mechanical motion as a required output force/torque and speed. Adjustment of torque and speed is typically achieved by including a gear and/or another form of transmission element in the electric motor assembly.

[0069] As discussed hereinabove, the size of motor 400 is selected such that it can rotate the rotary cutter 300 at a sufficient torque and speed so as to effect shaving, considering

the minimal contact between rotary cutter 300 and the user's skin, and considering the force required to cut more than one hair simultaneously. Since motor performance correlates to the size of the motor 400, the size limitation of the motor 400 can be derived from the following considerations: (i) the need for a compact minimal motor size which projects on the width of the shaving head and the size requirements of the power source (battery); and (ii) the need for sufficient torque and speed to accomplish fast and efficient shearing of more than one hair strand at the same time.

[0070] The assembly of the rotary cutter 300 and the motor 400 is, in turn, located within the internal cavity 211 of the tubular housing 202. The first end cap 205 is coupled to the first end 212 of the tubular housing 202. The first end cap 205 encloses a first end of the internal cavity 211 of the tubular housing 202 and a first end of the cavity 304 of the rotary cutter 300. Similarly, the second end cap 206 is coupled to the second end 213 of the tubular housing 202. The second end cap 206 encloses a second end of the internal cavity 211 of the tubular housing 202 and a second end of the cavity 304 of the rotary cutter 300. The first end cap 205 forms a first transverse wall 230 at the first end 212 of the tubular housing 202 while the second end cap 206 forms a second transverse wall 231 at the second end 213 of the tubular housing 202. These transverse walls 230, 231 assist in sealing the cavity 304 of the rotary cutter 300 from the ingress of water and other liquids that may damage the motor 400 and electrical connectors 501A, 501B. Of course, in certain alternate embodiments, the transverse end walls 230, 231 do not have to be formed by cap-like components but can be integrally formed as part of the tubular housing 202 or be mere plates or blocks extending from the handle 100. Furthermore, while the transverse walls 230, 231 are exemplified as flat plate-like structures, in alternate embodiments, the transverse walls 230, 231 can take the form of posts, blocks, struts and/or combinations thereof, and can also be contoured and/or inclined as desired.

[0071] Each of the transverse walls 230, 231 (or end caps 205, 206) comprise an inwardly extending axial posts 332, 333. The first annular bearing 250 is mounted to the first axial post 332 while the second annular bearing 251 is mounted to the second axial post 333. In the exemplified embodiment, both of the annular bearings 250, 252 are of the ball-bearing type. However, bearing types that can be used in the context of the present invention include, without limitation, plain bearings, also known as sliding or

slipping bearings which are based on rubbing surfaces and typically a lubricant (implemented by use of hard metals or plastics such as PTFE which has coefficient of friction of about 0.05); rolling element bearing, also known as ball bearings which are based on balls or rollers (cylinders) and restriction rings; or magnetic bearings and flexure bearings. In certain embodiments, the annular bearings **250**, **251** could take the form of the outer annular surfaces of the axial posts **332**, **333**, so long as these outer annular surfaces have been designed to achieve a desired coefficient of friction with the moving part in contact therewith. In certain alternate embodiments, at least one of the bearings may not be annular in nature. Finally, the term “annular” may include segmentally annular in certain embodiments.

[0072] The first annular bearing **250** rotatably mounts the first end **309** of the rotary cutter **300** to the first transverse wall **230** while the second annular bearing **251** rotatably mounts the second end **310** of the rotary cutter **300** to the second transverse wall **231**. The first annular bearing **250** nests within the cavity **304** of the rotary cutter **300** and is coupled to the first end **309** of the rotary cutter **300** via contact/engagement with the inner surface **303** of the rotary cutter **300**. The second annular bearing **251**, however, abuts the second end **310** of the rotary cutter **300** and is coupled to the second end **310** of the rotary cutter **300** via bearing posts **255** (best shown in FIG.7). Because the second annular bearing **251** is not positioned within the cavity **304** of the rotary cutter **300**, it has a larger central opening **256** than the central opening (not numbered) of the first annular bearing **250**. More specifically, the central opening **256** of the second annular bearing **251** has a transverse cross-sectional area that is greater than the transverse cross-sectional area of the central opening of the first annular bearing **250**. This, in turn, allows the second axial post **333** to have a larger transverse cross-sectional area (when compared to the transverse cross-sectional area of the first axial post **332**). In certain embodiments, this is beneficial because the increased transverse cross-sectional area of the second axial post **333** allows the second axial post **333** to maintain its strength and structural integrity despite having a channel **502** formed therein through which the electrical connectors **501A**, **501B** axially extend.

[0073] The motor **400** is mounted within the cavity **304** of the rotary cutter **300**. In the exemplified embodiment, the motor **400** is mounted to the second transverse wall **231** in

a cantilevered manner. More specifically, a first end **402** of the motor **400** is mounted to the second transverse wall **231** while a drive shaft **401** extends from a second end **403** of the motor **400**. The drive shaft **401** non-rotatably mates with an internal shaft-engagement element **375**, which is in the form of a transverse wall that is non-rotatably coupled to the cylindrical body **301** of the rotary cutter **300**. It will thus be seen that the rotary cutter **300** is driven by the motor **400** via the mating between the internal shaft-engagement piece **375** and the drive shaft **401**, and is mounted by the annular bearings **250**, **251** at its ends **309**, **310**, thereby providing a balanced coupling of the rotary cutter **300** to the motor **30** and the rotary cutter **300** within the tubular housing **202**.

[0074] As mentioned above, the motor **400** is electrically powered by the power source **105** in the handle **100**. The motor **400** is electrically coupled to the power source **105** by electrical connectors **501A**, **501B** which, in the exemplified embodiment are wires. In alternate embodiments, the electrical connectors take on other forms, including plating of surfaces with electrically conductive materials. The electrical connectors **501A**, **501B** are operably coupled to the motor **400** at one end and extend axially from the motor **400** through the second annular bearing **251** via the channel **502**. Once through the annular bearing **251**, the electrical connectors **501A**, **501B** extend radially away from the longitudinal axis **B-B** and into the handle **100** via the most desirable path selected.

[0075] There are clear advantages in having the entire driving mechanism housed within the head **200**, including a compact design and the locating of all of the motorized moving parts within the head **200**. Such a design also eliminates the need to house the motor **400** or parts of the drive transmission mechanism in a separate housing. Such design further enables substantially quiet and substantially vibration free operation due to the central and coaxial position of the motor and rotor. Further, a minimal number of moving parts is required, which in turn contributes to the minimization of energy loss due to friction, slack and slippage, thereby substantially decreasing the noise and vibrations, as well as the wear and tear plaguing many of the presently known drive transmission mechanisms.

[0076] Another advantage afforded by the concept of the internally motorized head **200** presented herein, is the ability to arrive at very high speeds of rotation of the rotary cutter unit, driven by an internal driving mechanism. Hence, the scissors-like cutting action

(energy-efficient cutting mechanism) coupled with an internally motorized shaving head affords the use of relatively small, low-energy and high-speed electric motors.

[0077] The internally motorized shaving head can be constructed with an internal driving mechanism having a capacity to rotate the rotary cutter unit at a speed of at least 300 revolutions per minute (rpm). Alternatively, the rotational speed of the rotary cutter unit may be at least 500 rpm, 800 rpm, 1000 rpm, 1500 rpm, 2000 rpm, 3000 rpm, 4000 rpm, 5000 rpm, 7000 rpm, 10000 rpm, 12000 rpm, 15000 rpm, 20000 rpm, 25000 rpm, 30000 rpm, 40000 rpm and 50000 rpm.

[0078] The optimal speed of rotation is effected by several factors, including the choice of electric motor, the current and voltage supplied to the electric motor, and optionally by use of an inline drive transmission, namely a particular assembly of gears, pins and the like, normally used to reduce or increase the output speed of a motor. Thus, the electric motor assembly may include an inline transmission device to control the output speed and torque of the electric motor in the internally motorized shaving head presented herein. As used herein, the phrase "inline transmission device" refers to a drive transmission device, or gear box, which is placed inline with the motor, namely the motor output shaft and the gearbox output shaft share the same axis of rotation. An inline transmission device may include epicyclic gearing, or planetary gearing. Such an inline gearing system can be selected so as to increase the torque of the motor and reduce its speed or the opposite, depending on the selected motor and desired terminal rotation output. It is to be understood that various parts of the internally motorized shaving head presented herein are presented as discrete and separate parts for the sake of clarity and definition. However, some of the parts described herein can be manufactured as a union with other parts, forming a single continuous unit, while some parts described herein as single continuous units can be formed by a plurality of sub-parts.

[0079] Referring now to FIG. 8, an alternate embodiment of the head **200** is exemplified. In this alternate embodiment, a portion of the motor **400** extends through the second annular bearing **251** rather than the electrical connectors **501A**, **501B**. Moreover, the second annular bearing **251** is mounted to the motor **400** while the second axial post **233** is omitted.

[0080] As used throughout, ranges are used as shorthand for describing each and every value that is within the range. Any value within the range can be selected as the terminus of the range. In addition, all references cited herein are hereby incorporated by reference in their entireties. In the event of a conflict in a definition in the present disclosure and that of a cited reference, the present disclosure controls.

[0081] The shaving apparatus, according to some embodiments of the present invention, equipped with the shaving head according to some embodiments presented herein, can be used to effect close shave of hair bristles, such as human facial hair, rapidly and safely.

[0082] Unlike traditional manual or mechanized scrapers, the shaving apparatus presented herein can be used with or without lubrication or wetting of the skin prior to or during the shaving process. Hence, since the shaving apparatus presented herein is based on scissors-action rather than pure scraping, the apparatus can be used effectively under wet or dry conditions substantially without requiring pretreatment or conditioning of the hair or skin. The phrase "pretreatment or conditioning of the hair or skin", as used herein, refers to any form of wetting the skin/hair by the application of water, a pre-shaving composition, a lotion and/or a foam. It is noted herein that pretreatment or conditioning of the hair or skin is not a prerequisite but an option of the shaving process using the shaving apparatus presented herein.

[0083] One exemplary mode of use of the shaving apparatus presented herein starts with a user gripping the apparatus at handle **100**, and switching switch **108** thereby turning the apparatus to the operational ("on") state, which means that rotary cutter **300** of the head **200** is rotating as a result of the rotation of motor **400**, which is powered by power source **105**. Once the apparatus is operational, the user presses front face **104** of the shaving head **200** flat on his/her skin, and glides the head **200** across the skin at a direction which is generally perpendicular to the longitudinal axis **B-B**. The direction of motion can be a forward or a backward motion. However, hair is shaved (or trimmed) essentially without movement of the head **200** with respect to the skin's surface as hair shearing occurs as a result of the relative motion between the cutting edges **307** of the rotary cutter **300** and the fixed blade **351**, and regardless of the relative motion of the head **200** to the user's skin. It is noted herein that the shaving process using the shaving apparatus presented herein can be carried out by lifting and re-contacting the head **200** with the surface of the

skin. However, in certain embodiments, the head **200** is moved by the user across the skin's surface while the head **200** is pressed against the surface of the skin so as to effect shaving at other areas of the skin surface in a continuous manner.

[0084] The shaving head presented herein can also effect hair cutting at any distance from the skin (where the hair follicle is found), leaving trimmed hair. This hair trimming can be achieved by adding an extension to the shaving head or building in a desired tolerance/gap, allowing the front face **204** of the head **200** to be placed on the hair growing surface at a pre-determined distance which corresponds to the length of the trimmed hair.

[0085] While the foregoing description and drawings represent the exemplary embodiments of the present invention, it will be understood that various additions, modifications and substitutions may be made therein without departing from the spirit and scope of the present invention as defined in the accompanying claims. In particular, it will be clear to those skilled in the art that the present invention may be embodied in other specific forms, structures, arrangements, proportions, sizes, and with other elements, materials, and components, without departing from the spirit or essential characteristics thereof. One skilled in the art will appreciate that the invention may be used with many modifications of structure, arrangement, proportions, sizes, materials, and components and otherwise, used in the practice of the invention, which are particularly adapted to specific environments and operative requirements without departing from the principles of the present invention. The presently disclosed embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being defined by the appended claims, and not limited to the foregoing description or embodiments.

Claims

What is claimed is:

1. A shaving apparatus head comprising:

a rotary cutter comprising a cylindrical body having an outer surface and an inner surface forming a cavity, and a plurality of spaced-apart cutting edges extending from the outer surface of the cylindrical body;

an electric motor located within the cavity and operably coupled to the rotary cutter to rotate the rotary cutter about an axis; and

a fixed blade having a cutting edge, the fixed blade mounted adjacent the rotary cutter so that a user's hairs are sheared between the cutting edge of the fixed blade and the cutting edges of the rotary cutter when the rotary cutter is rotating.

2. The shaving apparatus according to claim 1 wherein the rotary cutter further comprises a plurality of spaced-apart ridges protruding from the outer surface of the cylindrical body and terminating in outer surfaces that collectively define a reference cylinder that is concentric to the axis, the ridges comprising the cutting edges of the rotary cutter.

3. The shaving apparatus according to claim 2 wherein the diameter of the reference cylinder is in a range between 6 mm to 20 mm.

4. The shaving apparatus head according to any one of claims 1 to 3 wherein the diameter of the cavity of the rotary cutter is between 3 mm to 18 mm.

5. The shaving apparatus head according to any one of claims 1 to 4 wherein the diameter of the motor is between 3 mm to 12 mm.

6. The shaving apparatus head according to any one of claims 1 to 5 wherein the cutting edges of the rotary cutter oppose the cutting edge of the fixed blade during shearing of

the user's hair between the cutting edge of the fixed blade and the cutting edges of the rotary cutter.

7. The shaving apparatus head according to any one of claims 1 to 6 further comprising:

a tubular housing having an internal cavity, the rotary cutter rotatably mounted within the internal cavity of the tubular housing, and the fixed blade mounted to the housing; and

an elongated slot in the tubular housing forming a passageway into the internal cavity of the tubular housing, the slot defined by the cutting edge of the fixed blade and an edge of the housing, the cutting edge of the fixed blade extending substantially parallel to the axis.

8. The shaving apparatus head according to claim 7 wherein the tubular housing has a maximum transverse width that is no greater than 25 mm.

9. The shaving apparatus head according to any one of claims 7 to 8 wherein the fixed blade is mounted to the housing so that a cutting gap no greater than 0.5 mm exists between the cutting edge of the fixed blade and the cutting edges of the rotary cutter.

10. The shaving apparatus head according to any one of claims 7 to 9 further comprising:

a first transverse wall at a first end of the tubular housing;

a second transverse wall at a second end of the tubular housing, the first and second transverse walls enclosing opposite ends of the internal cavity of the tubular housing;

a first bearing rotatably mounting a first end of the rotary cutter to the first transverse wall; and

a second bearing rotatably mounting a second end of the rotary cutter to the second transverse wall.

11. The shaving apparatus head according to claim 10 wherein the motor is mounted in a cantilevered manner to the second transverse wall.

12. The shaving apparatus head according to claims 10 to 11 wherein the first and second bearings are annular bearings, the shaving apparatus head further comprising an electrical connector extending axially from the motor through the second annular bearing.
13. The shaving apparatus head according to any one of claims 1 to 9 further comprising:
a first bearing rotatably mounting a first end of the rotary cutter;
a second annular bearing rotatably mounting a second end of the rotary cutter; and
an electrical connector extending axially from the motor through the second annular bearing, and then radially outward from the axis toward a handle.
14. The shaving apparatus head according to any one of claims 1 to 9 further comprising:
a first bearing rotatably mounting a first end of the rotary cutter;
a second annular bearing rotatably mounting a second end of the rotary cutter;
a portion of the motor extending axially through the second annular bearing; and
an electrical connector electrically coupled to the portion of the motor.
15. The shaving apparatus according to any one of claims 1 to 14 wherein a cutting gap exists between the cutting edge of the fixed blade and the cutting edges of the rotary cutter, wherein the cutting gap has a fixed size.
16. A shaving apparatus comprising:
an elongated handle portion;
a power source; and
a head portion coupled to a distal end of the elongated handle portion, the head portion comprising:
a cylindrical rotary cutter comprising a cavity and a plurality of spaced-apart cutting edges;

an electric motor located within the cavity and operably coupled to the rotary cutter to rotate the rotary cutter about an axis, the electric motor electrically coupled to the power source; and

a fixed blade having a cutting edge, the fixed blade mounted adjacent the rotary cutter so that a user's hairs are sheared between the cutting edge of the fixed blade and the cutting edges of the rotary cutter when the rotary cutter is rotating.

17. The shaving apparatus according to claim 16 wherein the power source is housed within the elongated handle portion, the head portion further comprising: a first transverse wall; a second transverse wall; a first bearing rotatably mounting a first end of the rotary cutter to the first transverse wall; a second annular bearing rotatably mounting a second end of the rotary cutter to the second transverse wall; and an electrical connector electrically coupled to the motor and the power source, the electrical connector extending axially from the motor through the second annular bearing and then radially outward from the axis to the power source.

18. The shaving apparatus according to claim 17 wherein the head portion further comprises: a tubular housing having an internal cavity and extending between the first and second transverse walls, the rotary cutter disposed within the internal cavity of the tubular housing, and the fixed blade mounted to the tubular housing; an elongated slot in the tubular housing forming a passageway into the internal cavity of the tubular housing, the slot defined by the cutting edge of the fixed blade and an edge of the housing, the cutting edge of the fixed blade extending substantially parallel to the axis.

19. The shaving apparatus according to claim 16 wherein the power source is housed within the elongated handle portion, the head portion further comprising: a first transverse wall; a second transverse wall; a first bearing rotatably mounting a first end of the rotary cutter to the first transverse wall; a second annular bearing rotatably mounting a second end of the rotary cutter to the second transverse wall; a portion of the motor

extending axially through the second annular bearing; and an electrical connector electrically coupled to the portion of the motor and the power source.

20. The shaving apparatus according to any one of claims 16 to 19 wherein the cavity of the rotary cutter has a diameter that is no greater than 18 mm.

21. The shaving apparatus according to claim 16 wherein the head portion comprises a tubular housing having an internal cavity, the rotary cutter disposed within the internal cavity of the tubular housing, and the tubular housing having a maximum transverse width that is no greater than 25 mm.

22. The shaving apparatus according to any one of claims 16 to 21 wherein a cutting gap exists between the cutting edge of the fixed blade and the cutting edges of the rotary cutter, wherein the cutting gap has a fixed size.

23. The shaving apparatus according to claim 16 further comprising:
a first bearing rotatably mounting a first end of the rotary cutter;
a second annular bearing rotatably mounting a second end of the rotary cutter; and
an electrical connector extending axially from the motor through the second annular bearing, and then radially outward from the axis toward a handle.

24. The shaving apparatus according to claim 16 further comprising:
a first bearing rotatably mounting a first end of the rotary cutter;
a second annular bearing rotatably mounting a second end of the rotary cutter;
a portion of the motor extending axially through the second annular bearing; and
an electrical connector electrically coupled to the portion of the motor.