



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B29C 59/04, 39/14, 43/22	A1	(11) International Publication Number: WO 99/65664
		(43) International Publication Date: 23 December 1999 (23.12.99)

(21) International Application Number: PCT/US99/11024

(22) International Filing Date: 18 May 1999 (18.05.99)

(30) Priority Data:
09/099,562 18 June 1998 (18.06.98) US(71) Applicant: 3M INNOVATIVE PROPERTIES COMPANY
[US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN
55133-3427 (US).(72) Inventors: BENTSEN, James, G.; P.O. Box 33427, Saint
Paul, MN 55133-3427 (US). JOHNSTON, Raymond,
P.; P.O. Box 33427, Saint Paul, MN 55133-3427 (US).
BIERNATH, Rolf, W.; P.O. Box 33427, Saint Paul, MN
55133-3427 (US). POIRIER, Richard, J.; P.O. Box 33427,
Saint Paul, MN 55133-3427 (US).(74) Agents: ROGERS, James, A. et al.; 3M Innovative Properties
Company, Office of Intellectual Property Counsel, P.O. Box
33427, Saint Paul, MN 55133-3427 (US).(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG,
BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB,
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK,
MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW,
ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG,
ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI,
FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE,
SN, TD, TG).Published
With international search report.

(54) Title: MICROFLUIDIC ARTICLES AND METHOD OF MANUFACTURING SAME

(57) Abstract

A process for preparing a molded article that includes: (a) bringing a moldable material (10) and an open molding tool (16) comprising a molding surface into line contact with each other to imprint a microfluid processing architecture pattern onto the moldable material (10) and thereby form a molded article; and (b) separating the molded article from said molding surface. The invention also features various microfluid processing architecture-bearing, polymeric articles.

