

Description

STORAGE MEDIUM STORING TEXT-BASED SUBTITLE DATA INCLUDING STYLE INFORMATION, AND APPARATUS AND METHOD OF PLAYING BACK THE STORAGE MEDIUM

Technical Field

- [1] The present invention relates to playback of a storage medium, and more particularly, to a storage medium in which text-based subtitle data including style information is recorded, and an apparatus and a method of playing back the storage medium.

Background Art

- [2] Generally, storage media, such as, digital versatile displays (DVDs), store audio-visual (AV) data, which includes video data and audio data. The stored video data and audio data in the AV data are compressed according to a standard such as the motion picture experts group (MPEG) standards. The AV data optionally includes subtitle data. Hereinafter, AV data is referred to as moving image data.
- [3] Conventional storage media, such as, DVDs, use bitmap-based sub-picture data as subtitle data for providing a subtitle of a moving image. The sub-picture data has been compressed together with a video stream, an audio stream, and the like according to a standard, such as, MPEG2 or the like. When subtitle data is provided using conventional bitmap-based sub-picture data, the subtitle data is accurately synchronized with video stream data.

Disclosure of Invention

Technical Problem

- [4] However, the use of bitmap-based sub-picture data causes the following problems. First, because a subtitle is provided using a bitmap-based image, an output style of a subtitle reflected upon the manufacture of an image corresponding to the subtitle cannot be changed. Second, because sub-title data is multiplexed with a video stream, an audio stream, and the like, it is difficult to add new sub-title data to the multiplexed sub-title data or correct existing sub-title data. Third, the number of subtitle data that can be added is restricted to prevent degradation of the quality of an image.

Technical Solution

- [5] An aspect of the present invention provides a storage medium in which text-based

subtitle data including style information is recorded, and an apparatus and a method of playing back the storage medium.

Advantageous Effects

- [6] A storage medium according to an embodiment of the present invention includes text-based subtitle data recorded separately from moving image data. The text-based subtitle data includes a plurality of pieces of style information so that a style in which a subtitle is output can be arbitrarily changed. Thus, a subtitle of a moving image can be output in various styles without degradation of the image quality of a video stream, and manufacture and edition of sub-title data are easy. Also, the style in which a subtitle is output can be arbitrarily changed by a user.
- [7] Additionally, while described in terms of a subtitle used with moving image data, it is understood that aspects of the present invention could be used with still image data and/or with audio data. Also, while described in terms of stylesheets, it is understood that aspects of the invention can be applied to any set of information associated with an electronic document and which sets forth a grouping of data, a definition of a document's appearance in terms of such elements as typeface, size, and color for headings and body text, how sections should be laid out in terms of space, line spacing, margin widths, spacing between headings, and so forth.
- [8] Further, in a storage medium according to an aspect of the present invention in which text-based subtitle data including style information is recorded and a device and method of playing back the storage medium, a subtitle can be output using style information selected by a user. Also, a style in which a subtitle is being output can be changed. In other words, text-based subtitle data according to a feature of the present invention can be easily formed and edited and output in various styles. In addition, various subtitle output styles can be selected by a user using a plurality of pieces of style information included in the text-based subtitle data.

Description of Drawings

- [9] The above and/or other features and advantages of the present invention will become more apparent and more readily appreciated by describing in detail exemplary embodiments thereof with reference to the accompanying drawings of which:
- [10] FIG. 1 is a block diagram showing types of data recorded in a storage medium according to an embodiment of the present invention;
- [11] FIG. 2 is a table defining elements and attributes that are used in a Markup document as an example of text-based subtitle data shown in FIG. 1;
- [12] FIG. 3 illustrates an example of text-based subtitle data written in a Markup

language defined in FIG. 2;

[13] FIG. 4 is a conceptual block diagram of a playback apparatus supporting text-based subtitle data, according to an embodiment of the present invention;

[14] FIG. 5 illustrates some of player status registers (PSRs) which are system registers that register style information included in text-based subtitle data shown in FIG. 1;

[15] FIG. 6 illustrates some of general purpose registers (GPRs) which are system registers that register the style information included in the text-based subtitle data shown in FIG. 1;

[16] FIG. 7 illustrates an algorithm for selecting appropriate style information in response to a user command according to an aspect of the invention;

[17] FIG. 8 illustrates an example of an application program interface (API) used to change style information shown in FIG. 1;

[18] FIG. 9 illustrates an example of a Java application written using the API defined in FIG. 8;

[19] FIG. 10 is a flowchart illustrating a method of outputting a subtitle using text-based subtitle data shown in FIG. 1; and

[20] FIG. 11 is a flowchart illustrating a method of changing an output style of a subtitle using style information included in the text-based sub-title data of FIG. 1.

Best Mode

[21] According to an aspect of the present invention, there is provided a storage medium including: moving image data; and subtitle data for providing a subtitle for the moving image data, where the subtitle data is recorded based on a text to be separated from the moving image data and includes information used to select or change an output style of the subtitle.

[22] An aspect of the subtitle data includes script information indicating a text to be displayed as a subtitle for the moving image data; and style information indicating an output style of the subtitle.

[23] An aspect of the style information is divided into at least one stylesheet which is a unit in which the style information can be changed by a user.

[24] An aspect of the stylesheet includes information about an identifier for distinguishing stylesheets from one another.

[25] An aspect of the stylesheet includes information for designating a stylesheet to be initially applied upon a reproduction of the moving image data.

[26] An aspect of the subtitle data is recorded in the form of a Markup document expressed with elements and attributes.

- [27] An aspect of the subtitle data is recorded on a local storage separate from the storage medium.
- [28] An aspect of the storage medium is an optical disc which is detachable from a playback apparatus and from which data can be read using an optical device.
- [29] According to another aspect of the present invention, there is provided an apparatus playing back a storage medium comprising moving image data, and subtitle data for providing a subtitle for the moving image data. The subtitle data is recorded based on a text to be separated from the moving image data and includes information used to select or change an output style of the subtitle. The playback apparatus includes a text subtitle processor verifying and processing the subtitle data to output a subtitle of a selected style, and a system register storing information used to select or change a style in which the subtitle is output.
- [30] An aspect of the subtitle data includes script information indicating a text to be displayed as a subtitle for the moving image data, and style information indicating an output style of the subtitle.
- [31] An aspect of the text subtitle processor renders the script information to which the style information is applied.
- [32] An aspect of the style information is divided into at least one stylesheet, which is a unit in which the style information can be changed by a user, and each of the at least one stylesheet includes information about an identifier for distinguishing stylesheets from one another.
- [33] An aspect of the system register stores an identifier of the stylesheet that is applied to the script information currently being reproduced.
- [34] An aspect of the text subtitle processor renders a subtitle by applying the stylesheet to the script information with reference to an identifier of the stylesheet stored in the system register.
- [35] An aspect of the playback apparatus further includes a core data processor controlling reproduction of the moving image data; a full data processor providing an interaction with a user with respect to the moving image data; a moving image data processor decoding the moving image data and outputting a result of the decoding on a display screen; and a blender blending an image output by the full data processor and an image output by the moving image data processor and outputting a result of the blending on the display screen.
- [36] An aspect of the core data processor and/or the full data processor receives a subtitle output command from the user and transmit the subtitle output command to the

text subtitle processor.

- [37] An aspect of the text subtitle processor reads out the subtitle data, verifies whether the read-out subtitle data is consistent with a predefined sentence structure, and renders the script information using the style information included in the subtitle data.
- [38] An aspect of the moving image data processor decodes the moving image data and the rendered script information, blends a result of the decoding, and outputs a result of the blending on the display screen.
- [39] An aspect of the core data processor and/or the full data processor receives a command to change an output style of a subtitle from the user and transmits the command to the text subtitle processor.
- [40] An aspect of the text subtitle processor changes the style information used in rendering the script information and stores the changed style information in a system register.
- [41] An aspect of the full data processor transmits the command to change the output style of the subtitle to the text subtitle processor via a predefined application program interface (API).
- [42] An aspect of the full data processor supports one of a JAVA environment and/or Markup language environment.
- [43] An aspect of the application program interface includes one of a command to designate an identifier of the stylesheet, a command which refers to a stylesheet prior to a current stylesheet in a sequence of stylesheets, a command which refers to a stylesheet next to the current stylesheet in a sequence of the stylesheets, or combinations thereof.
- [44] According to another aspect of the present invention, there is provided a method of playing back a storage medium, the storage medium including: moving image data; and subtitle data for providing a subtitle for the moving image data, where the subtitle data being recorded is based on a text to be separated from the moving image data and includes information used to select or change an output style of the subtitle, and the playback method includes operations of: designating style information to be initially applied, with reference to the subtitle data; and checking whether a current subtitle-output status is a status in which a subtitle is output and rendering and outputting script information included in the subtitle data by using the style information.
- [45] According to an aspect of the invention, the operation of checking the current subtitle-output status and rendering and outputting the script information includes sub-operations of: if a command to change an output style of a subtitle is received from a

user, checking a type of an event for the received command; and if the event belongs to a subtitle toggle event type, determining whether the current subtitle-output status is the status in which the subtitle is output or a status in which the subtitle is not output, and not outputting a subtitle if the current subtitle-output status is the status in which the subtitle is output and outputting the subtitle if the current subtitle-output status is the status in which the subtitle is not output.

[46] According to an aspect of the invention, if the event belongs to a subtitle stylesheet change event type, the operation of checking the current subtitle-output status and rendering and outputting the script information includes a sub-operation of checking a sort of the event and changing an output style of the subtitle according to the sort of the event.

[47] According to an aspect of the invention, if the event is a setStylesheet event, style information is set to be a stylesheet selected by the user to be the style information, if the event is a nextStylesheet event, the style information is set to be a stylesheet next to a stylesheet currently being used in a sequence of the stylesheets, if the event is a prevStylesheet event, the style information is set to be a stylesheet prior to the stylesheet currently being used in a sequence of the stylesheets.

[48] Additional aspects and/or advantages of the invention will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the invention.

Mode for Invention

[49] Reference will now be made in detail to the embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout. The embodiments are described below to explain the present invention by referring to the figures.

[50] FIG. 1 is a block diagram showing types of data recorded in a storage medium according to an embodiment of the present invention. Referring to FIG. 1, the storage medium includes core data 100, full data 110, system data 120, and text-based subtitle data 130.

[51] The core data 100 is data for reproducing a moving image and includes moving image information 102, which has been compressed, and navigation information 101, which is used to control reproduction of the moving image information 102. The moving image information 102 includes one or more clip A/V stream files encoded according to a standard, such as, MPEG. Each of the clips is a unit in which data is recorded. The moving image information 102 includes a clip information file including

- encoding attributes of the clip A/V stream file, entry point information thereof, and the like. The moving image information 102 further includes a play list comprised of a plurality of play items, where the play item is a unit in which data is reproduced. Each of the play items indicates an in time location and an out time location over the clip information file. The moving image information 102 is reproduced with reference to the navigation information 101 of the storage medium, and a user watches a moving image, such as, a high-quality movie or the like reproduced from the moving image information 102. However, it is understood that the A/V data can be otherwise organized and that the data need not be compressed and/or can be compressed according to other standards.
- [52] The full data 110 is data for providing an extra function other than the reproduction of a moving image and includes program data 111, for providing an interaction with a user, and/or browser data 112, for reproducing information relating to the moving image from a Markup document. If the extra function is not necessary, the full data 110 may not be included.
- [53] According to aspects of the invention, the program data 111 is used to provide a game function using a moving image, a function of displaying a director's commentary while reproducing a part of a moving image, a function of displaying additional information while reproducing a part of a moving image, a function of executing chatting while reproducing a moving image, or the like. The program data 111 can support JAVA environments as well as other interactive environments.
- [54] The browser data 112 is a command to reproduce information relating to a moving image from a Markup document. The command can be expressed in a Markup language and/or an execution script language (e.g., the ECMA script language). The information relating to the moving image reproduced from the Markup document is played back together with the moving image. For example, recent news about movie actors stored in a web page, a file, or the like, news about opening of events relating to a movie, an updated subtitle of the movie, and the like can be reproduced from a storage medium storing the movie and played back together with the movie, and/or can be retrieved across a network or another storage medium to which the reproducing apparatus is connected. The full data 110 may further include another data for providing another function instead of the function of reproducing a moving image.
- [55] The system data 120 is data used to control reproduction of the core data 100 and/or the full data 110 and includes startup information 121 and title information 122. The startup information 121 indicates a location of an object to be first reproduced when

the storage medium is played by a playback apparatus. The title information 122 includes entry point information indicating a location of each object to be reproduced.

[56] The text-based subtitle data 130 is recorded separately from the core data 100, the full data 110, and the system data 120 and has a text-based data structure so that a style in which a manufactured subtitle is output can be changed, added, or corrected. For example, the text-based subtitle data 130 may be expressed in the text-based Markup language. The subtitle data 130 includes script information 131 and style information 132.

[57] The script information 131 denotes a text to be displayed as a subtitle of a moving image. The style information 132 denotes information about a style in which the subtitle is output. The information is used while the script information 131 is being rendered to be displayed on a display device. The subtitle data 130 may be recorded in a local storage separate from the storage medium.

[58] FIG. 2 is a table defining elements and attributes that are used in a Markup document for establishing an example of the text-based subtitle data 130 of FIG. 1. Referring to FIG. 2, the markup document includes script information 203 and style information 202 as described in a subtitle element 201. Hereinafter, a markup document for constructing subtitle data is referred to as a text subtitle document.

[59] Elements and attributes used in a text subtitle document will now be described in detail. The subtitle element 201 denotes a top-level element in the text subtitle document. Every text subtitle document starts with the subtitle element. The subtitle element includes the following attributes: an attribute 'subtitle_id' denoting a subtitle identifier (ID) for distinguishing each item of subtitle data from other items of subtitle data; an attribute 'lang' denoting a character code of a language of a subtitle displayed on a screen using subtitle data; and an attribute title denoting a title of a moving image that uses the subtitle data.

[60] A stylesheet element includes style information to be used in rendering subtitle data and includes at least one stylesheet element according to an aspect of the invention. The stylesheet element denotes a unit in which a style of the subtitle data is managed and changed. The stylesheet element includes at least one style element. If a plurality of stylesheet elements exist, each of the stylesheet elements includes an identical number of style elements, each of which is used to render subtitle data. If style elements are used for a manufacturer of a storage medium to render identical subtitle data although included in different stylesheet elements, the style elements have the same style_id value.

- [61] Each stylesheet element includes the following attributes. First, an attribute 'stylesheet_id' denotes a stylesheet ID for distinguishing stylesheet elements from each other. Since the attribute stylesheet_id is registered in a register of a playback apparatus, which will be described later, and used as a current style information value, the attribute stylesheet_id preferably has a binary value.
- [62] Second, an attribute 'default' designates a stylesheet to be initially applied when subtitle data is output on a display screen. Only one stylesheet element has a default value 'yes', and the remaining stylesheet elements have a default value 'no'.
- [63] Third, an attribute desc denotes descriptions of a style that is selected by the stylesheet element.
- [64] According to an aspect of the invention a style element stores style information to be used upon rendering of subtitle data and includes the following attributes. First, an attribute style_id denotes a style class value for distinguishing style elements included in a stylesheet element from one another. Second, an attribute font denotes a font to be used in a text used as script information by a dialog element. Third, an attribute color denotes a color of the text used as the script information by the dialog element. Fourth, an attribute bgcolor denotes a background color of the text used as the script information by the dialog element. Fifth, an attribute size denotes a size of each character of the text used as the script information by the dialog element. Sixth, an attribute position denotes a reference position at which characters of the text used as the script information by the dialog element are output. Seventh, an attribute align denotes an alignment of the text used as the script information by the dialog element. Eighth, an attribute region denotes a region over a screen on which the text is to be output using the dialog element. Ninth, an attribute lineheight denotes a line spacing of the text to be output on the screen using the dialog element.
- [65] A script element stores information about a subtitle text and includes at least one dialog element according to an aspect of the invention.
- [66] Each of the dialog elements stores information about a subtitle text to be displayed on the display screen and includes the following attributes. First, an attribute begin denotes information about a time when the subtitle text starts being displayed. Second, an attribute end denotes information about a time when the subtitle text ends being displayed. Third, an attribute ref_style_id denotes a class value of a specific style element for designating a style to be applied to the information about the subtitle text displayed on the display screen using the dialog element.
- [67] FIG. 3 illustrates an example of a file for the text-based subtitle data 130 written in

a markup language defined in FIG. 2. Referring to FIG. 3, a text subtitle document starts with a subtitle element 300. The subtitle element 300 includes a single stylesheet element 310, including style information to be used in rendering script information, and a single script element 320, including script information of a moving image. The subtitle element 300 corresponds to the text-based subtitle data 130 of FIG. 1, the stylesheet element 310 corresponds to the style information 132 of FIG. 1, and the script element 320 corresponds to the script information 131 of FIG. 1.

[68] The stylesheet element 310 includes first and second stylesheet elements 311 and 312. As described above, each of the stylesheet elements 311 and 312 denotes the unit in which a style can be managed and changed. Each of the stylesheet elements 311 and 312 includes the attribute `stylesheet_id`, which indicates an attribute value of the register of the playback apparatus, so as to reflect current style information.

[69] The first stylesheet element 311 having an attribute `stylesheet_id` of 0 is set to have a default value 'yes'. Hence, as long as no style change commands by a user are generated, the first stylesheet element 311 is basically applied to the information about the subtitle text. The first stylesheet element 311 indicates a normal size font using the attribute `desc`.

[70] The second stylesheet element 312 having an attribute `stylesheet_id` of 1 indicates a large size font using the attribute `desc`. Thus, when a style of a subtitle is changed by a user, a font size can be changed.

[71] Each of the stylesheet elements 311 and 312 includes an identical number of style elements. Each of the style elements has, as its attribute value, style information actually applied to a subtitle text.

[72] Style elements 311a, 311b, 312a, and 312b are used to indicate a plurality of pieces of style information that a manufacturer wants to apply to a subtitle text. As shown in FIG. 3, the first stylesheet element 311 includes the two style elements 311a and 311b, having attributes `style_id` of x and y, respectively. When the style element 311a having an attribute `style_id` of x is compared with the style element 311b having an attribute `style_id` of y, they have different style information. Particularly, the font size difference is large.

[73] For example, a manufacturer can apply style information indicated by the style element 311a to a part of the subtitle text information, such as, a title of the subtitle, and style information indicated by the style element 311b to subtitle text information corresponding to a dialog.

[74] While not required, it is preferable that the storage medium according to an

embodiment of the present invention is an optical disc that is detachable from a playback apparatus and capable of reading out data using an optical device of the playback apparatus. Examples of the storage medium include, but are not limited to, CD-ROMs, DVDs, Bluray and Advanced Optical Discs, optical discs to be developed, and the like.

- [75] A playback apparatus for playing back the aforementioned storage medium according to an embodiment of the present invention will now be described in detail with reference to FIGS. 1 and 4. FIG. 4 is a conceptual block diagram of a playback apparatus 410 supporting text-based subtitle data, according to an exemplary embodiment of the present invention. Referring to FIG. 4, the playback apparatus 410 includes a core data processor 411, a full data processor 412, a text subtitle processor 413, a moving image data processor 414, a blender 415, and a system register 416. While described in terms of a playback apparatus, it is understood that the apparatus can further have a recording capability and be a standalone device or incorporated into a general or special purpose computer.
- [76] The core data processor 411 controls reproduction of moving image data (i.e., the moving image information 102) using the navigation information 101 of FIG. 1. The core data processor 411 is also referred to as a navigation engine. The full data processor 412 processes application data providing an interaction with a user, such as, the program data 111 (e.g., a Java program or the like) and/or the browser data 112 (e.g., a markup document or the like). The full data processor 412 may include a program engine and a browser engine separated from the program engine, or the engines can be combined.
- [77] The text subtitle processor 413 verifies a construction of the text-based subtitle data 130, including the script information 131 and the style information 132, and processes the text-based subtitle data 130.
- [78] The moving image data processor 414 decodes the moving image data and outputs a result of the decoding on a screen of an output device 420. The moving image data processor 414 is also referred to as a presentation engine.
- [79] The blender 415 blends images output by the full data processor 412 and the moving image data processor 414 and outputs a result of the blending on the screen of the output device 420.
- [80] The system register 416 includes player status registers (PSRs), storing various types of status information about the playback apparatus, and general purpose registers (GPRs), which are used by the playback apparatus to temporarily record data.

- [81] Specifically, the core data processor 411 stores information necessary for playback in the system register 416 according to a navigation command for reproducing a moving image (such as, a movie), and transmits a reproduction command to the moving image data processor 414. In response to the reproduction command, the moving image data processor 414 decodes the moving image data using the information necessary for playback recorded in the system register 416. During reproduction of a moving image, when a subtitle output command is received by a user, the core data processor 411 transmits the subtitle output command to the text subtitle processor 413.
- [82] In response to the subtitle output command, the text subtitle processor 413 loads text subtitle data on a memory (not shown) and checks if a sentence structure of the text subtitle data matches with a predetermined sentence structure. If the sentence structure of the text subtitle data matches with the predetermined sentence structure, the text subtitle processor 413 parses script information and style information and renders the information about the subtitle text using the style information defined by the first stylesheet element 311 having the attribute value default=yes of FIG. 3. A result of the rendering is transferred to the moving image data processor 414 and output on the output device 420.
- [83] During the reproduction of the moving image, when receiving a user's command 401 to change an output style of the subtitle, the core data processor 411 transmits the user's command 401 to change the output style of the subtitle to the text subtitle processor 413. The text subtitle processor 413 changes the style information used upon the rendering of the information about the subtitle text (such as through changing a stylesheet to another stylesheet) and newly registers the changed style information in the system register 416.
- [84] When a movie is played back by the full data processor 412, the full data processor 412 records information necessary for reproducing an application included in the full data 110, in the system register 416 and controls the reproduction of the moving image using a pre-defined application program interface (API) for the moving image data processor 414. The moving image data processor 414 reproduces moving image data with reference to the information necessary for playback recorded in the system register 416 in the same manner as in a core mode (which denotes a moving image reproduction mode using core data and is referred to as a movie code).
- [85] During the reproduction of the moving image, when receiving the subtitle output command from the user, the full data processor 412 transmits the subtitle output

command to the text subtitle processor 413. In response to the subtitle output command, the text subtitle processor 413 outputs a subtitle using the text-based subtitle data 130 in the same manner as in the core mode.

- [86] During the reproduction of the moving image, when receiving the user's command 401 to change the output style of the subtitle, the full data processor 412 transmits the user's command 401 to the text subtitle processor 413 via a pre-defined style changing API for the text subtitle processor 413. In response to the user's command 401, the text subtitle processor 413 changes the output style of the subtitle in the same manner as in the core mode.
- [87] FIG. 5 illustrates some of player status registers (PSRs) which are system registers that register the style information 132 included in the text-based subtitle data 130 of FIG. 1. Referring to FIG. 5, PSRs denote registers that record various types of status information about a playback apparatus according to the present invention. PSR No. 1 indicates the number of an audio stream selected to reproduce a current moving image, PSR No. 2 indicates the number of a subtitle stream selected to reproduce the current moving image, and PSR No. 17 indicates a language code of the subtitle stream selected to reproduce the current moving image.
- [88] PSR No. 19 is used to indicate a stylesheet ID selected in rendering the script information when a subtitle is output using text subtitle data. PSR No. 19 is just an embodiment, so may be replaced by any of 32-bit PSRs Nos. 1 through 63 of the shown embodiment, or can be any appropriate indicator in registers having other sizes.
- [89] PSR No. 19 can be changed by a user operation to be described later, a Java API, or the like. When a content of PSR No. 19 is changed during the reproduction of the moving image data including text-based subtitle data, a subtitle output style applied to the script information is also changed.
- [90] The above-described style information applied to current script information is stored in PSRs as shown in FIG. 5. Alternatively, the above-described style information may be stored in general purpose registers (GPRs) to be described later or in an internal buffer (not shown) of the text subtitle processor 413 according to aspects of the invention.
- [91] An example of a user operation (hereinafter, referred to as a UOP) for a style change will now be described. Function `Text_subtitle_style_Change (stylesheet_id)`, which is a UOP, sets an ID of a stylesheet applied to the text subtitle data and changes the PSR No. 19. `stylesheet_id`, which is an argument of function `Text_subtitle_style_Change (stylesheet_id)`, can have any of 0 to 231, because the

number of styles applicable to a text subtitle is theoretically infinite, but a PSR according to the shown example has a 32-bit data size. An example of a new navigation command may be function SetSS(for stylesheet_id). The function SetSS(for stylesheet_id) changes a value of the PSR No. 19 indicating an ID of a stylesheet to be used in rendering the text subtitle data, to a designated argument value. Further, where a PSR has another storage size, it is understood that the stylesheet_id can have other numbers.

- [92] FIG. 6 illustrates some of GPRs which are system registers that register the style information 132 included in the text-based subtitle data 130 of FIG. 1. ID information about a stylesheet element defined in a styleset element is recorded in the GPRs as shown in FIG. 6. Alternatively, the ID information about the stylesheet element may be stored in the internal buffer of the text subtitle processor 413 or in the PSRs of FIG. 5.
- [93] Referring to FIG. 6, address No. 100 records 102 as a start address of ID information about a stylesheet element, and address No. 101 records 2 as the number of stylesheet elements used in a text subtitle document. Address 102 records an ID of a stylesheet element indicating a normal size of a font, and address 103 records an ID of a stylesheet element indicating a large size of a font. In other words, the text subtitle document described in FIG. 6 has two stylesheet elements that indicate a normal font size and a large font size, respectively.
- [94] A method in which the aforementioned playback apparatus reproduces moving image data using subtitle style information selected by a user from the aforementioned storage medium will now be described using FIG. 7. FIG. 7 illustrates an algorithm for selecting the style information 132 according to a user's command. When a command to change an output style of a subtitle is received from a user during reproduction of a moving image, the playback apparatus can change text subtitle data so that style information selected by the user can be applied using a function, such as function Subtitle_Stylesheet_Change (arg), which will be described later.
- [95] Referring to FIG. 7, argument Next_Style (case A) or Prev_Style (case B) may be used as the argument in the function Subtitle_Stylesheet_Change (arg). Alternatively, a specific attribute value stylesheet_ID may be indicated as the argument as in case C. The case C can be expressed in a function similar to the function for the aforementioned UOP.
- [96] In case A in which the Next_Style is used as the argument of the function Subtitle_Stylesheet_Change (arg), the playback apparatus increases a value of the

stylesheet_ID stored in the PSR No. 19, the GPRs, or the internal buffer of the text-based subtitle processor 413, and applies a next style having the increased ID value. If the value of the stylesheet_ID of a currently used style is the greatest as in case 701, a style having the smallest stylesheet_ID value is used. In case 702, a style having a stylesheet_ID value obtained by increasing a current stylesheet_ID value 1 by 1 is used.

- [97] Cases 703 and 704 represent style changing methods applied in case B that Prev_Style is used as the argument of the function Subtitle_Stylesheet_Change (arg). Case 705 represents a method of storing a designated stylesheet_ID value in the PSR No. 19, the GPRs, or the internal buffer of the text-based subtitle processor 413.
- [98] FIG. 8 illustrates an example of an API used to change the style information 132 according to an aspect of the invention. Referring to FIG. 8, a package BDROM can be used as a command group that can be used upon writing of an application included in the full data 110. The package BDROM includes a media package for controlling reproduction of a moving image according to an application.
- [99] The media package includes a subtitle package for controlling a text-based or a bitmap-based subtitle of a moving image. A TextSubtitle interface is defined as a part of the subtitle package for the text-based subtitle. The TextSubtitle interface may include the following APIs. The term 'status' denotes a parameter indicating an output on/off status of a subtitle. 'getAttribute()' obtains information about an attribute of a text subtitle file currently being used. 'getLangCode()' obtains a language code of the text subtitle file. 'getTitleName()' obtains a name of a title of moving image data. 'getSubtitleID()' obtains an ID of the current text subtitle file. 'getCurrentTextStylesheetID()' obtains a stylesheet_ID currently being used. 'setTextStylesheetID (unsigned int ID)' receives as an argument an ID of a stylesheet to be used in rendering a subtitle text and sets the PSR No. 19 to be a stylesheet corresponding to the received ID argument. 'nextTextStylesheet()' denotes a stylesheet next to a current stylesheet in an array of stylesheets and sets a stylesheet to be used in rendering the subtitle text. 'prev-TextStylesheet()' denotes a stylesheet previous to the current stylesheet in the array of stylesheets and sets the stylesheet to be used in rendering the subtitle text. 'getDefaultTextStylesheetID()' obtains a stylesheet set as a default from the array of stylesheets. 'getCurrentPresentationTime()' obtains a presentation time indicating the time when a subtitle is output from current text-based subtitle data. 'setPresentationTime (Time t)' sets a presentation time corresponding to a current reproduction time using time information t given as an argument. 'getCurrentTextSubtitle()' obtains an ID of the text

subtitle file current currently being used for a current subtitle output. 'set-TextSubtitle(String filename or unsigned int ID)' receives a file to be used in outputting a subtitle as an argument and sets the received file to be an ID of a received filename or a received text subtitle file. 'start()' starts outputting the text subtitle. 'stop()' stops outputting the text subtitle. However, it is understood that other APIs can be used or developed, and that each API shown in FIG. 8 need not be used in all aspects of the invention.

[100] FIG. 9 illustrates an example of a Java application written using the API defined in FIG. 8. Referring to FIG. 9, application PlayXlet inherits a function of application Xlet, which is a basic unit of the Java application and included in the full data 110 executed by the playback apparatus, and implements interface ControllerListener to process a command received from a user during reproduction of a moving image.

[101] When an application implemented by extending an Xlet function starts, portion init() of the application is first executed to initialize the application. Then, portion start() of the application is executed. As shown in FIG. 9, when the application PlayXlet is executed, it is initialized by a first operation of the portion init() (refer to line 4). Codes of the application PlayXlet will now be described in detail.

[102] In line 1, the media package described in FIG. 8 is imported to control moving image data. In line 2, an object of the application PlayXlet is declared. The application PlayXlet inherits the function of application Xlet and implements the interface ControllerListener. In line 3, an object Player, which is a moving image data controlling object used in the application PlayXlet, is declared. In lines 4 through 15, when the application PlayXlet is initially executed, it is initialized. In line 5, a layout of the application PlayXlet is set. In line 6, a file of the moving image data to be used by the application PlayXlet is named. In lines 7 through 13, an exception that may be generated while the object Player is being initialized is cached. In line 8, a path for moving-image data resources to be used by the application PlayXlet is designated. In line 9, a reproduction controlling object for the moving-image data resources corresponding to the designated path is produced and allocated to the object Player. In line 10, Event Listener used by the object Player to receive a command from a user and process the command is registered. In line 11, an object 'subtitle' for the object Player is produced. In line 12, a text-based subtitle to be used by the object 'subtitle' is designated. In lines 13 and 14, the exception that may be generated while the object Player is being initialized is processed. In line 14, an error message is output when the exception is generated. In lines 16 and 17, the portion start() is executed after the object Player is

- initialized. In line 17, reproduction of the moving image data controlled by the object Player starts. In lines 18 through 30, a control command received from the user is processed.
- [103] In lines 19 through 24, in an event type of SubtitleToggleEvent, when a current subtitle is being output, the subtitle output is stopped. On the other hand, when no subtitles are being output, a point in time when the subtitle is to be output is synchronized with a point in time when a current moving image is to be reproduced, and then the subtitle output starts.
- [104] In lines 25 and 26, in an event type of nextSubtitleStylesheetEvent, a stylesheet to be used in outputting a subtitle is changed to a stylesheet next to a stylesheet current being used. If the currently used stylesheet is the last one of an array of stylesheets, the stylesheet to be used in outputting the subtitle is changed to a first stylesheet of the array of stylesheets.
- [105] In lines 27 and 28 in an event type of prevSubtitleStylesheetEvent, the stylesheet to be used in outputting the subtitle is changed to a stylesheet previous to the stylesheet current being used. If the currently used stylesheet is the first one of the array of stylesheets, the stylesheet to be used in outputting the subtitle is changed to the last stylesheet of the array of stylesheets.
- [106] In lines 29 and 30, in an event type of setSubtitleStylesheetEvent, the stylesheet to be used in outputting the subtitle is changed to a stylesheet designated by an argument value included in an event object 'e'.
- [107] In an operation of the above-described Java application, when the application PlayXlet of FIG. 9 is executed, reproduction of designated moving image data starts. Once a subtitle output command is received from a user during reproduction of a moving image, an output of a subtitle starts. When another subtitle output command is received, the subtitle output is stopped.
- [108] When a command nextSubtitleStylesheetEvent is received from a user while the subtitle is being output, an output style of the subtitle is changed using style information having an attribute stylesheet_ID whose value is 1 greater than a value of an attribute stylesheet_ID of currently used style information. When a command prevSubtitleStylesheetEvent is received from the user while the subtitle is being output, the output style of the subtitle is changed using style information having an attribute stylesheet_ID whose value is 1 smaller than the value of the attribute stylesheet_ID of the currently used style information.
- [109] When a command setSubtitleStylesheet to set a current stylesheet to be a specific

stylesheet is received using the application of FIG. 9 a subtitle output style changing menu provided by a playback, or the like, the current stylesheet is changed to the specific stylesheet using stylesheet_ID input by a user.

- [110] FIG. 10 is a flowchart illustrating a method of outputting a subtitle using the text-based subtitle data 130. Referring to FIG. 10, when a subtitle output start command is received from a user, a stylesheet element having a default attribute 'yes' is set as style information to be used in rendering information about a subtitle text, in operation 1010. Thereafter, a point in time when a current moving image is reproduced is synchronized with a point in time when a subtitle is output by setting a presentation time, in operation 1020. It is checked whether a current subtitle-output status is a status in which a subtitle is output or a status in which the subtitle is not output, in operation 1030.
- [111] If the current subtitle output status is the status in which the subtitle is output, the subtitle output is performed, in operation 1040. If the current subtitle output status is the status in which the subtitle is not output, the subtitle output is concluded.
- [112] If the subtitle is output in operation 1040 and it is determined in operation 1050 that subtitle items to be continuously output remain, operations 1030 and 1040 are repeated. On the other hand, if it is determined in operation 1050 that no subtitle items to be continuously output remain, the subtitle output is concluded.
- [113] A stylesheet changing command by a user is applied to operations ranging from the operation 1030, in which an output status of the current subtitle is checked, to the operation 1050, in which it is checked whether the subtitle output is to be completed.
- [114] FIG. 11 is a flowchart illustrating a method of changing an output style of a subtitle using the style information 132 included in the text-based sub-title data 130 according to an aspect of the invention. Referring to FIG. 11, in operation 1110, a command to change an output style of a subtitle is received from a user. In operation 1120, it is determined whether an event for the received command is of a subtitle toggle event type or a subtitle stylesheet change event type.
- [115] If the event for the received command is of the subtitle toggle event type, it is determined whether a current subtitle-output status is a status in which a subtitle is output or a status in which a subtitle is not output, in operation 1130. If the current subtitle-output status is the status in which the subtitle is output, the subtitle status is changed to a status in which the subtitle is not output, in operation 1140. If the current subtitle-output status is the status in which the subtitle status is changed to the status in which the subtitle is not output, the subtitle is output, in operation 1150.

- [116] On the other hand, if the event for the received command is of the subtitle stylesheet change event type, it is determined whether the event for the received command is a setStylesheet event, a nextStylesheet event, or a prevStylesheet event, in operation 1160. The setStylesheet event designates a subtitle output style using an attribute stylesheet_id of a stylesheet selected by a user. The nextStylesheet event designates a subtitle output style using a stylesheet next to a stylesheet currently being used according to a sequence of stylesheets. The prevStylesheet event designates a subtitle output style using a stylesheet prior to the stylesheet currently being used according to the sequence of stylesheets. As described above with reference to FIG. 7, the setStylesheet event, the nextStylesheet event, and the prevStylesheet event are executed, in operations 1170, 1180, and 1190, respectively, so that a style of a subtitle displayed on a screen is changed according to the designated command.
- [117] A storage medium according to an embodiment of the present invention includes text-based subtitle data recorded separately from moving image data. The text-based subtitle data includes a plurality of pieces of style information so that a style in which a subtitle is output can be arbitrarily changed. Thus, a subtitle of a moving image can be output in various styles without degradation of the image quality of a video stream, and manufacture and edition of sub-title data are easy. Also, the style in which a subtitle is output can be arbitrarily changed by a user.
- [118] Additionally, while described in terms of a subtitle used with moving image data, it is understood that aspects of the present invention could be used with still image data and/or with audio data. Also, while described in terms of stylesheets, it is understood that aspects of the invention can be applied to any set of information associated with an electronic document and which sets forth a grouping of data, a definition of a document's appearance in terms of such elements as typeface, size, and color for headings and body text, how sections should be laid out in terms of space, line spacing, margin widths, spacing between headings, and so forth.
- [119] Further, in a storage medium according to an aspect of the present invention in which text-based subtitle data including style information is recorded and a device and method of playing back the storage medium, a subtitle can be output using style information selected by a user. Also, a style in which a subtitle is being output can be changed. In other words, text-based subtitle data according to a feature of the present invention can be easily formed and edited and output in various styles. In addition, various subtitle output styles can be selected by a user using a plurality of pieces of style information included in the text-based subtitle data.

[120] While not required, aspects of the invention can also be embodied as computer readable codes on at least one computer readable recording media. The computer readable recording medium is any data storage device that can store data which can be thereafter read by a general or special purpose computer system. Examples of the computer readable recording medium include read-only memory (ROM), random-access memory (RAM), CD-ROMs, magnetic tapes, floppy disks, optical data storage devices, and carrier waves (such as data transmission through the Internet). The computer readable recording medium can also be distributed over network coupled computer systems so that the computer readable code is stored and executed in a distributed fashion.

[121] While a few embodiments of the present invention have been particularly shown and described with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the present invention as defined by the following claims and equivalents thereof.

Industrial Applicability

[122] An aspect of the present invention provides a storage medium in which text-based subtitle data including style information is recorded, and an apparatus and a method of playing back the storage medium.

Claims

- [1] What is claimed is:
1. A storage medium for use with a recording and/or reproducing apparatus, comprising:
moving image data; and
subtitle data used by the apparatus to provide a subtitle for the moving image data,
wherein the subtitle data comprises a text to be separated by the apparatus from the moving image data and includes information used by the apparatus to select and/or change an output style of the subtitle generated using the text.
 - [2] 2. The storage medium of claim 1, wherein the subtitle data comprises:
script information indicating the text to be displayed as the subtitle for the moving image data; and
style information indicating the output style of the subtitle.
 - [3] 3. The storage medium of claim 2, wherein the style information is divided into at least one stylesheet, where each stylesheet is a unit in which the style information is changed.
 - [4] 4. The storage medium of claim 3, wherein the stylesheet comprises an identifier for distinguishing the stylesheet from another stylesheet.
 - [5] 5. The storage medium of claim 3, wherein the stylesheet comprises information which designates a stylesheet to be initially applied upon a reproduction of the moving image data by the apparatus.
 - [6] 6. The storage medium of claim 1, wherein the subtitle data is recorded in the form of a Markup document expressed with elements and attributes.
 - [7] 7. The storage medium of claim 1, wherein another portion of the subtitle data is recorded on a local storage medium separate from the storage medium having the motion image data.
 - [8] 8. The storage medium of claim 1, where the storage medium is detachable from a playback apparatus.
 - [9] 9. The storage medium of claim 8, whenever the storage medium comprise an optical disc from which data can be read using an optical device comprising the apparatus.
 - [10] 10. An apparatus which transfers data with respect to a storage medium, the storage medium comprising: moving image data; and subtitle data for providing

a subtitle for the moving image data, wherein the subtitle data comprises a text to be separated from the moving image data and includes information used to select and/or change an output style of the subtitle including the text, the apparatus comprising:

a text subtitle processor that verifies and processes the subtitle data to output the subtitle of a selected style; and

a system register that stores information used to select and/or change a style in which the subtitle is output.

- [11] 11. The apparatus of claim 10, wherein:
the subtitle data comprises: script information indicating the text to be displayed as the subtitle for the moving image data; and style information indicating an output style of the subtitle; and
the text subtitle processor renders the script information to which the style information is applied.
- [12] 12. The apparatus of claim 11, wherein:
the style information is divided into at least one stylesheet, with each of the at least one stylesheet being a unit in which the style information can be changed, and the stylesheet comprises an identifier for distinguishing the stylesheet from another stylesheet; and
the system register stores the identifier of the stylesheet that is applied to the script information currently being reproduced.
- [13] 13. The apparatus of claim 12, wherein the text subtitle processor renders the subtitle by applying the stylesheet to the script information with reference to the identifier of the stylesheet stored in the system register.
- [14] 14. The apparatus of claim 10, further comprising:
a core data processor that controls reproduction of the moving image data read from the storage medium;
a full data processor providing an interaction with a user with respect to the reproduced moving image data;
a moving image data processor that decodes the moving image data and outputs a result of the decoding to be displayed on a display screen; and
a blender that blends an image output by the full data processor and an image output by the moving image data processor and outputs a result of the blending to be displayed on the display screen.
- [15] 15. The apparatus of claim 14, wherein:

one or both of the core data processor and the full data processor receives a subtitle output command from the user and transmits the subtitle output command to the text subtitle processor;

the text subtitle processor reads out the subtitle data, verifies whether the read-out subtitle data is consistent with a predefined sentence structure, and renders the script information using the style information included in the subtitle data; and

the moving image data processor decodes the moving image data and the rendered script information, blends a result of the decoding, and outputs a result of the blending to be displayed on the display screen.

[16] 16. The apparatus of claim 15, wherein:

one or both of the core data processor and the full data processor receives a command to change an output style of the subtitle from the user and transmits the command to the text subtitle processor; and

the text subtitle processor changes the style information used in rendering the script information and stores the changed style information in a system register.

[17] 17. The apparatus of claim 16, wherein the full data processor transmits the command to change the output style of the subtitle to the text subtitle processor via a predefined application program interface (API).

[18] 18. The apparatus of claim 17, wherein the full data processor supports one of a JAVA environment and/or a Markup language environment.

[19] 19. The apparatus of claim 17, wherein the API includes a command to designate an identifier of the stylesheet, a command which refers to a stylesheet prior to a current stylesheet in a sequence of the stylesheets, a command which refers to a stylesheet next to the current stylesheet in a sequence of the stylesheets, or combinations thereof.

[20] 20. A method of playing back a storage medium, the storage medium comprising: moving image data; and subtitle data for providing a subtitle for the moving image data, wherein the subtitle data includes a text to be separated from the moving image data and includes information used to select and/or change an output style of the subtitle based on the text, the method comprising: designating style information to be initially applied, with reference to the subtitle data; and checking whether a current subtitle-output status is a status in which the subtitle is output, and rendering and outputting script information included in the subtitle

data by using the style information if the status is the status in which the subtitle is output.

- [21] 21. The method of claim 20, wherein the checking the current subtitle-output status and rendering and outputting the script information comprises:
if a command to change an output style of a subtitle is received, checking a type of an event for the received command; and
if the event belongs to a subtitle toggle event type, determining whether the current subtitle-output status is the status in which the subtitle is output or a status in which the subtitle is not output, and not outputting a subtitle if the current subtitle-output status is the status in which the subtitle is output and outputting the subtitle if the current subtitle-output status is the status in which the subtitle is not output.
- [22] 22. The method of claim 21, wherein if the event belongs to a subtitle stylesheet change event type, the checking the current subtitle-output status and rendering and outputting the script information comprises checking a type of the event and changing an output style of the subtitle according to the type.
- [23] 23. A computer readable medium encoded with instructions for implementing the method of claim 20 using a computer.
- [24] 24. The storage medium of claim 1, further comprising interactive data which the apparatus uses to generate an interactive display containing information related to the moving image data according to received input.
- [25] 25. The storage medium of claim 24, wherein the interactive data comprises director's commentary reproduced while the apparatus is reproducing a part of a moving image, additional information which is displayed automatically while reproducing a corresponding part of a moving image, a chat room generated by the apparatus while reproducing a moving image, or combinations thereof.
- [26] 26. The storage medium of claim 24, wherein the interactive data comprises browser data implemented by a browser of the apparatus and which retrieves webpages related to a part of a moving image being displayed.
- [27] 27. A storage medium for use with a recording and/or reproducing apparatus, comprising:
text to be reproduced by the apparatus with corresponding data to be separately reproduced and which the apparatus displays as a subtitle having a first text style while the data is being reproduced by the apparatus; and
style information comprising first style information used by the apparatus to

display the text in the first text style and second style information and which is selectable by the apparatus to display the text in a second text style other than the first text style while the data is being reproduced by the apparatus.

[28] 28. The storage medium of claim 27, further comprising moving image data, wherein the data being reproduced by the apparatus comprises the moving image data to be displayed with the subtitle in a combined display.

[29] 29. The storage medium of claim 27, wherein:
the data being reproduced by the apparatus comprises moving image data to be displayed with the subtitle in a combined display, and
the moving image data is reproduced by the apparatus from another storage medium not including the text.

[30] 30. The storage medium of claim 27, further comprising:
a markup document reproduced by the apparatus to display the text, and
a first style sheet referenced by the markup document and including the first style information such that the apparatus displays the text in the first text style when the apparatus selects the first text style, and
a second style sheet referenced by the markup document and including the second style information such that the apparatus displays the text in the second text style when the apparatus selects the second text style.

[31] 31. The storage medium of claim 30, further comprising an attribute which the apparatus uses to select between the first style sheet and the second style sheet according to a received command.

[32] 32. The storage medium of claim 30, further comprising a third style sheet referenced by the markup document and including third style information such that the apparatus displays the text in the third text style when the apparatus selects the third text style.

[33] 33. The storage medium of claim 27, further comprising style indicators which indicate that a first portion of the text is to be displayed in one of the first and second text styles and a second portion of the text is to be displayed in another one of the first and second text styles.

[34] 34. The storage medium of claim 33, wherein:
the first style information comprises information on a size of each character of the text used as script information by a dialog element, a reference position at which characters of the text used as script information by a dialog element are output, an alignment of the text used as script information by a dialog element, a

region over a screen on which the text is to be output using a dialog element, and a line spacing of the text to be output on the screen using the dialog element used by the apparatus to display the text in the first text style, and the second style information comprises information on a size of each character of the text used as script information by a dialog element, a reference position at which characters of the text used as script information by a dialog element are output, an alignment of the text used as script information by a dialog element, a region over a screen on which the text is to be output using a dialog element, and a line spacing of the text to be output on the screen using the dialog element used by the apparatus to display the text in the second text style.

- [35] 35. An apparatus which transfers data with respect to the storage medium of claim 27, the apparatus comprising:
a text subtitle processor that verifies and processes the text and the style information to display the text in subtitle with displayed moving images reproduced from the data, the subtitle being displayed in a style selectable between the first and second text styles; and
a system register that stores an identification number of a selected one of the first and second text styles and which is accessed by the text subtitle processor to select the style in which the text of the subtitle is output.
- [36] 36. The apparatus of claim 35, further comprising:
a moving image data processor which receives moving image data and outputs the moving images to be displayed; and
a blender which receives the moving images output from the moving image data processor and the text in the selected style as a combined image on a screen of a display device.
- [37] 37. The apparatus of claim 35, wherein, when a command is received to change from the selected text style to the other one of the first and second text styles, the system register is updated to store another identification number of the other one of the first and second text styles, and the text subtitle processor accesses the system register to change the style in which the text of the subtitle is output.
- [38] 38. The apparatus of claim 37, wherein the command comprises a command to change from the selected text style to a text style having an identification number which, in a sequence of identification numbers, is next to the identification number stored in the system register.
- [39] 39. The apparatus of claim 37, wherein the command comprises a command to

change from the selected text style to a text style having an identification number which, in a sequence of identification numbers, is prior to the identification number stored in the system register.