

9608988-3
spare As filed

SPECIFICATION

TITLE OF THE INVENTION

AIR CONDITIONER

BACKGROUND OF THE INVENTION

The present invention relates to an integral type air conditioner wherein the interior of a main body is partitioned into an indoor side chamber and an outdoor side chamber by means of a partitioning plate, and particularly to the structure for introducing the outdoor air (open air) into the interior of a room.

Conventionally, there has been disclosed an air conditioner capable of taking the open air in the interior of a room, for example, in Japanese Utility Model Publication No. sho 52-8296. In this air conditioner, the interior of the air conditioner is partitioned into an indoor side chamber and an outdoor side chamber by means of a partitioning plate. The outdoor air is sucked from suction ports opened on both sides of the outdoor side chamber by an outdoor blower (propeller fan), followed by being cooled or heated by means of an outdoor heat exchanger, and discharged from the central portion on the rear side of the outdoor side chamber. On the other hand, the indoor air is sucked from the lower portion of the indoor side chamber by an indoor blower (a cross-flow fan), followed by

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

being cooled or heated by an indoor heat exchanger, and supplied in the interior of a room from the upper and central portion.

The partitioning plate described above is provided with an opening which is opened/closed by a damper. When the opening is opened by operation of the damper, part of the outdoor air is allowed to flow in the indoor side chamber and is mixed with the indoor air, to be thus supplied from a blow-off port into the interior of a room.

Also, there has been described an air conditioner including an electric heater on the rear side of an indoor heat exchanger in Japanese Patent Publication No. hei 4-14248. In this air conditioner, an air suction port and an air blow-off port are respectively provided on the lower portion and the upper portion, and a heat exchanger, electric heater, cross-flow fan and the above air blow-off port are disposed from the above air suction port side in this order. The above air suction port is partitioned from the above air blow-off port by means of a partitioning plate provided on the upper portion of the above heat exchanger. The electric heater is disposed on the lower side of the cross-flow fan.

However, as in the former prior art, Japanese Utility Model Publication No. sho 52-8296, in the case of that the opening of the partitioning plate is opened to introduce the outdoor air in the interior of a room, when the damper is moved on the indoor side, a part of the ventilation passage on the

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

indoor side is blocked by the damper. By the partial blocking of the ventilation passage, the ventilation resistance of the ventilation passage in the indoor side chamber is increased. Consequently, the amount of the indoor air to be sucked in the ventilation passage is decreased, which causes a disadvantage of reducing the air conditioning ability of the air conditioner.


SUMMARY OF THE INVENTION

To solve the above problem, the present invention has been made, and its object is to provide an air conditioner capable of suppressing the reduction in the air conditioning ability to the utmost even in introducing the open air.

In a preferred mode of the present invention, there is provided an air conditioner wherein the interior of a main body is partitioned into an indoor side chamber and an outdoor side chamber. The above partitioning plate is provided with a suction port for introducing an air in the outdoor side chamber to the indoor side chamber, and a damper positioned at the outdoor side chamber for opening/closing the suction port. A cross-flow fan and a rear casing for this cross-flow fan are provided in the indoor side chamber, and auxiliary suction ports communicated to the above suction port are provided on the windward side of the rear casing.

With this construction, when the suction port is opened by the damper for introducing the open air to the interior of a

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

room, the outdoor air in the outdoor side chamber is introduced in the indoor side chamber through the suction port and the auxiliary suction ports, and which is joined to the indoor air flowing along the rear casing of the cross-flow fan on the windward side of the above cross-flow fan.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a vertical sectional view of an integral type air conditioner according to the present invention;

Fig. 2 is a plan view of a main body of the air conditioner according to the present invention;

Fig. 3 is an exploded view in perspective of each apparatus disposed in an indoor side chamber of the main body of the air conditioner according to the present invention; and

Fig. 4 is a perspective view showing the main part of the main body of the air conditioner according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Hereinafter, embodiments of the present invention will be described with reference to the drawings.

In Figs. 1 and 2, numeral 1 indicates an integral type air conditioner mounted so as to pass through a wall of a house.

The air conditioner 1 is constituted of a case 2 installed so as to pass through a wall of a house, a main body 3 inserted in

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

the case 2, and a front panel 4 mounted on the front portion of the main body 3.

Numeral 6 indicates a bottom plate of the main body 3, and 5 is a partitioning plate erected on the bottom plate 5. The partitioning plate 5 partitions the interior of the main body 3 into an indoor side chamber A and an outdoor side chamber B. Numeral 7 indicates an outdoor side motor fixed on the outdoor side wall surface of the partitioning plate 5. A rotational shaft 8 of the outdoor side motor 7 rotates an outdoor fan, for example a propeller fan 9. An outdoor blower is constituted of the propeller fan 9, the outdoor side motor 7 and the like. Numeral 10 indicates a slinger ring mounted around the outer periphery of the propeller fan 9, and 11 is an outdoor heat exchanger for performing the heat exchanger with the outdoor air (open air). The above slinger ring 10 is intended to scrape the drain water stayed on the bottom plate 6 of the main body 3 in the cooling operation and to scatter it to the outdoor heat exchanger 11.

Numeral 12 indicates a fan casing covering a part of the propeller fan 9. The fan casing 12 is connected to the outdoor heat exchanger 11. Numeral 13 indicates a suction port provided on one side (left side, in Fig. 2) of the partitioning plate 5 for introducing the open air. A suction frame 15 made of synthetic resin stretching the insect proof net 14 is provided on the surface of the suction port 13 on the side of the

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

outdoor side chamber B. The damper 16 is supported on the suction frame 15 in a manner to be mounted as shown in the arrow of Fig. 3.

Numeral 17 indicates a compressor, and 18 is a drain pump, which are disposed in the outdoor side chamber B in the opposed side (right side, in Fig. 2) to the side where the damper 16 is provided.

Numeral 19 indicates an indoor heat exchanger for performing the heat exchanger with an indoor air, and 20 is a cross-flow fan as an indoor fan disposed on the rear side of this indoor heat exchanger 19. Numeral 21 indicates an indoor side motor for driving the cross-flow fan 20, and 22 is a stabilizer serving as the partitioning plate disposed on the upper portion of the indoor heat exchanger 19.

A heater supporting device 23 is hung from the stabilizer 22. In the heater supporting piece 23 having the lower portion formed to be wider than the upper portion, electric heaters 24 and 24 are juxtaposed to each other. Accordingly, the electric heater positioned on the partitioning plate 5 side is situated under the cross-flow fan 20. Numeral 25 indicates an indoor drain pan disposed under the indoor heat exchanger 19, and 26 is an air filter. The air filter 26 is disposed on the rear side of a suction grill (air suction port) 27 of the front panels 4 and also on the front side of the indoor heat exchanger 19.

Numeral 28 indicates a rear casing of the cross-flow fan

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



20, wherein a lower end portion 29 is fixed at the rear portion of an indoor drain pan 25, a central portion 30 being fixed at a positioning piece 31 provided to be projected from the partitioning plate 5 to the indoor side chamber A, and the upper end portion 32 is fixed at an upper plate 33. An indoor blower is constituted of the rear casing 28, cross-flow fan 20, the indoor side motor 21 and the like. Numeral 34 indicates each auxiliary suction port formed on a portion of the rear casing 28 on the windward side (seen from the cross-flow fan 20), and which is formed in a shape called as a louver by cutting and rising of the plate made rear casing 28. Numeral 38 indicates a battery box.

Fig. 3 shows a state of mounting the apparatuses, which are disposed in the indoor side chamber A, out of the above apparatuses. The auxiliary suction ports 34 are made smaller in size gradually from the left side to the right side of the rear casing 28. Numeral 35 is a wind direction changing member mounted on the upper surface of the stabilizer 22 (omitted, in Fig. 1). The wind direction changing member 35 is constituted of wind direction changing blades 36, and a wiring net 37 disposed on the front side of the wind direction changing blades 36 for preventing the insertion of the fingers .

Numeral 39 indicates a checking portion (checking port) used for service checking of the cross-flow fan 20 and the electric heaters 24. The checking portion 39 is closed by an

THIS SHEET HAS BEEN
REPLACED.



auxiliary plate 40 touched from the outside thereof (left side, in Fig. 3). The auxiliary plate 40 is mounted with a bearing 41 which is supported by a non-drive shaft 42 of the cross-flow fan 20. Numeral 43 is a boss of the cross-flow fan, and which is mounted with a rotational shaft 44 of the indoor side motor 21.

In the integral type air conditioner 1 having such a construction, the compressor 17, the outdoor heat exchanger 11, a pressure reduction gear (not shown), the indoor heat exchanger 19 and the like are sequentially connected in communication to each other. In the cooling operation, the outdoor heat exchanger 11 actuates as a condenser, and the indoor heat exchanger 19 actuates as an evaporator.

When the propeller fan 9 in the outdoor side chamber B is rotated by driving of the outdoor side motor 7, an outdoor air is sucked from the suction ports 45 and 46 formed on the right and left sides of the back surface of the outdoor side chamber B into the outdoor side chamber B, followed by being cooled or heated in the outdoor heat exchanger 11, and is discharged from the central portion 47 on the back surface of the outdoor side chamber B (see the solid line arrows in Fig. 2).

Also, in the indoor side chamber A, when the cross-flow fan 20 is rotated by driving of the indoor side motor 21, an indoor air is sucked from the front surface of the indoor side chamber A, that is, the suction grill 27 of the front panel 4



into the indoor side chamber A, followed by being cooled or heated in the indoor heat exchanger 19, and is blown off from a discharge port 70 provided on the upper portion of the front panel 4 (see the solid line arrows in Fig. 1).

At this time, the damper 16 is not opened, that is, it is contacted with the surface of the insect proof net 14 on the outdoor side chamber B side, at the suction port 13 of the partitioning plate 5, thereby closing the suction port 13. Thus, the indoor side chamber A is separated from the outdoor side chamber B. In the outdoor side chamber B, an open air introducing passage 48 extending from one suction port 45 to the suction port 13 is connected to an open air discharging passage 49 extending from the open air introducing passage to the outdoor heat exchanger 11 (see Fig. 2).

Next, for introducing the open air into the indoor side chamber A, by manually operating a switching lever (not shown) provided on the side portion of the main body 3, the damper 16 is rotated around the supporting shaft 50 thereof by the tension of this lever. Thus, the leading edge portion of the damper 16 is made to be close to or to be abutted on the wall surface of a fan case 12, thus blocking the flow of the open air flowed in the the open air introducing passage 48 as described above to the open air discharging passage 49. On the other hand, the open air introducing passage 48 is communicated to the indoor side chamber A through the insect proof net 14 (see Fig.

2).

When the outside air introducing passage 48 (that is, the suction port 45) is communicated to the indoor side chamber A as described above, the open air is sucked in the suction port 13 of the partitioning plate 5 to flow in the indoor side chamber A by the negative pressure generated by the rotation of the cross-flow fan 20, and is introduced to the inside (front side) of the rear casing 28 from the auxiliary suction ports 34 through a space 51 between the partitioning plate 5 and the rear casing 28. The open air is then blown off from the discharge port 70 to the interior of a room together with the indoor air in the indoor side chamber A flowing by the rotation of the cross-flow fan 20 in the indoor side chamber A.

In this case, each of the auxiliary suction ports 34 is formed in a louver shape by cutting and rising of the windward side portion of the rear casing 28, and each of raised pieces 52 projects outwardly (rear side, that is, partitioning plate 5 side) of the rear casing 28, so that the inner wall 53 of the rear casing 28 is substantially kept in the smooth curve shape.

Accordingly, in introducing the open air, the reduction in the ventilation resistance in the indoor ventilation passage as shown in the prior arts is made smaller, and the flow of the indoor air flowing in the indoor ventilation passage formed of the rear casing 28 and the like is made to be smooth substantially as in the ordinary cooling operation (see the

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

solid line arrows of Fig. 1). Thus, it is possible to suppress the reduction in the air conditioning ability of the air conditioner 1 to the utmost in introducing the open air.

Also, even if the drain water and rain water scraped by the slinger ring 10 in the indoor side chamber B adhere on the rear casing 28 through the suction port 13, since each of the auxiliary suction ports is formed in the louver shape by cutting and rising of the rear casing 28, there is little a fear of permeation of these waters in the ventilation passage in the indoor side chamber A. Accordingly, there is no risk of the adhesion of the drain water and rain water on the electric heater 24, thus eliminating a fear of causing the insulation failure of the electric heaters 24 and the like by these waters. In addition, in the case that drain water and rain water permeate from the suction port 13, they are introduced to the indoor drain pan 25 through a drain guide gutter 54 disposed so as to be put between the suction port 13 and the indoor drain pan 25, to be thus discharged.

In this case, in the case of carrying out the service checking of the electric heaters 24, cross-flow fan 20 and the like, first, the front panel 4 is removed, and the main body 3 is drawn from the case 2. After that, the auxiliary plate 40 is removed as shown in the solid line arrow of Fig. 4, so that the non-drive shaft 42 of the cross-flow fan 20 supported by the bearing 41 of the auxiliary plate 40 is removed. Next, the

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



boss 43 on the drive side of the cross-flow fan 20 is loosened and removed from the rotational shaft 44 of the indoor side motor 21, and the cross-flow fan 20 is drawn from the checking portion 39 along the axial direction of the fan 20.

After the cross-flow fan 20 is thus removed from the main body 3, the stabilizer 22 disposed on the upper portion of the indoor heat exchanger 19 is removed upwardly (in the opposed direction to that shown in the solid line arrow of Fig. 3). By the removal of the stabilizer 22, the heater supporting piece 23 hung by the stabilizer 22 and the electric heaters 24 fixed to the supporting piece 23 can be integrally removed. Accordingly, even when the electric heaters 24 are disposed under the cross-flow fan 20, there may be no trouble in the service checking. Also, since the width dimension of the upper portion of the heater supporting piece 23 is set to be smaller than that of the electric heaters 24 juxtaposed in two lines, it is possible to make smaller the gap between the heat exchanger 19 and the cross-flow fan 20 than the width dimension of the electric heaters 24 and 24 juxtaposed in two lines, and hence to make smaller the depth dimension of the main body 3.

As described above, according to the present invention, the interior of the main body of the air conditioner is partitioned into the indoor side chamber and the outdoor side chamber by means of the partitioning plate. The partitioning plate is provided with the suction port for communicating the

both chambers to to each other, and the damper positioned in the indoor side chamber for opening/closing the suction port and for introducing an air in the outdoor side chamber into the indoor side chamber. Further, the rear casing of the cross-flow fan is provided in the indoor side chamber, and the auxiliary suction ports communicated to the suction port of the partitioning plate are provided on the windward side of the rear casing. Accordingly, the open air is smoothly joined to the indoor air flowing along the rear casing. Also, since the damper does not block the flow of the indoor air, it is possible to suppress the reduction in the air conditioning ability of the air conditioner to the utmost.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



This Sheet Has Been Replaced



WHAT IS CLAIMED IS:

1. An air conditioner wherein the inside of a body is separated into an outdoor side chamber and an inside chamber by a partitioning plate, comprising:

an indoor heat exchanger provided in said indoor side chamber for performing the heat exchange with an indoor air;

an indoor blower provided in said indoor side chamber, which is constituted of at least a cross-flow fan and a rear casing of said cross-flow fan for circulating said indoor air into said indoor heat exchanger;

auxiliary suction ports provided on a portion of said rear casing on the windward side;

an outdoor heat exchanger provided in said outdoor side chamber for performing the heat exchange with an outdoor air;

an outdoor blower provided in said outdoor side chamber for circulating said outdoor air into said outdoor heat exchanger;

a suction port provided in said partitioning plate for introducing an air in said outdoor side chamber into said indoor side chamber via said auxiliary suction ports; and

a damper provided in said partitioning plate for opening/closing said suction port;

whereby in opening said suction port by said damper, the air in said outdoor side chamber is introduced on the windward

THIS SHEET HAS BEEN
REPLACED



This Sheet Has Been Replaced



side of said cross-flow fan through said suction port and said auxiliary suction ports by a negative pressure generated by the rotation of said cross- flow fan.

2. An air conditioner according to claim 1, wherein said damper is provided on the surface of of said partitioning plate on the outdoor side, and is rotated in said outdoor side chamber to open said suction port.

3. An air conditioner according to claim 1, wherein said outdoor blower sucks the open air from a plurality of suction ports to circulate it in said outdoor heat exchanger; and

the damper opens said suction port to communicate a part of said suction port to said indoor side chamber, and blocks the space between a part of said suction port and said outdoor heat exchanger.

4. An air conditioner according to claim 1, wherein each of said auxiliary suction ports is formed by cutting and rising of the a portion of said rear casing on the partitioning plate side.

5. An air conditioner wherein the interior of a main body is partitioned into an indoor side chamber and an outdoor side chamber comprising:

an indoor heat exchanger provided in said indoor side chamber for performing the heat exchanger with an indoor air;

an indoor fan provided in said indoor side chamber for circulating said indoor air into said indoor heat exchanger;

THIS SHEET HAS BEEN
REPLACED



This Sheet Has Been Replaced



an outdoor heat exchanger provided in said outdoor side chamber for performing the heat exchanger with the open air;

an outdoor fan provided in said outdoor side chamber for circulating said open air into said outdoor heat exchanger;

an open air introducing passage opened on the windward side of said indoor fan for communicating said indoor side chamber to said outdoor side chamber; and

a damper provided in said outdoor side chamber for opening/closing said open air introducing passage.

6. An air conditioner substantially as hereinbefore described with reference to the accompanying drawings.

THIS SHEET HAS BEEN
REPLACED