CLAIMS

1. A treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel, wherein one or both of an active wheel and a passive wheel is composed of an eccentric transmission wheel and combined with a synchronous transmission belt for forming an eccentric wheel transmission wheel series, so that in the reciprocal treadle performed by the human's feet, when the feet input forces at different angles from the treadle shafts of the treadles to an active wheel shaft combined on the active wheel through cranks, the active wheel forms different transmission speed ratios relative to the passive wheel according to the treadle angle, and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the active wheels or the passive wheels to constitute the eccentric wheel series include the round eccentric wheel, non-round eccentric wheel, bimodal elliptical wheel and round wheel to constitute both or one of the active wheels and the passive wheels, so as to incorporate with timing pulleys and transmission belt, or chain wheels and the transmission chain, or directly constituted by the gear set with the function of periodically varied speed ratio;

According to the treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the transmission speed ratio can achieve the maximum while close to the maximum treadling force angle, and the maximum transmission speed ratio is defined as the rotation speed angle displacement of the active wheel being capable of relatively transmitting a higher rotation speed to the passive wheel

compared to other angle displacements during the whole period of the active wheel performing transmission to the passive wheel; the main constitutions of the eccentric transmission wheel series (1000) are as follow:

--Transmission belt (100): a non-slidable belt-shaped structure selected with respect to the wheel-shaped structures of the round active wheel (113) and the eccentric passive wheel (413) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped belt, so as to be provided for the transmission operation between the round active wheel (113) and the eccentric passive wheel (413) and the auxiliary wheel (312);

--Round active wheel (113): combined with the active wheel shaft (111), and the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), wherein the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), and the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the round active wheel (113) is composed of a non-slidable chain wheel or timing tooth-shaped pulley or gear;

--Eccentric passive wheel (413): composed of the same chain wheel, timing tooth-shaped pulley or gear of which the round active wheel (113) is composed, and installed on the passive wheel shaft (211), and the pitch diameter thereof is half of that of the round active wheel (113), and driven by the round active wheel (113) through the transmission belt (100) which incorporates with the mentioned round active wheel (113) and the eccentric passive wheel (413) and the auxiliary wheel (312), and provided for performing prestressed tightening to the periodical tightening/releasing alternation of the driven transmission belt through the auxiliary wheel (312), and the mechanical angle position of the eccentric upper protrusion directivity

(c) of the eccentric passive wheel (413), and the mechanical angle position between the directivity (b) constituted by the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) through the transmission belt (100) form a certain mechanical angle differentiation relation;

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one round active wheel (113) and one or more than one eccentric passive wheel (413), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley or gear of which the round active wheel (113) and the eccentric passive wheel (413) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the round active wheel (113) and the eccentric passive wheel (413), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to utilize the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to

the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the round active wheel (113) serving as an active wheel, the eccentric passive wheel (413) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with 180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103), and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive eccentric transmission wheel series (1000) is defined through the relation of the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and through the transmission belt (100) the mechanical angle position of the directivity (b) formed by the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111), so the round active wheel (113) periodically generates twice increase and decrease of the speed ratio to the eccentric passive wheel (413) during each treadle rotation; for example, the mechanical angle differentiation relation of the mentioned round active wheel (113) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the mechanical angle directivity (b) of the first treadle shaft (103) or the second treadle shaft (203) to the active wheel shaft (111) passing the upper stop directivity (a) and keeping to treadle along the treadle direction within a 180 degree range, thereby the round active wheel (113) to the eccentric passive wheel (413) is in a transmission varied speed ratio status of tending to

the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

2. A treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, wherein the active wheel is a round wheel and the passive wheel is a bimodal elliptical passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

In the treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the bimodal elliptical passive wheel (213) can be composed of the same chain wheel or timing tooth-shaped pulley of which the round active wheel (113) is composed; the transmission belt (100) is a belt-shaped structure selected with respect to the wheel-shaped structures of the round active wheel (113) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312), which includes a chain, timing tooth-shaped belt, tooth-shaped belt, so as to be provided for the transmission operations between the round active wheel (113), the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the round active wheel (113) and the bimodal elliptical passive wheel (213) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the round active wheel (113) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Round active wheel (113): combined with the active wheel shaft (111), and the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), wherein

the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), and the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the round active wheel (113) is composed of a non-slidable chain wheel or timing tooth-shaped pulley;

--Bimodal elliptical passive wheel (213): composed of a bimodal elliptical chain wheel or timing tooth-shaped pulley having the same circumference as the round active wheel (113), and installed on the passive wheel shaft (211), and the passive wheel is through the transmission belt (100) incorporating with the mentioned round active wheel (113) and the bimodal elliptical passive wheel (213) to be driven by the round active wheel (113), and through the auxiliary wheel (312) to perform prestressed tightening to the periodical tightening/releasing alternation of the driven transmission belt (100);

wherein the mechanical angle position between the bimodal of the bimodal elliptical passive wheel (213) and the passive wheel shaft (211), and the mechanical angle position between the round active wheel (113) and the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one round active wheel (113) and one or more than one bimodal elliptical passive wheel (213), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and

an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley of which the round active wheel (113) and the bimodal elliptical passive wheel (213) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the round active wheel (113) and the bimodal elliptical passive wheel (213), such as a chain or a timing tooth-shape pulley or a tooth-shaped chain, to utilize the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the round active wheel (113) serving as an active wheel, the bimodal elliptical passive wheel (213) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with 180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103), and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive elliptical transmission wheel series

is defined through the relation of the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111), and through the transmission belt (100) the set mechanical angle position between the bimodal elliptical passive wheel (213) and the passive wheel shaft (211), thereby the round active wheel (113) periodically generates twice increase and decrease of the speed ratio to the bimodal elliptical passive wheel (213) during each treadle rotation; for example the mechanical angle differentiation relation of the mentioned round active wheel (113) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the first treadle shaft (103) or the second treadle shaft (203) passing the upper stop and keeping to treadle along the treadle direction within a 180 degree range, thereby the round active wheel (113) to the bimodal elliptical passive wheel (213) is in a transmission varied speed ratio status of tending to the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

3. A treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, wherein the active wheel is a bimodal elliptical active wheel and the passive wheel is a bimodal elliptical passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

In the treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the bimodal elliptical passive wheel (213) can be composed of the same elliptical chain wheel or timing tooth-shaped belt of which the bimodal elliptical active wheel (112) is composed;

the transmission belt (100) is a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312), which includes a chain, timing tooth-shaped belt, tooth-shaped belt, so as to be provided for the transmission operations between the bimodal elliptical active wheel (112), the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the bimodal active wheel (112) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Bimodal elliptical active wheel (112): combined with the active wheel shaft (111), the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the bimodal elliptical active wheel (112) is composed of a non-slidable chain wheel or timing tooth-shaped pulley, and wherein the mechanical angle position between the bimodal of the bimodal elliptic and the active wheel shaft (111) and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

--Bimodal elliptical passive wheel (213): composed of the bimodal elliptical chain wheel or timing tooth-shaped pulley having the same shape and the same size as the bimodal elliptical active wheel (112),

and is installed on the passive wheel shaft (211) and forms a 90 degree mechanical angle differentiation relative to the bimodal elliptical active wheel (112), and through the transmission belt (100) for transmission and connection, so as to be driven by the bimodal elliptical active wheel (211), and through the auxiliary wheel (312) to perform prestressed tightening to the tightening/releasing alternation of the driven transmission belt (100);

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one bimodal elliptical active wheel (112) and one or more than one bimodal elliptical passive wheel (213), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley of which the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to use the prestressed pressure applied to the auxiliary wheel press helve (301)

from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the bimodal elliptical active wheel (112) serving as an active wheel, the bimodal elliptical passive wheel (213) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with 180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103), and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive elliptical transmission wheel series is defined through the relation of the mechanical angle position between the bimodal elliptical active wheel (112) and the active wheel shaft (111), and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111), and through the transmission belt (100) the set mechanical angle position between the bimodal elliptical passive wheel (213) and the passive wheel shaft (211), so the bimodal elliptical active wheel (112) periodically generates twice increase and decrease of the speed ratio to the bimodal elliptical passive wheel (213)during each treadle rotation; for example, the mechanical angle differentiation relation of the mentioned bimodal elliptical active wheel (112) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the first treadle shaft

(103) or the second treadle shaft (203) passing the upper stop and keeping to treadle along the treadle direction within a 90 degree range, thereby the bimodal elliptical active wheel (112) to the bimodal elliptical passive wheel (213) is in a transmission varied speed ratio status of tending to the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

4. A treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, wherein the active wheel is a bimodal elliptical active wheel and the passive wheel is an eccentric transmission passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

--Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the eccentric passive wheel (413) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the bimodal active wheel (112) and the eccentric passive wheel (413) and the auxiliary wheel (312);

--Bimodal elliptical active wheel (112): combined with the active wheel shaft (111), the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the bimodal elliptical active wheel (112) is composed of a non-slidable chain wheel or timing tooth-shaped pulley, and wherein the mechanical angle position between the bimodal of the

bimodal elliptic and the active wheel shaft (111) and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

--Eccentric passive wheel (413): composed of the same chain wheel, timing tooth-shaped pulley or gear of which the bimodal elliptical active wheel (112) is composed, and installed on the passive wheel shaft (211), and the pitch diameter thereof is half of that of the bimodal elliptical active wheel (112), and driven by the bimodal elliptical active wheel (112) through the transmission belt (100) which incorporates with the mentioned bimodal elliptical active wheel (112) and the eccentric passive wheel (413) and the auxiliary wheel (312), and provided for performing prestressed tightening to the periodical tightening/releasing alternation of the driven transmission belt through the auxiliary wheel (312), and the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and the mechanical angle position between the directivity (b) constituted by the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) through the transmission belt (100) form a certain mechanical angle differentiation relation;

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one bimodal elliptical active wheel (112) and one or more than one eccentric passive wheel (413), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and

an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley or gear of which the bimodal elliptical active wheel (112) and the eccentric passive wheel (413) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the bimodal elliptical active wheel (112) and the eccentric passive wheel (413), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to utilize the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the bimodal elliptical active wheel (112) serving as an active wheel, the eccentric passive wheel (413) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with 180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103), and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive eccentric transmission wheel series

(1000) is defined through the relation of the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and through the transmission belt (100) the mechanical angle position of the directivity (b) formed by the first treadle shaft (103) and the second treadle shaft (203) installed on the active wheel shaft (111), so the bimodal elliptical active wheel (112) periodically generates twice increase and decrease of the speed ratio to the eccentric passive wheel (413) during each treadle rotation; for example, the mechanical angle differentiation relation of the mentioned bimodal elliptical active wheel (112) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the mechanical angle directivity (b) of the first treadle shaft (103) or the second treadle shaft (203) to the active wheel shaft (111) passing the upper stop directivity (a) and keeping to treadle along the treadle direction within a 180 degree range, thereby the bimodal elliptical active wheel (112) to the eccentric passive wheel (413) is in a transmission varied speed ratio status of tending to the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

5. A treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, wherein includes being composed of the bimodal elliptical active wheel (112), round passive wheel (212) and the transmission belt (100), , and the front portion of the transmission belt (100) to be linked to engage with the bimodal elliptical active wheel (112) is further installed with the auxiliary wheel press helve (301), the auxiliary wheel shaft (311) and the auxiliary wheel (312), and the auxiliary wheel prestressed spring (302) is installed between the

machine body (800) and the auxiliary wheel press helve (301), so as the transmission belt (100) can be packed by the prestressed pressure in the direction of engagement with the bimodal elliptical active wheel (112).

6. A treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, wherein the active wheel is a bimodal elliptical active wheel and the passive wheel is a bimodal elliptical passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

In the treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the bimodal elliptical passive wheel (213) can be composed of the same elliptical chain wheel or timing tooth-shaped belt of which the bimodal elliptical active wheel (112) is composed; the transmission belt (100) is a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312), which includes a chain, timing tooth-shaped belt, tooth-shaped belt, so as to be provided for the transmission operations between the bimodal elliptical active wheel (112), the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the bimodal active wheel (112) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Bimodal elliptical active wheel (112): combined with the active

wheel shaft (111), the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the bimodal elliptical active wheel (112) is composed of a non-slidable chain wheel or timing tooth-shaped pulley, and wherein the mechanical angle position between the bimodal of the bimodal elliptic and the active wheel shaft (111) and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

--Bimodal elliptical passive wheel (213): composed of the bimodal elliptical chain wheel or timing tooth-shaped pulley having the same shape and the same size as the bimodal elliptical active wheel (112), and is installed on the passive wheel shaft (211) and forms a 90 degree mechanical angle differentiation relative to the bimodal elliptical active wheel (112), and through the transmission belt (100) for transmission and connection, so as to be driven by the bimodal elliptical active wheel (211), and through the auxiliary wheel (312) to perform prestressed tightening to the tightening/releasing alternation of the driven transmission belt (100);

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one bimodal elliptical active wheel (112) and one or more than one bimodal elliptical passive wheel (213), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press

helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley of which the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to use the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

The auxiliary wheel press helve (301), the auxiliary wheel shaft (311) and the auxiliary wheel (312) rotated on the auxiliary wheel shaft (311) are further installed at the front portion of the transmission belt (100) to be linked to engage with the bimodal elliptical active wheel (112), and the auxiliary wheel prestressed spring (302) is installed between the machine body (800) and the auxiliary wheel press helve (301), so as the transmission belt (100) can be packed by the prestressed pressure in the direction of engagement with the bimodal elliptical active wheel (112).

7. A treadle-drive transmission wheel series with periodically varied

speed ratio and having inward packing auxiliary wheel as claimed in claim 1, wherein the active wheel is a bimodal elliptical active wheel and the passive wheel is an eccentric transmission passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

--Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the eccentric passive wheel (413) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the bimodal active wheel (112) and the eccentric passive wheel (413) and the auxiliary wheel (312);

--Bimodal elliptical active wheel (112): combined with the active wheel shaft (111), the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the bimodal elliptical active wheel (112) is composed of a non-slidable chain wheel or timing tooth-shaped pulley, and wherein the mechanical angle position between the bimodal of the bimodal elliptic and the active wheel shaft (111) and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

--Eccentric passive wheel (413): composed of the same chain wheel, timing tooth-shaped pulley or gear of which the bimodal elliptical active wheel (112) is composed, and installed on the passive wheel shaft (211), and the pitch diameter thereof is half of that of the bimodal elliptical active wheel (112), and driven by the bimodal elliptical active

wheel (112) through the transmission belt (100) which incorporates with the mentioned bimodal elliptical active wheel (112) and the eccentric passive wheel (413) and the auxiliary wheel (312), and provided for performing prestressed tightening to the periodical tightening/releasing alternation of the driven transmission belt through the auxiliary wheel (312), and the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and the mechanical angle position between the directivity (b) constituted by the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) through the transmission belt (100) form a certain mechanical angle differentiation relation;

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one bimodal elliptical active wheel (112) and one or more than one eccentric passive wheel (413), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley or gear of which the bimodal elliptical active wheel (112) and the eccentric passive wheel (413) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the

transmission belt (100) incorporating with the bimodal elliptical active wheel (112) and the eccentric passive wheel (413), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to utilize the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

The auxiliary wheel press helve (301), the auxiliary wheel shaft (311) and the auxiliary wheel (312) rotated on the auxiliary wheel shaft (311) are further installed at the front portion of the transmission belt (100) to be linked to engage with the bimodal elliptical active wheel (112), and the auxiliary wheel prestressed spring (302) is installed between the machine body (800) and the auxiliary wheel press helve (301), so as the transmission belt (100) can be packed by the prestressed pressure in the direction of engagement with the bimodal elliptical active wheel (112).

8. A treadle-drive transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in any claim of claims 1, 2, 3, 4, 5, 6, or 7, wherein the transmission means between the passive wheel shaft (211) and the load wheel set (600) include:
   1) The load wheel set (600) is directly driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000); or
   2) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through the middle transmission (5000); or
   3) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through the step

or continuous inner variable speed device (2000); or

4) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through the middle transmission (5000) and the step or continuous inner variable speed device (2000); or

5) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through step or continuous outer variable speed device (3000).

CLAIMS

1. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel, wherein one or both of an active wheel and a passive wheel is composed of an eccentric transmission wheel and combined with a synchronous transmission belt for forming an eccentric wheel transmission wheel series, so that in the reciprocal treadle performed by the human's feet, when the feet input forces at different angles from the treadle shafts of the treadles to an active wheel shaft combined on the active wheel through cranks, the active wheel forms different transmission speed ratios relative to the passive wheel according to the treadle angle, and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

   In the treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the active wheels or the passive wheels to constitute the eccentric wheel series include the round eccentric wheel, non-round eccentric wheel, bimodal elliptical wheel and round wheel to constitute both or one of the active wheels and the passive wheels, so as to incorporate with timing pulleys and transmission belt, or chain wheels and the transmission chain, or directly constituted by the gear set with the function of periodically varied speed ratio;

   According to the treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the transmission speed ratio can achieve the maximum while close to the maximum treadling force angle, and the maximum transmission speed ratio is defined as the rotation speed angle displacement of the active wheel being capable of relatively transmitting a higher rotation speed to the passive wheel compared to other angle displacements during the whole period of the active wheel

performing transmission to the passive wheel; the main constitutions of the eccentric transmission wheel series (1000) are as follow:

--Transmission belt (100): a non-slidable belt-shaped structure selected with respect to the wheel-shaped structures of the round active wheel (113) and the eccentric passive wheel (413) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped belt, so as to be provided for the transmission operation between the round active wheel (113) and the eccentric passive wheel (413) and the auxiliary wheel (312);

--Round active wheel (113): combined with the active wheel shaft (111), and the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), wherein the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), and the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the round active wheel (113) is composed of a non-slidable chain wheel or timing tooth-shaped pulley or gear;

--Eccentric passive wheel (413): composed of the same chain wheel, timing tooth-shaped pulley or gear of which the round active wheel (113) is composed, and installed on the passive wheel shaft (211), and the pitch diameter thereof is half of that of the round active wheel (113), and driven by the round active wheel (113) through the transmission belt (100) which incorporates with the mentioned round active wheel (113) and the eccentric passive wheel (413) and the auxiliary wheel (312), and provided for performing prestressed tightening to the periodical tightening/releasing alternation of the driven transmission belt through the auxiliary wheel (312), and the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and the mechanical angle position between the directivity (b) constituted by the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) through the transmission belt (100) form a certain mechanical angle

differentiation relation;

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one round active wheel (113) and one or more than one eccentric passive wheel (413), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley or gear of which the round active wheel (113) and the eccentric passive wheel (413) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the round active wheel (113) and the eccentric passive wheel (413), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to utilize the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the round active wheel (113) serving as an active wheel, the eccentric passive wheel (413) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with

180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103), and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive eccentric transmission wheel series (1000) is defined through the relation of the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and through the transmission belt (100) the mechanical angle position of the directivity (b) formed by the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111), so the round active wheel (113) periodically generates twice increase and decrease of the speed ratio to the eccentric passive wheel (413) during each treadle rotation; for example, the mechanical angle differentiation relation of the mentioned round active wheel (113) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the mechanical angle directivity (b) of the first treadle shaft (103) or the second treadle shaft (203) to the active wheel shaft (111) passing the upper stop directivity (a) and keeping to treadle along the treadle direction within a 180 degree range, thereby the round active wheel (113) to the eccentric passive wheel (413) is in a transmission varied speed ratio status of tending to the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

2. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel, wherein the active wheel is a round wheel and the passive wheel is a bimodal elliptical passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

In the treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the bimodal elliptical passive wheel (213) can be composed of the same chain wheel or timing tooth-shaped pulley of which the round active wheel (113) is composed; the transmission belt (100) is a belt-shaped structure selected with respect to the wheel-shaped structures of the round active wheel (113) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312), which includes a chain, timing tooth-shaped belt, tooth-shaped belt, so as to be provided for the transmission operations between the round active wheel (113), the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the round active wheel (113) and the bimodal elliptical passive wheel (213) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the round active wheel (113) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Round active wheel (113): combined with the active wheel shaft (111), and the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), wherein the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), and the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the round active wheel (113) is composed of a non-slidable chain wheel or timing tooth-shaped pulley;

--Bimodal elliptical passive wheel (213): composed of a bimodal elliptical chain wheel or timing tooth-shaped pulley having the same circumference as the round active wheel (113), and installed on the passive wheel shaft (211), and the passive wheel is through the transmission belt (100)

incorporating with the mentioned round active wheel (113) and the bimodal elliptical passive wheel (213) to be driven by the round active wheel (113), and through the auxiliary wheel (312) to perform prestressed tightening to the periodical tightening/releasing alternation of the driven transmission belt (100);

wherein the mechanical angle position between the bimodal of the bimodal elliptical passive wheel (213) and the passive wheel shaft (211), and the mechanical angle position between the round active wheel (113) and the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one round active wheel (113) and one or more than one bimodal elliptical passive wheel (213), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley of which the round active wheel (113) and the bimodal elliptical passive wheel (213) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the round active wheel (113) and the bimodal elliptical passive wheel (213),

such as a chain or a timing tooth-shape pulley or a tooth-shaped chain, to utilize the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the round active wheel (113) serving as an active wheel, the bimodal elliptical passive wheel (213) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with 180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103), and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive elliptical transmission wheel series is defined through the relation of the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111), and through the transmission belt (100) the set mechanical angle position between the bimodal elliptical passive wheel (213) and the passive wheel shaft (211), thereby the round active wheel (113) periodically generates twice increase and decrease of the speed ratio to the bimodal elliptical passive wheel (213) during each treadle rotation; for example the mechanical angle differentiation relation of the mentioned round active wheel (113) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the first treadle shaft (103) or the second treadle shaft (203) passing the upper stop and keeping to treadle along the treadle direction

within a 180 degree range, thereby the round active wheel (113) to the bimodal elliptical passive wheel (213) is in a transmission varied speed ratio status of tending to the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

3. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel, wherein the active wheel is a bimodal elliptical active wheel and the passive wheel is a bimodal elliptical passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

In the treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel of the present invention, the bimodal elliptical passive wheel (213) can be composed of the same elliptical chain wheel or timing tooth-shaped belt of which the bimodal elliptical active wheel (112) is composed; the transmission belt (100) is a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) and the auxiliary wheel (312), which includes a chain, timing tooth-shaped belt, tooth-shaped belt, so as to be provided for the transmission operations between the bimodal elliptical active wheel (112), the bimodal elliptical passive wheel (213) and the auxiliary wheel (312);

--Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the bimodal active wheel (112) and the bimodal elliptical passive wheel (213) and the

auxiliary wheel (312);

--Bimodal elliptical active wheel (112): combined with the active wheel shaft (111), the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the bimodal elliptical active wheel (112) is composed of a non-slidable chain wheel or timing tooth-shaped pulley, and wherein the mechanical angle position between the bimodal of the bimodal elliptic and the active wheel shaft (111) and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

--Bimodal elliptical passive wheel (213): composed of the bimodal elliptical chain wheel or timing tooth-shaped pulley having the same shape and the same size as the bimodal elliptical active wheel (112), and is installed on the passive wheel shaft (211) and forms a 90 degree mechanical angle differentiation relative to the bimodal elliptical active wheel (112), and through the transmission belt (100) for transmission and connection, so as to be driven by the bimodal elliptical active wheel (211), and through the auxiliary wheel (312) to perform prestressed tightening to the tightening/releasing alternation of the driven transmission belt (100);

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one bimodal elliptical active wheel (112) and one or more than one bimodal elliptical passive wheel (213), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing

shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley of which the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the bimodal elliptical active wheel (112) and the bimodal elliptical passive wheel (213), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to use the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the bimodal elliptical active wheel (112) serving as an active wheel, the bimodal elliptical passive wheel (213) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with 180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103), and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive elliptical transmission wheel series is defined through the relation of the mechanical angle position between the

bimodal elliptical active wheel (112) and the active wheel shaft (111), and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111), and through the transmission belt (100) the set mechanical angle position between the bimodal elliptical passive wheel (213) and the passive wheel shaft (211), so the bimodal elliptical active wheel (112) periodically generates twice increase and decrease of the speed ratio to the bimodal elliptical passive wheel (213)during each treadle rotation; for example, the mechanical angle differentiation relation of the mentioned bimodal elliptical active wheel (112) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the first treadle shaft (103) or the second treadle shaft (203) passing the upper stop and keeping to treadle along the treadle direction within a 90 degree range, thereby the bimodal elliptical active wheel (112) to the bimodal elliptical passive wheel (213) is in a transmission varied speed ratio status of tending to the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

4. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel, wherein the active wheel is a bimodal elliptical active wheel and the passive wheel is an eccentric transmission passive wheel, and the main constitutions of the eccentric transmission wheel series (1000) are as follows:

   --Transmission belt (100): a belt-shaped structure selected with respect to the wheel-shaped structures of the bimodal elliptical active wheel (112) and the eccentric passive wheel (413) and an auxiliary wheel (312), which includes a chain, timing tooth-shaped belt or tooth-shaped chain, so as to be provided for the transmission operations between the bimodal active wheel (112) and the eccentric passive wheel (413) and the auxiliary wheel (312);

--Bimodal elliptical active wheel (112): combined with the active wheel shaft (111), the two sides of the active wheel shaft (111) are respectively combined with a first crank (101) and a second crank (201), the first crank (101) is installed with a first treadle shaft (103) for being provided with a first treadle (102), the second crank (201) is installed with a second treadle shaft (203) for being provided with a second treadle (202), and the bimodal elliptical active wheel (112) is composed of a non-slidable chain wheel or timing tooth-shaped pulley, and wherein the mechanical angle position between the bimodal of the bimodal elliptic and the active wheel shaft (111) and the mechanical angle position between the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) form a certain mechanical angle differentiation relation;

--Eccentric passive wheel (413): composed of the same chain wheel, timing tooth-shaped pulley or gear of which the bimodal elliptical active wheel (112) is composed, and installed on the passive wheel shaft (211), and the pitch diameter thereof is half of that of the bimodal elliptical active wheel (112), and driven by the bimodal elliptical active wheel (112) through the transmission belt (100) which incorporates with the mentioned bimodal elliptical active wheel (112) and the eccentric passive wheel (413) and the auxiliary wheel (312), and provided for performing prestressed tightening to the periodical tightening/releasing alternation of the driven transmission belt through the auxiliary wheel (312), and the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and the mechanical angle position between the directivity (b) constituted by the first treadle shaft (103) and the second treadle shaft (203) and the active wheel shaft (111) through the transmission belt (100) form a certain mechanical angle differentiation relation;

-- The eccentric transmission wheel series (1000) of one or more than one step different speed ratio is constituted through the transmission engagement between the transmission belt (100), one or more than one

bimodal elliptical active wheel (112) and one or more than one eccentric passive wheel (413), as well as through the operation of the speed variable device;

--Auxiliary wheel press helve (301): having one end coupled to a machine body (800) for swing motion through an auxiliary wheel press helve swing shaft (303), and the other end being installed with an auxiliary wheel shaft (311) for installing an auxiliary wheel (312), and an auxiliary wheel prestressed spring (302) is installed between the auxiliary wheel press helve (301) and the machine body (800) for generating an inward-packing prestressed pressure to the auxiliary wheel (312);

--Auxiliary wheel (312): composed of the same chain wheel or timing tooth-shaped pulley or gear of which the bimodal elliptical active wheel (112) and the eccentric passive wheel (413) are composed, and provided for rotating on the auxiliary wheel shaft (311) and driven by the transmission belt (100), thereby through linked with the transmission belt (100) incorporating with the bimodal elliptical active wheel (112) and the eccentric passive wheel (413), such as a chain or timing tooth-shape pulley or tooth-shaped chain, to utilize the prestressed pressure applied to the auxiliary wheel press helve (301) from the auxiliary wheel prestressed spring (302) to compel the auxiliary wheel shaft (311) and the auxiliary wheel (312), and random inward packing is performed to the transmission belt (100) of the engage end of the eccentric passive wheel (413) during the transmission for stabling the operation;

In the transmission wheel series composed of the bimodal elliptical active wheel (112) serving as an active wheel, the eccentric passive wheel (413) serving as a passive wheel and the installation of the auxiliary wheel (312), when a human uprightly treadle to ride a bicycle, the right foot and the left foot follow a simple harmonic motion to form a sine wave treadle track with 180 degree differentiation, wherein the right foot treadles with respect to the up/down displacement track of the first treadle shaft (103),

and the left foot treadles with respect to the up/down displacement track of the second treadle shaft (203), and during the continuous treadling of the right foot and the left foot, the speed ratio of the active wheel and the passive wheel of the treadle-drive eccentric transmission wheel series (1000) is defined through the relation of the mechanical angle position of the eccentric upper protrusion directivity (c) of the eccentric passive wheel (413), and through the transmission belt (100) the mechanical angle position of the directivity (b) formed by the first treadle shaft (103) and the second treadle shaft (203) installed on the active wheel shaft (111), so the bimodal elliptical active wheel (112) periodically generates twice increase and decrease of the speed ratio to the eccentric passive wheel (413) during each treadle rotation; for example, the mechanical angle differentiation relation of the mentioned bimodal elliptical active wheel (112) and the first treadle shaft (103) and the second treadle shaft (203) is selected to be set as, when treadling along the treadle direction, the mechanical angle directivity (b) of the first treadle shaft (103) or the second treadle shaft (203) to the active wheel shaft (111) passing the upper stop directivity (a) and keeping to treadle along the treadle direction within a 180 degree range, thereby the bimodal elliptical active wheel (112) to the eccentric passive wheel (413) is in a transmission varied speed ratio status of tending to the maximum speed accelerating ratio or the minimum speed decelerating ratio; the periodically varied speed ratio relation is upon the wheel shape of the eccentric transmission wheel series (1000).

5. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, 2, 3 or 4, wherein the transmission means between the passive wheel shaft (211) and the load wheel set (600) include:
   1) The load wheel set (600) is directly driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000); or

2) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through the middle transmission (5000); or
3) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through the step or continuous inner variable speed device (2000); or
4) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through the middle transmission (5000) and the step or continuous inner variable speed device (2000); or
5) The load wheel set (600) is driven by the passive wheel shaft (211) of the eccentric transmission wheel series (1000) through step or continuous outer variable speed device (3000).

6. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, 2, 3 or 4, wherein the passive wheel shaft (211) of the eccentric transmission wheel series (1000) directly drives the load wheel set (600), and the main constitutions are as follows:

--Eccentric transmission wheel series (1000): the active wheels or the passive wheels to constitute the eccentric wheel series include the round eccentric wheel, non-round eccentric wheel, bimodal elliptical wheel and round wheel to constitute one or both of the active wheels and the passive wheels, so as to incorporate with timing pulleys and transmission belt, or chain wheels and the transmission chain, or directly constituted by the gear set with the function of periodically varied speed ratio;

--Passive wheel shaft (211): related to a hollow or solid rotatable shaft structure combined to the output end of the passive wheel of the eccentric transmission wheel series (1000) for driving the sleeve (601);

--Sleeve (601): related to a hollow rotating shaft structure for sleeve to the

core axis (602), and driven by the passive wheel shaft (211) to drive the load wheel set (600);

--Load wheel set (600): related to a rotatable wheel set structure, and rotated on the core axis (602) through the sleeve (601), and thereby driven by the passive wheel shaft (211).

7. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, 2, 3 or 4, wherein the passive wheel shaft (211) of the eccentric transmission wheel series (1000) drives the load wheel set (600) through the middle transmission (5000), and the main constitutions are as follows:

--Eccentric transmission wheel series (1000): the active wheels or the passive wheels to constitute the eccentric wheel series include the round eccentric wheel, non-round eccentric wheel, bimodal elliptical wheel and round wheel to constitute one or both of the active wheels and the passive wheels, so as to incorporate with timing pulleys and transmission belt, or chain wheels and the transmission chain, or directly constituted by the gear set with the function of periodically varied speed ratio;

--Passive wheel shaft (211): related to a hollow or solid rotatable shaft structure combined to the output end of the passive wheel of the eccentric transmission wheel series (1000) for driving the primary drive wheel on the input end of the middle transmission (5000);

--middle transmission (5000): constituted by the transmission belt and pulley wheel train, or the transmission chain and chain wheel train, or the gear set, or the driving rod and the bevel gear set, wherein the input end thereof is subject to be driven by the passive wheel shaft (211) and the output end thereof is served to drive the sleeve (601);

--Sleeve (601): related to a hollow rotating shaft structure for sleeve to the core axis (602), and driven by the output end of the passive wheel of the middle transmission (5000);

--Load wheel set (600): related to a rotatable wheel set structure, and rotated on the core axis (602) through the sleeve (601), and thereby driven by the output end of the passive wheel of the middle transmission (5000) from the sleeve (601).

8. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, 2, 3 or 4, wherein the passive wheel shaft (211) of the eccentric transmission wheel series (1000) drives the load wheel set (600) through the step or continuous inner variable speed device (2000), and the main constitutions are as follows:

   --Eccentric transmission wheel series (1000): the active wheels or the passive wheels to constitute the eccentric wheel series include the round eccentric wheel, non-round eccentric wheel, bimodal elliptical wheel and round wheel to constitute one or both of the active wheels and the passive wheels, so as to incorporate with timing pulleys and transmission belt, or chain wheels and the transmission chain, or directly constituted by the gear set with the function of periodically varied speed ratio;

   --Passive wheel shaft (211): related to a hollow or solid rotatable shaft structure combined to the output end of the passive wheel of the eccentric transmission wheel series (1000) for driving the input end of the inner variable speed device (2000);

   --Inner variable speed device (2000): related to the step or continuous inner variable speed device with two or more than steps subject to the external operations, which is constituted by the gear or the friction wheel and the speed switch mechanism, and the input end thereof is driven by the passive wheel shaft (211) and the output end thereof is served to drive the load wheel set (600);

   --Load wheel set (600): related to a rotatable wheel set structure for being driven by the output end of the inner variable speed device (2000).

9. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, 2, 3 or 4, wherein the passive wheel shaft (211) of the eccentric transmission wheel series (1000) drives the load wheel set (600) through the middle transmission (5000) and the step or continuous inner variable speed device (2000), and the main constitutions are as follows:

--Eccentric transmission wheel series (1000): the active wheels or the passive wheels to constitute the eccentric wheel series include the round eccentric wheel, non-round eccentric wheel, bimodal elliptical wheel and round wheel to constitute one or both of the active wheels and the passive wheels, so as to incorporate with timing pulleys and transmission belt, or chain wheels and the transmission chain, or directly constituted by the gear set with the function of periodically varied speed ratio;

--Passive wheel shaft (211): related to a hollow or solid rotatable shaft structure combined to the output end of the passive wheel of the eccentric transmission wheel series (1000) for driving the primary drive wheel on the input end of the middle transmission (5000);

--Middle transmission (5000): constituted by the transmission belt and pulley wheel train, or the transmission chain and chain wheel train, or the gear set, or the driving rod and the bevel gear set, wherein the input end thereof is driven by the passive wheel shaft (211) and the output end thereof is served to drive the input end of the inner variable speed device (2000);

--Inner variable speed device (2000): related to the step or continuous inner variable speed device with two or more than steps subject to the external operations, which is constituted by the gear or the friction wheel and the speed switch mechanism, and the input end thereof is driven by the output end of the middle transmission (5000) and the output end thereof is served to drive the load wheel set (600);

--Load wheel set (600): related to a rotatable wheel set structure for being driven by the output end of the inner variable speed device (2000).

10. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, 2, 3 or 4, wherein the passive wheel shaft (211) of the eccentric transmission wheel series (1000) drives the load wheel set (600) through the step or continuous outer variable speed device (3000), and the main constitutions are as follows:

--Eccentric transmission wheel series (1000): the active wheels or the passive wheels to constitute the eccentric wheel series include the round eccentric wheel, non-round eccentric wheel, bimodal elliptical wheel and round wheel to constitute one or both of the active wheels and the passive wheels, so as to incorporate with timing pulleys and transmission belt, or chain wheels and the transmission chain, or directly constituted by the gear set with the function of periodically varied speed ratio;

--Passive wheel shaft (211): related to a hollow or solid rotatable shaft structure combined to the output end of the passive wheel of the eccentric transmission wheel series (1000) for driving the primary drive wheel of the input end of the outer variable speed device (3000);

--Outer variable speed device (3000): related to the step or continuous inner variable speed device with two or more than steps subject to the external operations, which is constituted by the chains and the chain wheel set, or the pulley or the pulley wheel set, or the gear the speed switch mechanism or clutch, and the input end thereof is driven by the passive wheel shaft (211) and the output end thereof is served to drive the load wheel set (600) through the sleeve (601);

--Sleeve (601): related to a hollow rotating shaft structure for sleeve to the core axis (602), and driven by the output end of the passive wheel of the outer variable speed device (3000);

--Load wheel set (600): related to a rotatable wheel set structure, and rotated on the core axis (602) through the sleeve (601), and thereby driven by the output end of the passive wheel of the outer variable speed device (3000) from the sleeve (601).

11. A treadle-drive eccentric wheel transmission wheel series with periodically varied speed ratio and having inward packing auxiliary wheel as claimed in claim 1, 2, 3 or 4, which can be constituted by one or more than one set of the eccentric transmission wheel series (1000) with different speed ratio in parallel connection, or can be switched between the active wheel and the passive wheel in turn to obtain multi-step speed ratios.