

Intraocular Pressure Measuring and/or Monitoring System with Inertial and/or Environmental Sensor

The present invention relates to a system for measuring and/or monitoring the intraocular pressure (IOP). The present invention relates in particular to a system comprising a device that can be placed on or in the eye of a user to monitor intraocular pressure over an extended period of time, wherein the system further comprises inertial and/or environmental sensors in order to allow correlating the thus collected inertial and/or environmental information with the intraocular pressure measurements.

Glaucoma is a widespread disease characterized by an elevated intraocular pressure (IOP). This elevated IOP produces a gradual loss of peripheral vision. There is therefore a need to have a detailed knowledge of IOP in glaucoma patients in order to provide reliable diagnostics or for setting up new therapies.

There are several types of devices that are commonly used for measuring IOP on patients. Some devices are configured for single measurements and are usually bulky fixed equipments. A pressure sensor is applied on the patient's eye with a determined pressure for a short period of time.

Other equipments allow IOP measurement over extended periods of time, for example some hours, days or more. These devices often comprise a miniaturized pressure sensor, for example in the form of a MEMS, that is worn by the patient during the entire measuring time period. The pressure sensor is for example integrated into or attached to a contact lens worn by the patient, or mounted on a support configured to be directly implanted into the eyeball. The pressure sensor continuously measures the IOP as long as it is in contact with the eye, and the measured pressure values are transmitted to and for example stored by a receiver over a wired or a wireless communication link.

An advantage of such pressure measuring devices or systems is that they allow measuring the IOP of a patient over an extended period of time, thereby allowing monitoring the evolution of the IOP during the day, allowing for example measuring possible pressure differences depending on whether the
5 patient is awake or asleep, tired or not, etc.

However, it might be sometimes difficult to analyze some of the measured IOP variations that can be due to external factors, for example the patient's physical activity and/or environment at the time of IOP measurement.

An aim of the present invention is thus to provide an intraocular pressure
10 measuring and/or monitoring system that allows a more accurate analysis of the IOP measurements taken over extended period of times.

Another aim of the present invention is to provide an intraocular pressure measuring and/or monitoring system that allows a more comprehensive analysis of IOP measurements done during an extended IOP monitoring period
15 of time.

These aims and other advantages are achieved by a system and a device comprising the features of the corresponding independent claim.

These aims and other advantages are achieved in particular by an intraocular pressure measuring and/or monitoring system, comprising an
20 intraocular pressure measuring device comprising a support and a pressure sensor united with the support, the support being configured for placing the pressure sensor in contact with an eye of a user for sensing the intraocular pressure (IOP) of the eye, a portable recording device configured for communicating with the intraocular pressure measuring device and for storing
25 data received from the intraocular pressure measuring device, wherein the system further comprises an inertial and/or environmental sensor.

The support is for example a contact lens or a support configured to be implanted in the eye.

In embodiments, the inertial and/or environmental sensor is located in
30 the intraocular pressure measuring device.

In other embodiments, the inertial and/or environmental sensor is located in the portable recording device.

The portable recording device for example comprises an antenna for wirelessly communicating with the intraocular pressure measuring device. The antenna is for example located in a patch adapted to surround the eye of a user when the intraocular pressure measuring and/or monitoring system is worn by the user. The inertial and/or environmental sensor is then for example located in the patch, or in a communication module forming an interface to the antenna, the communication module being adapted to be placed on a user's head when the intraocular pressure measuring and/or monitoring system is worn by the user.

In embodiments, the portable recording device is configured for communicating with the inertial and/or environmental sensor and for storing data received from the inertial and/or environmental sensor.

In embodiments, the intraocular pressure measuring and/or monitoring system comprises at least two inertial and/or environmental sensors. The at least two inertial and/or environmental sensors for example comprise a first and a second inertial sensor, the first inertial sensor being located in a housing of the portable recording device adapted to be worn against the chest of a user, and the second inertial sensor being located in a communication module adapted to be placed on a user's head when the intraocular pressure measuring and/or monitoring system is worn by the user.

These aims and other advantages are also achieved in particular by an intraocular pressure measuring device comprising a support and a pressure sensor united with the support, the support being configured for placing the pressure sensor in contact with an eye of a user for sensing the intraocular pressure (IOP) of the eye, wherein the device further comprises an inertial and/or environmental sensor.

The support is for example a contact lens or a support configured to be implanted in the eye.

With the inertial and/or environmental sensor, information is collected about movements, physical activity and/or the environment of the patient during the IOP measuring and/or monitoring period. The information obtained from the inertial and/or environmental sensor, which is attached to the user, preferably
5 close to the pressure sensor, during the IOP measuring and/or monitoring period, for example includes one or more parameters from the group comprising the physical activity of the patient, the intensity of the physical activity, the position of the patient, the ambient temperature, the local atmospheric pressure, the altitude, etc. The system and/or device of the invention thus allows
10 correlating information on IOP with information on patient activity and/or environment measured and/or monitored during the same period of time in order for example to analyse the effect of one or more of the measured inertial and/or environmental parameters on the IOP.

In embodiments, the intraocular pressure measuring and/or monitoring
15 system of the invention comprises an inertial sensor detecting and/or measuring the position and/or the movements of the user, for example accelerations or shocks to which the user may be submitted, the position of the user, in particular of the user's head in order to determine whether the user is standing, sitting or laying down, etc. The inertial sensor is for example a MEMS
20 comprising accelerometers and/or gyroscopes allowing the measurement of linear accelerations along three orthogonal directions and/or angular rates around three orthogonal rotation axis.

Using two inertial sensors, for example a first one located against or near the chest of a user, and a second one located on or near the head of the user
25 furthermore allows for example determining the relative position of the user's head and body.

In embodiments, the intraocular pressure measuring and/or monitoring system of the invention comprises an environmental sensor, for example a barometer, an altimeter, a GPS receiver and/or a thermometer, for recording
30 corresponding information about the environment of the patient wearing the intraocular pressure measuring and/or monitoring system.

In embodiments, the intraocular pressure measuring and/or monitoring system of the invention comprises one or more inertial sensors and one or more environmental sensors.

The present invention will be better understood with the help of the following description illustrated by the figures, where:

Fig. 1 shows an intraocular pressure measuring device according to an embodiment of the invention;

Fig. 2 is a schematic cut view of an eye wearing the intraocular pressure measuring device of Fig. 1;

Fig. 3 is a schematic cut view of an eye wearing an intraocular pressure measuring device according to another embodiment of the invention;

Fig. 4 is a schematic representation of an example of an intraocular pressure measuring and/or monitoring system of the invention;

Fig. 5 shows a user wearing an intraocular pressure measuring and/or monitoring system according to an embodiment of the invention.

In embodiments, the intraocular pressure measuring and/or monitoring system of the invention comprises an intraocular pressure measuring device to be placed on or in the eye of a patient for measuring the intraocular pressure of said eye, and a portable recording device for communicating with the intraocular pressure measuring device and storing information collected by the intraocular pressure measuring device during IOP monitoring phases.

In an embodiment illustrated in Fig. 1, the intraocular pressure measuring device 1 comprises a pressure sensor 2 united with a support in the form of a contact lens 3, for example a soft contact lens. The pressure sensor 2 is located such that, when the contact lens 3 is worn by a user, the pressure sensor 2 is applied against an eyeball of the user for sensing the intraocular pressure (IOP) of the corresponding eye.

Fig. 2 schematically illustrates an example of an IOP measuring device 1 having a support in the form of a contact lens, placed on an eye 8 of a patient or

user. According to the illustrated example, the user wears the IOP measuring device 1 just like a standard contact lens, wherein the contact lens is centered on the cornea 80. Other types of IOP measuring device having a support in the form of a contact lens are however possible within the frame of the invention, for
5 example IOP measuring devices wherein the support is designed to be placed on the sclera, for example under the eyelid, which is not represented in Fig. 2.

Alternatively, and with reference to Fig. 3, the intraocular pressure measuring device 1 is an implantable device, whereas the support is adapted to be implanted in the eye, for example between the cornea 80 and the iris 82, or
10 in any other appropriate location within a patient's eye 8. Implanting the implantable IOP measuring device 1 is an ambulatory surgical operation, which is usually performed by a medical doctor.

According to embodiments of the invention, and with reference to Fig. 1, the intraocular pressure measuring device 1 further comprises an inertial and/or
15 environmental sensor 9 for sensing for example the position, orientation and/or movements of the eye of the user when the user wears said device 1.

As explained below, according to other embodiments of the invention, the inertial and/or environmental sensor is located in other parts of the intraocular pressure measuring and/or monitoring system, for example in the
20 portable device.

The inertial and/or environmental sensor 9 is for example an inertial sensor comprising accelerometers and/or gyroscopes for detecting accelerations along three axis orthogonal to each other (three dimensional
accelerator) and/or angular rates around three rotation axis orthogonal to each
25 other (three dimensional gyroscope), thus allowing detecting and/or measuring the movements of a user wearing said inertial and/or environmental sensor 9.

In other embodiments the inertial and/or environmental sensor 9 is for example an inertial sensor comprising a position and/or orientation sensor for determining the position and/or the position of a user or at least a part of a user,

for example the head of a user, when said user wears said inertial and/or environmental sensor 9.

In still other embodiments the inertial and/or environmental sensor 9 is for example an environmental sensor comprising for example a barometer, a thermometer, an altimeter and/or a GPS receiver for measuring the ambient
5 atmospheric pressure, the ambient temperature and/or the temperature of the eye, the altitude and/or the geographic position of the intraocular pressure measuring and/or monitoring system of the invention.

In embodiments, the intraocular pressure measuring and/or monitoring
10 system of the invention comprises a plurality of inertial and/or environmental sensors, possibly located in different parts of the system, for example of the IOP measuring device and/or of the portable device, the location of each sensor depending for example on its size and/or on its power requirement and/or on its nature.

15 Due to size constraints, one or more inertial and/or environmental sensors are MEMS, in particular when said inertial and/or environmental sensor is located in the IOP measuring device to be worn on or in the eye.

In embodiments, as illustrated for example in Fig. 1, the intraocular pressure measuring device 1 further comprises, united with the contact lens 3, a
20 microcontroller 5 in electrical contact with the pressure sensor 2 and with the inertial and/or environmental sensor 9 for powering the sensors 2, 9 and/or for receiving electrical signals from the pressure sensor 2 that correspond to the measured pressure and/or for receiving electrical signals from the inertial and/or environmental sensor 9 that correspond to the measured inertial and/or
25 environmental parameters. The IOP measuring device 1 also comprises an antenna 4 in electrical contact with the microcontroller 5 for wirelessly transmitting data, for example data received from the sensors 2, 9, to a remote equipment, for example to the portable device of the system of the invention, which is not represented in Fig. 1.

In an embodiment, the intraocular pressure measuring device 1, in particular the microcontroller 5 and/or one or both sensors 2, 9, is preferably wirelessly inductively powered through the antenna 4, for example by the portable device. In a variant embodiment, the pressure measuring device
5 comprises a power source, for example a battery or micro fuel cell or a wireless energy source like infrared or solar cells, for powering the microcontroller and/or one or both sensors. The power source is for example located on or inside the support, or on an external device, in which case it is for example electrically
10 connected through thin and insulated electrical wires to the microcontroller and/or to the sensors.

The pressure sensor 2 is for example a miniaturized pressure sensor comprising a piezoresistive silicon micromachined pressure sensor on a ceramic or silicon carrier. Other types of pressure sensors are however possible within the frame of the invention, for example strain gage pressure sensors that
15 comprises thin resistance elements that are elongated or retracted under the effect of the IOP, or any other adapted pressure sensor. The choice of the most appropriate pressure sensor will depend for example on the nature and size of the support, on the location of the IOP measuring device when worn by a user, on the desired measurement accuracy, etc.

20 In variant embodiments, the pressure sensor and the inertial and/or environmental sensor are manufactured as a single device, for example a single MEMS performing both functions.

With reference to Fig. 1, measuring the pressure sensed by the pressure sensor 2 is for example performed in that the microcontroller 5 powers the
25 pressure sensor 2 with a given voltage and receives in return from the pressure sensor 2 an electrical signal that corresponds to the sensed pressure, for example an electrical signal whose magnitude depends from the electrical resistance of the circuit formed by the piezo-resistors. The received signal is stored and/or processed for example in the microcontroller 5 for determining the
30 measured pressure. The pressure measurement is for example performed at regular intervals, for example each time the intraocular pressure measuring

and/or monitoring device 1 is inductively powered by an external device, for example an external RFID reader or similar. In variant embodiments, the pressure measurement is performed for example continuously or at randomly spaced intervals.

5 In embodiments, for example in embodiments wherein the inertial and/or environmental sensor 9 is located within the pressure measuring device 1, the inertial and/or environmental sensor 9 is powered simultaneously with the pressure sensor 2 and the measurement of the inertial and/or environmental parameters is performed similarly as described above in relation with the
10 intraocular pressure measurement.

 In other embodiments, for example in embodiments wherein the inertial and/or environmental sensor is located in other locations of the IOP measuring and/or monitoring system of the invention, for example in the portable device, the measurement of the inertial and/or environmental parameters is performed
15 continuously or at any other appropriate frequency. The inertial and/or environmental sensor is for example continuously powered from an electrical source, for example batteries or accumulators, located in the portable device.

 With reference to Fig. 1, the contact lens 3 is for example a soft contact lens made of a transparent hydrogel containing water in a concentration greater
20 than 10%, or of any other appropriate material having similar mechanical and/or optical properties, for example a flexible polysiloxane, a silicone elastomer, a pure soft silicone containing water in a concentration less than 0.5% or silicone-hydrogel. The contact lens 3 has a typical diameter of 14.1 mm and a typical radius of curvature between 8.4 and 9mm and is for example softer than the
25 surface of the eyeball of a user, such that when the pressure measuring and/or monitoring device 1 is worn by a user, the contact lens 3 is slightly deformed, for example stretched, to adapt its shape to the shape of the eyeball, in particular to the curvature of the user's eye. This deformation of the contact lens 3 provides for a regular contact and a strong adherence between the contact
30 lens 3 and the user's eyeball across the surface of the contact lens which

adapts to the shape of the eye, thus providing for a close and constant contact between the pressure sensor 2 placed within this area and the eyeball.

Optionally, the pressure measuring device 1 further comprises additional and/or other measuring devices such as for example an ElectroRetinoGraph, a
5 chemical analysis sensor and/or a second pressure sensor of the same or of another type as the first one.

Fig. 4 is a schematic representation of an intraocular pressure measuring and/or monitoring system according to an embodiment of the invention. According to the illustrated embodiment, the intraocular pressure measuring
10 and/or monitoring system comprises an intraocular pressure measuring device 1, for example an intraocular pressure measuring device 1 with a support in the form of a contact lens, and a portable recording device 6 for communicating with the pressure measuring device 1 and storing the information collected during the IOP monitoring phases.

15 The portable recording device 6 comprises a first communication interface for communicating with the pressure measuring device 1. The first communication interface is for example a wireless communication interface comprising an antenna 60, for example a loop antenna, which is advantageously placed near the pressure measuring device 1 when the
20 pressure measuring device 1 is worn by a user.

The portable recording device 6 comprises a second communication interface 16 for communicating with a remote computing device 7, for example a personal computer, for storing, analyzing, computing and/or displaying the data collected and stored by the portable communication device 6.

25 When monitoring IOP, the user wears the pressure measuring and/or monitoring system of the invention as showed by way of an illustrative but in no way limiting example in Fig. 5. Accordingly, the user 100 wears the intraocular pressure measuring device 1 on or in an eye 8 and carries the portable recording device 6, for example in a pocket 62 hanging from his or her neck and
30 for example secured with straps on his or her chest. Any other adapted solution

is however possible within the frame of the invention for the user 100 to carry the portable device 6, preferably without significantly impacting his comfort.

The antenna 60 is preferably placed as close as possible to the user's eye 8 wearing the pressure measuring device 1 in order to allow the
5 establishment of the first wireless communication channel between the pressure measuring device 1 and the recording device 6. Preferably, the antenna 60 is furthermore oriented in a plane as parallel as possible to the plane of the antenna of the pressure measuring device 1 in order to allow for an efficient
10 powering of the microprocessor, of the pressure sensor and/or of the inertial and/or environmental sensor over the first communication channel, which is for example a close distance inductive communication channel. The antenna 60 is for example integrated into a patch 600 surrounding the eye 8, for example into a disposable, flexible and hypoallergenic patch, which is worn by the user during the IOP monitoring periods.

15 Alternatively, the antenna of the portable device is for example integrated into eyeglasses and/or in a cap or another piece of clothing or accessory worn by the user during IOP monitoring periods. Other means are however possible within the frame of the invention for placing the antenna of the portable device at a suitable distance from the pressure measuring device when the latter is
20 worn by a user.

Preferably, the antenna 60 of the portable device 6 is centered with the antenna of the pressure measuring device 1 when the pressure measuring device 1 and the portable recording device 6 are both worn by the user 100. The diameter of the antenna 60 of the portable recording device 6 is preferably
25 larger than the diameter of the pressure measuring device 1. The shape of the antenna 60 of the portable recording device 6 is for example round, oval, rectangular, or any other appropriate shape. The shape of the antenna 60 of the portable recording device 6 is preferably adapted to the shape of the element, for example the patch 600, the eyeglasses, the piece of garment, etc., to which
30 it is attached.

In embodiments, the inertial and/or environmental sensor, which is not represented in Fig. 5, is comprised in the intraocular pressure measuring device 1, for example attached to the contact lens or to the implantable support of the IOP measuring device 1. An advantage of locating the inertial and/or
5 environmental sensor in the intraocular pressure measuring device 1 is that the inertial and/or environmental sensor is located directly on or inside the eye 8 and close to the pressure sensor of the pressure measuring device 1 that senses the IOP. The inertial and/or environmental sensor is thus subjected to the same inertial conditions as the eye 8 of the patient 100 and/or to the same
10 environmental conditions as the pressure sensor of the IOP measuring device 1. Accordingly, the inertial and/or environmental parameters measured by the inertial and/or environmental sensor correspond directly to the ones that may have an influence on the measured IOP.

In other embodiments, the inertial and/or environmental sensor is
15 comprised in the portable device 6. Locating the inertial and/or environmental sensor in the portable device 6 allows the use of a sensor larger than a sensor to be embedded in the intraocular pressure device 1. When located in the portable device 6, the inertial and/or environmental sensor is preferably powered over a wired link from the source of electric energy of the portable
20 device 6.

The inertial and/or environmental sensor is for example located near the antenna 60 of the portable device 6, for example in the patch 600, in spectacles carrying the antenna, or a in a communication module 61 forming an interface to the antenna 60 and located on the user's head when the user wears the
25 system of the invention. An advantage of locating the inertial and/or environmental sensor on the head of the user 100 when the user wears the system of the invention is that the inertial and/or environmental sensor is subjected to inertial and/or environmental conditions that are identical or very similar to the ones to which the IOP pressure sensor and the monitored eye are
30 subjected.

Alternatively, the inertial and/or environmental sensor is located in a housing of portable device 6 that is worn for example in a pocket 62 located for example on the chest of the user 100 when the user wears the system of the invention, or in any other appropriate part of the portable device 6, depending
5 for example on the nature of the measurement or measurements to be performed by the inertial and/or environmental sensor. This location of the inertial and/or environmental sensor allows the use of even larger and/or more sophisticated sensors with possibly higher power consumption.

In still other embodiments, the intraocular pressure measuring and/or
10 monitoring system of the invention comprises at least two inertial and/or environmental sensors that are located in different parts of the system and/or of the portable device 6.

According to embodiments, while monitoring IOP, the portable recording device 6 powers the pressure measuring device 1 through the first
15 communication channel at for example regularly spaced time intervals and collects data sent by the microprocessor through the antenna of the pressure measuring device 1. Collected data for example comprises electrical signals from the pressure sensor and/or an IOP value calculated by a microprocessor of the pressure measuring device 1. In embodiments, collected data also
20 comprises electrical signals from the inertial and/or environmental sensor and/or values of one or more inertial and/or environmental parameters, calculated by a microprocessor of the pressure measuring device 1. The collected data is stored in internal memory of the portable recording device 6. The intraocular pressure and/or one or more inertial and/or environmental parameters, are for
25 example measured at a frequency of 10 to 20 Hz during 10 to 60 seconds every 5 to 10 minutes. This allows a precise monitoring of the IOP variations over extended periods of time, including at night, while the user is asleep.

Preferably, the measurement frequency of the one or more inertial and/or environmental parameters is the same as the measurement frequency of the
30 IOP, and the measurements are even more preferably simultaneous or almost simultaneous. However, according to embodiments of the invention, the

measurement scheme of the one or more inertial and/or environmental parameters is different from the measurement scheme of the intraocular pressure. This is for example the case when the inertial and/or environmental sensor is located in the portable device 6 and is continuously powered, whereas
5 the measurement is for example performed continuously. Other measurement schemes are however possible within the frame of the invention.

At some preferably predefined moments in time, for example once a day, once a week or once a month, the user and/or a practitioner connects the portable recording device 6 to the remote computing device, for example a
10 personal computer, over a second, preferably wireless, communication channel, for example a Bluetooth communication channel. The second communication channel can however also be a wired communication channel, for example a USB or any other appropriate communication channel. The data collected and stored in the internal memory of the portable recording device 6 is then
15 transferred over the second communication channel to the computing device for further analysis and/or computing by the user and/or by the practitioner.

The IOP measurements are correlated, for example by the computing device 7, with the inertial and/or environmental measurements, for example by displaying all measurements in a single graph having the same time baseline,
20 or any other appropriate representation. IOP variation analysis can then be performed and, for example at least partly automatically, correlated with the simultaneous variations of the measured inertial and/or environmental parameters, in order for example for a practitioner to analyze the effects of these parameters on the IOP.

25 In variant embodiments, the intraocular pressure measuring and/or monitoring system of the invention comprises two pressure measuring devices in order to allow simultaneously monitoring both eyes of a patient, for example over extended periods of time. Preferably, both pressure measuring devices simultaneously and/or alternately communicate with the same portable
30 recording device 6 that for example is connected to and/or comprises two

antennas. Accordingly, the portable recording device preferably stores or records data received from both intraocular pressure measuring devices.

Claims

1. Intraocular pressure measuring and/or monitoring system, comprising:

5 - an intraocular pressure measuring device (1) comprising a support (3) and a pressure sensor (2) united with said support (3), said support (3) being configured for placing said pressure sensor (2) in contact with an eye (8) of a user for sensing the intraocular pressure (IOP) of said eye (8),

10 - a portable recording device (6) configured for communicating with said intraocular pressure measuring device (1) and for storing data received from said intraocular pressure measuring device (1);

 characterized in that said system further comprises an inertial and/or environmental sensor (9).

15 2. Intraocular pressure measuring and/or monitoring system according to the preceding claim, wherein said support is a contact lens (3).

 3. Intraocular pressure measuring and/or monitoring system according to claim 1, wherein said support is configured to be implanted in said eye (8).

20 4. Intraocular pressure measuring and/or monitoring system according to any one of the preceding claims, wherein said inertial and/or environmental sensor (9) is located in said intraocular pressure measuring device (1).

25 5. Intraocular pressure measuring and/or monitoring system according to any one of claims 1 to 3, wherein said inertial and/or environmental sensor (9) is located in said portable recording device (6).

 6. Intraocular pressure measuring and/or monitoring system according to any one of claims 1 to 3, wherein said portable recording

device (6) comprises an antenna (60) for wirelessly communicating with said intraocular pressure measuring device (1).

7. Intraocular pressure measuring and/or monitoring system according to the preceding claim, wherein said antenna (60) is located in a patch (600) adapted to surround the eye (8) of a user when said intraocular pressure measuring and/or monitoring system is worn by said user.

8. Intraocular pressure measuring and/or monitoring system according to the preceding claim, wherein said inertial and/or environmental sensor (9) is located in said patch (600).

9. Intraocular pressure measuring and/or monitoring system according to any one of claims 6 or 7, wherein said inertial and/or environmental sensor (9) is located in a communication module (61) forming an interface to said antenna (60), said communication module (61) being adapted to be placed on a user's head when said intraocular pressure measuring and/or monitoring system is worn by said user.

10. Intraocular pressure measuring and/or monitoring system according to any one of the preceding claims, wherein said portable recording device (6) is configured for communicating with said inertial and/or environmental sensor (9) and for storing data received from said inertial and/or environmental sensor (9).

11. Intraocular pressure measuring and/or monitoring system according to any one of the preceding claims, comprising at least two inertial and/or environmental sensors.

12. Intraocular pressure measuring and/or monitoring system according to the preceding claim, wherein said at least two inertial and/or environmental sensors comprise a first and a second inertial sensor, said first inertial sensor being located in a housing of said portable recording device (6) adapted to be worn against the chest of a user, and said second

inertial sensor being located in a communication module (61) adapted to be placed on a user's head when said intraocular pressure measuring and/or monitoring system is worn by said user.

5 13. Intraocular pressure measuring device (1) comprising a support (3) and a pressure sensor (2) united with said support (3), said support (3) being configured for placing said pressure sensor (2) in contact with an eye (8) of a user for sensing the intraocular pressure (IOP) of said eye (8),
characterized in that said device further comprises an inertial and/or environmental sensor (9).

10 14. Intraocular pressure measuring device (1) according to the preceding claim, wherein said support is a contact lens (3).

 15. Intraocular pressure measuring device (1) according to claim 13, wherein said support is configured to be implanted in said eye (8).