



159159

- 1 -



G00002

Glasses

The invention relates to a pair of glasses, comprising at least one sight piece and two ear pieces which are foldable in relation to the sight piece or
5 a frame allocated to the sight piece about a substantially horizontal pivoting axis by approximately 180° towards the inside of the sight piece.

Glasses of the generic type are known from EP 02 708 295, FR-A-
2 751 431 or GB 2 168 499 A1. US 5 457 505 and US 6 332 681 describe
10 conventional glasses with inclination arrangements.

In most glasses the ear pieces are attached by pivot joints of a vertical pivoting axis, with the ear pieces, for safekeeping, folding inwards about this vertical pivoting axis.
15

The above documents teach solutions that proceed from a horizontal pivoting axis in particular for glasses with a single continuous sight piece which is comparatively strongly curved, extending over a large angular area. In these cases the ear pieces regularly possess a curvature which approxi-
20 mately corresponds to that of the sight piece so that the ear pieces, when folding inwards, conform to the curve of the sight piece.

A serious drawback of prior art constructions resides in that the angular position of the ear pieces in relation to the sight piece may be misaligned
25 inadvertently or is not adjustable at all.

It is an object of the invention to embody a pair of glasses of the type mentioned at the outset for improved conveniences of wearing.

According to the invention, this object is attained by an inclination arrangement being provided by which, when the glasses are used, to adjust the angular position of the ear pieces in relation to the sight piece for a stable stop position, with the inclination arrangement being comprised of an array of ribs and grooves that is concentric of the pivoting axis of each ear
5 piece and a locking projection that cooperates therewith, the locking projection being disposed on the bottom side of a top frame member which stands out inwards at least by sections.

10 In this way, any user will be able to regulate the inclination of the ear pieces in relation to the sight piece for convenience of wearing, any inadvertent pivoting of the ear pieces relative to the sight piece being simultaneously precluded. This is accompanied with simplicity of construction, which can be put into practice at a low cost, nevertheless being aesthetically attractive. Outside the angular area spanned by the array of ribs and
15 grooves, the locking projection does not snap-engage.

The array of ribs and grooves covers an angle of up to 45° , which is the standard area of ear-piece inclination adjustment, with the ear pieces, if
20 pivoted beyond this angle, being able to fold inwards again without any resistance.

Details of the invention will become apparent from the ensuing description of a preferred embodiment, taken in conjunction with the drawing, in
25 which

Fig. 1 is a perspective view of a pair of glasses according to the invention; and

Fig. 2 is an illustration, on an enlarged scale, of the inclination arrangement.

A pair of glasses 1 seen in the drawing comprises two ear pieces 2 which
5 are mounted on a top frame member 4 that holds a sight piece 3, the ear
pieces 2 folding inwards about a substantially horizontal pivoting axis 5 by
180° in the direction of the arrow P so that the ear pieces 2, when folded
inwards, substantially conform to the curvature of the sight piece 3. In the
exemplary embodiment, the pivoting axes 5 are located in the vicinity of
10 enlargements 6 on the outer ends of the top frame member 4.

On their top surface the inner ends 7 of the ear pieces 2 comprise a plurality of ribs 8 with a groove 9 forming between every two of these ribs 8.

15 In the vicinity of the top edge of the top frame member 4 a locking projection 10 extends downwards, cooperating with the grooves 9 in such a way
that when the ear piece 2 is pivoted, the locking projection 10 snap-engages
successively with the grooves 9, it being possible in this way to adjust a
certain angular position of the ear pieces 2 in relation to the top frame
20 member 4 and thus to the sight piece 3.

The locking projection 10 is free on both sides, i.e. recesses are provided
where it passes into the top frame member 4, this improving the properties
of flexibility and locking engagement.

25

Opposite the grooves 9, provision is made for another groove 11, with
which to snap-engage the locking projection 10 when the ear pieces are
pivoted completely inwards so that they are arrested in this position.

Claims

1. A pair of glasses comprising at least a sight piece and two ear pieces which are foldable in relation to the sight piece or a frame allocated to the sight piece about a substantially horizontal pivoting axis by approximately 180° towards the inside of the sight piece, wherein an inclination arrangement (8, 9, 10) is provided by which, upon use, to adjust the angular position of the ear pieces (2) in relation to the sight piece (3) for a stable stop position.
5
- 10 2. A pair of glasses according to claim 1, wherein the inclination arrangement (8, 9, 10) is comprised of an array of ribs (8) and grooves (9) and a locking projection (10) cooperating therewith.
- 15 3. A pair of glasses according to claim 1, wherein the locking projection (10) is disposed on a top frame member (4).
4. A pair of glasses according to claim 2, wherein the array of ribs (8) and grooves (9) is formed on the top surface of each ear piece (2).
20
5. A pair of glasses according to claim 4, wherein the array of ribs (8) and grooves (9) covers an angle at circumference of up to 45°.