TUBING HANGER

The present disclosure claims benefit of U.S. Provisional Patent Application No. 61/090,462, filed Aug. 20, 2008, and U.S. Provisional Patent Application No. 61/090,000, filed Aug. 19, 2008, both of which applications are hereby incorporated by reference in their entirety.

BACKGROUND

The present disclosure relates generally to a tubing hanger for use with a subsea wellhead, and in particular, a mechanism for positioning and locking a tubing hanger into a subsea wellhead.

Tubing hangers are employed in subsea wellheads used in, for example, oil and gas wells. The tubing hanger supports the tubing, or "string", which extends down into the production zone of the well. The process of installing a tubing hanger into a wellhead generally involves positioning the tubing hanger on a landing seat in the wellhead using, for example, a running tool attached to the tubing hanger.

Movement of the tubing hanger inside the wellhead after installation is a known problem. Tubing hanger movement can be caused by, for example, torsional force applied to the tubing hanger due to thermal expansion and contraction of the tubing string. Excessive movement can change the orientation of the tubing hanger with respect to the wellhead, making it difficult to reinstall the running tool during subsequent operations or to subsequently install the subsea tree on the wellhead. Movement of the tubing hanger can also cause premature failure of the sealing system between the tubing hanger body and the wellhead housing, and the seals at the hydraulic and electric connectors between the tubing hanger and the subsea Christmas tree.

Various mechanisms for securing tubing hangers in wellheads have been devised in order to reduce movement of the tubing hanger in the wellhead. For example, locking mechanisms are often employed to lock the tubing hanger into place in the wellhead. In addition, means for preloading the tubing hanger in order to reduce undesirable axial and rotational movement of the tubing hanger have also been devised.

However, providing the desired preloading of the locked tubing hanger can be difficult to achieve when the landing seat of the tubing hanger inside the wellhead has uncertain axial position. The uncertainty of the axial position can be due, at least in part, to tolerance accumulations caused by the stacking of many components in the wellhead and debris that can accumulate on the landing seat during drilling operations.

To account for this uncertainty in axial seating position, tubing hanger designs have employed adaptive mechanisms in order to accommodate large dimensional variations and still achieve preloading. One typical form of this type of mechanism employs a locking ring with tapered inner surface, being pushed into the receptive profiles by applying a measured force to wedge a locking sleeve behind the locking ring. Because this type of locking ring relies on the friction between the tapered surfaces of the locking ring and the locking sleeve to maintain the locking ring in a preloaded locking state, it is necessary to employ additional locking (or anti-backoff) to prevent the loss of preload from the movements of the locking sleeve under vibration and other disturbance over long term field service. Moreover, the final axial position of the locking sleeve has large variation because the small taper angle used for maintaining the frictional self lock amplifies the manufacturing tolerance in diametric dimensions of the relevant components. Thus implementation of anti-backoff of the locking sleeve is often adaptive in nature

and sometimes depending on friction itself. One example of a design that employs a lockdown mechanism with an actuating mandrel that includes an anti-backoff mechanism is disclosed in U.S. Pat. No. 6,516,875.

One design for a tubing hanger with a preloaded lockdown mechanism is disclosed in U.S. Pat. No. 5,145,006, issued to David R. June. In the June patent design, the tubing hanger is locked into place and then a torque ring is rotated to preload the locking mechanism. However, this design requires a tool, such as a mechanical torque tool, that can be run to the subsea wellhead to rotate the torque ring to its preloaded position. Further, the torque applied to provide the desired preload using the June patent design can be problematic. In deep water well completions, for example, applying torque at the top side over a long running string can be undesirable.

Other tubing hanger designs achieve preloaded locking with non-adaptive components, such as a locking ring with a non-tapered, cylindrical inner surface. Once the locking sleeve is forced into an axial position behind the locking ring, the preload is entirely determined by the deflections of the components within the load path that have controlled dimensional interferences and that are insensitive to the axial position of the locking sleeve. In one previous design, where a tubing hanger with such a locking mechanism was landed onto a shoulder with large axial position variation, a pre-installation measurement trip had to be made for each installation to determine the position of each landing shoulder so that the tubing hanger could be adjusted before installation to obtain the required dimensional interference. Such measurement trips not only add operational cost, which is significant in deep water application, but also introduce additional uncertainty.

Improved designs for locking a tubing hanger into a wellhead with preload would be a welcome addition in the art. The present disclosure is directed to overcoming, or at least reducing the effects of, one or more of the issues set forth above.

SUMMARY

An embodiment of the present disclosure is directed to a tubing hanger for use in a wellhead. The wellhead includes a throughbore, a landing seat positioned in the throughbore, a landing groove positioned above the landing seat in the throughbore, and a locking groove in the throughbore. The tubing hanger comprises an expandable landing ring positioned on the tubing hanger for engaging the landing groove and a landing mechanism for expanding the landing ring radially outward from the tubing hanger. A locking ring for engaging the locking groove can be positioned on the tubing hanger. The tubing hanger can further include a locking mechanism for expanding the locking ring radially outward from the tubing hanger body and locking it into the locking groove.

Another embodiment of the present disclosure is directed to a method for locking a tubing hanger in a wellhead. The wellhead includes a throughbore, a landing seat positioned in the throughbore, a landing groove positioned above the landing seat in the throughbore, and a locking groove positioned in the throughbore. The method comprises expanding a landing ring positioned on the tubing hanger to engage the landing groove. A locking ring can be expanded to engage the locking groove, the locking ring being positioned on the tubing hanger. The locking ring is expanded after the expanding of the landing ring.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** illustrates the presented tubing hanger in locked state and supported by the integral expandable landing ring, according to an embodiment of the present disclosure.

FIGS. **2** to **5** illustrate the operation of a landing mechanism as the tubing hanger is landed in the well, according to an embodiment of the present disclosure.

FIG. **6** illustrates a cross-sectional view of a landing ring, according to an embodiment of the present disclosure.

While the concepts of the present disclosure are susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described in detail herein. However, it should be understood that the present disclosure is not intended to be limited to the particular forms disclosed. Rather, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

FIG. **1** illustrates a subsea tubing hanger **100** positioned in a wellhead **102**. A tubing hanger running tool **104** engaging the tubing hanger **100** is also shown. As is well known in the art, the tubing hanger running tool **104** can be used to lower the tubing hanger **100** into position in the wellhead **102**.

The wellhead **102** includes a throughbore **106** defined by a wellhead housing wall **108**. A landing seat **110** is positioned in throughbore **106** and can be any top profile of installed equipment below the tubing hanger, usually with large axial positional variation. In an embodiment, the landing seat **110** can be a casing hanger packoff, which may act to seal the wellhead housing wall **108** and the casing hanger. In other embodiments, the landing seat may be another piece of equipment that does not act as a seal, such as other equipment installed before the tubing hanger **100**.

A landing groove **114** can be positioned above the landing seat **110** in the throughbore **106** for receiving a landing ring **116**. A locking groove **118** can be positioned above the landing groove **114** in the throughbore **106**. Landing groove **114** and locking groove **118** can be formed in throughbore **106** by any suitable method, such as by machining the grooves in the surface of wellhead housing wall **108** that forms the outer perimeter of throughbore **106**.

Tubing hanger **100** can include a tubing hanger body **214**. Tubing hanger body **214** can include one or more fluid passages therein (not shown), as is well known in the art. In an embodiment, tubing hanger **100** can also include one or more annulus fluid passages **124** positioned around the tubing hanger production bore **122**.

As discussed above, an expandable landing ring **116** is positioned on the tubing hanger **100** for engaging the landing groove **114**. As more clearly illustrated in FIGS. **2** and **3**, expandable landing ring **116** can be configured to work in conjunction with a landing mechanism **200** for expanding the landing ring **116** radially outward from the tubing hanger body **214**.

The landing mechanism **200** can be positioned to engage the landing seat **110** during installation of the tubing hanger **100** into the wellhead. As illustrated in FIG. **2**, the expandable landing ring **116** can be retracted inside of the hanger profile during the installation run. The landing mechanism **200** can be configured so that a downward force of the landing mechanism **200** on the landing seat **110** during the installation is capable of expanding the landing ring **116** into the landing groove **114**.

The embodiment of the landing mechanism illustrated in FIGS. **2** to **5** is similar to that of FIG. **1**, except that landing ring **116**, landing ring actuator **202** and lower load ring **204** have slightly simplified designs. However, the landing mechanisms illustrated in both FIG. **1** and FIGS. **2** to **5** func-

tion in a similar manner and the discussion of FIGS. **2** to **5** applies to the design of FIG. **1**.

In an embodiment according to FIG. **2**, the landing mechanism **200** can include a landing ring actuator **202** and a lower load ring **204**. The landing ring actuator **202** can be positioned below the expandable landing ring **116**, so as to make first contact with the landing seat **110** during the tubing hanger installation run. As shown in FIGS. **2** and **3**, once the landing ring actuator **202** engages the landing seat **110**, the continued downward movement of the tubing hanger will create reaction forces at the tapered surfaces **206**,**209** of landing ring **116** as it contacts landing ring actuator **202** and lower load ring **204**. The resultant forces can expand landing ring **116** radially outward to make initial contact with landing groove **114** (FIG. **4**). At this position, landing ring **116** contacts lower load ring **204** at a tapered surface **211** that is angled more steeply relative to the axial downward motion of lower load ring **204** than is the tapered surface **209**. This is illustrated in FIG. **6**, which shows an arrow "D" that represents the direction of movement of the tubing hanger into the well. As shown in FIG. **6**, the angle, θ_1, between the surface **211** and the arrow D, is smaller than the angle, θ_2, between the surface **209** and the arrow D. In an embodiment, the line representing surface **217** in FIG. **6** is substantially parallel to the line of motion represented by arrow D, so that θ_1 and θ_2 also indicate the angle between surface **217** and surfaces **211** and **209**, respectively.

The resultant force from landing ring **116** contacting landing groove **114** and lower load ring **204** can enable landing ring **116** to expand along the lower tapered surfaces **114**A, **114**B of landing groove **114** upward, thereby separating landing ring **116** from landing ring actuator **202**. This separation is illustrated by the space **223** shown in FIG. **5**. In other embodiments, separation of the landing ring **116** form the landing ring actuator **202** may not occur.

Surface **217** of landing ring **116** and surface **219** of load ring **204** are shaped so that continued travel of the tubing hanger into the well will not significantly change the lateral position of landing ring **116**. For example, in the illustrated embodiment, surface **217** and surface **219** are both cylindrically shaped without a taper relative to the axial movement of load ring **204**, so that little or no lateral force is applied to landing ring **116** as the load ring **204** continues moving into the well. The tubing hanger can be stopped when the load bearing surface **221** of lower load ring **204** makes contact with landing ring **116**, resulting in the tubing hanger being fully supported by landing ring **116**, as shown in FIG. **5**. Thus the final position of landing ring **116**, and hence the position of the tubing hanger, can be entirely defined by landing groove **114** and lower load ring **204**, and does not necessarily depend on the precise location of landing seat **110** on which landing ring actuator **202** rests. Therefore the positional variation of landing seat **110** does not affect the position of the tubing hanger.

In FIGS. **2** to **5** the radial expansion of landing ring **116** is energized in three stages. To avoid the premature radial expansion of landing ring **116** before reaching the intended landing position, the top of landing ring **116** initially contacts lower load ring **204** at a small flat face **213** (shown more clearly in FIG. **6**) that is substantially perpendicular to the axial movement of lower load ring **204** into the well, so that accidental contact of landing ring **116** against the outside wall during downward trip will not likely produce an expansion force from lower load ring **204** onto landing ring **116** (FIG. **2**).

The initial expansion of landing ring **116** can therefore result from landing ring actuator **202** reaching a stop (such as making contact with preinstalled landing seat **110**) so that the

tapered contact between landing ring **116** and landing ring actuator **202** creates a resultant radial expansion force for landing ring **116**. Due to the initial radial expansion, the tapered surface **211** of landing ring **116** contacts lower load ring **204** and a surface **215** of landing ring **116** contacts landing ring actuator **202**, thereby producing the resultant expansion force in the second stage until the landing ring **116** makes contact with landing groove **114** (See FIG. **3** and FIG. **4**). The third stage of expansion is produced by the resultant force from landing ring **116** reacting with landing groove **114** and with lower load ring **204**, resulting in landing ring **116** more fully engaging landing groove **114** (FIG. **5**).

Various other designs of the landing mechanism are contemplated. For example, in an embodiment of FIG. **2**, the lower load ring **204** is a separate and discrete component of the tubing hanger **100**. In another embodiment (FIG. **4**), lower load ring **204** can be integrally connected with tubing hanger body **214**.

Referring again to FIG. **1**, and as discussed above, a locking ring **120** for engaging the locking groove **118** and thereby locking tubing hanger **100** into place can be positioned on the tubing hanger **100** above the landing ring **116**. The locking ring **120** can have any suitable shape that will function to hold tubing hanger **100** in position within a desired preload. The landing ring **116** described above allows the locking ring **120** to have a deterministic geometry, such as illustrated embodiment of lock ring **116** with cylindrical back, which can be used when the tubing hanger does not necessarily depend on pre-installed equipment for landing support. In an embodiment, the preload can be substantially or entirely determined by the elastic deformation of the locking ring and the components surrounding the locking ring without employing friction dependant mechanisms, such as tapered or threaded components, to preload the tubing hanger.

The locking ring can be made of any suitable material that will provide the desired support, and one of ordinary skill in the art would readily be capable of choosing suitable materials. Examples of suitable materials include metals, such as INCONEL 718, which is commercially available from Alloy Wire International LDT, a company located in the U.K. Other examples of suitable materials are well known in the art.

Referring back to FIG. **1**, a locking mechanism **126** can be employed for expanding the locking ring **120** radially outward from the tubing hanger body **214** and locking it into the locking groove **118**. Any suitable locking mechanism can be employed. In an embodiment of FIG. **1**, locking mechanism **126** includes a sleeve that can be coupled to a control mechanism **128** of tubing hanger running tool **104**. Using the control mechanism **128**, the locking ring **120** can be actuated to engage the locking groove **118** at any suitable time.

The locking mechanism **126** can be mechanically independent of the landing mechanism **200**. For example, the landing mechanism **200** is capable of expanding the landing ring **116** by employing the downward force of the tubing hanger **100** during installation without actuation by the running tool **104**. After the landing ring **116** has been expanded into the landing groove **114**, the locking mechanism **126** is capable of direct actuation via the controls of running tool **104** to expand the locking ring **120** into the locking groove **118**. In an embodiment, the landing mechanism **200** is not capable of direct actuation via the running tool **104** controls to expand the landing ring **116**.

A potential benefit of this system is the ability to lock the tubing hanger without significant friction forces on the locking ring **120**. This is because the landing ring **116** can support

the weight of the tubing hanger, in the manner discussed above, during the engagement of the locking ring **120** with the locking groove **118**.

The tubing hangers of the present application can be operated by any suitable method that provides the desired preloading and locking. The method can include expanding a landing ring positioned on the tubing hanger to engage a landing groove. The landing ring can be expanded by any suitable method.

In an embodiment, the method can be carried out using the apparatus in the embodiment of FIG. **1**, as described above, wherein expanding the landing ring **116** can comprise running the tubing hanger **100** downward into the wellhead **102** so that a landing mechanism **200** positioned on the tubing hanger **100** is forced against the landing seat **110**, the downward force of the landing mechanism **200** against the landing seat **110** causing the landing mechanism **200** to expand the landing ring **116** without further actuation by the running tool. After expanding the landing ring **116** to fix the axial position of tubing hanger **100** in wellhead **102**, a locking ring **120** can be expanded to engage the locking groove **118**. In an embodiment, the locking ring **120** can be positioned on the tubing hanger **100** above the landing ring **116**. In alternative embodiments, the locking ring can be placed in any other suitable position, including in positions below the landing ring **116**.

In the above described embodiments, the landing ring and locking ring are illustrated as comprising a single integral component. However, in an alternative embodiment, both a landing ring and a locking ring can be replaced by segmented components with similar cross sections.

In an alternative embodiment, both a landing ring and a locking ring can be expanded using, for example, running tool or some other apparatus that can control the expansion of the landing and locking rings. Thus, the landing and locking rings can be actuated by any suitable methods that allow the tubing hanger to be accurately positioned in the wellhead prior to locking, so that locking of the tubing hanger can provide the desired preloading. Given the teachings of the present application, one of ordinary skill in the art would readily be able to make and use tubing hangers for implementing such methods.

Although various embodiments have been shown and described, the present disclosure is not so limited and will be understood to include all such modifications and variations as would be apparent to one skilled in the art.

What is claimed is:

1. A tubing hanger for use in a wellhead, the wellhead including a throughbore, a landing seat positioned in the throughbore, a landing groove positioned above the landing seat in the throughbore, and a locking groove in the throughbore, the tubing hanger comprising:

an expandable landing ring positioned on the tubing hanger for engaging the landing groove;

a landing mechanism for expanding the landing ring radially outward from the tubing hanger;

a locking ring for engaging the locking groove, the locking ring being positioned on the tubing hanger;

a locking mechanism for expanding the locking ring radially outward from the tubing hanger body and locking it into the locking groove; and

wherein the landing mechanism is positioned to engage the landing seat during installation of the tubing hanger into the wellhead, the landing mechanism being configured so that a downward force of the landing mechanism on the landing seat during the installation is capable of expanding the landing ring into the landing groove.

2. The tubing hanger of claim **1**, wherein the landing mechanism comprises a landing ring actuator positioned between the expandable landing ring and the landing seat, the landing ring actuator being configured to engage the landing seat in a manner that provides radial expansion of the landing ring by a first distance.

3. The tubing hanger of claim **2**, wherein the landing mechanism further comprises a lower load ring positioned above the expandable landing ring, the lower load ring being configured to engage the landing ring and provide additional radial expansion of the landing ring by a second distance so that the landing ring fully engages the landing groove.

4. The tubing hanger of claim **1**, wherein the landing ring and the locking ring comprise segmented components.

5. The tubing hanger of claim **1**, wherein the locking ring engaged in the locking groove provides a desired preload to the tubing hanger.

6. The tubing hanger of claim **5**, wherein the preload is determined by the elastic deformation of the locking ring and the components surrounding the locking ring without employing an additional friction dependent preloading mechanism chosen from a tapered feature and a threaded feature.

7. The tubing hanger of claim **1**, wherein the landing groove is positioned a first distance from the landing seat and the locking groove is positioned a second distance from the landing seat, the second distance being greater than the first distance.

8. A method for locking a tubing hanger in a wellhead, the wellhead including a throughbore, a landing seat positioned in the throughbore, a landing groove positioned above the landing seat in the throughbore, and a locking groove positioned in the throughbore, the method comprising:

expanding a landing ring positioned on the tubing hanger to engage the landing groove; and

expanding a locking ring to engage the locking groove, the locking ring being positioned on the tubing hanger, wherein the locking ring is expanded after the expanding of the landing ring, wherein expanding the landing ring comprises running the tubing hanger downward into the wellhead using a running tool so that a landing mechanism positioned on the tubing hanger reacts against the landing seat, the downward force of the landing mechanism against the landing seat causing the landing mechanism to expand the landing ring.

9. The method of claim **8**, wherein other than by running the tubing hanger into the wellhead, the landing mechanism is not directly actuated via the running tool controls to expand the landing ring.

10. The method of claim **9**, wherein the locking mechanism is actuated via the running tool controls to expand the locking ring after the landing ring has been expanded into the landing groove.

11. The method of claim **8**, wherein expanding the locking ring to engage the locking groove provides a preload to the tubing hanger.

12. The method of claim **8**, wherein the preload is determined by the elastic deformation of the locking ring and the components surrounding the locking ring without employing an additional friction dependent preloading mechanism chosen from at least one of a tapered feature and a threaded feature.

13. A tubing hanger for use in a wellhead, the wellhead including a throughbore, a landing seat positioned in the throughbore, a landing groove positioned above the landing seat in the throughbore, and a locking groove in the throughbore, the tubing hanger comprising:

an expandable landing ring positioned on the tubing hanger for engaging the landing groove;

a landing mechanism for expanding the landing ring radially outward from the tubing hanger;

a locking ring for engaging the locking groove, the locking ring being positioned on the tubing hanger; and

a locking mechanism for expanding the locking ring radially outward from the tubing hanger body and locking it into the locking groove, wherein the tubing hanger is capable of engaging a running tool, and further wherein the landing mechanism is capable of expanding the landing ring by employing the downward force of the tubing hanger during installation without actuation by the running tool.

14. The tubing hanger of claim **13**, wherein the locking mechanism is capable of actuation to expand the locking ring after the landing ring has been expanded into the landing groove.

15. The tubing hanger of claim **14**, wherein the running tool actuates the locking ring.