CLAIMS

1. An eyewear comprising

a frame to receive a pair of lens;

a pair of temple bars extending from the frame;

a pair of side supports pivotable about a zygomatic arch ~~region~~ of a wearer's face; and

a pair of temple cables arranged to:

contact back ear portions of the wearer; and

contact neither ear recess portions nor ear inside protrusion portions of the wearer~~;~~,

wherein the pair of temple cables is arranged as an extension from the pair of temple bars;

wherein each of the temple cables is adjustable so as to provide a counter-weight to the frame; and

wherein the pair of side supports is shaped and dimensioned to contact the zygomatic arch of the wearer~~positioned~~ such that the weight of the frame is redistributed onto the zygomatic arch~~region~~.

2. The eyewear of claim 1, further ~~comprises~~ comprising a weight attached to an end portion of each of the temple cables.

~~3. The eyewear of claim 1 or 2, wherein each of the pair of side supports is shaped and dimensioned to contact a zygomatic arch of the wearer.~~

~~4~~3. The eyewear of ~~claim 3~~any one of the preceding claims, wherein each side support comprises a pad formed from at least one of: silicone, plastic, and a combination of the aforementioned.

4. The eyewear of claim 3, wherein each side support further comprises a cord portion extending from the pad to one of the temple bars.

5. The eyewear of ~~claim 3 or 4~~any one of the preceding claims, wherein each of the side supports is arranged in an inclined manner and biased towards each other.

~~6. The eyewear of any one of the preceding claims, wherein each temple bar comprises a hook portion configured to engage a portion of the wearer's ear.~~

~~7. The eyewear of claim 6, wherein the hook portion engages the back of the wearer's ear.~~

~~8~~6. The eyewear of any one of the preceding claims, wherein the pair of temple cables are detachable from the temple bars.

~~9~~7. The eyewear of any one of the preceding claims, wherein the pair of side supports are detachable.

~~10~~8. A method of producing an eyewear comprising the steps of:

(a.) providing a frame, the frame shaped and dimensioned to receive a pair of lens;

(b.) providing a pair of side supports, the pair of side supports pivotable about a zygomatic arch ~~region~~ of a wearer's face;

(c.) providing a pair of temple bars extending from the frame; and

(d.) providing a pair of temple cables arranged to:

contact back ear portions of the wearer; and

contact neither ear recess nor ear inside protrusion portions of the wearer,

wherein each of the temple cables is adjustable so as to provide a counterweight to the frame; and

wherein the pair of side supports is positioned such that the weight of the frame is redistributed onto the zygomatic arch~~region~~.

~~11. The method of claim 10, wherein the step of providing a pair of side supports include a step of pivoting about a zygomatic arch of the wearer.~~

~~12~~9. The method of claim ~~10 or 11~~8, wherein step (~~c~~d.) includes the step of providing a weight at an end portion of each of the temple cables.

~~13. A method for using the eyewear of claim 1 comprising the steps of: (a.) adjusting the pair of side supports such that when worn the pair of side supports is adapted to pivot about a zygomatic region of a wearer's face; and (b.) adjusting the pair of temple cables so as to provide a counter-weight to the frame.~~