

Description

This invention relates to the feeding of correction tape and more particularly to the mechanism for incrementing the correction tape in a correction cartridge on a typewriter.

Background of the Invention

The feeding of a correction tape requires a separate feed device from that which feeds the printing ribbon on a typewriter or printer. This duplication of drive hardware is not only expensive, but provides additional potential for mechanism malfunction, thereby creating additional reliability problems.

In typewriters which utilize an oscillating cartridge system, the drives for feeding the ribbon and the correction tapes must, of necessity, either be mounted such that they move with the cartridges as the cartridge oscillates or alternatively must provide a flexible connection to the drive of the cartridge from the drive mechanism mounted

a fixed hardware mounting in the typewriter. US-A-4,302,118 discloses a ribbon and correction feed mechanism which is mounted on an oscillating ribbon feed plate which oscillates with the cartridge, thus functioning as if the cartridge and the ribbon mechanism were spacially fixed.

US-A-3,863,749 and US-A-3,871,507, disclose a mechanism for drivingly engaging the ratchet teeth of a drive mechanism from the exterior of the cartridge while at the same time providing a lifting of oscillating mechanical input to the cartridge to effect ribbon lift. The device disclosed in these two documents is a multiple link lever chain driven by a cam to cause the feed of the ribbon. This document does not disclose any technique for feeding of correction tape inasmuch as only one feed mechanism is disclosed.

As may be seen from the above mentioned documents, the oscillating cartridges complicate feed mechanisms since the feed mechanism must be able to feed and also accommodate the oscillatory motion of the cartridge.

It is an object of the invention to eliminate complex mechanical drives necessary to effect the incrementing of correction tape for an oscillating ribbon feed cartridge system.

It is a further object of the invention to simplify the correction tape feed in a ribbon feed system having both a ribbon and correction tape contained in oscillating ribbon cartridge and correction tape cartridge.

Summary of the Invention

The shortcomings of the prior art are overcome and the objects of the invention accomplished by the incorporation of correction tape drive means into the correction ribbon cartridge, which drive means is drivingly connected to the take-up spool of the cartridge. The correction tape drive means derives its motion from the oscillation of the cartridge with respect to a fixed support and camming surface. This eliminates the separate powered feed mechanism from the overall ribbon

feed/correction tape mechanism for the typewriter.

The correction tape drive means includes a feed pawl which is mounted interiorly to the cartridge with an extension projecting from the cartridge confines thereby making the extension capable of interacting with the said camming surface as a cam follower. The feed pawl, when extended, will interact with the take-up spool and pull the correction tape from the supply spool, across the print zone.

The cam surface fixed on the frame of the carrier, or the ribbon feed mechanism, provides the pawl the input through the extension or cam follower. The cam surface or channel is configured such that the cam follower of the feed pawl rides in a portion of the channel configured so that the cam follower is not significantly displaced relative to the cartridge during the oscillations of the cartridge assembly needed to raise the printing ribbon to the print point. When the cartridge assembly is oscillated to the extent necessary to present correction tape at the print point, the cam follower is moved through a portion of the cam channel configured to cause the pawl to be retracted relative to the teeth of the ratchet and prepare the pawl for a feeding movement upon the subsequent lowering of the correction tape. As the cartridge is oscillated downward, the cam profile forces the cam follower to displace and during such displacement the cam follower moves the ratchet to feed the tape.

The oscillation of the printing ribbon cartridge and the correction tape cartridge to the necessary positions for printing will not effect tape feed and conserves the correction tape. Cartridge oscillation to the elevated position necessary for correction will cause pawl retraction and conditions the mechanism for tape feed only during those cycles where a correction is to be accomplished.

Description of the Drawings

Fig. 1 illustrates the ribbon feed mechanism together with a correction tape cartridge and a ribbon cartridge mounted on the feed mechanism.

Fig. 2 illustrates the ribbon feed plate with the correction tape cartridge positioned as it would be when the ribbon cartridge is mounted on the ribbon feed plate, with the top of the correction tape cartridge removed.

Fig. 3 illustrates a preferred embodiment of the ratchet and pawl drive arrangement together with the cam follower extending outwardly from the confines of the correction tape cartridge.

Fig. 4 is an alternative pawl and cam follower design to the one illustrated in Fig. 3.

Detailed Description of the Invention

Referring to Fig. 1, a ribbon feed plate 10 supports a correction tape cartridge 12 and a ribbon cartridge 14 pivotally. The support is provided by support members 16 which engage the print ribbon cartridge 14 and pivot the print ribbon cartridge 14 with respect to the support

10

members 16. Referring to Fig. 2, correction tape cartridge 12 has at least walls 11 and floor 13 and a top cover 15 partially shown for visibility, to define a housing or chamber.

Correction tape cartridge 12 is physically attached and latched to print ribbon cartridge 14 and becomes a part of the cartridge assembly 18. The attachment of tape cartridge 12 to ribbon cartridge 14 may be as disclosed in US-A-4,239,107. The raising and lowering of the ribbon 20 and the correction tape 22 is accomplished by means of the ribbon lift/feed mechanism 24 which comprises a drive motor 26 having a drive gear 28 and a driven gear 30. Driven gear 30 has formed on one face thereof a raised cam follower 34 which, when rotated, will act against cylindrical face cam 33 to exert an upward force against the rear of the ribbon cartridge 14. This will cause ribbon cartridge 14 to oscillate around pivot points of the cartridge to lower the ribbon 20 with respect to the print line of a typewriter (not shown) to permit visibility of the writing line. On a printer such as might be used with a small office computer, visibility is not critical and the system may not provide for this last described cartridge positioning.

In order to raise the print ribbon 20 or correction tape 22 to the elevated position necessary to accomplish their function at the writing line, the cam follower 34 on gear 30 is rotated such that a lower rise of the cam profile 32 is engaged with the cam follower 34 thereby allowing the rear end of the cartridge 14 to be lowered under the influence of spring 36 which is mounted to the ribbon feed plate 10.

In order to control the feed of the correction tape 22, cam surfaces 39 are attached to or formed as a part of ribbon feed plate 10 and remain fixed relative thereto. Cam surfaces 39 form a channel 38. Channel 38 confines cam follower 40 and controls its movement relative to the correction tape cartridge 12. Channel 38 is formed with a generally vertical portion 37 which approximates the unimpeded path of movement of follower 40 during the oscillation of cartridge assembly 18 which raises the ribbon 20 to the printing position.

Thus as the cartridge assembly 18 oscillates through a range of movement necessary for normal printing operations, cam follower 40 remains in portion 37 and therefore will not be displaced relative to cartridge 12 by any significant amount. However, when the oscillation of the cartridge assembly 18 is extended further to effect the positioning of correction tape 22 at the print line of the typewriter, the cam follower 40 will ride into the upper forward directed regions of channel 38, and will be forced forward as the cartridge assembly 18 is oscillated to raise the ribbon 20 and tape 22.

After the correction operation has occurred and the correction tape 22 is no longer needed at the print line, the ribbon feed/lift mechanism 24 is operated in reverse to lower the ribbon 20 and tape 22 from the print line. As lowering occurs,

the cartridge assembly 18 oscillates and lowers the front portion of the cartridge assembly 18 together with the cam follower 40. As cam follower 40 is forced downward, it will engage the lower camming surface 39 of channel 38 causing the cam follower to be moved rearward with respect to cartridge 12.

Referring to Figs. 2 and 3, as the cam follower 40 is moved rearward, it will oscillate about the axis of pin 42. Cam follower 40 is a portion or extension of a pawl member 44 having a sleeve which may be fitted over pin 42. Extending from the sleeve to pawl 44 is a pawl arm 46. Pawl arm 46 is fashioned of a flexible material such as a resilient plastic and is capable of flexing primarily at the bend 48 in the arm 46 and is relatively rigid in compression. Pawl tip 50 is fashioned to engage the teeth 52 of ratchet 54.

As cartridge 12 is oscillated downward at the front edge to lower the correction tape 22, cam follower 40 will ride against one of the cam surfaces 39 forming channel 38. As the cam follower rides within channel 38, it will be forced rearward with respect to cartridge 12 and thus move pawl tip 50 into forcible driving engagement with one of the teeth 52 to cause the ratchet 54 to rotate about its axis.

The rotating of the ratchet 54 rotates the take-up spool 55 to wind the tape 22 thereon. As tape 22 is wound onto the take-up spool 55, the tape is unspooled from supply spool 57 and directed outside the cartridge to form a span across the cartridge 12 for presentation to the print point.

During a subsequent raising of the cartridge 12 to present the correction tape 22 at the print line, channel 38 will displace cam follower 40 in a forward direction, thus withdrawing the pawl tip 50 from the tooth 52 with which it was engaged and retracting it such that it may re-engage another tooth 52 for a subsequent driving operation.

To prevent the unwinding of the correction tape 22 on take-up spool 55 during this phase of the operation, backcheck 60 is provided. Backcheck 60 is a pawl which yieldably engages teeth 52 of ratchet 54 preventing the reverse rotation of ratchet 54.

Fig. 4 illustrates an alternative structure of a pawl 70 which is driven by the cam follower 40. Pawl 70 is engaged, by pawl tip 72, with ratchet teeth 52 on ratchet wheel 54. Pawl 70 is an extension of a slide member 74 which, in turn, is rigidly attached to cam follower 40. Slide member 74 is constrained against lateral movement by constraining walls 76 and 78 which are formed as a part of the structure of cartridge 12. Follower 40 exits cartridge 12 at an oblong slot 80, the upper and lower sides of which constrain follower 40 against vertical movement.

Thus, the slide member 74 is capable of reciprocating along its axis between constraining walls 76 and 78 to cause the reciprocal movement of pawl tip 72.

In the case of the structure illustrated in Fig. 4, the driving portion of the operation would be

accomplished as the cartridge is raised to present correction feed tape 22 to the print line and tip 72 of pawl 70 is extended for a subsequent feed cycle upon the lowering of the cartridge 12 and the correction tape 22.

If this sequence of operations proves to be undesirable as requiring a substantially stronger spring 36 and the commensurate loads on the ribbon feed/lift assembly 24, it would be possible, by merely reversing the form of the channel 38 to reverse the appropriate drive by reversing the directions of motion of cam follower 40.

Claims

1. A correction tape cartridge (12) for a typewriter using a print ribbon cartridge (14) and including means (16) for mounting the correction tape cartridge (12) with said print ribbon cartridge (14), means (10) for carrying the print ribbon feed (24) and print ribbon and tape cartridges (14, 12) thereon, and means (16, 24, 36) for pivoting said print ribbon cartridge (14) and said correction tape cartridge (12) to present ribbon (20) and tape (22) at a point for printing, said correction tape cartridge (12) being characterized in that it comprises in combination:

means (15, 13) defining upper and lower surfaces spaced apart to define a chamber therebetween to embrace a supply spool (57) and take-up spool (55) and tape (22) between said upper and lower surfaces (15, 13); means for permitting said tape (22) to leave said tape cartridge (12) intermediate said supply and said take-up spools (57, 55) for presenting said tape (22) to a print point for utilization; correction tape drive means (54, 44) associated with said take-up spool (55) to effect tape movement from said supply spool (57) to said take-up spool (55); and cam follower means (40) projecting from said correction tape drive means (54, 44) for engagement with a cam (37, 38, 39) on said means (10) for carrying so that upon reciprocation of said correction tape cartridge (12) between at least the level of presentation of said tape (22) to said print point and a lower position, said cam follower means (40) follows said cam (37, 38, 39) to effect tape feed.

2. The correction tape cartridge of claim 1 wherein said cam follower (40) drives a pawl (44, 70) to effect feed of said tape (22).

3. The correction tape cartridge of claim 2 wherein said drive means (54, 44) comprises a ratchet (54) drivingly associated with said take-up spool (55) and engaged in a driving fashion by said pawl (44, 70).

4. The correction tape cartridge of claim 2 wherein said pawl (44) is pivotally mounted within said correction tape cartridge.

5. The correction tape cartridge of claim 2 wherein said pawl (70) is reciprocatingly mounted within said correction tape cartridge.

Patentansprüche

1. Korrekturbandkartusche (12) für eine

Schreibmaschine mit einer Farbbandkartusche (14) und Mitteln (16) zum Einsetzen der Korrekturbandkartusche (12) mit besagter Farbbandkartusche (14), Mitteln (10) zum Tragen des Farbbandvorschubs (24) und der darauf eingesetzten Farbband- und Korrekturbandkartuschen (14, 12), und Mitteln (16, 24, 36) zum Schwenken der besagten Farbbandkartusche (14) und der besagten Korrekturbandkartusche (12), um das Farbband (20) bzw. das Korrekturband (22) an einem Punkt zum Drucken anzulegen, wobei das besagte Korrekturband (12) dadurch gekennzeichnet ist, dass es zusammen enthält:

Mittel (15, 13), die eine obere und eine untere Fläche begrenzen, die auseinandergehalten sind, um eine Kammer zu bilden, die eine Versorgungsspule (57) und eine Aufnahmespule (55) und ein Band (22) zwischen der besagten oberen und unteren Fläche (15, 13) enthält; Mittel, die es dem besagten Band (22) gestatten, die besagte Bandkartusche (12) zu verlassen, die sich zwischen der besagten Versorgungs- und Aufnahmespule (57, 55) befindet, um das besagte Band (22) zur Verwendung an einem Druckpunkt anzuhalten; Mittel für den Antrieb des Korrekturbandes (54, 44), der der besagten Aufnahmespule (55) zugeordnet, um eine Bandbewegung von der besagten Versorgungsspule (57) auf die besagte Aufnahmespule (55) auszuführen; und Nockenstösselmittel (40), die aus den besagten Mitteln für den Antrieb des Korrekturbands (54, 44) vorstehen, um in eine Nocke (37, 38, 39) auf besagten Tragmitteln (10) einzugreifen, sodass bei Hin- und Herbewegung der besagten Korrekturbandkartusche (12) zwischen mindestens der Anhalteebene des besagten Bands (22) am besagten Druckpunkt und einer unteren Position besagte Nockenstösselmittel (40) besagter Nocke (37, 38, 39) folgen, um den Bandvorschub auszuführen.

2. Korrekturbandkartusche gemäss Anspruch 1, in der besagter Nockenstössel (40) eine Klinke (44, 70) betätigt, um besagtes Band (22) vorzurücken.

3. Korrekturbandkartusche gemäss Anspruch 2, in der besagte Antriebsmittel (54, 44) ein Klinkenrad (54) enthalten, das treibend mit der besagten Aufnahmespule (55) verbunden ist und in das die besagte Klinke (44, 70) antreibend eingreift.

4. Korrekturbandkartusche gemäss Anspruch 2, in der besagte Klinke (44) schwenkbar innerhalb der besagten Korrekturbandkartusche montiert ist.

5. Korrekturbandkartusche gemäss Anspruch 2, in der besagte Klinke (70) so innerhalb des besagten Korrekturbandkartusche montiert ist, dass sie sich hin- und herbewegt.

Revendications

1. Une cartouche de ruban de correction (12) pour une machine à écrire utilisant une cartouche de ruban d'impression (14) et comprenant des moyens (16) pour monter ladite cartouche de ruban de correction (12) avec ladite cartouche de ruban d'impression (14), des moyens (10) pour porter le dispositif d'alimentation de ruban d'im-

pression (24) et les cartouches de ruban d'impression et de ruban de correction (14, 12) et des moyens (16, 24, 36) pour faire pivoter ladite cartouche de ruban d'impression (14) et ladite cartouche de ruban de correction (12) afin de présenter le ruban (20) et le ruban (22) à un point d'impression, ladite cartouche de ruban de correction (12) étant caractérisée en ce qu'elle comprend en combinaison:

des moyens (15, 13) définissant des surfaces supérieure et supérieure séparées pour définir une chambre entre elles contenant une bobine d'alimentation (57) et une bobine de réception (55) et ledit ruban (22) entre lesdites surfaces supérieure et inférieure (15, 13), des moyens pour permettre audit ruban (22) de quitter ladite cartouche de ruban (12) entre lesdites bobines d'alimentation et de réception (57, 55) pour présenter ledit ruban (22) à un point d'impression pour son utilisation, des moyens d'entraînement de ruban de correction (54, 44) associés à ladite bobine de réception (55) pour assurer le mouvement du ruban de ladite bobine d'alimentation (57) à ladite bobine de réception (55) et des moyens suiveurs de came (40) montés sur lesdits moyens d'entraînement de ruban de correction (54, 44) fonctionnant en association avec une came (37, 38, 39) sur

lesdits moyens (10) de support de façon que lors du mouvement de va et vient de ladite cartouche de ruban de correction (12) entre au moins le niveau de présentation dudit ruban (22) audit point d'impression et une position inférieure, lesdits moyens suiveurs de came (40) suivent lesdites came (37, 38, 39) pour assurer l'alimentation du ruban.

2. La cartouche de ruban de correction de la revendication 1 dans laquelle ledit suiveur de came (40) commande un cliquet (44, 70) pour assurer l'alimentation dudit ruban (22).

3. La cartouche de ruban de correction de la revendication 2 dans laquelle lesdits moyens d'entraînement (54, 44) comprennent une roue à rochet (54) associée en entraînement à ladite bobine de réception (55) et engrenée en entraînement par ledit cliquet (44, 70).

4. La cartouche de ruban de correction de la revendication 2 dans laquelle ledit cliquet (44) est monté à pivot dans ladite cartouche de ruban de correction.

5. La cartouche de ruban de correction de la revendication 2 dans laquelle ledit cliquet (70) est monté de façon à être animé d'un mouvement de va et vient à l'intérieur de ladite cartouche de ruban de correction.



* C L M S *