



(51) International Patent Classification:
H04L 25/02 (2006.01)

(21) International Application Number:
PCT/CN2010/000045

(22) International Filing Date:
12 January 2010 (12.01.2010)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET L M ERICSSON (PUBL)** [SE/SE]; S-164 83 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HU, Yang** [CN/CN]; Ericsson Tower, No.5, Lize East Street, Chaoyang District, Beijing 100102 (CN). **ASTELY, David** [SE/SE]; Stobaevsvägen 22, S-168 56 Bromma (SE). **SONG, Xinghua** [CN/CN]; Ericsson Tower, No.5, Lize East Street, Chaoyang District, Beijing 100102 (CN). **WANG, Jianfeng** [CN/CN]; Ericsson Tower, No.5, Lize East Street, Chaoyang District, Beijing 100102 (CN).

(74) Agent: **CHINA PATENT AGENT (H.K.) LTD.**; 22/F, Great Eagle Centre, 23 Harbour Road, Wanchai, Hong Kong (CN).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD AND APPARATUS FOR CHANNEL ESTIMATION AND DETECTION IN MIMO SYSTEM




Figure 5

(57) Abstract: The present invention provides a method for performing channel estimation and detection in a Multiple-Input-Multiple-Output (MIMO) system, including: generating a demodulation reference signal, DM-RS, pattern for an extended cyclic prefix (CP); and estimating and detecting channel performance based on the generated DM-RS signal pattern. The DM-RS pattern supports from rank 1 to rank 8 patterns for 8 layer transmission. A transmitter, a receiver and a system thereof are also provided. The solution of the present invention improves channel estimation accuracy, saves channel estimation implementation and implementation complexity at terminals.