

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification ⁶ : F16L 41/16, 37/32		A1	(11) International Publication Number: WO 99/41539
			(43) International Publication Date: 19 August 1999 (19.08.99)
(21) International Application Number: PCT/IL99/00002		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 5 January 1999 (05.01.99)			
(30) Priority Data: 123260 11 February 1998 (11.02.98) IL			
(71) Applicant (for all designated States except US): HABONIM INDUSTRIAL VALVES LTD. [IL/IL]; Galil Elion 1, 12305 Kfar Hanassi (IL).			
(72) Inventor; and (75) Inventor/Applicant (for US only): NEMENOFF, Amir [IL/IL]; Galil Elion 1, 12305 Kfar Hanassi (IL).		Published <i>With international search report.</i>	
(74) Agent: REINHOLD COHN AND PARTNERS; P.O. Box 4060, 61040 Tel Aviv (IL).			



162162

(54) Title: **FLUID DISTRIBUTION SYSTEM AND A JUNCTION ELEMENT THEREFOR**

G00002



(57) Abstract

A junction element (10) for a fluid delivery system comprising an inlet port (12) for connecting to a main up-stream pipe section (20) and an outlet port (14) for connecting to a main down-stream pipe section (22), the outlet port being in flow communication with the inlet port. The junction element is integrally fitted with at least one duct portion being in flow communication with the inlet port or the outlet port and being integrally fitted with a valve member and having coupling means for coupling thereto a delivery element. Fluid flow through the duct portion may be shut off without interrupting the fluid flow through the main delivery pipe sections.