

Air cavity vessel

The invention relates to a vessel Vessel (1) comprising a hull (2) with a stem (5), bow (7) and bottom (3), an air cavity (6) formed at the bottom (3) of the hull (2) and comprising a cavity top surface (27), a front wall (28) and a front section (10) located nearest to the bow (7), and an air inlet (8) located in the air cavity (6) connected to an air supply means (35) to provide air to the cavity.

Such a vessel is known from patent NL9301476. In this publication a vessel is described having an air cavity formed at the bottom of the hull into which air is injected. In view of reduced friction between the layer of air in the cavity and the water flowing past the hull, the resistance of the vessel is reduced resulting in fuel savings and more economic propulsion. The known vessel has the disadvantage that it can only be used in flat water. When the known vessel is used on water with waves, e.g. on the ocean, the air is not properly contained in the air cavity. Therefore the air cavity does not function well, causing a higher resistance of the vessel and thus lower fuel savings and a less economic propulsion.

From US 6,575,106 A a marine vessel is known which has an air inlet for drawing in air at ambient pressure into a plenum. Because of the sub-pressure created in the plenum when the vessel moves forward, water and a stream of air bubbles move along a mixing chamber at the bottom of the plenum plate, into the cavity. The plenum is closed towards the aft via a vertical plate 58 (Figure 3). When the vessel is operated under sea going conditions, waves may enter into the cavity and expell the air therefrom such that the effectiveness of the cavity is reduced. Futhermore, the known system will not be able to provide an air-filled cavity under all operative conditions, at deeper draft levels.

From WO 95/14604 a high speed planing or semi-planing hull (SES) is described in which in a dagger-shaped cavity an air deflector is situated underneath the air inlet in order to deflect air that is injected in a downward direction, into the cavity in a generally horizontal rearward direction. The air deflector plate is situated close to the air inlet, in order to move air into the cavity, such that the position of the plate will be higher up in the cavity, close to the top side of the cavity and close to the air inlet. Waves may hence enter into the cavity before they reach the plate such that its wave deflection action is negligible, the deflector known deflector having no

hydrodynamic function.

In accordance with an aspect of the present invention, there is provided a vessel comprising a hull with a stern, bow and bottom, an air cavity formed at the bottom of the hull and comprising a cavity top surface, a front wall and a front section located nearest to the bow, and an air inlet located in the air cavity connected to an air supply means to provide air to the cavity, characterised in that the vessel comprises a wave deflector defining a lower surface and a water side, which wave deflector is situated in the front section of the air cavity and at a distance from the cavity top surface and extends from the front wall to a free side substantially in the direction of the stern, the front wall comprising a height measured from the cavity top surface in a direction perpendicular to said top surface, the wave deflector comprising a thickness H_2 between the lower surface and the water side measured in the direction perpendicular to said top surface of substantially 0.2-0.5 and preferably 0.25-0.4 of H_i .

Embodiments of the present invention, seek to provide a vessel with an air cavity, which vessel has good ocean going properties. The vessel is characterised in that the vessel may comprise a wave deflector (9) defining a lower surface (12) and a water side (11), which wave deflector (9) is situated in the front section (10) of the air cavity (6) and at a distance from the cavity top surface (27) and extends from the front wall (28) to a free side (14) substantially in the direction of the stern (5), the front wall (28) comprising a height (H_i) measured from the cavity top surface (27) in a direction perpendicular to said top surface, the wave deflector comprising a thickness H_2 between the lower surface (12) and the water side (11) measured in the direction perpendicular to said top surface (27) of substantially 0.2-0.5 and preferably 0.25-0.4 of H_i . The effect of the wave deflector is that it in use may deflect the waves which try to move through the air cavity, and especially through the front section. Hereby it can prevent that the waves enter the air cavity and push air out of the air cavity. This can ensure that when the vessel, according to the embodiments, is used in water with a non flat surface water or ocean like waves, the air can be kept in the air cavity. Hereby the air cavity can function optimally.

In an embodiment of the invention, the wave deflector comprises a turbulence edge for creating turbulence in water flowing past the turbulence edge. Due to the

turbulence created in the water flowing over the edge, the water is prevented from flowing back over the lower surface of the wave deflector and from there in the front section of the cavity. The cross section of the wave deflector may comprise in the direction of the longitudinal axis of the vessel substantially a box shape. The turbulence edge may be an edge of a plurality of turbulence creating members provided on the free side of the wave deflector.

The height H1 may be between the 2 and 4 m, preferably 3 m, and the thickness H2 may be between the 0,5 and 1,5 m, preferably 1 m.

In an embodiment of the vessel according to the invention the wave deflector comprises a first edge and a second edge which extend from a common apex point at a first distance D1 from the bow, respectively to a first and second point at a second distance D2 from the bow, which second distance D2 is larger than the first distance D1. This specific form of the wave deflector has a positive effect on the ability thereof to prevent that a wave enters the air cavity, and especially the front section. The first

and second edges may extend substantially in a straight line such that the directions of the, first and second edges are positioned to each other under an angle α of between 5° and 45° , and preferably 25° . The first and second edges may extend from and in the region adjacent to the common apex point such that the first and second edges are curved and are part of a parabolic circle. The first and second distances D_1 and D_2 may in relation to the vessel length L correspond to: $0,2 L \leq D_2 - D_1 \leq 0,6 L$.

In an embodiment of the vessel according to the invention the wave deflector comprises displacement means for moving the wave deflector relative to cavity top surface. Hereby the positioning of the wave deflector can be adjusted to the specific circumstances, like wave size and wave frequency. The displacement means may be connected to a control system for controlling the positioning of the wave deflector. The displacement means may be arranged to displace the wave deflector in the direction substantially perpendicular to the cavity top surface and/or to displace the wave deflector in the direction substantially along to the cavity top surface.

In an embodiment of the vessel according to the invention the cavity top surface comprises a first surface part which extends from the front side of a top cavity level towards the stern and substantially parallel to the horizontal direction and a second surface part which extends from the first surface part towards the stern to a bottom cavity level and under an angle α_1 of between $0,5^\circ$ and 10° , preferably $1,5^\circ$ relative to the horizontal direction. This specific form of the cavity top surface has a positive effect on the ability to keep the air in the air cavity, and especially in the front section.

In a further embodiment of the vessel according to the invention, the vessel comprises emission gas producing driving means which comprise a first gas outlet for transporting emission gas produced by the driving means into the air cavity. By transporting the emission gas from the driving means in the air cavity, the emission gasses will pass through the seawater. As a result of this the emission gasses are subjected to a cleaning process. This cleaning process is generally known as scrubbing. This embodiment enables the user to meet strict environmental regulations. The driving means may comprise a second gas outlet for the discharge of the emission gas outside the air cavity and a second control system for controlling the discharge of the emission gas through the first and second outlet. Hereby the user of the vessel can choose whether the emission gas is transported inside the air cavity to achieve the scrubbing effect or whether the emission gas is discharged outside the air cavity, for

example in the free air. This is favourable when the vessel at certain places, for example in a harbour, is not allowed to discharge the emission gasses through the seawater.

By providing air removing means to an air cavity vessel, the air can be removed rapidly from the air cavity. By doing so, the friction between the vessel and the water is increased. This has a positive effect on the braking distance of a vessel cavity vessel. The invention will in the subsequent part be discussed in detail with reference to the accompanying figures, wherein:

Fig. 1a shows a schematically side view in cross section of an embodiment of the vessel according to the invention, and

Fig. 1b shows a schematically bottom view of the vessel of fig. 1.

Fig. 2 shows a schematically bottom view of the vessel of fig. 1 provided with an adjustable wave deflector,

Fig. 3 shows a schematically bottom view of the vessel of fig. 1 provided with an adjustable wave deflector,

Fig. 4 shows a schematically bottom view of a vessel according to the invention, provided with more than one air cavities, and

Fig. 5 shows an embodiment wherein the exhaust gases are fed through the water of the ballast tanks prior to entering into the air cavity.

Figure 1 a and b show an embodiment of the vessel 1 according to the invention. The vessel 1 comprises a hull 2, a bottom 3, a bow 7, a stem 5 and a longitudinal axis 20. The longitudinal axis 20 extends in the horizontal direction. The transverse direction of the vessel is indicated by the arrow 39. An air cavity 6 is formed at the bottom 3 of hull 2. The air cavity 6 comprises a cavity top surface 27, a front wall 28 and a front section 10. The front section 10 is located nearest to the bow 7. An air supply means 35 connected air inlet 8 is located in the front section 10 to provide air to the air cavity 6. A wave deflector 9 is situated in the front section 10 of the air cavity 6 and at a distance of the cavity top surface 27. The wave deflector 9 has a connection side with which the wave deflector 9 is connected to the front wall 28. The wave deflector 9 extends from the front section 10 in the direction of the stem 5 to a free side 14 of the wave deflector 9, which free side extends freely across the air cavity 6.

The wave deflector 9 has a box shape in cross section. The turbulence edge 29 of the wave deflector 9 creates turbulence in water which in use flows past the turbulence edge 29. One side of the wave deflector 9 forms the lower surface 12 of the air cavity 6 and the other side forms the water side 11 of the wave deflector 9. The wave deflector 9 has a thickness H2, measured in the direction perpendicular to the cavity top surface 27. The free side 14 of the wave deflector 9 has a first edge 15 and an opposite second edge 16, which edges 15 and 16 extend from a common apex point 17 to a first and second point 18 and 19. The common apex point 17 is located at a first distance D1 from the bow 7 and the first and second points 18 and 19 are located at a second distance D2 from the bow 7. The vessel length is indicated by L. L may be between 100 and 300 meters. The width of the vessel may be between 20 and 50 meters and the height between 15 and 30 meters. The first and second edges 15 and 16 extend from and in the region of the common apex point 17 such that the edges 15 and 16 are curved and are part of a parabolic curve. From there the edges 15 and 16 each extend further in a substantially straight line, wherein said straight lines of the edges 15 and 16 are positioned to each other under an angle α of 25°. The first and second points 18 and 19 intersect with the bottom edges 24 of the bottom 3.

The front wall 28 has a height H_I , of substantially 3 meters, measured from the cavity top surface 27 and in the direction perpendicular to the cavity top surface 27.

The cavity top surface 27 extends from a top cavity level 33 to a bottom cavity level 34 and comprises a first, second and third surface part 30, 31 and 32. The first surface part 30 extends from the front side 28 towards the stem 5 and parallel to the horizontal direction. The second surface part 31 extends from the first surface part 30 towards the stern 5 under an angle β_1 of $1,5^\circ$ relative to the horizontal direction. The third surface part 32 extends from the second surface part 31 towards the stem 5 under an angle β_2 of 7° relative to the horizontal direction. The angle β_2 may also be between the 4° and 10° .

The vessel 1 further comprises emission gas producing driving means 43 which are connected to a screw propeller 46 by an actuation connection 45. The driving means 43 comprises a first gas outlet 49 which is connected to the air supply means 35 and a second gas outlet 50 which discharges the emission gas in the free air. The driving means 43 and the air supply means 35 are by a second and third communication connection 47 and 48 respectively connected to a second control system 44. The second control system 44 controls whether the emission gas is discharged in the first or second gas outlet 49 and 50. The emission gas transported through the first gas outlet 49 enters the air supply means 35 which blows the emission gas (in combination with air) through the air outlet 8 and inside the air cavity 6.

Figure 2 shows the vessel of fig. 1 provided with an adjustable wave deflector 9'. The wave deflector 9' comprises displacement means 23 for moving the deflector 9' relative to the vessel 1. The displacement means 23 comprise a first drive member 50 which moves the free side 14 of the wave deflector 9' relative to the cavity top surface 27. The free side 14' is pivotable around a pivot axis 38 extending in the transverse direction (39 of fig. 1b). The displacement means 23 are by a communication connection 40 connected to control means 37 for controlling the positioning of the wave deflector 9'.

Figure 3 shows the vessel of fig. 1 provided with an adjustable wave deflector 9". In this case the wave deflector 9" is displaceable in the direction substantially along the cavity top surface 27. The common apex point 17" and the first and second point 18" and 19" function as displaceable hinging points which allow adjusting of the wave deflector 9". The wave deflector 9" can be adjusted such that the common apex point

17" is displaced in the direction of the longitudinal axis 20, as indicated by arrow 40. Hereby the first distance D1 will be adjusted. This displacement is actuated by a second drive member 53 which is located inside the air cavity 6. The first and second edges 15" and 16" can be displaced such that the angle α " is adjusted, as indicated by the arrows 42. This may result in an adjustment of the second distance D2 (displacement of the first and second points 18" and 19"). This displacement is actuated by a third and fourth drive member 51 and 52 which are located inside the air cavity 6. The displacements indicated by the arrows 40 and 42 may be performed independently or combined.

Figure 4 shows a vessel according the invention, provided with more than one air cavities 109. The vessel 101 comprises a hull 102 with a stem 105, bow 107 and bottom 103. At the bottom 103 of the hull 102 are four air cavities 106 formed. Each of the air cavities 106 comprises a wave deflector 9 which can comprise all features disclosed above. The air cavities 106 are positioned substantially parallel to each other and extend substantially in the direction of the longitudinal axis 120 of the vessel 101. The vessel comprises preferably between 2 and 5 air cavities.

As shown in Fig. 5, the exhaust gases from the driving means 43 are passed via the duct 48' through the water in the ballast tanks 90, 91. By passing the exhaust gases from the ship's diesel engine through the ballast water prior to entering the exhaust gases into the cavity for powering the cavity, not only an effective filling of the cavity is achieved but also can the water in the ballast tanks be disinfected so as to reduce bacterial activity. It was furthermore found that passing the exhaust gases through the ballast water, an effective wet scrubbing of said gases can be achieved so as to reduce the particulate matter in the exhaust gases, such as soot, and to cool the gases prior to entering into the cavity. The reduced temperature results in reduced corrosion of the cavity.

It will be clear to the person skilled in the art that many modifications of the embodiments of the present invention are possible without departing from the scope of protection as defined in the accompanying claims.

Claims

1. Vessel comprising a hull with a stern, bow and bottom, an air cavity formed at the bottom of the hull and comprising a cavity top surface, a front wall and a front section located nearest to the bow, and an air inlet located in the air cavity connected to an air supply means to provide air to the cavity, characterised in that the vessel comprises a wave deflector defining a lower surface and a water side, which wave deflector is situated in the front section of the air cavity and at a distance from the cavity top surface and extends from the front wall to a free side substantially in the direction of the stern, the front wall comprising a height measured from the cavity top surface in a direction perpendicular to said top surface, the wave deflector comprising a thickness H_2 between the lower surface and the water side measured in the direction perpendicular to said top surface of substantially 0.2-0.5 and preferably 0.25-0.4 of H_1 .
2. Vessel according to claim 1, wherein the water side of the wave deflector is situated substantially at the height of the bottom.
3. Vessel according to claim 1, wherein the wave deflector comprises a turbulence edge for creating turbulence in water flowing past said turbulence edge.
4. Vessel according to any of the preceding claims, wherein the cross sections of the wave deflector in the direction of the longitudinal axis of the vessel are substantially a box-shaped.
5. Vessel according to any of the preceding claims, wherein the wave deflector comprises a water side which in use is in contact with water and the distance between the water side and the lower surface of the air cavity is between 0,5 and 1,5 m, and preferably 1 m.

6. Vessel according to any of the preceding claims, wherein the wave deflector comprises a first edge and a second edge which extend from a common apex point at a first distance (D1) from the bow, respectively to a first and second point at a second distance (D2) from the bow, which second distance (D2) is larger than the first distance (D1).
7. Vessel according to claim 6 wherein the first and second edges extend substantially in a straight line such that the directions of the first and second edges are positioned to each other under an angle α of between 5° and 45° , and preferably 25° , and the first and second distances (D1 and D2) in relation to the vessel length (L) correspond to: $0,2 L \leq D2 - D1 \leq 0,6 L$.
8. Vessel according to the claims 6 and 7, wherein the first and second edges extend from and in the region adjacent to the common apex point such that the first and second edges are curved and arc part of a parabolic circle.
9. Vessel according to any of the preceding claims, wherein the wave deflector comprises displacement means for moving the wave deflector relative to cavity top surface.
10. Vessel according to claim 9, wherein the displacement means are arranged to displace the wave deflector in the direction substantially perpendicular to the cavity top surface.
11. Vessel according to the claim 9 and 10, wherein the displacement means are arranged to displace the free side in the direction substantially along to the cavity top surface.
12. Vessel according to any of the preceding claims, wherein the cavity top surface comprises a first surface part which extends from the front side of a top cavity level towards the stern and substantially parallel to the horizontal direction and a second surface part which extends from the first surface part

towards the stern to a bottom cavity level and under an angle of between $0,5^{\circ}$ and 10° , preferably about $1,5^{\circ}$ relative to the horizontal direction.

13. Vessel according to any of the preceding claims, wherein the air inlet is located in the front section of the air cavity.

14. Vessel according to any of the preceding claims, wherein the vessel comprises emission gas producing driving means which comprise a first gas outlet for transporting emission gas produced by the driving means into the air cavity.

15. Vessel according to claim 14, wherein the driving means comprise a second gas outlet for the discharge of the emission gas outside the air cavity and a second control system for controlling the discharge of the emission gas through the first and second outlet.

16. Vessel according to any of the preceding claims, wherein the vessel comprises more than one air cavities which comprise a wave deflector and wherein the air cavities are positioned substantially parallel to each other and extend substantially in the direction of the longitudinal axis of the vessel.

17. Vessel according to any of the preceding claims, the vessel comprising a combustion engine for propulsion of the vessel, and ballast tanks comprising water, characterised in that exhaust gases from the combustion engine are led to the air cavity via the ballast tanks through the ballast water.

18. Air cavity vessel according to claim 17, the combustion engine comprising a diesel engine.

19. Air cavity vessel according to claim 17 or 18, the exhaust gases reducing bacterial activity in the ballast water.

20. Air cavity vessel according to claim 17, 18 or 19, the concentration of particulate matter in the exhaust gases that exit from the ballast tanks being lower compared to the particulate matter concentration of the exhaust gases before entering into the ballast tank.

21. Air cavity vessel according to any of the preceding claims, wherein the temperature of the exhaust gases exiting from the ballast tanks is lower than the temperature of the exhaust gases entering the ballast tanks.