

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
03 November 2022 (03.11.2022)



(10) International Publication Number
WO 2022/231956 A1

(51) International Patent Classification:
F16L 41/02 (2006.01)

(21) International Application Number:
PCT/US2022/025876

(22) International Filing Date:
22 April 2022 (22.04.2022)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
63/180,115 27 April 2021 (27.04.2021) US

(71) Applicant: **VICTAULIC COMPANY** [US/US]: 4901
Kesslesville Road, Easton, PA 18040 (US).

(72) Inventors: **BOWMAN, Matthew, A.**; 2215 Donald Street,
Palmer, PA 18045 (US). **RICHARDS, Christopher, A.**;
2702 North Delaware Drive, Easton, PA 18040 (US). **AL-**
BRIGHT, Christopher; 1820 Elbow Lane, Allentown, PA
18103 (US).

(74) Agent: **CHIONCHIO, John, A.** et al.; Ballard Spahr LLP,
1735 Market Street, 51st Floor, Philadelphia, PA 19103
(US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, IT, JM, JO, JP, KE, KG, KH,
KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA,
MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM,
ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

(54) Title: MECHANICAL OUTLET




FIG. 1

(57) Abstract: A mechanical outlet forms a Tee joint by using a strap to cinch a pipe element to a saddle having a duct. One end of the strap and saddle are attached via an adjustable fastener. Angularly oriented action and reaction surfaces on the saddle and strap engage one another when the fastener is tightened to place a tensile load on the strap which substantially conforms to the pipe element and compresses it against the saddle. The opposite ends of the strap and saddle engage one another via a yoke and enlarged head, allowing those ends to be disengaged to permit insertion of the pipe element between strap and saddle.

[Continued on next page]

EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*