

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 April 2006 (20.04.2006)

PCT

(10) International Publication Number
WO 2006/039937 A1

(51) International Patent Classification⁷: **E21B 34/04**,
33/038, F16L 37/10, F16K 31/04

(21) International Application Number:
PCT/EP2004/011426

(22) International Filing Date: 12 October 2004 (12.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **COOPER CAMERON CORPORATION** [US/US]; 1333 West Loop South, Suite 1700, Houston, TX 77027-9109 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BIESTER, Klaus** [DE/DE]; Am Maschsee 2, 29342 Wienhausen (DE).

(74) Agent: **HILGERS, Hans**; Grünecker, Kinkeldey, Stockmair & Schwanhäusser, Maximilianstrasse 58, 80538 München (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LOCKING DEVICE



(57) Abstract: A locking device (1) for locking an exchangeable unit (2) in an insertion opening (3) of an associated housing (4), comprises locking elements (7) adjustable between an insertion opening (15) and a locking position (6), wherein in its insertion direction the unit (2) can be inserted into the insertion opening (3), and is locked in the locking position (6) within the insertion opening (3) and relative to the housing (4). This device has a simpler structure and can at the same time be operated more easily by keeping the safe sealing between the unit (2) and the housing (4), the locking elements (7) are formed as thread segments (10) spaced apart by insertion gaps (8) in the circumferential direction and arranged on the outer side of the unit (2) and being assigned to the insertion opening (3), said thread segments (10) being arranged in the insertion opening (3) at a gap (8) and being in thread engagement in the locking position (6).