

Description

Permanent contact mechanism

- 5 The invention relates to a permanent contact mechanism for an office chair or the like.

Permanent contact mechanisms, also known as asynchronous mechanisms, are characterised in that a chair back is
10 connected movably to a fixed seat. The chair back follows the movements of the seated person from a front (upright) to a rear ("lying") position and vice versa. Permanent contact mechanisms thus facilitate and support frequently changing seating positions which are preferred for orthopaedic
15 reasons, i.e. due to the associated reciprocal weight bearing of intervertebral discs.

To ensure secure and pleasant motion sequence the chair back pivots mostly against the force of a spring component. An
20 adjustment option for changing the resilient force is often also provided. But the drawback to solutions known from the prior art is that the construction elements, such as for example worm gears, threaded rods etc. required for resilient force adjustment, considerably increase the necessary overall
25 height of the permanent contact mechanism.

An aim of the present invention is to provide a comparatively low permanent contact mechanism.

- 30 This task is solved by a permanent contact mechanism according to Claim 1. According to this a permanent contact mechanism is provided with a seat frame placeable on a chair column, with a chair back frame arranged pivotably about a

transverse axis on the seat frame, with at least one spring-loaded or intrinsically resilient lever element which cooperates with the chair back frame such that pivoting of the chair back frame occurs constantly against a resilient
5 force, whereby the position of the lever fulcrum of the lever element is different from the position of the transverse axis.

A fundamental idea of the invention is the spaced positioning
10 of the lever fulcrum of the lever element impacting the chair back frame on the one hand and on the other hand the position of the transverse axis, about which the chair back frame can be pivoted.

15 The result of this constructive arrangement is that the lever element moving with the chair back frame travels another travel distance than does the chair back frame. This forms the basis for a structurally very simple and thus economic resilient force adjustment which can also be made in the
20 smallest space, in particular realizing a particularly small overall height of the permanent contact mechanism.

A further fundamental idea of the invention is to provide a resilient force adjustment without a resilient element having
25 to be (pre)stressed. It has proven advantageous in particular if the length of the effective lever arm can be changed without effort having to be directed against the resilient force via a change in the position of the articulation point of a lever arm of the lever element on the chair back frame.
30 Otherwise expressed, a particularly easy, "feeble" resilient force adjustment is made.

An exemplary embodiment of the invention with further advantageous configurations will now be explained hereinbelow in greater detail by means of the drawings, shown here partly simplified and schematically, in which:

5

Figure 1 shows a permanent contact mechanism in a side view,

Figure 2 shows a permanent contact mechanism in a first exploded illustration,

10

Figure 3 shows a permanent contact mechanism in a second exploded illustration,

15

Figure 4 shows a permanent contact mechanism without seat plate in a perspective view,

Figure 5 shows a permanent contact mechanism without seat frame in a perspective view,

20

Figure 6 shows a permanent contact mechanism in a sectional view along line VI-VI in Figure 4,

Figure 7 shows a schematic illustration of the position of the contact slide in a rear position,

25

Figure 8 shows a schematic illustration of the position of the contact slide in a front position,

30

Figure 9 shows a permanent contact mechanism in a sectional view along line IX-IX in Figure 6,

Figure 10 shows a permanent contact mechanism in a sectional view along line X-X in Figure 6,

Figure 11 shows a permanent contact mechanism in a sectional view along line XI-XI in Figure 6 in a front position in an "easy" setting,

5

Figure 12 shows a permanent contact mechanism in a sectional view along line XI-XI in Figure 6 in a rear position in an "easy" setting,

10 Figure 13 shows a permanent contact mechanism in a sectional view along line XI-XI in Figure 6 in a front position in a "harder" setting, und

Figure 14 shows a permanent contact mechanism in a sectional
15 view along line XI-XI in Figure 6 in a rear position in a "harder" setting.

The exemplary embodiment shows a permanent contact mechanism
1 for an office chair or the like, with a fixed, i.e.
20 immovable seat frame 3 placeable by means of a conical flange 2 onto the upper end of a chair column (not shown), and with a seat plate 4 attached to the seat frame 3, which together with the seat frame 3 forms a housing for the actual pivoting mechanism, cf. Figure 1. In the process the seat plate 4
25 extends well out over the leading edge 5 of the seat frame 3. The seat frame is preferably made of a fibreglass-reinforced plastic material (Pa6Gf30), while the seat plate comprises polypropylene.

30 In addition, the permanent contact mechanism 1 includes a chair back frame 7 arranged pivotably about a transverse pivot axis 6 on the seat frame 3, fork-shaped in plan view, the bearers 8 of which are arranged on both sides of the seat

frame 3. The seat fitted with an upholstered seat area is mounted on the seat plate 4; alternatively, a seat bearer or the like can also complete the seat frame 3 in an upward direction, instead of the seat plate 4 (neither shown).

5

As is evident in particular in Figures 2 to 6, the whole permanent contact mechanism 1 is built mirror-symmetrically with respect to a medium-length plane M(cf. Figure 4), which relates to the actual kinematics. The following description is always based on paired construction elements of the actual pivoting mechanism.

Attached to the chair back frame 7 is a chair back 9, cf. Figures 4 and 5. For this, the upper free ends of the chair back frame 7 have a cradle 11 which is designed for pivotable bearing of the chair back 9 about a pivot axis 12, cf. Figure 2. Otherwise expressed, the chair back 9 can perform a pendulum motion, serving to effectively prevent lordosis separation. In other words, the result is permanent contact of the lordosis region of the seated person with the chair back 9. This pivoting mechanism for the chair back 9 preferably also comprises a resilient element (not shown) for resetting the chair back 9 into its normal position, as soon as the seated person stands up. In order to perform the pendulum motion the seated person must therefore overcome a specific resilient force. The chair back is preferably made of plastic (Pa6).

The chair back frame 7 is articulated with the seat frame 3 to the front end 13 of its bearer 8, which runs obliquely upwards starting from a horizontal main bearer element 14, beginning approximately in the region of the conical flange 2. For this purpose, a hollow crossmember 15 connecting both

bearers 8 lies in U-shaped recesses 16 provided on both sides of the seat frame 3 and is held there by corresponding parts 17 with likewise U-shaped recesses 18, arranged inside the seat frame 3 and mountable from above, cf. Figure 4, whereby
5 a pivot bearing is designed for the chair back frame 7.

The position of the pivot axis 6, about which the chair back frame 7 can be pivoted, and corresponding to the constructive edge parameter is in a position which effectively minimizes
10 the so-called "shirt-pull effect". The pivot axis 6 is arranged not directly under the actual H point of the seated person, but is offset relative to the actual H point in the direction of the leading edge 5 of the seat frame 3. The pivot axis 6 is located in particular in a longitudinal
15 direction 19, as viewed from the conical flange 2, therefore offset from the conical flange 2 in the direction of the seat leading edge 21. In addition, the pivot axis 6 is in the immediate vicinity of the seat plate 4 terminating the seat frame 3.

20 The crossmember 15 as integral part of the chair back frame 7 is connected integrally to a latch plate 22 which extends in the direction of the trailing edge 23 of the seat frame 3 and whereby at least its underside 24 runs parallel to the bearer
25 main elements 14. This latch plate 22 performs every movement of the chair back frame 7 in the direction of pivoting 25 and at the same time moves inside the seat frame 3. The chair back frame 7 with all its components (latch plate 22, ...) is preferably made of Pa6Gf30.

30 Inside the seat frame 3 a spring arrangement is provided with two torsion springs 27 aligning with one another in a transverse direction 26. These are torsion springs with two

legs in each case. The shorter fixed legs 28 point in the direction of the leading edge 5 of the seat frame 3 and are supported in specially provided openings 29 in the underside 31 of the seat frame 3, through which they protrude outwards.

5 The longer free leg 32 points in the direction of the trailing edge 23 of the seat frame 3 and is supported on a contact slide 33, described in greater detail hereinbelow, acting mechanically reciprocally to the latch plate 22. The torsion springs 27 themselves lie in specially provided

10 prisms 34, designed as part of the seat frame 3.

The torsion springs 27 thus form lever elements, cooperating with the chair back frame 7 such that moving the chair back frame 7 in the direction of pivoting 25 occurs constantly

15 against the resilient force of the torsion springs 27. At the same time, both legs (fixed leg 28 and free leg 32) act as lever arms. The middle points 35 of the torsion springs 27 form the lever fulcrums of the lever elements and are spaced at a distance from the position of the pivot axis 6.

20 A particular advantage is a structural form realized with this exemplary embodiment, wherein the middle points 35 of the torsion springs 27 are at any time on a horizontal plane 36 (illustrated in Figure 10) with the centre of the pivot

25 axis 6, cf. Figures 10 to 15. This arrangement enables a minimal overall height of the permanent contact mechanism 8 and at the same time enables an adequate regulating range of the chair back frame, thus constituting an optimal centre path between overall height and regulating range.

30 A particular advantage also is a further structural form realized with this exemplary embodiment, wherein the middle points 35 of the torsion springs 27 are located directly over

the conical flange 2 and thus directly over the chair column. The advantage is that all areas subject to a high force influence, specifically the conical flange 2 made of steel, the bearing (shaft 46, ...) of the chair back frame 7 as well
 5 as the bearing (prism 34) of the torsion spring 27, lie close together. A particularly stable construction can be achieved accordingly with particularly low material use.

The contact slide 33 arranged centrally in the seat frame 3
 10 is designed substantially T-shaped and preferably comprises plastic (Pa6). On the undersides 37 of both its T-legs 38 running in a transverse direction 26 it has in each case a U-shaped groove 39 running in a longitudinal direction 19. In these grooves 39 lie the free legs 32 of the torsion springs
 15 27. In other words, the free legs 32 of the torsion springs 27 are supported on the T-legs 38 of the contact slide 33.

Fixed to the underside 41 of the T base 42 of the contact slide 33 is a gear rack 43 which cooperates with a cog 44 to
 20 form a rack gear. The cog 44 is arranged in a specially provided recess 45 of the crossmember 15 and mounted on a shaft 46 running inside the crossmember 15 and at the same time acting as pivot axis 6 for the chair back frame 7. An actuating element (not shown), for example a hand wheel, is
 25 attached to an end of the shaft 46 for actuating the cog 44.

The top side 47 of the contact slide 33 cooperates with the underside 24 of the latch plate 22 as follows: at the point where both T-legs 38 of the contact slide 33 collide,
 30 therefore in a central position, is a cuboid block 48, projecting upwards from the top side 47 in the direction of the latch plate 22 or respectively seat plate 4, which is connected preferably in one piece to the contact slide 33 for

reasons of improved mechanical strength and load-bearing capacity.

To the right and left of this block 48 on the top side 47 of
5 the contact slide 33 a number of latch elements 49 is
provided. At the same time, these are evenly spaced, cogged
locking steps, arranged in the transverse direction 26. These
extend in the direction of the free ends 51 of the T-legs 38
as far as approximately the middle of the T-legs 38, so that
10 the top sides 52 of the T-legs 38 are free of the latch
elements 49 in the region of their free ends 51 and exhibit
smooth surfaces corresponding to the material selected.

Down the middle the underside 24 of the latch plate 22 has a
15 rectangular opening 53 running in the longitudinal direction
19. A number of latch elements 54 again extends on both sides
of the opening 53 in the longitudinal direction 19. These are
designed as counter-elements to the latch elements 49 on the
top side 47 of the contact slide 33. Again corresponding to
20 the selected material the surface is smooth on both sides of
the latch element 54, therefore on the lateral edge regions
55 of the underside 24 of the latch plate 22.

Contact slide 33 and latch plate 22 are arranged relative to
25 one another such that the block 48 arranged on the top side
47 of the contact slide 33 never contacts the latch plate 22,
but is arranged constantly in the region of the rectangular
opening 53.

30 When the chair back frame 7 swivels into a rear position the
free "active" legs 32 of the torsion springs 27 cover a
longer distance than the chair back frame 7. The swivel
movement of the free legs 32 occurs in other words over a

greater range of angle than the swivel movement of the chair back frame 7. At the same time, shearing forces occur in the construction elements concerned.

5 If the chair back frame 7 is in a pivoted, rear position (cf. Figures 12 and 14), the force constituents of the torsion springs 27 acting on the contact slide 33 in the direction of the trailing edge 23 of the seat frame 3 are greater than the frictional forces between the smooth surfaces on the top side
10 47 of the contact slide 33 and the underside 24 of the latch plate 22. According to the invention therefore the latch elements 49, 54 of contact slide 33 and latch plate 22 in this position are meshed in one another and form a self-arresting latch pawl, cf. Figures 7 and 10. The shearing
15 forces can be absorbed, whereby the mechanical stability of the construction in a pivoted chair back frame 7 is guaranteed. At the same time, the smooth outer regions 56 of the T-legs 38 of the contact slide 33 rest on the smooth edge regions 55 of the latch plate underside 24.

20

As a result this means that the contact slide 33 can no longer be moved in a longitudinal direction 19. Therefore neither can any adjustment of the resilient force of the torsion springs 27 be made in this rear position. At the same
25 time, the abovementioned construction elements are aligned to one another such that when the chair back frame 7 is in the rear position the block 48 lies freely in the rectangular opening 53 and does not contact the underside 57 of the seat plate 4.

30

If the chair back frame 7 swivels back into its front position (cf. Figure 11 and 13), the distance 58 between the block 48 and the underside 57 of the seat plate 4 continues

to lessen until the block 48 rests on the seat plate 4. The underside 57 of the seat plate 4 is designed correspondingly.

If the chair back frame 7 then swivels further into its front position (see direction of pivoting 25 in Figure 7) the block 48 collides with the immovable seat plate 4. Since the contact slide 33 is supported by the free ends 51 of its T-legs 38 on the free legs 32 of the torsion springs 27, this causes sagging of the contact slide 33 in its top region, therefore in the region of the T-legs 38. At the same time, the more the contact slide 33 sags, the further the chair back frame 7 is pivoted back with its contact plate 22.

If the chair back frame 7 is swung back into its starting position the smooth outer regions 56 of the T-legs 38 of the contact slide 33 are still resting on the smooth edge regions 55 of the latch plate underside 24. The latch elements 49, 54 of contact slide 33 and latch plate 22 are however no longer meshed in one another, but lie free, cf. Figure 8. Since there are no shearing forces in this position, meshing is also no longer necessary. No force constituents of the torsion springs 27 are acting on the contact slide 33 in the direction of the trailing edge 23 of the seat frame 3, since chair back frame 7 and torsion springs 27 are lying parallel to one another and the angle of rotation is zero.

As a result, this means that the contact slide 33 can now be moved in the longitudinal direction 19. Adjustment of the resilient force of the torsion springs 27 can now occur.

30

Blocking wedges 59 act to fix the front position, and are arranged inside the seat frame 3 on a blocking device 60 and can be pivoted in the direction of pivoting 61 from a rest

position to a blocking position, in which they engage with their free ends 62 on the underside 24 of the latch plate 22 and prevent pivoting of the latch plate 22 and thus pivoting of the chair back frame 7. The blocking wedges 59 can be
5 actuated by means of an actuating element, not illustrated in greater detail, from outside the seat frame 3. For this, a fastening for a Bowden cable is provided on the blocking device 60, by means of which the blocking device can be pivoted altogether.

10

With further pivoting of the chair back frame 7 rearwards separation of the block 48 from the underside 57 of the seat plate 4 occurs. This results in the contact slide 33 again being released and approaching the underside 24 of the latch
15 plate 22. The latch elements 49, 54 engage again so that adjusting the resilient force of the torsion springs 27 is no longer possible.

The cog 44 is actuated to adjust the resilient force in the
20 front position, whereby a position change of the contact slide 33 occurs in a longitudinal direction 19. At the same time, the positions of the U-shaped grooves 39 on the free legs 32 of the torsion springs 27 change, and thus the articulation points 63 of the torsion springs 27 on the chair
25 back frame 7 which rests on the contact slide 33.

The resilient force adjustment now takes place "feebly" according to the invention, specifically such that the length of the effective lever arm - therefore of the smallest, i.e.
30 vertical distance between the line of influence of the resilient force and the fulcrum 35 - can be changed by a change in position of the articulation points 63 of the free leg 32 of the torsion springs 27 on the latch plate 33 of the

chair back frame 7, without effort having to be directed against the resilient force of the torsion springs 27. This enables particularly easy resilient force adjustment.

5 The permanent contact mechanism can be set to "easy" or "hard". With an "easy" setting (as shown in Figure 4, 5, 9, 10, 11 and 12) the articulation points 63 are pushed in the grooves 39 on the T-legs 38 by means of the rack gear in the direction of the free ends 64 of the free legs 32 of the
10 torsion springs 27, resulting in comparatively long lever arms. The force constituents of the torsion springs 27 acting on the contact slide 33 in the direction of the trailing edge 23 of the seat frame 3 in the pivoted state (cf. Figure 12) are comparatively minimal.

15 In the case of "hard" setting (as shown in Figures 13 and 14) the articulation points 63 are shifted by means of the rack gear in the direction of the fulcrums 35 of the torsion springs 27, resulting in comparatively short lever arms. The
20 force constituents of the torsion springs 27 acting on the contact slide 33 in the direction of the trailing edge 23 of the seat frame 3 in the pivoted state (cf. Figure 12) are comparatively big.

25 The construction described in the present invention provides a permanent contact mechanism 1 which has an extremely flat structural form. This is accomplished substantially by the inventive separation of the position of the fulcrum 35 of the torsion springs 27 from the position of the pivot axis 6 of
30 the chair back frame 7.

Instead of an intrinsically resilient lever element, such as the torsion spring 27 used here, other constructive

arrangements can understandably also be employed to achieve the inventive function. Non-resilient construction parts can also be used in particular as lever elements which are impacted by a spring, for example a draw or compression
5 spring.

Legend

	1	permanent contact mechanism
	2	conical flange
5	3	seat frame
	4	seat plate
	5	leading edge of the seat frame
	6	pivot axis of the chair back frame
	7	chair back frame
10	8	bearer
	9	chair back
	10	(free)
	11	cradle
	12	pivot axis of chair back
15	13	front end of the chair back frame
	14	bearer main element
	15	crossmember
	16	recess
	17	corresponding part
20	18	recess
	19	longitudinal direction
	20	(free)
	21	seat leading edge
	22	latch plate
25	23	trailing edge of the seat frame
	24	underside of the latch plate
	25	direction of pivoting
	26	transverse direction
	27	torsion spring
30	28	fixed leg
	29	opening
	30	(free)
	31	underside of the seat frame

	32	free leg
	33	contact slide
	34	prism
	35	middle point of the torsion spring
5	36	horizontal plane
	37	underside of the T-leg
	38	T-legs
	39	groove
	40	(free)
10	41	underside of the T base
	42	T base
	43	gear rack
	44	cog
	45	recess
15	46	shaft
	47	top side of the contact slide
	48	block
	49	latch element
	50	(free)
20	51	free end of the T-leg
	52	top side of the T-leg
	53	opening
	54	latch element
	55	edge region
25	56	outer region
	57	underside of the seat plate
	58	distance
	59	blocking wedge
	60	blocking device
30	61	direction of pivoting
	62	free end of the blocking wedge
	63	articulation point
	64	free end of the free leg

Claims

1. Permanent contact mechanism (1) for an office chair or the like,
 - 5 - with a seat frame (3) placeable on a chair column,
 - with a chair back frame (7) arranged pivotably about a pivot axis (6) on the seat frame (3),
 - with at least one spring-loaded or intrinsically resilient lever element (27) which cooperates with the chair back frame
 - 10 (7) such that pivoting of the chair back frame (7) occurs constantly against a resilient force, whereby the position of the lever fulcrum (35) of the lever element (27) is different from the position of the pivot axis (6).
- 15 2. Permanent contact mechanism (1) according to Claim 1, wherein the position of the lever fulcrum (35) of the lever element (27) lies substantially on a horizontal plane with the position of the pivot axis (6).
- 20 3. Permanent contact mechanism (1) according to Claim 1 or 2, wherein the position of the lever fulcrum (35) of the lever element (27) is located directly above the chair column.
4. Permanent contact mechanism (1) according to any one of
- 25 Claims 1 to 3, with a resilient force adjustment such that the length of the effective lever arm can be changed without effort having to be directed against the resilient force via a change in the position of the articulation point (63) of a lever arm (32) of the lever element (27) on the chair back
- 30 frame (7).
5. Permanent contact mechanism (1) according to Claim 4, wherein a change in the position of the articulation point

(35) takes place via shifting a contact element (33) arranged between chair back frame (7) and lever arm (32) on the lever arm (32), whenever the chair back frame (7) is in a non-pivoted position.

5

6. Permanent contact mechanism (1) according to Claim 5, wherein shifting of the contact element (33) when the chair back frame (7) is in a pivoted position is prevented by a device (22) arranged on the chair back frame (7) itself.