

AVERAGING ORIFICE PRIMARY FLOW ELEMENT

FIELD OF THE INVENTION

[0001] The present invention relates generally to a process flow device that includes a self-averaging orifice plate type of primary flow element for measuring, by a differential pressure process, the volumetric rate of fluid flow at a point in a fluid carrying conduit where the velocity profile of the fluid is asymmetric with respect to the longitudinal axis of the conduit.

BACKGROUND OF THE INVENTION

[0002] Orifice plate flow meters having a single centered opening in a plate constriction that is disposed diametrically within a fluid-carrying pipe, with differential pressure measurement means on the upstream and downstream sides of the constriction, have been in existence for a long period of time. While the accuracy of such devices is good for long runs of pipe, orifice plate flow meters suffer the disadvantage of poor performance when placed in short pipe runs that follow a flow disturbance created by upstream apparatus, such as an elbow, expander, reducer, valve or other discontinuity. For measurement accuracy with an orifice plate flow meter, a long straight run of pipe (in excess of ten diameters in some instances) upstream of the flow meter is required in order to present a fully developed symmetrical velocity profile to the orifice plate, with the highest fluid velocity occurring coaxially with the center of the orifice plate constriction. When an upstream pipe fitting or other device skews the velocity profile, the pressures measured at the orifice flow meter pressure taps is in error.

[0003] To reduce the asymmetry of the velocity profile created by an upstream fitting, the commonly used apparatus is a flow straightener, of the type disclosed in U.S. Patent No. 5,596,152 or apparatus similar to the flow conditioner described in U.S. Patent No. 3, 733, 898. A more complex apparatus, employing a plurality of elongated openings arranged in a predetermined pattern in a transversely disposed plate within the fluid-conducting pipe, together with a computer to deal with the necessary algorithms, is disclosed in U.S. Patent No. 5,295,397. Yet another device for reducing the adverse measuring effects of a distorted velocity profile is known as the piezometer ring. This appliance may surround the orifice on both sides of the orifice plate and, by means of a plurality of circumferentially disposed pressure sensing ports, averages pressures around the upstream and downstream sides of the orifice. Although not shown with an orifice plate flow meter, a piezometer type of averaging sensor is described generally in U.S. Patent No. 5,279,155.

[0004] Flow straighteners, conditioners, computers and piezometers are moderately effective to properly condition the velocity profile for introduction to an orifice plate flowmeter, or average the asymmetric velocity of the flow, but have the disadvantage of adding separate and additional components to the process piping with the attendant initial cost, pressure drop in the fluid, and increased maintenance requirements.

[0005] Accordingly, the primary object of the present invention is to provide a primary flow element that achieves the accuracy benefits of the orifice plate type of flow meter, but is not restricted to long runs of upstream piping prior to the flow meter's positioning in the pipe.

[0006] A corresponding objective of the invention is to provide a primary flow element where the means for interrupting the fluid flow is a differential pressure orifice plate that achieves an averaging of the differential pressures across the plate, despite velocity profile distortion of the fluid presented to the primary flow element, and without the added piezometer and its computer, flow straightening or flow conditioning apparatus.

[0007] Other and further objects, features and advantages of the invention will become apparent from the following description of embodiments of the invention, taken in conjunction with the accompanying drawings.

SUMMARY OF THE INVENTION

[0008] The successful operation of traditional orifice plate flow meters is based on Bernoulli's theorem which states that along any one streamline in a moving fluid, the total energy per unit mass is constant, being made up of the potential energy, the pressure energy and the kinetic energy of the fluid. Thus, when fluid passes through the orifice in a constricting pipe plate, the velocity of the fluid through the orifice increases. This increase in fluid velocity causes the dynamic pressure of the fluid immediately downstream of the orifice plate to increase, while simultaneously decreasing the static pressure of the fluid at that same point. By sensing the static pressure on the upstream and downstream sides of the orifice plate, the decrease of static pressure on the downstream side results in a measurement of the pressure differential, dP , between the upstream side of the orifice plate and the downstream side. The rate of fluid flow q is proportional to $\sqrt{dP}$. As earlier stated, prior art orifice plate flow meters work well when the

velocity profile is symmetrical about the longitudinal axis of the pipe in which the fluid is flowing. In such a case, the highest velocity fluid is along the central axis of the pipe, coaxial with the orifice of the constricting pipe plate. When traveling through the orifice, the highest velocity fluid is the fluid that produces the pressure differential across the plate to provide the flow rate result.

[0009] However, if the velocity profile is skewed a lower velocity fluid will pass through the orifice and the downstream static pressure will be a reflection of that lower velocity fluid. The differential pressure thus produced across the constricting plate will not be a true indication of the rate of fluid flow.

[0010] According to the present invention, a constrictive plate, or flow impedance device, having a plurality of variously positioned orifices is placed in a fluid-carrying conduit with static pressure measurement taken on the upstream and downstream sides of the plate. Each of the plurality of orifices will conduct a part of the total fluid flow within the conduit. According to Bernoulli's theorem, the velocity of the fluid through each of the orifices will increase, and the static fluid pressure on the downstream side of the constricting plate that is attributable to each of the separate orifices will be averaged within the fluid to provide an average downstream static pressure. The average downstream static pressure is compared with the upstream static pressure to provide an average differential pressure for whatever velocity profile is presented to the multiple orifice plate, resulting in an accurate measurement of the rate of fluid flow in the pipe.

[0011] Integrally incorporating the multiple orifice plate into the central opening of an annular ring with intermediate upstream and downstream static pressure measuring ports disposed within the ring,

provides added simplicity to the primary flow element. This simplicity is further enhanced when the annular ring is provided with a projecting stem that is capable of conducting the sensed differential pressure to other flow processing accessories mounted on the stem.

DESCRIPTION OF THE DRAWINGS

[0012] Figure 1 is a perspective exploded view of an averaging orifice primary flow element of the present invention positioned between two opposing mounting flanges fixed to the ends of a fluid carrying conduit. Dashed lines indicate the connection of accessory flow processing devices with the upstream and downstream pressure ports disposed within the mounting flanges.

[0013] Figure 1A is a fragmentary cross sectional view of the piping and primary flow element of Figure 1, illustrating a representative velocity profile of the fluid in the pipe that would exist shortly downstream of an elbow in the piping.

[0014] Figures 2, 2A and 2B are plan views of three different configurations of the averaging orifice primary flow element of the present invention. The views are taken from a position downstream of the orifice plate, looking upstream.

[0015] Figure 3 is a cross sectional view taken along lines 3-3 of Figure 2A.

[0016] Figure 4 is an enlarged fragmentary detail of a portion of Figure 3.

[0017] Figure 5 is a perspective view of the embodiment of the present invention wherein the averaging orifice primary flow element is integrally incorporated intermediate the ends of an annular mounting

ring with a projecting pressure communicating stem that mounts a valve-carrying manifold.

[0018] Figure 6 is a fragmentary perspective view of the Figure 5 embodiment of the present invention, as supported between opposing mounting flanges on the ends of a fluid carrying conduit.

[0019] Figure 7 is an exploded view of the assembly of Figure 6.

[0020] Figure 8 is a prospective view of a modified form of the annular mounting ring of Figure 5 wherein the annular ring supports a pitot tube type of primary flow element instead of the averaging orifice plate, as shown in Figure 5.

DETAILED DESCRIPTION

[0021] A simplified version of the present invention is shown in Figures 1 and 1A. An averaging orifice primary flow element 2 is positioned between two opposing mounting flanges 4 and 6 fixed to the ends of a fluid-carrying conduit 8 just below an elbow 9 where the velocity profile 7 is skewed. Each of the mounting flanges contain a radially extending pressure sensing port 10 and 12 that communicate with the fluid flowing in the pipe and are respectively connected through conduits 14 and 16 to a valve manifold 18 and into a pressure transducer 19. An electrical signal that represents the sensed differential pressure between the ports 10 and 12 is transmitted by transmitter 20 to a processing unit (not shown).

[0022] The primary flow element 2, also shown in figure 2, comprises a circular plate having four apertures 22 symmetrically arranged around the center of the plate 2. The center of the flow element plate 2 is positioned coaxially with the longitudinal centerline of the pipe 8. The plate 2 is retained in place by the sandwiching

pressure of flanges 4 and 6. As shown in Figures 3 and 4, the circumferential edges 24 of the apertures 22 on the downstream side of the flow element plate 2 are preferably, but not necessarily, chamfered in order to facilitate expansion of the fluid column that flows through each aperture.

[0023] Figures 2A and 2B illustrate additional embodiments of the primary flow element in which there are an increased plurality of apertures 22A and 22B clustered around the center of primary flow element plates 2A and 2B. While the invention will be described with respect to the four aperture embodiment of Figure 2, it is understood that four apertures in the primary flow element plate is only one of many possible configurations of apertures. One particular configuration and number of apertures may be more appropriate to a given fluid, fluid profile and piping characteristics than another. However, the principal of operation is the same, regardless of the number or location of apertures in the constricting plate. The number or configuration of apertures is not limited by the illustrations of Figures 2 through 2B.

[0024] It is seen from Figure 1A that the velocity of the fluid approaching the upper pair of apertures 22 in the constricting plate 2 is less than the velocity of the fluid approaching the lower pair of apertures 22. These initial differences in fluid velocity will not only influence the static pressure sensed by the pressure port 10 on the upstream side of the plate 2, they will also impact the velocity of the fluid that passes through the respective pairs of apertures and accordingly, will affect the static fluid pressure sensed by the downstream port 12. Because the velocity of fluid through each of the apertures, or each pair of apertures, will be different, the static pressure on the downstream side of the plate 2 that is a function of

the fluid velocity through each of the apertures will be averaged within the fluid and the downstream pressure port 12 will sense that averaged static pressure. With a plurality of apertures positioned around the center of the plate 2, such as, for example, the four apertures 22 shown in Figures 2 and 5, the static pressure will be averaged, even when the fluid profile is nonsymmetrical about two pipe axes, as it would be when the fluid is swirling.

[0025] A modified form of a four-aperture primary flow element plate 30 is shown in Figure 5, integrally formed with the annular ring, or wafer, 32 that is insertable between the flanges 34 and 36 attached to the ends of two sections of a fluid-carrying pipe 40. Upstream and downstream pressure sensing ports 35 and 37 are located on each side of the flow element plate 30, as seen in Figure 6. The pressure sensing ports 35 and 37 connect through conduits 39 and 41 in the stem 45 to conduits 46 and 47 in the manifold 18. The Figure 5 embodiment is also illustrated in Figures 6 and 7, illustrating the total flow meter assembly inserted between pipe sections that carry the fluid whose flow rate is to be measured.

[0026] The wafer 32 is an annular ring whose inside diameter corresponds to the inside diameter of the fluid-carrying pipe 40. The flow element plate 30 is positioned across the ring opening substantially equi-distant from each of the lateral sides of the wafer ring 32. The wafer is mounted between two gaskets 48 and 49 that interface with the pipe end flanges 34 and 36. A semi-circular positioning ring 50 functions to position and secure the wafer 32 in its proper place between the pipe flanges. Positioning of the wafer 32 is achieved by placing it into the cradle formed by the interior of the ring

50 and seating the shanks of the fastening bolts 55 into the outer grooves of the ring.

[0027] With the averaging orifice plate 30 being integrally constructed with the mounting ring wafer 32 and the conduit carrying stem 45 and with the transmitter mounting manifold 18 being directly attached to the stem 45, several important advantages are achieved. Most importantly, the differential pressure generating mechanism, the pressure sensing ports, the manifold and the transmitter components are incorporated into a single unit that is easily insertable between the flanges of pipe sections. In addition, the differential pressure generating mechanism may comprise types of primary flow elements other than orifice plates. For example, as shown in Figure 8, an averaging pitot tube 70, such as that disclosed in U.S. Patent No. 6,321,166 B1, may be diametrically disposed across the opening of the ring wafer 32, with its high and low pressure conducting conduits connected to the conduits 71 and 72 housed in the stem 45.

CLAIMS

What is claimed is:

1 1. An averaging differential pressure primary flow measuring
2 element for insertion between sections of a fluid carrying conduit,
3 comprising,
4 first and second annular mounting flanges having circumferential
5 outside surfaces and interior openings that correspond in shape and
6 size to the inside cross section of the conduit,
7 planer flow impedance means having a center point, said means
8 being disposed between the first and second annular mounting flanges,
9 where the center point is coaxial with the longitudinal axes of the
10 interior openings of the flanges, and said means having
11 a plurality of circular apertures eccentrically disposed with
12 respect to the center point of the impedance means.

1 2. The apparatus of claim 1 where the flow impedance means
2 is a flat plate.

1 3. The apparatus of claim 2 where the first and second
2 annular mounting flanges are integrally formed as a single annular ring
3 having flat parallel sides and where the flat plate is disposed
4 transversely across the interior opening in the ring and parallel to the
5 sides of the ring.

1 4. The apparatus of claim 1 and further including,
2 first and second pressure conducting bores radially disposed in
3 the first and second flanges for establishing fluid communication

4 between the respective interior openings in the flanges and the
5 circumferential outside surfaces of the flanges.

1 5. The apparatus of claim 3 and further including,
2 first and second pressure conducting bores radially disposed in
3 the annular ring on opposite sides of the flat plate.

1 6. The apparatus of claim 5 and further including,
2 an elongated mounting stem radially extending from the
3 circumferential outside surface of the annular ring and having first and
4 second conduits longitudinally therethrough that communicate with the
5 respective first and second pressure conducting bores.

1 7. The apparatus of claim 1 where the circular apertures have
2 opposing circumferential edges, one of which is beveled.

1 8. An averaging differential pressure flow meter for
2 determining the volumetric rate of fluid flow in a circular conduit,
3 comprising,
4 an annulus where the central opening corresponds in shape and
5 size to the inside cross section of the circular conduit,
6 a disk, congruent with the central opening, and having a center
7 point, said disk being disposed within the central opening coincident
8 with a plane that is perpendicular to the longitudinal axis of the central
9 opening, said disk having a plurality of circular apertures eccentrically
10 disposed with respect to the center point of the disk.

1 9. The apparatus of claim 8 and further including,

2 a supporting arm extending radially from the annulus, said arm
3 including first and second interiorly disposed fluid transporting conduits
4 that extend into the annulus, and

5 first and second pressure sensing ports communicating with the
6 interior opening of the annulus on respective opposite sides of the disk.

1 10. The apparatus of claim 9 where the plurality of circular
2 apertures is four, comprising first and second pairs of apertures that
3 are bilaterally disposed with respect to the disk center point, and
4 where a line connecting the centers of the apertures defines a square.

1 11. The apparatus of claim 9 where the plurality of circular
2 apertures is three, said three apertures being disposed in a triangular
3 pattern around the center point of the disk.

1 12. The apparatus of claim 9 where the plurality of circular
2 apertures is five, comprising a comprising first and second pairs of
3 apertures that are bilaterally disposed with respect to the disk center
4 point and a single aperture spaced from the center point of the disk
5 and where a line connecting the centers of the apertures defines a
6 pentagon.

1 13. The apparatus of claim 9 where the plurality of circular
2 apertures is six, said apertures being spaced apart from the center
3 point of the disk and where a line connecting the centers of the
4 apertures defines a hexagon.

1 14. The apparatus of claim 8 where the circular apertures have
2 opposing circumferential edges, one of which is beveled.

1 15. The apparatus of claim 9 where the circular apertures have
2 opposing circumferential edges, one of which is beveled.

1 16. A differential pressure flow meter for determining the
2 volumetric rate of fluid flow in a circular conduit, comprising,
3 an annulus having,
4 a circumferential outside surface,
5 a central opening that corresponds in shape and size to the inside
6 cross section of the circular conduit, and
7 a pitot tube having upstream and downstream facing surfaces,
8 said tube being disposed within and diametrically across the central
9 opening.

1 17. The combination of claim 16 where the pitot-static tube
2 includes,
3 at least one total pressure port in the upstream facing surface,
4 at least one suction pressure port in the downstream facing
5 surface, and
6 total and suction pressure plenums within the tube connected in
7 fluid communication respectively to the total and static pressure ports.

1 18. The combination of claim 17 and further including,
2 first and second bores radially disposed in the annulus,
3 respectively connected in fluid communication with the total and static
4 pressure plenums.

1 19. The combination of claim 18 and further including,
2 a supporting arm extending radially from the annulus, said arm
3 including first and second interiorly disposed fluid transporting conduits
4 that extend into the annulus and connect in fluid communication with
5 the first and second bores in the annulus.

1 20. An averaging orifice plate fluid flow meter for measuring
2 the volumetric rate of fluid flow in a conduit, comprising,
3 a conduit for carrying fluid from an upstream to a downstream
4 location,

5 planar flow impedance means disposed transversely across the
6 interior of the conduit,

7 at least three circular apertures in the impedance means
8 eccentrically disposed with respect to the longitudinal axis of the
9 conduit,

10 first static pressure sensing means disposed within the conduit
11 upstream of the flow impedance means and proximate thereto, and

12 second static pressure sending means disposed with the conduit
13 downstream of the flow impedance means and proximate thereto.