



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 11/04, H02J 1/00, H01H 35/00	A1	(11) International Publication Number: WO 98/49824 (43) International Publication Date: 5 November 1998 (05.11.98)
(21) International Application Number: PCT/US98/08151 (22) International Filing Date: 22 April 1998 (22.04.98) (30) Priority Data: 08/850,275 29 April 1997 (29.04.97) US (71) Applicant: INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95054 (US). (72) Inventors: CONNELLY, Jay; 4415 N.W. Kahneeta Drive, Portland, OR 97229 (US). MCARTHUR, Kelly; 5860 S.W. 18th, Portland, OR 97201 (US). (74) Agents: TAYLOR, Edwin, H. et al.; Blakely, Sokoloff, Taylor & Zafman LLP, 17th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US).	(81) Designated States: AL, AM, AT, AT (Utility model), AU (Petty patent), AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	

(54) Title: CONTROL SYSTEM INCLUDING CIRCUITRY TO DETERMINE A POWER STATE**(57) Abstract**

A control system (50) includes remote computer circuitry (54) that controls at least one feature of an electronics device (56A), such as a television, through local control circuitry. The remote computer circuitry (68) and local control circuitry are separated from each other by a communication medium (60), such as a power line. Power is selectively provided to the electronics device (56A) through a conductor (86) connected to the power line. Power consumption sensing circuitry provides a power state signal indicative of whether the power signal is being provided through the conductor to the electronic device. Current monitoring circuitry may be used. Local control circuitry creates power state information indicative of the power state signal. In many cases, a different command will be given to control an electronic device (56A) that is on, than will be given to control the same electronic device (56A) that is off. The power state information is considered in selecting commands. In one embodiment, the power state information is considered by the remote computer circuitry (68). In another embodiment, the power state information is considered by the local control circuitry. The remote computer circuitry (68) may employ voice recognition circuitry and/or an electronic program guide to control a cluster of consumer electronic devices.

