

The invention claimed is:

1. A cartridge comprising:

a frame;

a rotatable carrying member for carrying developer;

a rotatable member rotatably supported by the frame;

a coupling member rotatable about a rotational axis thereof and including a first portion provided with a through-hole and a second portion more remote from the rotatable member than the first portion, the coupling member being movable between a first position in which the rotational axis of the coupling member is coaxial with a rotational axis of the rotatable member and a second position in which the rotational axis of the coupling member is inclined relative to the rotational axis of the rotatable member;

a shaft portion penetrating the through-hole so that the coupling member is movable relative to the shaft portion, and having opposite end portions supported by the rotatable member; and

an urging member urging the coupling member toward the second position.

2. A cartridge according to claim 1, wherein the rotatable carrying member is a photosensitive drum.

3. A cartridge according to claim 1, wherein the rotatable carrying member is a developing roller.

4. A cartridge comprising:

a frame;

a rotatable carrying member for carrying developer;

a rotatable member rotatably supported by the frame;

a coupling member rotatable about a rotational axis thereof and including a first portion provided with a through-hole and a second portion more remote from the rotatable member than the first portion, the coupling member being movable between a first position in which the

rotational axis of the coupling member is coaxial with a rotational axis of the rotatable member and a second position in which the rotational axis of the coupling member is inclined relative to the rotational axis of the rotatable member; and

a shaft portion penetrating the through-hole and having opposite end portions supported by the rotatable member,

wherein an angle formed between the rotational axis of the coupling member and the rotational axis of the rotatable member when the inclination of the coupling member is limited by contact between the coupling member and the frame is larger than an angle formed between the rotational axis of the coupling member and the rotational axis of the rotatable member when the inclination of the coupling member is limited by contact between the shaft portion and the through-hole.

5. A cartridge according to claim 4, wherein the rotatable carrying member is a photosensitive drum.

6. A cartridge according to claim 4, wherein the rotatable carrying member is a developing roller.