

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(10) 国际公布号
WO 2022/021405 A1

(43) 国际公布日
2022 年 2 月 3 日 (03.02.2022)

(51) 国际专利分类号:

H04W 56/00 (2009.01) *H04W 84/06* (2009.01)
H04W 74/08 (2009.01)

(21) 国际申请号: PCT/CN2020/106376

(22) 国际申请日: 2020 年 7 月 31 日 (31.07.2020)

(25) 申请语言: 中文

(26) 公布语言: 中文

(71) 申请人: 北京小米移动软件有限公司 (BEIJING XIAOMI MOBILE SOFTWARE CO., LTD.) [CN/CN]; 中国北京市海淀区西二旗中路33号院6号楼8层018号, Beijing 100085 (CN)。

(72) 发明人: 江小威 (JIANG, Xiaowei); 中国北京市海淀区西二旗中路33号院6号楼8层018号, Beijing 100085 (CN)。

(74) 代理人: 北京博思佳知识产权代理有限公司 (BEIJING BESTIPR INTELLECTUAL PROPERTY LAW CORPORATION); 中国北京市海淀区上地三街9号嘉华大厦B座409室, Beijing 100085 (CN)。

(81) 指定国 (除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU,

CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW。

(84) 指定国 (除另有指明, 要求每一种可提供的地区保护): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), 欧亚 (AM, AZ, BY, KG, KZ, RU, TJ, TM), 欧洲 (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG)。

本国际公布:

— 包括国际检索报告 (条约第21条 (3))。

(54) Title: RANDOM ACCESS METHOD AND APPARATUS, AND CONFIGURATION INDICATION METHOD AND APPARATUS

(54) 发明名称: 随机接入方法和装置、配置指示方法和装置

响应于终端自主确定定时提前量, 根据第一接收时机信息在随机接入过程中接收基站的反馈信息; 响应于所述终端非自主确定定时提前量, 根据第二接收时机信息在随机接入过程中接收基站的反馈信息; 其中, 所述第一接收时机信息和所述第二接收时机信息不同

图 1

S101 In response to a terminal autonomously determining a timing advance, according to first reception occasion information, receive feedback information of a base station during a random access process, and in response to a terminal non-autonomously determining the timing advance, according to second reception occasion information, receive the feedback information of the base station during the random access process, wherein the first reception occasion information is different from the second reception occasion information

(57) Abstract: A random access method and apparatus, and a configuration indication method and apparatus. The random access method comprises: in response to a terminal autonomously determining a timing advance, according to first reception occasion information, receiving feedback information of a base station during a random access process; and in response to a terminal non-autonomously determining the timing advance, according to second reception occasion information, receiving the feedback information of the base station during the random access process, wherein the first reception occasion information is different from the second reception occasion information. When a timing advance is autonomously determined, it is easy to reduce the amount of time consumed by a random access process. Moreover, when a timing advance is non-autonomously determined, it is easy to ensure that feedback information of a base station can be received so as to successfully complete a random access process.

(57) 摘要: 随机接入方法和装置、配置指示方法和装置, 其中, 随机接入方法包括: 响应于终端自主确定定时提前量, 根据第一接收时机信息在随机接入过程中接收基站的反馈信息; 响应于终端非自主确定定时提前量, 根据第二接收时机信息在随机接入过程中接收基站的反馈信息; 其中, 第一接收时机信息和第二接收时机信息不同。在自主确定定时提前量的情况下, 便于缩短随机接入过程的耗时。而在非自主确定定时提前量的情况下, 便于确保能够接收到基站的反馈信息, 从而顺利完成随机接入过程。

WO 2022/021405 A1