

This Sheet Has Been Replaced



1

REPLACED SHEETS SG

☒ Description : paged 1 to paged 22
☒ Claim(s) : paged 23 to paged 45
☒ Drawing(s) : paged 1 to paged 10
☒ Abstract : paged 46 to paged 47

INK-SUPPLIED PRINTER HEAD AND INK SUPPLY TANK

BACKGROUND OF THE INVENTION

This is a continuation-in-part application of pending application Serial No. 08/357,639 filed December 16, 1994 entitled INK-SUPPLIED PRINTER HEAD AND INK CONTAINER, which is a continuation-in-part application of application Serial No. 08/150,676, filed November 10, 1993, which issued as U.S. Patent No. 5,421,658, which is a continuation of application Serial No. 07/962,959, filed October 16, 1992, which issued as U.S. Patent No. 5,328,279, which is a continuation of application Serial No. 07/612,010, filed on November 9, 1990, which issued as U.S. Patent No. 5,156,471, which is a continuation of application Serial No. 07/401,539, filed on August 31, 1989, which issued as U.S. Patent No. 4,969,759, which is a continuation of application Serial No. 07/161,216, filed on February 17, 1988, now abandoned, which is a continuation of application Serial No. 07/035,251, filed on March 23, 1987, now abandoned, which is a continuation of application Serial No. 06/873,871, filed on June 12, 1986, now abandoned, which is a continuation of application Serial No. 06/659,816, now abandoned.

The present invention relates generally to an ink-supplied printer head being supplied with ink from an ink supply tank and more particularly to an ink supply tank which allows for the continuous supply of ink to the printer head while avoiding adverse effects from temperature, atmospheric changes or vibrations. The present invention allows for a larger volume of ink in the ink supply tank and allows for a greater percentage of the ink in the tank to be transferred to the printer head. Also, the present invention comprises a tank with transparent sides so the user is able to easily determine the remaining quantity of ink, and also means for dampening of the unwanted movement of ink within the ink supply tank.

This invention also relates to an ink cartridge for an ink jet printer in which an ink jet recording head, and an ink cartridge are mounted on a movable carriage, and in particular an



ink jet cartridge in which upon depletion of the ink from the old cartridge, is replaced with a new ink cartridge.

Ink supply systems for a wire dot matrix printer are known in which no ink ribbon is used, but ink is supplied from an ink tank to the distal ends of the wire and transferred from the wires directly to a sheet of print paper. Portions of these ink supply systems, including the supply tanks thereof, are also adaptable to be used in ink jet type printers.

In the parent applications to this application, improved ink storage and delivery was achieved by providing a porous member in an ink tank that essentially filled the tank and carried essentially the entire supply of ink. It was found that while this construction offered substantial improvement over the prior art, the use of the full porous member limited the quantity of ink which would be stored in an ink tank of a given size, increasing the frequency of ink tank replacement.

A prior art ink jet printer in which an ink containing unit and an ink jet recording head are mounted on a carriage is disclosed in European Patent Publication No. 581,531. In the disclosed printer, in order to prevent printing failures caused by variation of the ink level or air bubbles due to movement of the ink cartridge, which is caused by the movement of the carriage, the ink container is divided into two regions. A first region of the container adjacent the recording head houses ink impregnated in a porous member, and a second region contains liquid ink without a porous member. This structure enables the ink to be conducted to the recording head via the porous member so that the problems arising from movement of the ink in the cartridge are prevented from occurring to a certain extent.

The porous member is held in fluid communication with the recording head by a projecting member which is inserted through a hole formed in the side portion of the container. However, such a structure cannot be applied to a recording head in which air bubbles must be stopped from entering a ^{pressure} ~~pressurized~~ chamber, such as that for an ink jet printer in which a piezoelectric vibrator is used as an actuator for ink ejection.



Accordingly, a ink jet printer which solves the above-mentioned problems is derived.

SUMMARY OF THE INVENTION

Generally speaking, in accordance with the present invention, there is provided an ink-supplied printer ~~head~~. Ink is supplied to ^athe printer head by an ink supply system, including an ink tank having an ink supply port and a pair of side walls. An ink absorbing member is contained therein adjacent the ink supply port which occupies less than the total volume of the ink tank. ~~A plurality of support members extend within the ink tank between the opposed side walls, positioned to locate the ink absorbing member against the ink supply port and for dampening movement of the ink in the portion of the ink supply tank not occupied by the ink absorbing member.~~ The walls of the ink supply tank may be transparent so the user can more easily determine the amount of ink remaining in the ink supply tank.

An ink receiving and transferring member terminating in an ink port may extend into the ink tank, in which case the ink absorbing member abuts and is locally compressed by the ink receiving and transmitting member. The ink receiving and transmitting member has a capillary ink path communicating with the printer head and is supplied with ink from the ink absorbing member.

More specifically an ink cartridge is formed of a ink chamber for storing ink and a foam chamber for receiving a porous member for absorbing ink. A partition separates the ink chamber from the foam chamber and has a hole therein so that the foam chamber is in fluid communication with the ink chamber. The ink cartridge is also formed with an ink supply port. A funnel shaped packing member is disposed within the supply port and supplies ink to a recording head by generation of a pressure difference through the porous member. The packing member is disposed facing upward in the ink supply port. The packing member is resilient.

When an ink supply needle of the recording head is inserted into the ink supply port, the tip of the needle



resiliently contacts with the packing member. Since the packing member has a funnel-like shape which opens upward, the packing member is easily deformed so as to follow the ink supply needle. Furthermore, the packing member is caused to closely contact with the needle by its resiliency. Therefore, a relative misalignment between the ink supply needle and the ink supply port can be accommodated so that the ink supply port is securely sealed.

Accordingly, it is an object of the invention to provide an improved ink cartridge for an ink jet printer.


It is an object of the present invention to provide a high-quality and highly reliable ink-supplied printer ~~head~~ of a simple construction which is capable of supplying a stable and appropriate quantity of ink from an ink tank to ^athe printer head and is less subject to the influence of environmental changes such as temperature or atmospheric variations.

It is a further object of the invention to provide a cartridge for an ink jet printer which can be mounted using minimal force and with a large tolerance for misalignment of the ink supply needle, which can cooperate with a recording head to attain a sufficient hermetic seal, while producing a dead space as small as possible.

Yet another object of the invention is to prevent air bubbles from entering the recording head while maintaining a negative pressure in the chamber containing the porous member.

Still other objects, features and advantages of the present invention will become more apparent from the following description when taken in conjunction with the accompanying drawings in which preferred embodiments of the present invention are shown by way of illustrative example and not in a limiting sense.

The invention accordingly comprises the several steps and relation of one or more of such steps with respect to each of the others, and the apparatus embodying features of construction, combinations of elements and arrangement of parts which are adopted to effect such steps, all as exemplified in the following detailed disclosure, and the scope of the invention will be indicated in the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a full understanding of the invention, reference is had to the following description taken in connection with the accompanying drawings, in which:

FIG. 1 is an exploded perspective view of a wire dot printer head according to an embodiment of the present invention;

FIG. 2 is a vertical cross-sectional view of the printer head shown in FIG. 1;

FIG. 3 is an exploded perspective view of an ink guide for use with a wire dot printer according to the present invention;

FIG. 4 is a perspective view, partly cut away, of an ink tank according to the present invention;

FIG. 5 is a side elevational view showing the manner in which said ink tank is mounted in place on a print head;

FIG. 6 is a vertical cross-sectional view of an ink guide for a wire dot printer according to another embodiment of the present invention;

FIG. 7 is an exploded perspective view of an ink guide for a wire dot printer according to another embodiment of the present invention;

FIG. 8 is an exploded perspective view of an ink tank according to a still further embodiment of the present invention;

FIG. 9 is a perspective view, partly broken away, of an ink tank according to the invention;

FIG. 10 is a schematic view illustrative of the manner in which air trapped in the ink tank of FIG. 9 is expanded;

FIG. 11 is a schematic view of an arrangement of wires according to the present invention used with a seven-color wire dot printer;

FIG. 12 is a perspective view of an ink tank according to a further embodiment of the present invention with the cover removed, shown exploded from an ink jet print head;

FIG. 13 is a cross-sectional view of the ink tank of FIG. 12;



FIG. 14 is a perspective view of an ink tank with the cover removed according to a still further embodiment of the present invention;

FIG. 15 is a side cross-sectional view of the ink tank of FIG. 14;

FIG. 16 is a perspective view of an ink tank with the cover removed according to a still further embodiment of the present invention;

FIG. 17 is a cross-sectional view of the ink tank of FIG. 16;

FIG. 18 is a side elevational view of an ink jet type printer of the present invention with the ink supply tank in cross section.

FIG. 19 is a perspective view of an ink tank according to still another embodiment of the present invention shown exploded from an ink jet print head;

FIG. 20 is a cross-sectional view of an ink tank according to a still further embodiment of the present invention;

FIG. 21 is a cross-sectional view of an ink tank according to a further embodiment of the present invention; and

FIG. 22 is a cross sectional view of an ink tank according to a further embodiment of the present invention.

FIG. 23² is a cross-sectional view of a multi-color ink jet printer cartridge constructed in accordance a first ~~additional~~ embodiment of the invention;

FIG. 24³ is a cross-sectional view of the first ~~additional~~ embodiment rotated 90° from the view in FIG. 23²;

FIG. 25⁴ is a perspective view showing the ink cartridge of FIGS. 23² and 24³ with the lid removed;

FIG. 26⁵ is a perspective view showing a single color ink cartridge constructed in accordance with a second ~~additional~~ embodiment of the invention;

FIG. 27⁶(a) is a ^{top}bottom plan view of the lid of FIG. 23²;

FIG. 27⁶(b) is a ^{top}bottom plan view showing the lid with a seal affixed thereto;

Fig. 1 is a schematic view showing an ink supply system of an ink-jet type recording apparatus according to one embodiment of the present invention;



FIG. ⁷~~28~~(a) is a cross-sectional view showing a packing member with an ink supply needle inserted therein in accordance with the invention;

FIG. ⁷~~28~~(b) is a cross-sectional view of the packing member prior to insertion;

FIG. ⁸~~29~~ is a graph showing the relationships of the ink consumption, the ^{pressure}~~ink~~ level, and the amount of ink remaining in an ink chamber;

FIG. ⁹~~30~~ is a partial cross-sectional view of the ink cartridge showing the boundary between ink and foam chambers in accordance with a third ~~additional~~ embodiment of the invention;

FIG. ¹⁰~~31~~ is a partial cross-sectional view of the ink cartridge showing the boundary between ink and foam chambers in accordance with a fourth ~~additional~~ embodiment of the invention;

FIG. ¹¹~~32~~ is a partial cross-sectional view of the boundary between ink and foam chambers of an ink cartridge constructed in accordance with a fifth ~~additional~~ embodiment of the invention;

FIG. ¹²~~33~~ is a cross-sectional view taken along line 33-33 of FIG. ¹¹~~32~~;

FIG. ¹³~~34~~ is a partial cross-sectional view showing the boundary between ink and foam chambers of an ink cartridge constructed in accordance with a sixth ~~additional~~ embodiment of the invention;

FIG. ¹⁴~~35~~ is a cross-sectional view taken along line 35-35 of FIG. ¹³~~34~~;

FIG. ¹⁵~~36~~ is a cross-sectional view showing an ink cartridge constructed in accordance with a seventh ~~additional~~ embodiment of the invention;

FIG. ¹⁶~~37~~ is a cross-sectional view showing an ink cartridge constructed in accordance with a eighth ~~additional~~ embodiment of the invention;

FIG. ¹⁷~~38~~ is a cross-sectional view showing an ink cartridge for an ink jet printer constructed in accordance with a ninth ~~additional~~ embodiment of the invention; and

FIG. ¹⁸~~39~~ is a cross-sectional view of the ninth ~~additional~~ embodiment of the invention rotated 90° from FIG. ¹⁷~~38~~.



DESCRIPTION OF THE PREFERRED EMBODIMENTS

A printer head according to the present invention may be used in four-color printer plotter or color image printer and has four-color ink systems and ~~wires or~~ ink jets corresponding respectively to four ink colors. The four-color printer plotter employs black, red, green and blue inks, and moves the head or a sheet of print paper or both and then ~~projects a wire, or~~ ejects ink ~~without the use of a projecting wire~~ as in a conventional ink jet print head, corresponding to a desired one of the colors against the print paper at a prescribed position thereon to form an ink dot. Desired characters and figures can thus be recorded by repeating the above cycle. The present invention is applicable to ink jet printers of all varieties, including print heads using heat from heated resistors or the like or the displacement of piezoelectric or with transducers to project a drop of ink from a chamber upon application of a print signal. The ink supply tanks according to the invention can supply ink continuously to said chambers through capillary paths.

In a color image printer using inks of four colors, that is, black, red, green and blue, a sheet of print paper is scanned by a printer head in a direction perpendicular to the direction of feed of the print paper to form one-dot line in one scanning stroke, and the print paper is fed along by line pitches to record images. In seven-color printers, inks of four colors, that is, black, yellow, magenta and cyan, are used, and the colors of red, green and blue are formed on a sheet of print paper by superimposing inks of two out of the three desired colors other than black, thereby recording color images of seven colors.

The present invention is concerned primarily with the printer head, and in particular with the ink tanks, and detailed description of the overall printer construction will be given only by way of a single example.

FIG. 1 is an exploded perspective view of a printer head, and FIG. 2 is a vertical cross-sectional view of the printer head constructed in accordance with the invention. An ink tank, shown generally as 2, is detachably mounted by a holder 70 on top of a




Fig. 1 is a schematic view showing an ink supply system of an ink-jet type recording apparatus according to one embodiment of the present invention.

A print head unit 1 of an ink-jet type is connected to an ink tank 3 through a connecting member 2. Ink is supplied from the ink tank 3 to the print head unit 1 through a hollow needle 2a and an ink supply passage 2b of the connecting member 2, so that the print head unit 1 emits ink droplets in accordance with print signals.

The apparatus shown in Fig. 1 also includes a cap member 4 disposed at non-printing area, which cap member comes into abutment against the nozzle plate of the print head unit 1 by a drive mechanism (not shown) for preventing the nozzle openings from drying. The cap member 4 is connected through a tube 8 to a suction pump 5 which is operated by a control device 6 to suck ink from the print head unit 1 through the cap member 4. The apparatus shown in Fig. 1 is also provided with an effluent tank 7 connected to an outlet port of the suction pump 5 through a tube 9.

The recording head may be of any structure such as described in European Patent Publication Nos. 581,531, 609,863, 584,823 and so on.




26 10

With the present invention, ink can be uniformly supplied through a simple construction from an ink tank to a printer head, and ink is uniformly provided to the printer head for producing a uniform and proper ink density. In the printer head of the invention, ink flow will not be interrupted in an ink guide path to prevent an ink supply failure. A quantity of ink absorbed in the ink guide path is smaller than would be absorbed with a conventional arrangement in which a porous member is used to apply ink directly to the tip end of the wire. Therefore, any wasted ink which is not used for printing is of a small quantity, and all the ink in an ink tank can effectively be used for printing. When the ink tank runs short of ink, and the ink in the tank is rendered highly viscous by being dried at high temperature, or is solidified and thus failing to supply ink, a cartridge ink tank can be mounted in place so that fresh ink can immediately be supplied to the print head for resuming desired printing operation.

According to the printer head of the present invention, no ink flow interruption occurs due to variations in temperature and atmospheric pressure and a uniform ink density is produced. Unintentional ink flow out of the ink tank is avoided, thus avoiding smearing the print paper with the undesired ink spots. Ink will not enter the printer head mechanism, preventing malfunctioning. The cartridge ink tank can easily be detached and attached for ink replenishment.

Since the ink supply system of the invention is simple in construction, it takes up a small space. Where a multicolor printer head employs ink supply systems of the invention, the ink supply systems for different ink colors can be spaced widely so that mixing of colors can be avoided.

The ink cartridge is ~~also~~ configured so as to be mounted with a small force and with accommodating a misalignment of a certain degree. Reference is first made to FIGS. ²~~23~~ and ³~~24~~ which depict an ink cartridge constructed in accordance with a first ~~additional~~ embodiment of the invention. A main container 501, is divided into three compartments 504, 505, and 506 by partitions 502 and 503 as shown in FIG. ³~~24~~. Each of the three compartments 504,



11

27

505, and 506 is divided by a center partition wall 510 into foam chambers 511, 511' or 511" housing a respective porous member 520, 520' or 520" and ink chambers 512, 512' or 512" which are adapted to contain liquid ink. Foam chambers 511, 511', 511" are dimensioned to receive a respective porous member 520, 520' 520".

The volume of each of porous members 520, 520' and 520" is selected so as to be larger than the capacity of each of the respective foam chambers 511, 511' or 511", so as to be compressed while being retained in the respective foam chamber in a preferred embodiment. The ratio of the capacities of each foam chamber 511, 511' or 511" and each ink chamber 512, 512' or 512" is selected so that each foam chamber 511, 511' or 511" is dimensioned to hold 20 to 30% more ink than the respective ink chamber 512, 512' or 512".

When inks of three colors are contained within a single cartridge as in FIGS. ²~~23~~ - ⁴~~25~~, it may be difficult to see if different amounts of ink remain in the chambers, which may be caused by unbalanced consumption of the different color inks. When ink of one color is depleted, and the user wishes to dispose of the cartridge, the user need not unnecessarily worry about any remaining ink of the other colors in the cartridge leaking. When a cartridge of the invention is disposed of, ink is prevented from flowing out of the cartridge because ink of each color is absorbed by each respective porous member, thereby protecting the environment from any leakage of ink.

Ink supply ports 513, 513' and 513" (not shown), chamber 511 being exemplary of each chamber 511, 511' and 511", are formed in main container 501 within a respective foam chamber 511, 511', 511". Each ink supply port 513, 513' and 513" is adapted to engage with a respective ink supply needle (not shown) of the recording head which are inserted at the lower end of each of the foam chambers 511, 511' and 511".

Referring now to FIG. ^{2 and 3}~~24~~, the upper end of the main container 501 is sealed by a lid 516. Two ink filling ports 514 and 515 are formed at positions on lid 516 corresponding to foam chamber 511. Similarly, as shown in FIG. ⁶~~27~~(a), each chamber 511, 511' and 511" includes corresponding ink filling ports 514 and 515,



28 12

514' and 515', and 514" and 515". Projections 516a and 516b, FIG. ²~~23~~, are integrally formed with the inner surface of lid 516 and are positioned in foam chamber 511, so as to surround filling ports 515 and 514, respectively. Porous member 520 is compressed by projections 516a and 516b against the bottom wall of foam chamber 511 in which ink supply port 513 is formed. Projections 516a' and 516b', and 516a" and 516b" are similarly formed in the inner wall of lid 516, and are positioned in foam chambers 511' and 511", which contain ink supply ports 513' and 513", respectively as shown in FIG. ³~~24~~.

Projection 516a which opposes ink supply port 513 is formed with its lower tip located at a position lower than the lower tip of projection 516b, whereby the portion of porous member 520 in the vicinity of ink supply port 513 is compressed to the greatest extent.

Protrusion portions 522, 522' and 522" (collectively "522"), which cooperate with lid 516 to compress porous members 520, 520' and 520" respectively are formed on the bottom of each of foam chambers 511, 511' and 511". Recesses 523, 523' and 523" (collectively "523"), which define spaces having a fixed opening area, are formed at the upper end of respective protrusion portions 522. Through holes 524, 524' and 524" (collectively "524") are disposed within the respective protrusion portions 522. One end of each through hole 524 is in fluid communication with the spaces defined by recesses 523 and the other end with a respective packing (collectively "530"), which will be hereinafter described. Filters 525, 525' and 525" (not shown) (collectively "525") are fixed to the upper end of recesses 523 respectively.

Packing members 530 of which only 530 is shown, are disposed at the lower end of ink supply ports 513, 513' and 513" respectively and are made of a resilient material such as rubber. Packing members 530, are configured as a funnel-shaped packing which opens upward. The lower ends of tubular portions 531 are thicker than the other portions. The respective upper peripheral edges 533 of taper portions 532 of respective packing members 530 contact with step portions 513a of respective ink supply ports 513,




29 13

513' and 513". Each packing member 530 is formed with protrusions 535 received by ^{groove}stepped portion 527 within the inner wall of ink supply port 513. The boundary between tubular portions 531 and taper portions 532, are configured as thin connection portions 534.

In this design, packing members 530 are fixed by tubular portions 531 to respective ink supply ports 513. Additionally, upward movement of upper peripheral edges 533 is prevented by respective step portions 513a. Thus, even when the respective ink supply needle is inserted or extracted, packing members 530 are adequately fixed to ink supply ports 513. Since taper portions 532 serve to attain the hermetic seal between the packing member and the ink supply needle of the respective ink supply port 513 by the respective thin connection portions 534, the taper portions can be moved somewhat without causing deformation. Consequently, the air tight seal between the respective packing member and ink supply needle can be maintained while accommodating a relative misalignment between the respective ink supply needle and ink supply port.

Communicating holes 519, 519' and 519" are formed in center partition wall 510, which separates foam chambers 511, 511' and 511" from ink chambers 512, 512' and 512" respectively. Slots 519a, 519a' 519a" which extend ~~from the bottom of container 501~~ to a predetermined height are formed to be in communication with communicating holes 519, 519' and 519" respectively for gas-liquid ^{replacement}~~separation~~. Between each respective pair of foam and ink chambers 511 and 512, 511' and 512', and 511" and 512", porous members 520, 520' and 520" are housed in the foam chambers 511, 511' and 511" respectively in such a manner that each porous member is held against the respective communicating hole 519, 519' or 519". Ribs 518, 518', and 518" are formed on a back wall 501a of container 501 within a respective ink chamber 512, 512' and 512". An individual communication hole is formed between each respective chamber pair 511, 512, and extend along only a portion of the length of partition 510 formed thereat.

In a second ~~additional~~ embodiment of the invention an ink cartridge is utilized for a single color ink. A cartridge 5100 for



30 14

a single color, or black ink can be made smaller in size than that for color inks, but the ink chamber 5112 for black ink would have a larger capacity than each of the corresponding chambers for a color ink. According to the second additional embodiment of the invention, a cartridge for black ink is shown in FIG. ⁵~~25~~ having a partition wall 5117 formed within a container 5100 so as to extend between center partition wall 5110 which separates a foam chamber 5111 from a ink chamber 5112 and a side wall 5100a of main container 5100, thereby dividing ink chamber 5112 into two cells 5112a and 5112b. This structure prevents container 5100 from being deformed by a negative pressure produced during the ink filling process which will be hereinafter described, or by an external pressure during usage, thereby preventing any ink from leaking. Cells 5112a and 5112b are retained in fluid communication with foam chamber 5111 via a communicating hole 5119 in center partition 5110 which extends along only a portion of the length of partition 5110. In addition, a communicating hole may be formed in the lower portion of partition wall 5117.

On the inner face of wall 5100a, which can easily be seen when the cartridge is mounted on a carriage, a plurality of ribs 5118 are formed which extend vertically along inner face 5100a. These ribs allow ink to flow more easily down along wall 5100a, and the user can easily recognize the amount of ink remaining in the cartridge by seeing the ink level.

Reference is now made to FIGS. ⁶~~27~~(a) and ⁶~~27~~(b) which depict lid 516 constructed in accordance with the first additional embodiment of the invention. Ink filling holes 514, 514' and 514", and 515, 515' and 515" are formed in the regions of lid 516 corresponding to the placement of porous members 520, 520' and 520" within container 501. Air communicating ports 541, 541' and 541" are connected to ink filling holes 514, 514' and 514" via grooves 540, 540' and 540", respectively.

When a seal 542 for covering ink filling holes 514, 514' and 514", 515, 515' and 515", and air vent ports 541, 541' and 541" is fixed to the ^{upperside}~~underside~~ of lid 516, FIG. ⁶~~27~~(b), after ink ~~compartments~~ 511, 511' and 511" are filled, grooves 540, 540' and ~~foam chambers~~



2115

540" form capillary tubes with seal 542. A tongue piece 545 of seal 542, which protrudes from lid 516, is formed with a neck portion 543 disposed in seal 542 at a midpoint of the route of air vent ports 541, 541' and 541". When tongue piece 545 is peeled from lid 516, tongue piece 545 is easily separated from seal 542. This in turn exposes air vent ports 541, but no other portions of the underside of ^{seal 542}~~lid 516~~.

In a preferred embodiment, seal 542 is formed with patterns such as characters and illustrations printed on its main portion 544 which permanently seals grooves 540, 540' and 540". Patterns, colors, or other printing different from that printed on main portion 544 of seal 542 may be placed on tongue piece 545 which is connected to main portion 544 of seal 542 via neck portion 543.

For example, in a further preferred embodiment, the main portion 544 of seal 542 has a blue background, black characters and other illustrations printed thereon. The background color of tongue piece 545 is a color such as yellow or red which contrasts with the background color of main portion 544. Characters and illustrations are printed on the background in colors which are mainly black or blue. In this way, main portion 544 and tongue piece 545 are distinguished from each other in color and pattern. Consequently, it is possible to call the user's attention to the need for the removal of tongue piece 545.

Each of ink supply ports 513, 513' and 513" are sealed by a film 546 (FIG. 23), and ink filling needles are hermetically inserted into the ink filling holes 514, 514' and 514" and 515, 515' and 515" respectively. The first of filling holes 514, 514' and 514" is connected to evacuating means, and the second of the filling holes 515, 515' and 515" is closed.

The evacuating means reduces the pressure in each of foam chambers 511, 511' and 511" and in each of ink chambers 512, 512' and 512". When the pressure is reduced to a predetermined value, the evacuating operation is stopped and the first filling hole is closed. Thereafter, the second filling hole is placed in fluid communication with a measuring tube filled with ink. Ink contained



32 16

in the measuring tube is drawn into the evacuated container and is then absorbed by respective porous member 520, 520' and 520" and thereafter flows into ink chamber 512, 512' or 512" via communicating holes 519, 519' or 519" respectively.

After the specified amount of ink flows into the appropriate ink chamber, seal 542 is fixed to the ~~inner~~^{outer} surface of lid 516 so that the ink filling holes 514, 514' and 514" and 515, 515' and 515", grooves 540, 540' and 540", and communicating ports 541, 541' and 541" are sealed under reduced pressure. Seal 542 thereafter maintains the reduced pressure states of foam chambers 511, 511' and 511" and ink chambers 512, 512' and 512".

Before use of the cartridge, tongue piece 545 of ~~lid 516~~^{seal 542} is then peeled off so that tongue piece 545 is broken at neck portion 543 and is separated from main portion 544. Thus, ink filling holes 514, 514' and 514" are placed in fluid communication with air vent ports 541, 541' and 541" via grooves 540, 540' and 540". Also, foam chambers 511, 511' and 511" are placed in fluid communication with air vent ports 541, 541' and 541" and therefore ambient air, via grooves 540, 540' and 540". Thus, while the ink is prevented from evaporating, the ink cartridge is ventilated.

Reference is now made to FIGS. 28⁷(a) and 28⁷(b), wherein an ink supply port 513 of the ink cartridge is positioned so as to be aligned with an ink supply needle 550 of the recording head. Thereafter the ink cartridge is pushed toward the recording head upon insertion of the ink cartridge. A taper portion 551 of ink supply needle 550 passes through a film seal 546 and engages the hole of packing member 530 as shown in FIG. 28⁷(a). Since packing member 530 opens upward, packing member 530 allows ink supply needle 550 to pass therethrough while packing member 530 is resiliently deformed by taper portion 551 of ink supply needle 550.

When the cartridge is used, ink supply needle 550 passes through packing member 530. The resiliency of connection portion 534 of packing member 530 enables taper portion 532 to engage ink supply needle 550. Even if ink supply needle 550 of the recording head and the center of packing 530 are somewhat misaligned, ink supply port 513 and ink supply needle 550 are hermetically sealed.



2317

To conduct ink into the recording head after the ink cartridge is mounted, or to ~~restart the flow of ink to the recording head~~ ^{recover the ink ejection performance.}, a negative pressure is applied to the recording head and through ink supply needle 550 so that ink in the cartridge flows through ink supply needle 550 and into the recording head. Because of the pressure difference, this high negative pressure applied to the cartridge causes taper portion 532 of packing member 530, which hermetically seals and isolates the cartridge from ambient air, to deform upward in FIG. 28⁷(a) toward the interior of the ink cartridge. Thus, the pressure difference aids in causing taper portion 532 of packing member 530 to be resiliently pressed against ink supply needle 550, and thereby aids in hermetically sealing the ink cartridge.

Even if ink supply needle 550 is not positioned completely through packing member 530, the resilient force in taper portion 532 of packing member 530 allows taper portion 532 to remain in contact with ink supply needle 550 as long as the tapered portion 551 of ink supply needle 550 remains in contact with taper portion 532 as shown in FIG. 28⁷(b). Consequently, it is possible to secure the air tightness of packing member 530 and ink supply needle 550 even if the needle is not properly inserted.

Since the tip of ink supply needle 550 is sealed upon contact with packing member 530, the dead space in the cartridge can be made very small, and any air bubbles which may be produced by the piston effect upon insertion of the cartridge onto the recording head are prevented from entering the cartridge.

When a negative pressure is applied from the nozzle openings of the recording head, ink absorbed by porous member 520 flows into the recording head via through hole 524 and through holes 552 of ink supply needle 550. When ink of a predetermined amount is consumed from porous member 520 and the ink level in porous member 520 is reduced, the pressure of ink chamber 512 overcomes the holding force of porous member 520 in the vicinity of communicating hole 519, so that air bubbles enter ink chamber 512 via communicating hole 519. Consequently, the pressure in a



3418

ink chamber 512 is increased and ink therefore flows into a foam chamber 511.

The ink flowing into foam chamber 511 is absorbed by porous member 520 and causes the ink level in foam chamber 511 to be raised. At the instant when the ink holding force of porous member 520 in the vicinity of communicating hole 519 is balanced with the pressure in ink chamber 512, the flow of ink from ink chamber 512 into foam chamber 511 is stopped.

The graph of FIG. 2⁸ illustrates this process. In the figure, the letter F indicates the ^{pressure} ~~ink~~ level in porous member 520 of foam chamber 511, and the letter G indicates the ink level in ink chamber 512. When a predetermined amount of ink w₁ which was initially contained in porous member 520 is consumed so that the ink level in porous member 520 is reduced to a predetermined value at which the pressure in ink chamber 512 overcomes the ink holding force of porous member 520 in the vicinity of communicating hole 519, ink gradually flows in a stepwise manner from ink chamber 512 into the foam chamber 511. This process occurs until the balance between the pressure of the ink chamber 512 and the ink holding force of porous member 520 in the vicinity of communicating hole 519 is restored. As a result, although the ink level in ink chamber 512 is gradually reduced, the ink level in porous member 520 can be maintained at a substantially constant level so that ink is supplied to the recording head by a constant pressure difference at a constant rate.

After a predetermined amount of ink w₂ is consumed by the recording head, no ink will remain in ink chamber 512, but the amount of ink contained in porous member 520 will be at a level equal to the level when ink was intermittently being supplied to foam chamber 511 from ink chamber 512. Therefore, ~~although~~ printing can be continued using the amount of ink absorbed in porous member 520, ^{although} ~~no~~ further ink is available in ink chamber 512 to replenish the ink supply ^{into} ~~in~~ porous member 520. After a predetermined amount of ink w₃ is consumed during printing, the ink supply in porous member 520 will be depleted, and the ink cartridge will no longer support printing.



19
35

all the ink contained in ink chamber 512 has been absorbed in porous member 520

During the entire printing operation from when ~~the cartridge is filled~~ until the ink is depleted, a constant amount of ink is supplied to the recording head. The depletion of ink from ink chamber 512 indicates the impending depletion of ink ~~and accompanying print failure~~. If a fresh cartridge is inserted at this stage, it is possible to ensure a constant supply of ink to the recording head without interruption.


in the ink tank cartridge.

As described above, the inner space of the ink cartridge of the invention must be maintained at a negative pressure during the printing process. In addition to the achievement of the above-described hermetic seal between the ink supply port and the ink supply needle, the transfer of ink from ink chamber 512 to the foam chamber 511 must be performed properly to ensure a constant flow of ink to the recording head. Hereinafter, the structure for controlling the supply of ink from ink chamber 512 to foam chamber 511 will be described.

Reference is now made to FIG. ⁹~~30~~ which depicts the boundary between foam chamber 511 and ink chamber 512 in a third additional embodiment of the invention. Like numerals are utilized to indicate like structures, the primary difference between this embodiment and the first additional embodiment being a step portion formed in hole 519.

A step portion 560 is formed in communicating hole 519. A portion 563 of the base of ink chamber 512 is higher than that of foam chamber 511, step portion 560 being the dividing point. A groove ⁵⁶¹~~562~~ connecting the foam and ^{the}ink chamber ~~is~~ is formed in the lower part of step portion 560.

Porous member 520 is in contact with communicating hole 519 and is received by step portion 560 so that the portion of porous member 520 in the vicinity of communicating hole 519 is compressed, whereby the required pressure difference between ink chamber 512 and foam chamber 511 via communicating hole 519 can be attained. When the ink level of ink chamber 512 is reduced to a low level, groove 561 enables ink from ink chamber 512 to be collected and then absorbed by porous member 520 in foam chamber 511. Consequently, all of the ink in ink chamber 512 can be




supplied to the recording head for printing without wasting any ink.

Reference is now made to FIG. ¹⁰~~31~~, which depicts an ink cartridge constructed in accordance with a fourth ~~additional~~ embodiment of the invention. Again, like numerals are used to indicate like structures, the primary difference between this embodiment and the first additional embodiment is the different leveled bottoms of the respective chambers.

The bottom face 564 of ink chamber 512 is higher than the bottom face 567 of foam chamber 511, thereby forming a step portion 562. Step portion 562 receives the lower portion of porous member 520 so that the portion of porous member 520 in the vicinity of communicating hole 519 is compressed. When required, a slope 563 which is directed from the ink chamber 512 to the foam chamber 511 may be formed to aid in the supply of ink. Since slope 563 allows ink in ink chamber 512 to flow more easily toward foam chamber 511, irrespective of the inclination of the carriage, ink from ink chamber 512 can be constantly supplied to the recording head.

Reference is now made to FIGS. ¹¹~~32~~ and ¹²~~33~~ which depict an ink jet cartridge constructed in accordance with a fifth additional embodiment of the invention. Like structures are indicated by like reference numerals, the primary difference between this embodiment and the first additional embodiment is the formation of a through hole. *This embodiment is the same as shown in FIGS. 4 and 5.*

Groove 519a (FIGS. ⁴~~25~~ and ⁵~~26~~) is formed in the face of center partition 510 separating foam chamber 511 from ink chamber 512. Groove 519a is formed in the face of partition 510 on the side of the foam chamber 511 and is in communication with the upper portion of communicating hole 519 of center partition 510 within the respective chambers 511, 512. In order to allow air to pass from ink chamber 512 to foam chamber 511 and to retain these chambers in fluid communication with each other, a through hole 519b is formed in the lower end of the groove 519a. Thus, the upper portion of porous member 520 which exhibits a relatively small capillary force is maintained in fluid communication with communicating hole 519 via the space formed by thin groove 519a.

2/
~~37~~

Therefore, ink can be smoothly replaced with air so that ink in ink chamber 512 constantly flows into foam chamber 511, thereby preventing too much or not enough ink from being supplied.

Reference is now made to FIGS. ~~34~~¹³ and ~~35~~¹⁴ which depict an ink cartridge constructed in accordance with a sixth additional embodiment of the invention. Like numerals are utilized to depict like structures, the primary difference being the use of a projection into foam chamber 511.

A horseshoe-shaped projection 565 is formed on the bottom of foam chamber 511 as is shown in FIG. ~~35~~¹⁴. Projection 565 ensures a space in the vicinity of communicating hole 519 so that ink from ink chamber 512 can easily flow into foam chamber 511.

As described above, foam chamber 511 and ink chamber 512 are separated from each other by the single center partition 510. In seventh or eighth additional embodiments of a single-color ink cartridge, as shown in FIGS. ~~36~~¹⁵ and ~~37~~¹⁶ respectively, an ink chamber 571 may be formed so as to surround two or three sides of a foam chamber 570, and a communicating hole 573 may be formed in at least one of the walls 572 separating the foam chamber 570 from the ink chamber 571. An exit port 574 is positioned within foam chamber 570. An ink cartridge of this design can store an amount of ink which is relatively large as compared with the volume of the whole ink cartridge. Furthermore, because of the location of the chambers, the user can easily see if replacement of the ink cartridge is required because of depletion of the ink.


References is now made to FIGS. ~~38~~¹⁷ and ~~39~~¹⁸ wherein an ink jet printer cartridge constructed in accordance with a ninth additional embodiment of the invention is provided. This embodiment is similar to the first additional embodiment, the primary difference being the use of a resilient O-ring 5300 which is retained in contact with the peripheral face of an ink supply needle of the recording head upon insertion of the ink supply needle into the ink supply cartridge. However, this ink jet printer results in other problems solved by the first additional embodiment. A large frictional force may be produced when mounting the cartridge on the carriage and inserting the ink supply needle

22.
~~38~~

into the cartridge. This results in an extra strain on the recording head and the carriage. Furthermore, O-ring 5300 is supported at its periphery by the body 5302 of the cartridge. If there is a misalignment between the cartridge and the ink supply needle of the recording head upon insertion of the ink supply needle in the ink supply cartridge, it is very difficult to mount the cartridge. Furthermore, when a three color ink cartridge in which tanks 5304, 5306, and 5308 for the three color inks are integrated into one piece as shown in FIG. 29, it is extremely difficult to mount such a cartridge on the recording head if the cartridge and any of the ink supply needles are misaligned.

It will thus be seen that the objects set forth above, among those made apparent from the preceding description are efficiently attained and, since certain changes may be made in carrying out the above construction and method set forth without departing from the spirit and scope of the invention, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

It is also to be understood that the following claims are intended to cover all of the generic and specific features of the invention herein described, and all statements of the scope of the invention which, as a matter of language, might be said to fall there between.



23

41

CLAIMSWHAT IS CLAIMED IS:

1. An ink tank cartridge for an ink-jet type recording apparatus, comprising:

a first chamber;

a second chamber adjacent to and formed integral with said first chamber;

a porous member received in said second chamber;

a partition wall separating said first chamber from said second chamber, said partition wall being formed with a communicating hole therethrough, said communicating hole being positioned in the vicinity of the bottom of said partition wall and extending along a portion of the width of said partition wall as viewed in the direction of said bottom of said partition wall, said second chamber communicating with said first chamber through said communicating hole;

an ink supply port extending through a wall of said second chamber, said ink supply port supplying ink to the exterior of said cartridge from said porous member;

an air vent port spaced from said ink supply port and communicating hole to provide ambient air to the interior of said second chamber said porous member and said first chamber containing ink;

the pressure in said first chamber and said second chamber being at a value less than normal atmospheric pressure, with a pressure ^{balance} ~~difference~~ being maintained between said first chamber and said second chamber by the surface tension of said porous member in the vicinity of said communicating hole to maintain ink in said first chamber; and

said first and second members, partition wall, communicating hole, air vent port and ink supply port being positioned and dimensioned so that when said pressure ^{balance} ~~difference~~ between said chambers is no longer maintained as said ink



24
42



impregnated in said porous member is at least partially transmitted through said ink supply port, ink is supplied from said first chamber to said porous member in said second chamber as required until the pressure ^{balance} ~~difference~~ between said first chamber and said second chamber is restored.

2. The ink tank cartridge of claim 1, further comprising a step portion formed at a lower portion of said communicating hole, a groove connecting said first and second chambers being formed in said ink cartridge below said step portion.

3. The ink tank cartridge of claim 1, further comprising a protrusion portion formed on an inner surface of said partition wall on the side thereof facing said second chamber, said protrusion maintaining a space about said communicating hole to aid in the flow of ink therethrough.

4. The ink tank cartridge of claim 1, further comprising a step portion formed below said communicating hole in said partition wall.

5. The ink tank cartridge of claim 4, wherein the part of said step portion adjacent said first chamber is higher than the part adjacent said second chamber.

6. The ink tank cartridge of claim 1, further comprising a vertically extending thin groove formed in said partition wall above said communicating hole on the side facing said second chamber, said groove being in fluid communication with said communicating hole and aiding in the flow of air and ink between said first and second chambers.

7. The ink tank cartridge of claim 1, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

8. The ink tank cartridge of claim 7, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.



25
43



9. The ink tank cartridge of claim 7, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

10. The ink tank cartridge of claim 1, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

11. The ink tank cartridge of claim 1, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

12. The ink tank cartridge of claim 1, further comprising a portion of said air vent port being formed in an exterior surface of said cartridge and an air-impermeable sealing member for selectively sealing said air vent port by engagement with said exterior surface when said ink cartridge is not used and unsealing said air vent port when said ink cartridge is to be used.

13. The ink tank cartridge of claim 12, wherein said air vent port is formed at least in part as a groove on said exterior surface.

14. The ink tank cartridge of claim 13, wherein said groove is a meandering groove.

15. The ink tank cartridge of claim 12, wherein said exterior surface forms a part of a lid.

16. The ink tank cartridge of claim 12, wherein said sealing member comprises a main portion, and a tongue piece which is removably connected to said main portion via a neck portion.

17. The ink tank cartridge of claim 16, wherein at least one of different patterns and colors are printed on said main portion and said tongue piece, said neck portion acting as a boundary between said main portion and said tongue piece.

18. The ink tank cartridge of claim 12, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.



26
~~44~~



19. The ink tank cartridge of claim 18, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

20. The ink tank cartridge of claim 18, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

21. The ink tank cartridge of claim 12, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

22. The ink tank cartridge of claim 12, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

23. The ink tank cartridge of claim 1, further comprising a dividing wall disposed in said first chamber extending in a direction essentially perpendicular to said partition wall at a central region thereof and extending between said partition wall and a wall of said first chamber situated opposite said center partition wall, said dividing wall being shaped so as not to block the ink flow between sections of said first chamber on either side of said dividing wall and between said first and second chambers.


24. The ink tank cartridge of claim 1, wherein said cartridge is constructed to be removably mounted on said recording apparatus so that an ink supply needle of said apparatus is received in said ink supply port.

25. An ink tank cartridge for an ink-jet type recording apparatus comprising:

a first chamber;

a second chamber adjacent to and formed integral with said first chamber;

a partition wall separating said first chamber from said second chamber, said partition wall being formed with a communicating hole therethrough, said communicating hole being positioned in the vicinity of the bottom of said partition wall and



extending along a portion of the width of said partition wall as viewed in the direction of said bottom of said partition wall;

a dividing wall disposed in said first chamber extending in a direction essentially perpendicular to said partition wall at a central region thereof and extending between said partition wall and a wall of said first chamber situated opposite said partition wall, said dividing wall being shaped so as to not block the flow of ink between sections of said first chamber on either side of said dividing wall and between said first and second chambers;

an ink supply port extending through a wall of said second chamber, said ink supply port supplying ink to the exterior of said ink cartridge; and

an air vent port spaced from said ink supply port and communicating hole to provide ambient air to the interior of said second chamber.

26. The ink tank cartridge of claim 25, and including a porous member received in said second chamber positioned to deliver ink to said ink supply port.

27. The ink tank cartridge of claim 26, wherein said porous member is impregnated with ink and said first chamber contains ink.

28. The ink tank cartridge of claim 25, further comprising a step portion formed at a lower portion of said communicating hole, a groove connecting said first and second chambers being formed in said ink cartridge below said step portion.

29. The ink tank cartridge of claim 25, further comprising a protrusion portion formed on an inner surface of said partition wall on the side thereof facing said second chamber, said protrusion maintaining a space about said communicating hole to aid in the flow of ink therethrough.

30. The ink tank cartridge of claim 25, further comprising a step portion formed below said communicating hole in said partition wall.



31. The ink tank cartridge of claim 30, wherein the part of said step portion adjacent said first chamber is higher than the part adjacent said second chamber.

32. The ink tank cartridge of claim 25, further comprising a vertically extending thin groove formed in said partition wall above said communicating hole on the side facing said second chamber, said groove being in fluid communication with said communicating hole and aiding in the flow of air and ink between said first and second chambers.

33. The ink tank cartridge of claim 25, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

34. The ink tank cartridge of claim 33, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

35. The ink tank cartridge of claim 25, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

36. The ink tank cartridge of claim 25, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

37. The ink tank cartridge of claim 25, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

38. The ink tank cartridge of claim 25, further comprising a portion of said air vent port being formed in an exterior surface of said cartridge and an air-impermeable sealing member for selectively sealing said air vent port by engagement with said exterior surface when said ink cartridge is not used and unsealing said air vent port when said ink cartridge is to be used.

39. The ink tank cartridge of claim 38, wherein said air vent port is formed at least in part as a groove on said exterior surface.



29
47



40. The ink tank cartridge of claim 38, wherein said groove is a meandering groove.

41. The ink tank cartridge of claim 38, wherein said exterior surface forms a part of a lid.

42. The ink tank cartridge of claim 38, wherein said sealing member comprises a main portion, and a tongue piece which is removably connected to said main portion via a neck portion.

43. The ink tank cartridge of claim 42, wherein at least one of different patterns and colors are printed on said main portion and said tongue piece, said neck portion acting as a boundary between said main portion and said tongue piece.

44. The ink tank cartridge of claim 38, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

45. The ink tank cartridge of claim 44, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

46. The ink tank cartridge of claim 44, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

47. The ink tank cartridge of claim ²⁶38, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

48. The ink tank cartridge of claim 38, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

49. An ink-jet type recording apparatus for outputting ink onto a recording medium, comprising:

a recording head for ejecting ink;

~~an ink supply needle coupled to said recording head, and~~

~~an ink tank cartridge being removably mountable onto said recording head~~
~~ink supply needle of said ink-jet type recording apparatus, said~~
ink tank cartridge further comprising: *for delivery of ink thereto*



a first chamber;

a second chamber adjacent to and formed integral with said first chamber;

a porous member received in said second chamber;

a partition wall separating said first chamber from said second chamber, said partition wall being formed with a communicating hole therethrough, said communicating hole being positioned in the vicinity of the bottom of said partition wall and extending along a portion of the width of said partition wall as viewed in the direction of said bottom of said partition wall, said second chamber communicating with said first chamber through said communicating hole;

an ink supply port extending through a wall of said second chamber, said ink supply port supplying ink to the exterior of said cartridge from said porous member;

an air vent port spaced from said ink supply port and communicating hole to provide ambient air to the interior of said second chamber said porous member and said first chamber containing ink;

the pressure in said first chamber and said second chamber being at a value less than normal atmospheric pressure, with a pressure ^{balance} ~~difference~~ being maintained between said first chamber and said second chamber by the surface tension of said porous member in the vicinity of said communicating hole to maintain ink in said first chamber; and

said first and second members, partition wall, communicating hole, air vent port and ink supply port being positioned and dimensioned so that when said pressure ^{balance} ~~difference~~ between said chambers is no longer maintained as said ink impregnated in said porous member is at least partially transmitted through said ink supply port, ink is supplied from said first chamber to said porous member in said second chamber as required until the pressure ^{balance} ~~difference~~ between said first chamber and said second chamber is restored.



~~50. The ink-jet type recording apparatus of claim 49, further comprising a step portion formed at a lower portion of said communicating hole, a groove connecting said first and second chambers being formed in said ink cartridge below said step portion.~~

~~51. The ink-jet type recording apparatus of claim 49, further comprising a protrusion portion formed on an inner surface of said partition wall on the side thereof facing said second chamber, said protrusion maintaining a space about said communicating hole to aid in the flow of ink therethrough.~~

~~52. The ink-jet type recording apparatus of claim 49, further comprising a step portion formed below said communicating hole in said partition wall.~~


~~53. The ink-jet type recording apparatus of claim 52, wherein the part of said step portion adjacent said first chamber is higher than the part adjacent said second chamber.~~

50 54. The ink-jet type recording apparatus of claim 49, further comprising a vertically extending thin groove formed in said partition wall above said communicating hole on the side facing said second chamber, said groove being in fluid communication with said communicating hole and aiding in the flow of air and ink between said first and second chambers.

5/ 55. The ink-jet type recording apparatus of claim 49, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

52 56. The ink-jet type recording apparatus of claim 55, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

53 57. The ink-jet type recording apparatus of claim 55, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.



54 58. The ink-jet type recording apparatus of claim 49, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

55 59. The ink-jet type recording apparatus of claim 49, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

56 60. The ink-jet type recording apparatus of claim 49, further comprising a portion of said air vent port being formed in an exterior surface of said cartridge and an air-impermeable sealing member for selectively sealing said air vent port by engagement with said exterior surface when said ink cartridge is not used and unsealing said air vent port when said ink cartridge is to be used.

57 61. The ink-jet type recording apparatus of claim 60, wherein said air vent port is formed at least in part as a groove on said exterior surface.

58 62. The ink-jet type recording apparatus of claim 61, wherein said groove is a meandering groove.

59 63. The ink-jet type recording apparatus of claim 60, wherein said exterior surface forms a part of a lid.

60 64. The ink-jet type recording apparatus of claim 60, wherein said sealing member comprises a main portion, and a tongue piece which is removably connected to said main portion via a neck portion.

61 65. The ink-jet type recording apparatus of claim 64, wherein at least one of different patterns and colors are printed on said main portion and said tongue piece, said neck portion acting as a boundary between said main portion and said tongue piece.

62 66. The ink-jet type recording apparatus of claim 60, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.



33

51



63 ⁶²67. The ink-jet type recording apparatus of claim 66, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

64 ⁴⁹68. The ink-jet type recording apparatus of claim 66, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

65 ⁵⁶69. The ink-jet type recording apparatus of claim 60, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

66 ⁵⁶70. The ink-jet type recording apparatus of claim 60, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

67 ⁵⁶71. The ink-jet type recording apparatus of claim 49, further comprising a dividing wall disposed in said first chamber extending in a direction essentially perpendicular to said partition wall at a central region thereof and extending between said partition wall and a wall of said first chamber situated opposite said center partition wall, said dividing wall being shaped so as not to block the ink flow between sections of said first chamber on either side of said dividing wall and between said first and second chambers.

68 72. The ink-jet type recording apparatus of claim 49, wherein said cartridge is constructed to be removably mounted on said recording apparatus so that an ink supply needle of said apparatus is received in said ink supply port.

69 73. An ink-jet type recording apparatus for outputting ink onto a recording medium, comprising:

a recording head for ejecting ink;

~~an ink supply needle coupled to said recording head, and~~

an ink tank cartridge being removably mountable onto said ^{recording head} ~~ink supply needle~~ of said ink-jet type recording apparatus, said

ink tank cartridge further comprising: *for delivery of ink thereto*

a first chamber;



a second chamber adjacent to and formed integral with said first chamber;

a partition wall separating said first chamber from said second chamber, said partition wall being formed with a communicating hole therethrough, said communicating hole being positioned in the vicinity of the bottom of said partition wall and extending along a portion of the width of said partition wall as viewed in the direction of said bottom of said partition wall;

a dividing wall disposed in said first chamber extending in a direction essentially perpendicular to said partition wall at a central region thereof and extending between said partition wall and a wall of said first chamber situated opposite said partition wall, said dividing wall being shaped so as to not block the flow of ink between sections of said first chamber on either side of said dividing wall and between said first and second chambers;

an ink supply port extending through a wall of said second chamber, said ink supply port supplying ink to the exterior of said ink cartridge; and

an air vent port spaced from said ink supply port and communicating hole to provide ambient air to the interior of said second chamber.

70 74. The ink-jet type recording apparatus of claim ⁶⁹ 73, and including a porous member received in said second chamber positioned to deliver ink to said ink supply port.

71 75. The ink-jet type recording apparatus of claim ⁷⁰ 74, wherein said porous member is impregnated with ink and said first chamber contains ink.

~~76. The ink-jet type recording apparatus of claim 73, further comprising a step portion formed at a lower portion of said communicating hole, a groove connecting said first and second chambers being formed in said ink cartridge below said step portion.~~

~~77. The ink-jet type recording apparatus of claim 73, further comprising a protrusion portion formed on an inner surface~~

35
53

of said partition wall on the side thereof facing said second chamber, said protrusion maintaining a space about said communicating hole to aid in the flow of ink therethrough.

~~78. The ink-jet type recording apparatus of claim 73, further comprising a step portion formed below said communicating hole in said partition wall.~~

~~79. The ink-jet type recording apparatus of claim 78, wherein the part of said step portion adjacent said first chamber is higher than the part adjacent said second chamber.~~

72 80. The ink-jet type recording apparatus of claim ⁶⁹~~73~~, further comprising a vertically extending thin groove formed in said partition wall above said communicating hole on the side facing said second chamber, said groove being in fluid communication with said communicating hole and aiding in the flow of air and ink between said first and second chambers.

73 81. The ink-jet type recording apparatus of claim ⁶⁹~~73~~, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port. ⁷³

74 82. The ink-jet type recording apparatus of claim ⁷³~~81~~, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

75 83. The ink-jet type recording apparatus of claim ⁷³~~82~~, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

76 84. The ink-jet type recording apparatus of claim ⁷³~~83~~, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

77 85. The ink-jet type recording apparatus of claim ⁶⁹~~73~~, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

78 86. The ink-jet type recording apparatus of claim ⁶⁹~~73~~, further comprising a portion of said air vent port being formed in an exterior surface of said cartridge and an air-impermeable

36
54

sealing member for selectively sealing said air vent port by engagement with said exterior surface when said ink cartridge is not used and unsealing said air vent port when said ink cartridge is to be used.

79⁷⁸ 87. The ink-jet type recording apparatus of claim 86, wherein said air vent port is formed at least in part as a groove on said exterior surface.

80⁷⁸ 88. The ink-jet type recording apparatus of claim 86, wherein said groove is a meandering groove.

81⁷⁸ 89. The ink-jet type recording apparatus of claim 86, wherein said exterior surface forms a part of a lid.

82⁷⁸ 90. The ink-jet type recording apparatus of claim 86, wherein said sealing member comprises a main portion, and a tongue piece which is removably connected to said main portion via a neck portion.

83⁸² 91. The ink-jet type recording apparatus of claim 90, wherein at least one of different patterns and colors are printed on said main portion and said tongue piece, said neck portion acting as a boundary between said main portion and said tongue piece.

84⁷⁸ 92. The ink-jet type recording apparatus of claim 86, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

85⁸⁴ 93. The ink-jet type recording apparatus of claim 92, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

86⁸⁴ 94. The ink-jet type recording apparatus of claim 92, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

87⁷⁸ 95. The ink-jet type recording apparatus of claim 86, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.



37
55



88~~96~~⁷⁸. The ink-jet type recording apparatus of claim 86, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

89~~87~~. A system for supplying ink to an ink-jet type recording apparatus and outputting ink onto a recording medium, said system comprising:

a recording head for ejecting ink;
~~an ink supply needle coupled to said recording head,~~ and
 an ink tank cartridge being removably mountable onto said ~~ink supply needle~~ ^{recording head} of said ink-jet type recording apparatus, said ink tank cartridge further comprising: *for delivery of ink thereto*

a first chamber;
 a second chamber adjacent to and formed integral with said first chamber;

a porous member received in said second chamber;
 a partition wall separating said first chamber from said second chamber, said partition wall being formed with a communicating hole therethrough, said communicating hole being positioned in the vicinity of the bottom of said partition wall and extending along a portion of the width of said partition wall as viewed in the direction of said bottom of said partition wall, said second chamber communicating with said first chamber through said communicating hole;

an ink supply port extending through a wall of said second chamber, said ink supply port supplying ink to the exterior of said cartridge from said porous member;

an air vent port spaced from said ink supply port and communicating hole to provide ambient air to the interior of said second chamber said porous member and said first chamber containing ink;

the pressure in said first chamber and said second chamber being at a value less than normal atmospheric pressure, with a pressure ^{balance} ~~difference~~ being maintained between said first chamber and said second chamber by the surface tension of said



porous member in the vicinity of said communicating hole to maintain ink in said first chamber; and

said first and second members, partition wall, communicating hole, air vent port and ink supply port being positioned and dimensioned so that when said pressure ^{balance} difference between said chambers is no longer maintained as said ink impregnated in said porous member is at least partially transmitted through said ink supply port, ink is supplied from said first chamber to said porous member in said second chamber as required until the pressure ^{balance} difference between said first chamber and said second chamber is restored.

98. The system of claim 97, further comprising a step portion formed at a lower portion of said communicating hole, a groove connecting said first and second chambers being formed in said ink cartridge below said step portion.

99. The system of claim 97, further comprising a protrusion portion formed on an inner surface of said partition wall on the side thereof facing said second chamber, said protrusion maintaining a space about said communicating hole to aid in the flow of ink therethrough.

100. The system of claim 97, further comprising a step portion formed below said communicating hole in said partition wall.

101. The system of claim 100, wherein the part of said step portion adjacent said first chamber is higher than the part adjacent said second chamber.

90 102. The system of claim 97, further comprising a vertically extending thin groove formed in said partition wall above said communicating hole on the side facing said second chamber, said groove being in fluid communication with said communicating hole and aiding in the flow of air and ink between said first and second chambers.

91 103. The system of claim 97, further comprising a projection formed on an inside wall of said second chamber opposite



39
57



said ink supply port, said projection compressing said porous member against said ink supply port. ⁹¹

⁹² 104. The system of claim ⁹¹ 103, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

⁹³ 105. The system of claim ⁹¹ 103, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

⁹⁴ 106. The system of claim ⁸⁹ 97, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

⁹⁵ 107. The system of claim ⁸⁹ 97, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

⁹⁶ 108. The system of claim ⁸⁹ 97, further comprising a portion of said air vent port being formed in an exterior surface of said cartridge and an air-impermeable sealing member for selectively sealing said air vent port by engagement with said exterior surface when said ink cartridge is not used and unsealing said air vent port when said ink cartridge is to be used.

⁹⁷ 109. The system of claim ⁹⁶ 108, wherein said air vent port is formed at least in part as a groove on said exterior surface.

⁹⁸ 110. The system of claim ⁹⁷ 109, wherein said groove is a meandering groove.

⁹⁹ 111. The system of claim ⁹⁶ 108, wherein said exterior surface forms a part of a lid.

¹⁰⁰ 112. The system of claim ⁹⁶ 108, wherein said sealing member comprises a main portion, and a tongue piece which is removably connected to said main portion via a neck portion.

¹⁰¹ 113. The system of claim ¹⁰⁰ 112, wherein at least one of different patterns and colors are printed on said main portion and said tongue piece, said neck portion acting as a boundary between said main portion and said tongue piece.



40
58



⁹⁶
102 114. The system of claim 108, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

¹⁰²
103 115. The system of claim 114, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

¹⁰²
104 116. The system of claim 114, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

^{87 89}
105 117. The system of claim 108, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

⁹⁶
106 118. The system of claim 108, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.


⁸⁹
107 119. The system of claim 97, further comprising a dividing wall disposed in said first chamber extending in a direction essentially perpendicular to said partition wall at a central region thereof and extending between said partition wall and a wall of said first chamber situated opposite said center partition wall, said dividing wall being shaped so as not to block the ink flow between sections of said first chamber on either side of said dividing wall and between said first and second chambers.

⁸⁹
108 120. The system of claim 97, wherein said cartridge is constructed to be removably mounted on said recording apparatus so that an ink supply needle of said apparatus is received in said ink supply port.

¹⁰⁹
121. A system for supplying ink to an ink-jet type recording apparatus and outputting ink onto a recording medium, said system comprising:

a recording head for ejecting ink;

~~an ink supply needle coupled to said recording head, and~~



an ink tank cartridge being removably mountable onto ~~said ink supply needle of~~ said ink-jet type recording apparatus, said ink tank cartridge further comprising: *for delivery of ink thereto*

a first chamber;

a second chamber adjacent to and formed integral with said first chamber;

a partition wall separating said first chamber from said second chamber, said partition wall being formed with a communicating hole therethrough, said communicating hole being positioned in the vicinity of the bottom of said partition wall and extending along a portion of the width of said partition wall as viewed in the direction of said bottom of said partition wall;

a dividing wall disposed in said first chamber extending in a direction essentially perpendicular to said partition wall at a central region thereof and extending between said partition wall and a wall of said first chamber situated opposite said partition wall, said dividing wall being shaped so as to not block the flow of ink between sections of said first chamber on either side of said dividing wall and between said first and second chambers;

an ink supply port extending through a wall of said second chamber, said ink supply port supplying ink to the exterior of said ink cartridge; and

an air vent port spaced from said ink supply port and communicating hole to provide ambient air to the interior of said second chamber.

110 ~~122~~¹⁰⁹. The system of claim ~~121~~¹⁰⁹, and including a porous member received in said second chamber positioned to deliver ink to said ink supply port.

111 ~~123~~¹¹⁰. The system of claim ~~122~~¹¹⁰, wherein said porous member is impregnated with ink and said first chamber contains ink.

~~124. The system of claim 121, further comprising a step portion formed at a lower portion of said communicating hole, a groove connecting said first and second chambers being formed in said ink cartridge below said step portion.~~



42
.60



~~125. The system of claim 121, further comprising a protrusion portion formed on an inner surface of said partition wall on the side thereof facing said second chamber, said protrusion maintaining a space about said communicating hole to aid in the flow of ink therethrough.~~

~~126. The system of claim 121, further comprising a step portion formed below said communicating hole in said partition wall.~~

~~127. The system of claim 126, wherein the part of said step portion adjacent said first chamber is higher than the part adjacent said second chamber.~~

112 128. The system of claim ¹⁰⁹121, further comprising a vertically extending thin groove formed in said partition wall above said communicating hole on the side facing said second chamber, said groove being in fluid communication with said communicating hole and aiding in the flow of air and ink between said first and second chambers.

113 129. The system of claim ¹⁰⁹121, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

114 130. The system of claim ¹¹³129, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

115 131. The system of claim ¹⁰⁹121, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

116 132. The system of claim ¹⁰⁹121, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

117 133. The system of claim ¹⁰⁹121, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

43
61

* C L M S *

¹¹⁸
134. The system of claim ¹⁰⁹121, further comprising a portion of said air vent port being formed in an exterior surface of said cartridge and an air-impermeable sealing member for selectively sealing said air vent port by engagement with said exterior surface when said ink cartridge is not used and unsealing said air vent port when said ink cartridge is to be used.

¹¹⁹ 135. The system of claim ¹¹⁸134, wherein said air vent port is formed at least in part as a groove on said exterior surface.

¹²⁰ 136. The system of claim ¹¹⁸134, wherein said groove is a meandering groove.

¹²¹ 137. The system of claim ¹¹⁸134, wherein said exterior surface forms a part of a lid.

¹²² 138. The system of claim ¹¹⁸134, wherein said sealing member comprises a main portion, and a tongue piece which is removably connected to said main portion via a neck portion.


¹²³ 139. The system of claim ¹²²138, wherein at least one of different patterns and colors are printed on said main portion and said tongue piece, said neck portion acting as a boundary between said main portion and said tongue piece.

¹²⁴ 140. The system of claim ¹¹⁸134, further comprising a projection formed on an inside wall of said second chamber opposite said ink supply port, said projection compressing said porous member against said ink supply port.

¹²⁵ 141. The system of claim ¹²⁴140, wherein said ink supply port includes a portion including its entrance projecting into said second chamber.

¹²⁶ 142. The system of claim ¹²⁴140, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.

¹²⁷ 143. The system of claim ¹¹⁸134, wherein the volume of said porous member before placement in said second chamber is larger than the volume of said second chamber.



44
62



128 ¹¹⁸144. The system of claim ¹¹⁸134, further comprising a vertically extending rib formed on an inner face of said first chamber, said rib assisting in the flow of ink.

129 ¹²⁹145. A method for providing ink to an ink-jet type recording head, comprising the steps of:

providing an ink tank cartridge having a first chamber adapted to store ink and a second chamber adapted to store a porous member impregnated with said ink;

separating said first and second chambers from each other by use of a partition wall;

communicating ink between said first and second chambers through a communicating hole adjacent the bottom of said partition wall and extending only a portion of the width of said partition wall as viewed in the direction of the bottom of said partition wall;

withdrawing ink from said porous member through an ink supply port extending through a wall of said second chamber; and

providing ambient air to said second chamber at a location spaced from said ink supply port.

130 ¹²⁹146. The method of claim ¹²⁹145, further comprising the steps of:

maintaining the pressure in said first and second chambers below normal atmospheric pressure;

maintaining a pressure ^{balance} difference between said first and second chambers by the surface tension of said porous member in the vicinity of said communicating hole;

the withdrawal of ink from said porous member through said ink supply port upsetting the pressure balance between said first and second chambers so that ink flows from said first chamber to said second chamber until said pressure balance is restored.

130
131 ¹³⁰147. The method of claim ¹³⁰146, further comprising the step of:



45
63



forming said air vent at least in part as a winding groove in a surface of said ink tank cartridge to protect the ink against evaporation.

/32 148. The method of claim ¹³¹~~147~~, further comprising the steps of:

sealing said groove with a seal member;

removing a portion of said seal to place the interior of said ink supply tank in fluid communication with ambient air through said winding groove.

/33 ~~149~~. The method of claim ¹³²~~145~~, further comprising the step of strengthening said first compartment by providing a support wall situated in said first chamber extending essentially perpendicular to said partition wall at a central region thereof.