



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/22		A1	(11) International Publication Number: WO 96/37079
			(43) International Publication Date: 21 November 1996 (21.11.96)
(21) International Application Number: PCT/US96/06930 (22) International Filing Date: 17 May 1996 (17.05.96) (30) Priority Data: 412,648 17 May 1995 (17.05.95) US (71) Applicant: QUALCOMM INCORPORATED [US/US]; 6455 Lusk Boulevard, San Diego, CA 92121 (US). (72) Inventor: QUICK, Roy, F.; 4502 Del Monte Avenue, San Diego, CA 92107 (US). (74) Agents: MILLER, Russell, B. et al.; Qualcomm Incorporated, 6455 Lusk Boulevard, San Diego, CA 92121 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
		<div style="border: 1px solid black; padding: 5px;"> REPLACED SHEETS SG ☐ Description : paged to paged ☒ Claim(s) : paged 46... to paged 54... ☐ Drawing(s) : paged to paged ☐ Abstract : paged to paged </div>	

(54) Title: RANDOM ACCESS COMMUNICATIONS CHANNEL FOR DATA SERVICES

(57) Abstract

In a digital communication system for communicating digital information (100), the digital communication system having a forward link (120) and a reverse link (130), a system and method for communicating a data packet. The system comprises a communicating transceiver (202), from among a number of digital transceivers (102), for sending the data packet on a random access channel (208) over the reverse link and for receiving the digital information from the forward link. The system also comprises a base station (108) for receiving the data packet on the random access channel (208) from the reverse link (130) and for sending the digital information over the forward link (120). The digital transceivers (102) share the random access channel (208). The digital transceivers (102) have a bandwidth demand. The system (100) may also include a dedicated channel (214) for communicating the data packet between the communicating transceiver (202) and the base station (108) and a processor (212) for switching from the random access channel (208) to the dedicated channel (214) when the bandwidth demand exceeds a first threshold, and for switching from the dedicated channel (214) to the random access channel (208) when the bandwidth demand drops below a second threshold. The system is well suited for use in CDMA applications.

