

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
24 January 2002 (24.01.2002)

PCT

(10) International Publication Number
WO 02/06106 A1

(51) International Patent Classification⁷: **B62B 3/00**, 3/12,
5/04, 7/04, 9/08, B60B 33/02

Leslie [AU/AU]; 377 Williamstown Road, Yarraville,
Victoria 3013 (AU).

(21) International Application Number: PCT/AU01/00808

(74) Agent: **FREEHILLS CARTER SMITH BEADLE**;
Level 43, 101 Collins Street, Melbourne, Victoria 3000
(AU).

(22) International Filing Date: 6 July 2001 (06.07.2001)

(25) Filing Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA,
ZW.

(26) Publication Language: English

(30) Priority Data:
PQ 8820 17 July 2000 (17.07.2000) AU

(71) Applicant (*for all designated States except US*): **IGC
(AUSTRALIA) PTY LTD** [AU/AU]; 377 Williamstown
Road, Yarraville, Victoria 3013 (AU).


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **BIDWELL, Alan**,

[Continued on next page]

(54) Title: BRAKING AND STEERING LOAD-CARRYING ASSEMBLIES



(57) Abstract: A moveable load carrying assembly (10) including a chassis (12) having a first end (20) and a second end (40), there being provided one or more wheels (18) at or adjacent to the first end (20) of the chassis (12) and one or more wheels (16) at or adjacent to the second end (40) of the chassis (12). Each wheel (16, 18) is swivelable relative to the chassis (12) and braking means (35) are provided to act on at least one of the front wheel or wheels (18) in order to brake the front wheel or wheels (18). The braking means (35) is arranged to enable the front wheel or wheels (35) to be braked in any swivelled position relative to the chassis (12). A moveable load carrying assembly (10) including a chassis (12) having a first end (20) and a second end (40), there being provided one wheel (18) at or adjacent to the first end (20) of the chassis (12) and one or more wheels (16) at or adjacent to the second end (40) of the chassis (12). Each wheel (16, 18) is swivelable relative to the chassis (12) and means (50, 54) are provided to switch the front wheel (18) between a first steering mode in which the front wheel (18) is swivelable relative to the chassis (12), and a second steering mode in which the front wheel (18) is fixed in a straight-ahead direction relative to the chassis (12). The switch between steering modes occurs independently of the rear wheel or wheels (16).



162162

WO 02/06106 A1

WO 02/06106 A1

IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*