9803317-8

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
H01M 8/24, 8/02, 10/04, 6/46, 2/02, C25B 9/02, B01D 63/08

A1

(11) International Publication Number: WO 97/24778

(43) International Publication Date: 10 July 1997 (10.07.97)

(21) International Application Number: PCT/GB96/03162

(22) International Filing Date: 19 December 1996 (19.12.96)

(30) Priority Data:
9526577.3 28 December 1995 (28.12.95) GB

(71) Applicant (*for all designated States except US*): NATIONAL POWER PLC [GB/GB]; Windmill Hill Business Park, Whitehill Way, Swindon, Wiltshire SN5 6PB (GB).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): CLARK, Duncan, Guy [GB/GB]; Westham House, Mariston Road, Hermitage, Berkshire RG18 9SU (GB). JOSEPH, Stephen, Hampden [GB/GB]; 12 Grange Crescent Road, Sheffield S11 8FX (GB). MALE, Stewart, Ernest [GB/GB]; 68 Farm Close, East Grinstead, West Sussex RH19 3QG (GB).

(74) Agent: BOULT WADE TENNANT; 27 Furnival Street, London EC4A 1PQ (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: METHOD FOR THE FABRICATION OF ELECTROCHEMICAL CELLS

(57) Abstract

A method of fabricating an electrochemical or galvanic cell comprising a plurality of electrochemical components, which electrochemical components are joined together in a stack, which method comprises: i) providing a first component (1) formed from a deformable polymeric material with at least one substantially continuous groove (2) comprising a female opening having a width of w and a depth of h; ii) providing a second component (3) with at least one substantially continuous upstand (4) having a width of > w and a height of < h; iii) pressing the first and second components together in order to provide an integral seal between the upstand on the second component and the opening in the first component, with the seal between the parts being provided by sealing engagement of the sides of the upstand with the sides of the openings; and iv) joining a plurality of first and second components together to form a stack.



