

Description

The invention relates to a record player comprising a deck plate, which carries a turntable and a pick-up arm, and a lifting device which can be moved upwards and downwards to lift and lower the pick-up arm relative to the upper side of the turntable, which lifting device comprises an arm support and a lift rod which forms an integral unit with said support and is guided by a guide element connected to the deck plate, the lift rod cooperating with an actuating member for moving the lifting device upwards and downwards, and damping means which comprise a highly viscous substance being provided to damp at least the downward movement of the lifting device.

Such a record player is known from Patents Abstracts of Japan, Volume 5, No. 115 (p. 72) (787) 24 July 1981 and JP-A-5654601. This known record player has a damped-action lifting device in order to ensure that a stylus carried by the pick-up arm is lowered gently onto a record on the turntable. In the known record players the lifting device comprises a comparatively large number of parts. These parts include a separate guide sleeve mounted in the deck plate, which sleeve ensures that the vertical movements of the lift rod are performed accurately, and damping means which are arranged underneath the deck plate and which comprise a hydraulically damped lever, which lever is separately connected to the deck plate and cooperates with a separate actuating rod on the lifting device. Thus, the known record players have intricate, comparatively bulky and relatively expensive lifting devices. Therefore, such a lifting device adds substantially to the overall price of the record player.

It is the object of the invention to provide a record player of the type specified in the opening paragraph, which is provided with a compact lifting device which comprises a small number of parts and which is cheap to produce.

To this end the invention is characterized in that the lift rod comprises a first pair of longitudinal flat peripheral walls which make an angle with each other and which cooperate with a first pair of guide walls of the guide element, the guide element forms an integral unit with the deck plate, the highly viscous substance is retained between said first pair of longitudinal flat peripheral walls of the lift rod and said first pair of guide walls, and a spring element arranged between the deck plate and the lift rod exerts on the lift rod a force which is directed obliquely downwardly towards the line of intersection between the planes of said first pair of longitudinal flat peripheral walls of the lift rod to urge said first pair of longitudinal flat peripheral walls against said first pair of guide walls. Thus, the record player in accordance with the invention can be equipped with a lifting device comprising only two parts, namely the unit comprising the arm support and the lift rod, and the spring element, the guide walls being formed integrally with the deck plate. During assembly

only the highly viscous substance need be applied between the walls of the lift rod and the guide walls, after which the lifting device is ready for use. The lifting device is particularly suitable for manufacture from a plastics by injection moulding, because possible tolerances are effectively compensated for by the cooperating walls of the lift rod and the guide walls. The lifting device renders the record player in accordance with the invention very suitable for low-cost mass production.

A preferred embodiment of the invention is characterized in that the lift rod has a square cross-section and the force vector of the spring element extends in a plane which bisects the angle between said first pair of longitudinal flat peripheral walls of the lift rod. With a square cross-section the lift rod and thus the lifting device can readily be formed by injection-moulding, which may provide a proper engagement of the walls of the lift rod with the guide walls, which is important in order to retain the highly viscous substance between said walls.

Another preferred embodiment of the invention is characterized in that the spring element is a helical spring and in that a recess with a cylindrical wall is formed in the lift rod at a location where the walls of a second pair of peripheral walls of the lift rod join each other, which recess has a central axis situated in said bisecting plane and contains that end portion of the helical spring which is remote from the deck plate. If the lifting device is injection-moulded the recess can be positioned easily and accurately in the lift rod, so that the direction of the force exerted by the spring of the lifting device can be defined accurately by the position of the central axis of the recess.

Yet another preferred embodiment of the invention is characterized in that the arm support is disposed asymmetrically towards at least one of the walls of the first pair of longitudinal flat peripheral walls of the lift rod relative to a plane of symmetry of the lift rod. Thus, when the pick-up arm is lifted and lowered relative to the turntable the pick-up arm exerts an auxiliary torque on the lift rod via the arm support, which torque ensures that near the top of at least one guide wall the lift rod remains firmly urged against this wall. This ensures a constant and correct guidance, also near the upper ends of the guide walls.

Still another preferred embodiment of the invention is characterized in that at least near the location where it adjoins the deck plate the guide element is of tubular shape with a square cross-section and comprises a second pair of guide walls which, at a distance below the deck plate, are formed with an opening through which the spring element passes to act on the lift rod. Since during guiding of the lifting device the guide element cooperates in practice with the first-mentioned pair of walls of the lift rod, the walls of the second pair of guide walls may readily be formed with openings. Such an opening is used for the passage of the spring which acts on the lift

rod. Again it is advantageous that tolerances of the guide element have no adverse effect on the correct operation of the lifting device.

A preferred embodiment of the invention is characterized in that the first-mentioned pair of guide walls are flat, the first pair of longitudinal flat peripheral walls of the lift rod engage the first pair of guide walls adjacent the edges, and between the first pair of longitudinal flat peripheral walls of the lift rod and the first pair of guide walls gaps are formed which contain the highly viscous substance. This provides a capillary action between the first-mentioned pair of guide walls and the first-mentioned pair of walls of the lift rod, which ensures that the highly viscous substance, such as silicone oil, is retained between said walls. The advantage of making the guide walls flat is that the deck plate can easily be formed by injection-moulding. This is important because the deck plate is manufactured in a comparatively large moulding die. The guide walls may then even have a slight taper relative to each other. This does not affect the operation of the lifting device, provided that said guide walls are flat.

A record player embodying the invention will now be described in more detail, by way of example, with reference to the accompanying drawings. In the drawings:

Fig. 1 is a plan view of a record player in accordance with the invention,

Fig. 2 shows a part of the record player in an enlarged-scale sectional view taken on the lines II—II in Fig. 1,

Fig. 3 is an enlarged-scale sectional view taken on the lines III—III in Fig. 2,

Fig. 4 is a perspective view showing the lifting device of the record player of Fig. 1 in the lowered position, and

Fig. 5 is a perspective view showing the lifting device of the record player of Fig. 1 in the raised position.

The record player shown in Fig. 1 comprises a deck plate 1 in which a turntable is mounted for rotation about an axis 3. The deck plate 1 carries a pick-up arm 4 provided with a pick-up head 4a. The pick-up head 4a carries a stylus by means of which a gramophone record on the turntable 3 can be played. The pick-up arm 4 is pivotable about a pivot 4b (see also Fig. 2) which extends parallel to the deck plate and which connects the pick-up arm to an arm support 5 mounted on a rotatable disc 6. The disc 6 and hence the pick-up arm 4 are rotatable about an axis 6a which extends perpendicularly to the deck plate.

A part of a lifting device 7 for raising and lowering the pick-up arm 4 relative to the upper side of the turntable 2 projects above the deck plate 1. The lifting device 7 comprises an arm support 8 on which the pick-up arm rests during raising or lowering. The arm support 8 has a curved shape, suitably the shape of an arc of a circle concentric with the rotational axis 6a of the disc 6. The arm support 8 is fixed on the upper end of a vertical lifting rod 9 (see also Figs. 3, 4 and 5).

The lift rod 9 has a substantially square cross-

section and is manufactured as an integral unit with the arm support 8 from a plastics by injection-moulding. It extends from the arm support 8 down to a point below the deck plate 1. The lift rod 9 is slidably guided in a vertical guide element 10 of tubular shape which forms an integral unit with the deck plate 1. The guide element has a substantially square cross-section corresponding to that of the lift rod 9 and comprises a first pair of adjoining guide walls 10a and 10b and a second pair of guide walls 10c and 10d which adjoin one another in the upper part of the guide element but below that are interrupted by an opening which extends over part of the lift rod 9 where the walls 9c and 9d of the rod join another. The purpose of this opening will be described later herein. Preferably, the guide element 10 is injection-moulded with the deck plate 1 from a plastics.

As its lower end the lift rod 9 carries a pin 11 which bears on an actuating member 12 comprising two supporting surfaces 12a and 12b which are situated at different levels and between which a ramp surface 12c extends. The actuating member 12, which is preferably constructed as a plastics slide, can be moved from the position shown in Figs. 2 and 4 to the position shown in Fig. 5 by a rectilinear sliding movement in the direction indicated by the arrow *a* in Fig. 2. During this movement the ramp surface 12c cooperates with the pin 11 to raise the lift rod 9, preferably in a direction perpendicular to the deck plate, the rod being guided by the guide element 10. The lifting device 7 can thus raise the pick-up arm 4 as a result of this movement of the actuating member. For lowering the pick-up arm the actuating member 12 is moved in the reverse direction. The actuating member 12 is coupled by means not shown to an actuating button 13 on the upper side of the deck plate 1. By means of the actuating button 13 the actuating member 12 can be moved in the direction indicated by the arrow *a*, or in the opposite direction, to actuate the lifting device.

The lift rod 9 comprises a first pair of adjoining longitudinal peripheral walls 9a, b which slidably engage the guide walls 10a, b, respectively of the guide element 10, and a second pair of adjoining longitudinal peripheral walls 9c, 9d, which slidably engage the guide walls 10c, 10d, respectively of the guide element. Owing to the substantially square cross-section of the lift rod 9, in cross-section the walls 9a—9d are arranged in a square pattern relative to each other. It is to be noted that the term "square" is to be understood to mean an approximation to a square, because the longitudinal edges of walls of the first pair of adjoining walls 9a, 9b of the lift rod are situated at the corners of the square, but portions of the walls between these edges are slightly recessed. The purpose of this construction is to form between each wall of the first pair of adjoining walls 9a, 9b, of the lift rod 9 and the flat guide wall 10a, 10b respectively, of the guide element 10, a gap for containing a highly viscous substance. In the present embodiment this substance is silicone oil, which has a hydraulic action and which remains in these narrow gaps

between the walls of the lift rod and the guide walls under the influence of capillary action. Thus, there is no risk of the silicone oil leaking out of the lifting device 7.

In the part of the lift rod 9 which is exposed through the aforesaid opening in the guide walls 10c and 10d of the guide element 10 a recess 14 is formed in the adjoining edge portions of the walls 9d, 9c of the rod, which recess has a cylindrical wall and a central axis 14a which in the present embodiment makes an acute angle of preferably approximately 60° with the upper surface of the deck plate 1. The central axis 14a is situated in a plane 15 (see Fig. 3) which bisects the angle between the walls 9a and 9b of the lift rod. One end of a helical compression spring 16 having turns of substantially equal diameter bears against the bottom of the recess 14 and the other end engages in a recess 17 formed in the lower surface of the deck plate 1, the spring passing through the opening in the guide walls 10c and 10d. In this way the spring 16 exerts a force F (see Fig. 2) on the lift rod 9, which force is directed obliquely downwards. The force F may be decomposed into a force F1 which is directed perpendicularly to the deck plate and a force F2 which is directed parallel to the deck plate 1. The force F2 may be decomposed into forces F21 and F22 (see Fig. 3) whose directions are such that these forces urge the walls 9a and 9b of the lift rod 9 against the guide walls 10a and 10b, respectively. The downward force F1 of the spring 16 ensures that when the actuating member 12 is moved from the position shown in Fig. 5 to that shown in Fig. 4 the lifting device 7 is automatically lowered. During this movement an effective damping is obtained as a result of the presence of the silicone oil in the gaps between the walls 9a, 9b of the lift rod and the guide walls 10a and 10b respectively.

The operation of the record player, in particular of the lifting device and the parts which cooperate therewith, will now be described in more detail.

In its rest position the pick-up arm 4 rests on the arm support 8. In this position the lifting device 7 occupies the position shown in Fig. 4, in which the lift rod 9 with the pin 11 is positioned in the lower position under the influence of the pressure exerted by the spring 16. As already stated, the force F exerted by the spring 16 firmly presses the walls 9a, 9b of the lift rod against the guide walls 10a, 10b. The lifting device 7 can be actuated by pressing the actuating button 13, which is latched in the depressed position. As a result of the depression of the button 13 the actuating member 12 is moved in the direction indicated by the arrow a in Figs. 2 and 4, so that the ramp surface 12c cooperates with the pin 11 to push the lift rod 9 upwards. As the pick-up arm 4 is resting on the arm support 8 the pick-up arm 4 is now moved upwards. The spring 16 is thereby further compressed so that the walls 9a, 9b of the lift rod are constantly urged firmly against the guide walls 10a, 10b of the guide

element 10 during the upward movement of the lift rod 9. Consequently, during the upward movement of the lift rod 9, a capillary action is sustained in the gaps between the walls 9a, b and 10a, b, so that the silicone oil remains between these walls. When the lifting device 7 has reached the position shown in Fig. 5, the pick-up arm 4 is lifted off the support 8 and positioned above the turntable and the desired part of the gramophone record either manually or by means of a mechanism, not shown, underneath the deck plate 1, after which the pick-up arm is again rested on the support 8. Subsequently, by pressing the button 13 again, this button is unlatched and it is then moved up under spring force, as a result of which the actuating member 12 returns to the initial position shown in Fig. 4. This results in the lifting device 7 being lowered again so that the pick-up arm resting on the arm support 8, is moved downwards, which movement is damped effectively by the silicone oil. The damping is important in order to ensure that the stylus of the pick-up head 4a is lowered gently into the groove of the gramophone record.

The lift rod 9 is lowered *inter alia* under the influence of the force P exerted on the lifting device 7 by the weight of the pick-up arm 4, see Fig. 2. In this respect, it is advantageous that the arm support 8 is disposed asymmetrically towards the wall 9a of the lift rod 9 relative to a plane of symmetry 19 of the lift rod 9, which plane contains the central longitudinal axis of the lift rod and extends parallel to the walls 9a and 9c of the rod (see Figs. 2, 3), so that the force P acting on the arm support 8 during lowering results in an auxiliary torque being exerted on the lift rod 9, which torque ensures that near the upper end of the guide wall 10a the lift rod 9 remains constantly in contact with this wall. A similar effect is obtained when the pick-up arm 4 is lifted. It is to be noted that the plane 19 is situated at equal distances from and extends parallel to the walls 9a and 9c of the lift rod 9. Alternatively, this plane may be a diagonal plane containing the line of intersection of the planes of the walls 9a, 9d and the line of intersection of the planes of the walls 9b, 9c, in which case the auxiliary torque has the advantage that the lift rod is pressed against both the upper end of both the guide wall 10a and the guide wall 10b. Thus, *inter alia* under the influence of the weight of the pick-up arm 4, it is ensured that during raising and lowering the wall 9a and 9b of the lift rod are guided correctly by the guide element 9. In this respect it is advantageous that a square cross-section is selected for the lift rod 9 and a corresponding cross-section for the guide element 10. It is to be noted that the lift rod the guide element may have a different cross-sectional shape, but care should be taken that the vector of the force F exerted by the spring 16 extends in the bisecting plane which contains the line of intersection of the planes of two walls of the lift rod which correspond to the walls 9a, 9b.

Further, it is important that between the two walls of the lift rod and the two guide walls cooperating therewith, gaps are formed of a size such that a satisfactory capillary action is obtained to ensure that the highly viscous material remains in the gaps and does not leak away.

The record player in accordance with the invention has the advantage that its lifting device comprises a minimum number of parts. For assembling the lifting device only the integral unit which is injection-moulded in one piece and which comprises the arm support 8 and the lift rod 9 with the pin 11 is required. Further, when the silicone oil has been applied to the walls 9a, 9b of the lift rod 9 the rod has merely to be pressed into the guide element 10 and the spring 16 fitted in the recess 14 and the recess 17, after which the lifting device is ready for use. It is to be noted that the guide element 10 can be manufactured integrally with the deck plate 1 by injection-moulding using one die, so that the guide element 10 need not be mounted separately. In this respect it is advantageous that the guide walls 10a, 10b are flat, because such a construction is easy to achieve with the comparatively large die required for the deck plate. The guide walls may taper slightly relative to each other, provided that these walls are flat. Tolerances in the parts used cannot affect the correct operation of the lifting device. Such tolerances are eliminated automatically because the walls 9a, 9b of the lift rod 9 are urged against the guide walls 10a, 10b. Hence, it is not necessary for the other guide walls 10c, 10d to provide accurate guidance for the second pair of walls 9c, 9d of the lift rod.

The use of a small number of parts, which are preferably injection-moulded from a plastics the easy assembly and the reliable operation of the damped lifting device, enable the record player in accordance with the invention to be manufactured cheaply in mass production.

Claims

1. A record player comprising a deck plate (1), which carries a turntable (2) and a pick-up arm (4), and a lifting device (7) which can be moved upwards and downwards to lift and lower the turntable, which lifting device (7) comprises an arm support (8) and a lift rod (9) which forms an integral unit with said support (1) and is guided by a guide element (10) connected to the deck plate (1), the lift rod (9) cooperating with an actuating member (12) for moving the lifting device (7) upwards and downwards, and damping means which comprise a highly viscous substance being provided to damp at least the downward movement of the lifting device, characterized in that the lift rod comprises a first pair of longitudinal flat peripheral walls (9a, 9b) which make an angle with each other and which cooperate with a first pair of guide walls (10a, 10b) of the guide element (10), the guide element (10) forms an integral unit with the deck plate (1), the highly viscous sub-

stance is retained between said first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) and said first pair of guide walls (10a, 10b), and a spring element (16) arranged between the deck plate (1) and the lift rod (9) exerts on the lift rod a force, which is directed obliquely downwards towards the line of intersection of the planes of said first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) to urge said first pair of longitudinal flat peripheral walls (9a, 9b) against said first pair of guide walls (10a, 10b).

2. A record player as claimed in Claim 1, characterized in that the lift rod (9) has a square cross-section and the force vector of the spring element (16) extends in a plane which bisects the angle between said first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9).

3. A record player as claimed in Claim 2, characterized in that the spring element (16) is a helical spring, and in that a recess (14) with a cylindrical wall is formed in the lift rod (9) at a location where the walls of a second pair of peripheral walls (9c, 9d) of the lift rod (9) join each other, which recess (14) has a central axis (14a) situated in said bisecting plane and contains that end portion of the helical spring (16) which is remote from the deck plate (1).

4. A record player as claimed in any of the preceding claims, characterized in that the arm support (8) is disposed asymmetrically towards at least one of the walls (9a) of the first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) relative to a plane of symmetry of the lift rod (9).

5. A record player as claimed in any of the Claims 2 to 4, characterized in that at least near the location where it adjoins the deck plate (1) the guide element (10) is of tubular shape with a square cross-section and comprises a second pair of guide walls (10c, 10d) which, at a distance below the deck plate (1), are formed with an opening through which the spring element (16) passes to act on the lift rod (9).

6. A record player as claimed in any of the preceding Claims, characterized in that the first pair of guide walls (10a, 10b) are flat, the first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) engage the first pair of guide walls (10a, 10b) adjacent the edges, and between the first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) and the first pair of guide walls (10a, 10b) gaps are formed which contain the highly viscous substance.

Patentansprüche

1. Plattenspieler mit einer Gestellplatte (1), die einen Plattenteller (2) und einen Tonabnehmerarm (4) trägt, sowie mit einer Hebevorrichtung (7), die zum Heben bzw. Absenken des Tonabnehmerarms gegenüber der Oberseite des Plattentellers aufwärts bzw. abwärts bewegt werden kann, wobei diese Hebevorrichtung (7) einen Armträger (8) sowie einen Teil mit der gestellplatte (9) bildende Hebestange (9) aufweist.

Further, it is important that between the two walls of the lift rod and the two guide walls cooperating therewith, gaps are formed of a size such that a satisfactory capillary action is obtained to ensure that the highly viscous material remains in the gaps and does not leak away.

The record player in accordance with the invention has the advantage that its lifting device comprises a minimum number of parts. For assembling the lifting device only the integral unit which is injection-moulded in one piece and which comprises the arm support 8 and the lift rod 9 with the pin 11 is required. Further, when the silicone oil has been applied to the walls 9a, 9b of the lift rod 9 the rod has merely to be pressed into the guide element 10 and the spring 16 fitted in the recess 14 and the recess 17, after which the lifting device is ready for use. It is to be noted that the guide element 10 can be manufactured integrally with the deck plate 1 by injection-moulding using one die, so that the guide element 10 need not be mounted separately. In this respect it is advantageous that the guide walls 10a, 10b are flat, because such a construction is easy to achieve with the comparatively large die required for the deck plate. The guide walls may taper slightly relative to each other, provided that these walls are flat. Tolerances in the parts used cannot affect the correct operation of the lifting device. Such tolerances are eliminated automatically because the walls 9a, 9b of the lift rod 9 are urged against the guide walls 10a, 10b. Hence, it is not necessary for the other guide walls 10c, 10d to provide accurate guidance for the second pair of walls 9c, 9d of the lift rod.

The use of a small number of parts, which are preferably injection-moulded from a plastics the easy assembly and the reliable operation of the damped lifting device, enable the record player in accordance with the invention to be manufactured cheaply in mass production.

Claims

1. A record player comprising a deck plate (1), which carries a turntable (2) and a pick-up arm (4), and a lifting device (7) which can be moved upwards and downwards to lift and lower the pick-up arm relative to the upper side of the turntable, which lifting device (7) comprises an arm support (8) and a lift rod (9) which forms an integral unit with said support (1) and is guided by a guide element (10) connected to the deck plate (1), the lift rod (9) cooperating with an actuating member (12) for moving the lifting device (7) upwards and downwards, and damping means which comprise a highly viscous substance being provided to damp at least the downward movement of the lifting device, characterized in that the lift rod comprises a first pair of longitudinal flat peripheral walls (9a, 9b) which make an angle with each other and which cooperate with a first pair of guide walls (10a, 10b) of the guide element (10), the guide element (10) forms an integral unit with the deck plate (1), the highly viscous sub-

stance is retained between said first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) and said first pair of guide walls (10a, 10b), and a spring element (16) arranged between the deck plate (1) and the lift rod (9) exerts on the lift rod a force, which is directed obliquely downwards towards the line of intersection of the planes of said first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) to urge said first pair of longitudinal flat peripheral walls (9a, 9b) against said first pair of guide walls (10a, 10b).

2. A record player as claimed in Claim 1, characterized in that the lift rod (9) has a square cross-section and the force vector of the spring element (16) extends in a plane which bisects the angle between said first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9).

3. A record player as claimed in Claim 2, characterized in that the spring element (16) is a helical spring, and in that a recess (14) with a cylindrical wall is formed in the lift rod (9) at a location where the walls of a second pair of peripheral walls (9c, 9d) of the lift rod (9) join each other, which recess (14) has a central axis (14a) situated in said bisecting plane and contains that end portion of the helical spring (16) which is remote from the deck plate (1).

4. A record player as claimed in any of the preceding claims, characterized in that the arm support (8) is disposed asymmetrically towards at least one of the walls (9a) of the first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) relative to a plane of symmetry of the lift rod (9).

5. A record player as claimed in any of the Claims 2 to 4, characterized in that at least near the location where it adjoins the deck plate (1) the guide element (10) is of tubular shape with a square cross-section and comprises a second pair of guide walls (10c, 10d) which, at a distance below the deck plate (1), are formed with an opening through which the spring element (16) passes to act on the lift rod (9).

6. A record player as claimed in any of the preceding Claims, characterized in that the first pair of guide walls (10a, 10b) are flat, the first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) engage the first pair of guide walls (10a, 10b) adjacent the edges, and between the first pair of longitudinal flat peripheral walls (9a, 9b) of the lift rod (9) and the first pair of guide walls (10a, 10b) gaps are formed which contain the highly viscous substance.

Patentansprüche

1. Plattenspieler mit einer Gestellplatte (1), die einen Plattenteller (2) und einen Tonabnehmerarm (4) trägt, sowie mit einer Hebevorrichtung (7), die zum Heben bzw. Absenken des Tonabnehmerarms gegenüber der Oberseite des Plattentellers aufwärts bzw. abwärts bewegt werden kann, wobei diese Hebevorrichtung (7) einen Armträger (8) sowie eine einen Teil mit der genannten Gestellplatte (9) bildende Hebestange (9) aufweist.



und durch ein mit der Gestellplatte (1) verbundenes Führungselement (10) geführt wird, wobei die Hebestange (9) zum Bewegen der Hebevorrichtung (7) in der Aufwärts- sowie Abwärtsrichtung mit einem Betätigungselement (12) zusammenarbeitet, und mit Dämpfungsmitteln, die eine hochviskose Substanz enthalten zum Dämpfen wenigstens der Abwärtsbewegung der Hebevorrichtung, dadurch gekennzeichnet, dass die Hebestange ein erstes Paar länglicher flacher Umfangswände (9a, 9b) aufweist, die mit einander einen Winkel einschließen und mit einem ersten Paar Führungswände (10a, 10b) des Führungselementes (10) zusammenarbeiten, wobei das Führungselement (10) mit der Gestellplatte (1) einen Teil bildet, wobei die hochviskose Substanz sich zwischen dem genannten ersten Paar länglicher flacher Umfangswände (9a, 9b) der Hebestange (9) und dem genannten ersten Paar Führungswände (10a, 10b) befindet und wobei ein zwischen der Gestellplatte (1) und der Hebestange (9) angeordnetes Federelement (16) auf die Hebestange eine Kraft ausübt, die schräg nach unten in Richtung der Schnittlinie der Ebene des genannten ersten Paares länglicher flacher Umfangswände (9a, 9b) der Hebestange (9) gerichtet ist um das genannte erste Paar länglicher flacher Umfangswände (9a, 9b) gegen das genannte erste Paar Führungswände (10a, 10b) zu drücken.

2. Plattenspieler nach Anspruch 1, dadurch gekennzeichnet, dass die Hebestange (9) einen quadratischen Querschnitt hat und der Kraftvektor des Federelementes (16) sich in einer Ebene erstreckt, die den Winkel zwischen dem genannten ersten Paar länglicher flacher Umfangswände (9a, 9b) der Hebestange (9) halbiert.

3. Plattenspieler nach Anspruch 2, dadurch gekennzeichnet, dass das Federelement (16) eine Schraubenfeder ist und dass in der Hebestange (9) an der Stelle, wo die Wände eines zweiten Paares von Umfangswänden (9c, 9d) der Hebestange (9) einander berühren eine Ausnehmung (14) mit einer zylinderförmigen Wand gebildet ist, wobei diese Ausnehmung (14) eine Zentralachse (14a) aufweist, die in der genannten halbierenden Ebene liegt und denjenigen Endteil der Schraubenfeder (16) enthält, der in einem Abstand von der Gestellplatte (1) liegt.

4. Plattenspieler nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, dass der Armträger (8) auf der Seite wenigstens einer der Wände (9a) des ersten Paares länglicher flacher Umfangswände (9a, 9b) der Hebestange (9) asymmetrisch gegenüber einer Symmetrieebene der Hebestange (9) liegt.

5. Plattenspieler nach einem der Ansprüche 2 bis 4, dadurch gekennzeichnet, dass das Führungselement (10) wenigstens in der Nähe des Anschlusses an die Gestellplatte (1) rohrförmig ist mit einem quadratischen Querschnitt und ein zweites Paar Führungswände (10c, 10d) aufweist, die in einem Abstand unter der Gestellplatte (1) eine Öffnung aufweisen, durch die das Federelement (16) hindurchgeht um mit der Hebestange (9) zusammenzuarbeiten.

6. Plattenspieler nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, dass die das erste Paar bildenden Führungswände (10a, 10b) flach sind, das erste Paar länglicher flacher Umfangswände (9a, 9b) der Hebestange (9) mit dem ersten Paar Führungswände (10a, 10b) bei den Rändern zusammenarbeiten und dass zwischen dem ersten Paar länglicher flacher Umfangswände (9a, 9b) der Hebestange (9) und dem ersten Paar Führungswände (10a, 10b) Spalte gebildet sind, in denen die hochviskose Substanz vorhanden ist.

Revendications

1. Tourne-disque comprenant une plaque d'habillage (1), qui porte un plateau (2) et un bras de lecture (4), et un lève-bras (7) qui peut être déplacé vers le haut et vers le bas pour lever et abaisser le bras de lecture par rapport à la face supérieure du plateau, ce lève-bras (7) comprenant un support de bras (8) et une tige élévatrice (9) qui fait corps avec ce support (8) et qui est guidée par un élément de guidage (10) relié à la plaque d'habillage (1), la tige élévatrice (9) coopérant avec un organe d'actionnement (12) pour déplacer le lève-bras (7) vers le haut et vers le bas, et un dispositif amortisseur qui comprend une substance très visqueuse prévue pour amortir au moins le déplacement vers le bas du lève-bras, caractérisé en ce que la tige élévatrice comprend une première paire de faces périphériques planes longitudinales (9a, 9b) qui font un angle l'une avec l'autre et qui coopèrent avec une première paire de faces de guidage (10a, 10b) de l'élément de guidage (10), l'élément de guidage (10) faisant partie intégrante de la plaque d'habillage (1), la substance hautement visqueuse est retenue entre la première paire de faces périphériques planes longitudinales (9a, 9b) de la tige élévatrice (9) et la première paire de faces de guidage (10a, 10b), et un élément à ressort (16) disposé entre la plaque d'habillage (1) et la tige élévatrice (9) exerce sur cette tige élévatrice une force qui est dirigée obliquement vers la bas vers la ligne d'intersection entre les plans de la première paire de faces périphériques planes longitudinales (9a, 9b) de la tige élévatrice (9) pour solliciter la première paire de faces périphériques planes longitudinales (9a, 9b) contre la première paire de faces de guidage (10a, 10b).

2. Tourne-disque suivant la revendication 1, caractérisé en ce que la tige élévatrice (9) présente une section transversale carrée et le vecteur de force de l'élément à ressort (16) s'étend dans un plan bissecteur de l'angle formé entre la première paire de faces périphériques planes longitudinales (9a, 9b) de la tige élévatrice (9).

3. Tourne-disque suivant la revendication 2, caractérisé en ce que l'élément à ressort (16) est un ressort hélicoïdal et en ce qu'un évidement (14) présentant une paroi cylindrique est ménagé dans la tige élévatrice (9) à un endroit où les faces d'une seconde paire de faces périphériques (9c, 9d) de la tige élévatrice (9) se raccordent l'une à l'autre, cet évidement (14) présentant un axe central (14a)



situé dans le plan bissecteur et contenant la partie d'extrémité du ressort hélicoïdal (16) qui est éloignée de la plaque d'habillage (1).

4. Tourne-disque suivant l'une quelconque des revendications précédentes, caractérisé en ce que le support de bras (8) est disposé asymétriquement vers au moins une des faces (9a) de la première paire de faces périphériques planes longitudinales (9a, 9b) de la tige élévatrice (9) par rapport à un plan de symétrie de cette tige.

5. Tourne-disque suivant l'une quelconque des revendications 2 à 4, caractérisé en ce qu'au moins près de l'endroit où il se raccorde à la plaque d'habillage (1), l'élément de guidage (10) est de forme tubulaire à section transversale carrée et comprend une seconde paire de faces de guidage (10a, 10b) qui, à une certaine distance en

dessous de la plaque d'habillage (1), présentant une ouverture que l'élément à ressort (16) traverse pour agir sur la tige élévatrice (9).

6. Tourne-disque suivant l'une quelconque des revendications précédentes, caractérisé en ce que la première paire de faces de guidage (10a, 10b) comprend des faces planes, les faces périphériques planes longitudinales (9a, 9b) de la première paire de la tige élévatrice (9) attaquent les faces de guidage (10a, 10b) de la première paire près des bords de celles-ci et, entre les faces périphériques planes longitudinales (9a, 9b) de la tige élévatrice (9) de la première paire et les faces de guidage (10a, 10b) de la première paire, sont ménagés des interstices qui contiennent la substance hautement visqueuse.

5

10

15

20

25

30

35

40

45

50

55

60

65

7

