

METHOD AND APPARATUS FOR PROCESSING SCREEN SENSITIVE INFORMATION

Technical Field

The present invention relates to the field of information processing technologies, and in particular, to a screen information processing method and apparatus.

Background

With the rapid development of electronic technologies, electronic devices such as mobile phones, tablets, and computers are more widely applied to people's daily study, work, and lives. In using an electronic device, the screen is a major means through which people acquire various information. However, in conventional techniques, various information includes some personal privacy-related sensitive information, which is generally presented on the screen directly and is easily spied by other people, causing leakage of personal information and bringing about unnecessary trouble to people's life.

Summary of Invention

An objective of embodiments of the present application is to provide a screen sensitive information processing method and apparatus, to protect information displayed on a screen of an electronic device from peeping, and to improve security of information viewing for users.

To achieve the foregoing objective, an embodiment of the present application provides a screen sensitive information processing method, including:

monitoring whether light intensity detected by a light sensor increases to a first threshold, and when it is monitored that the light intensity increases to the first threshold, identifying an area where predefined sensitive information in display content of a screen is located, and masking content displayed in the area where the sensitive information is located.

In a preferred embodiment, the method further includes: monitoring whether the light intensity detected by the light sensor decreases to a second threshold, and when it is monitored that the light intensity decreases to the second threshold, identifying the masked area where the sensitive information is located, and canceling masking of the area where the sensitive information is located.

In a preferred embodiment, the masking content displayed in the area where the sensitive information is located includes: displaying a rectangular picture in the area where the sensitive information is located.

In a preferred embodiment, the masking content displayed in the area where the sensitive information is located includes:

rendering the rectangular picture, and displaying the rendered rectangular picture in the area where the sensitive information is located, the rectangular picture covering original display content in the area where the sensitive information is located.

In a preferred embodiment, the masking content displayed in the area where the sensitive information is located includes: setting a background color attribute of the area where the sensitive information is located to be a sensitive information color attribute.

In a preferred embodiment, the canceling masking of the area where the sensitive information is located includes: displaying, in the area where the sensitive information is located, the sensitive information of the area.

In a preferred embodiment, the canceling masking of the area where the sensitive information is located includes: rendering original display content in the display content of the screen.

In a preferred embodiment, the canceling masking of the area where the sensitive information is located includes: setting a background color of the area where the sensitive information is located to be an original background color attribute of the area.

Another aspect of the present application further provides a screen sensitive information processing apparatus, the apparatus including:

a first monitoring unit configured to monitor whether light intensity detected by a light sensor increases to a first threshold;

a first identification unit configured to identify, when the first monitoring unit monitors that the light intensity increases to the first threshold, an area where predefined sensitive information in display content of a screen is located; and

a first masking unit configured to mask, after the first identification unit identifies the area where the predefined sensitive information is located in the display content of the screen, content displayed in the area where the sensitive information is located.

In a preferred embodiment, the apparatus further includes:

a second monitoring unit configured to monitor whether the light intensity detected by the light sensor decreases to a second threshold;

a second identification unit configured to identify, when the second monitoring unit monitors that the light intensity decreases to the second threshold, the area where the predefined sensitive information is located in the display content of the screen; and

a second masking unit configured to cancel, after the second identification unit identifies the area where the predefined sensitive information is located in the display content of the screen, masking of the area where the sensitive information is located.

As can be seen from the technical solutions provided by the embodiments of the present application, the embodiments of the present application achieve the function of protecting sensitive information by identifying an area where predefined sensitive information in display content of a screen is located and masking content displayed in the area where the sensitive information is located, which significantly improves the security of information viewing for users compared with the conventional techniques.

Brief Description of Drawings

To describe the technical solutions in the embodiments of the present application or the conventional techniques more clearly, the accompanying drawings required for illustrating the embodiments or the conventional techniques will be introduced briefly below. Apparently, the drawings in the following description are only some embodiments in the present application, and those of ordinary skill in the art may further obtain other drawings according to these accompanying drawings without paying creative efforts.

FIG. 1 is a schematic flowchart of a screen sensitive information processing method according to an embodiment of the present application;

FIG. 2 is a schematic flowchart of a screen sensitive information processing method according to Embodiment 1 of the present application;

FIG. 3 is a schematic diagram of an initial display state of an electronic device, in which a mobile phone is used as an example;

FIG. 4 is a schematic diagram of a screen display state of the electronic device after sensitive information is masked by displaying a rectangular picture;

FIG. 5 is a schematic diagram of a screen display state of the electronic device after a user presses a light sensor with a finger to cancel masking;

FIG. 6 is a schematic flowchart of a screen sensitive information processing method according to Embodiment 2 of the present application;

FIG. 7 is a schematic flowchart of a screen sensitive information processing method according to Embodiment 3 of the present application; and

FIG. 8 is a schematic diagram of a screen sensitive information processing apparatus according to an embodiment of the present application.

Detailed Description

To help those in the art better understand the technical solutions in the present application, the technical solutions in the embodiments of the present application will be described clearly and completely in conjunction with the accompanying drawings in the embodiments of the present application. Apparently, the described embodiments are only some of the embodiments rather than all of the embodiments of the present application. All other embodiments obtained by those of ordinary skill in the art based on the embodiments in the present application without paying creative efforts shall fall in the protection scope of the present application.

When a current electronic device is in use, user information will be directly presented on the screen, which makes it extremely easy to spy the user information, causing leakage of some sensitive privacy information and bringing about unnecessary trouble to users.

To solve the foregoing problem, an embodiment of the present application provides a screen sensitive information processing method. As shown in FIG. 1, the method includes:

Step S101: It is monitored whether light intensity detected by a light sensor increases to a first threshold.

Step S102: When it is monitored that the light intensity increases to the first threshold, an area where predefined sensitive information in display content of a screen is located is identified, and content displayed in the area where the sensitive information is located is masked.

As can be seen, in this embodiment of the present application, when it is monitored that the light intensity increases to the first threshold, the area where the predefined sensitive information is located in the display content of the screen may be identified, and the content displayed in the area where the sensitive information is located may be masked, which can effectively prevent leakage of sensitive information of a user, and security of information viewing is significantly improved for the user compared with the conventional

techniques.

In practice, there may be multiple implementations of masking the sensitive information displayed on the screen, and specific implementations of the embodiments of the present application are described below in detail by using several specific examples.

Embodiment 1

FIG. 2 is a schematic flowchart of a screen sensitive information processing method according to this embodiment. The screen sensitive information processing method may be applied to any electronic device that can display information, such as a mobile smart phone, a tablet electronic device, a portable computer (such as a notebook computer), a personal digital assistant (PDA), a laptop computer, or other devices that can display information through a screen. Applications corresponding to information displayed on the screen include, but are not limited to, a social platform application (such as Facebook, Twitter, or Weibo), an email application, a short messaging service (SMS) application, a multimedia messaging service (MMS) application, and the like.

As shown in FIG. 2, the screen sensitive information processing method includes the following steps:

Step S201: An electronic device 1 opens an application, and a screen 10 displays information of a current application page.

FIG. 3 displays content displayed on the screen 10 after the electronic device 1 opens the application, and it is assumed that all information currently displayed on the screen 10 includes information A 101, information B 102, information C 103, information D 104, and information E 105, wherein the information A101 is predefined sensitive information.

Step S202: It is monitored whether light intensity detected by a light sensor 11 increases to a first threshold.

In practice, the current application may monitor ambient light intensity by invoking a light sensor API of the electronic device 1. The light sensor API of the electronic device 1 cannot be invoked to monitor the light intensity until the application is started; therefore, when the application is just started in step S201, an initial display state of the screen 10 is a state in which sensitive information is not masked; after the light sensor API of the electronic device is invoked, if the detected light intensity is lower than the first threshold, the current page is continued to be displayed, and if the monitored light intensity is higher than the first threshold, step S203 is performed.

Step S203: When it is monitored that the light intensity increases to the first threshold, an area where sensitive information is located is identified in display content of the screen 10, and content displayed in the area where the sensitive information is located is masked by displaying a rectangular picture 101'.

FIG. 4 is a schematic diagram of a screen display state of the electronic device after sensitive information is masked by displaying a rectangular picture. When an event that the light intensity increases to the first threshold occurs, the area where the predefined sensitive information is located is identified. To identify the area where the sensitive information is located, a label may be set for each display area in advance, and the labels are identified when the event that the light intensity increases to the first threshold occurs; the area where the sensitive information is located may be positioned according to a label, and masking of the sensitive information is implemented by covering, in the area where the sensitive information is located, the sensitive information with a set rectangular picture 101', or masking of the sensitive information may also be implemented by replacing original sensitive information with the set rectangular picture 101' for display. Specifically, the area where the sensitive information is located is a rectangular space, and the rectangular space is determined by using a coordinate point and an area; when it is monitored that the light intensity is greater than the first threshold, a coordinate point at the lower left corner of the area where the sensitive information is located is positioned first, and then a rectangular is acquired starting from the coordinate point at the lower left corner, to mask the sensitive information.

In addition, the coordinate point may also be another position of the area where the sensitive information is located, for example, the upper left corner, the lower right corner, or the like, and may also be in other forms in practice, which are not limited in this embodiment of the present application.

Step S204: It is monitored whether the light intensity detected by the light sensor 11 decreases to a second threshold.

Step S205: When it is monitored that the light intensity decreases to the second threshold, the masked area where the sensitive information is located is identified in the screen 10, the sensitive information is displayed in the area where the sensitive information is located, and the rectangular picture 101' displayed in the area where the sensitive information is located is canceled, thus canceling masking of the area where the sensitive information is located.

In the screen display state shown in FIG. 4, specifically, an event that the light intensity decreases to the second threshold is triggered by covering the light sensor 11 with a finger 111, the area where the predefined sensitive information is located is identified, and masking display of the sensitive information is canceled, as shown in FIG. 5. Those skilled in the art should clearly know that a trigger manner for implementing a decrease of the light intensity detected by the light sensor 11 to the second threshold is not limited to only the manner of covering the light sensor 11 with the finger 111 shown in FIG. 5, but may be in other forms in practice, which are not limited in this embodiment of the present application.

In addition, when the finger 111 of the user is moved away from the light sensor 11, the light intensity increases gradually, and when the light sensor 11 monitors that the light intensity is lower than the first threshold, the sensitive information is continued to be displayed; and when the light sensor 11 monitors that the light intensity increases to the first threshold, step S203 is performed to mask the sensitive information.

It should be further noted that the first threshold mentioned in this embodiment is greater than or equal to the second threshold.

Through the screen sensitive information processing method of this embodiment, after it is monitored that light intensity increases to a first threshold, an area where sensitive information is located can be positioned, and the sensitive information is masked by displaying a rectangular picture in the area where the sensitive information is located, so that leakage of sensitive information of a user can be effectively prevented; moreover, after it is monitored that the light intensity decreases to a second threshold, masking of the area where the sensitive information is located may be canceled, thus meeting an information viewing requirement of the user, and security of information viewing is significantly improved for the user compared with the conventional techniques.

Embodiment 2

FIG. 6 is a schematic flowchart of a screen sensitive information processing method according to this embodiment. The screen sensitive information processing method may be applied to any electronic device that can display information, such as a mobile smart phone, a tablet electronic device, a portable computer (such as a notebook computer), a personal digital assistant (PDA), a laptop computer, or other devices that can display information through a screen. Applications corresponding to information displayed on the screen include, but are not limited to, a social platform application (such as

Facebook, Twitter, or Weibo), an email application, a short messaging service (SMS) application, a multimedia messaging service (MMS) application, and the like.

As shown in FIG. 6, the screen sensitive information processing method includes the following steps:

Step S301: An electronic device opens an application, and a screen displays information of a current application page.

It is assumed that information displayed on the screen after the electronic device opens the application includes information A, information B, information C, information D, and information E, wherein the information A is sensitive information.

Step S302: It is monitored whether light intensity detected by a light sensor increases to a first threshold.

In practice, the current application may monitor ambient light intensity by invoking a light sensor API of the electronic device. The light sensor API of the electronic device cannot be invoked to monitor the light intensity until the application is started; therefore, when the application is just started in step S301, an initial display state of the screen is a state in which sensitive information is not masked; after the light sensor API of the electronic device is invoked, if the detected light intensity is lower than the first threshold, the current page is continued to be displayed, and if the monitored light intensity is higher than the first threshold, step S303 is performed.

Step S303: When it is monitored that the light intensity increases to the first threshold, an area where predefined sensitive information in display content of a screen is located is identified, and original display content is rendered for the display content of the screen in the area.

Based on the rendering of the original display content, a rectangular picture is rendered, the area where the sensitive information is located displays the rendered rectangular picture, and the rectangular picture covers the original display content in the area where the sensitive information is located.

In practice, to identify the area where the predefined sensitive information is located, a label may be set for each display area in advance, and the labels are identified when the event that the light intensity increases to the first threshold occurs; the area where the sensitive information is located may be positioned according to a label. Interface rendering is performed twice in the area where the sensitive information is located; the sensitive information is rendered at the first time, that is, all display content is

drawn on the screen, and at the second time, a covering picture is rendered in the area where the sensitive information is located. In other words, the interface picture rendered at the second time will cover the sensitive information rendered at the first time, thus masking the sensitive information.

Step S304: It is monitored whether the light intensity detected by the light sensor decreases to a second threshold.

Step S305: When it is monitored that the light intensity decreases to the second threshold, the masked area where the sensitive information is located is identified in the screen, the original display content in the area where the sensitive information is located is rendered, and masking of the area where the sensitive information is located is canceled.

In the case where the sensitive information is masked, specifically, an event that the light intensity decreases to the second threshold is triggered by covering the light sensor with a finger, the area where the predefined sensitive information is located is identified, and masking display of the sensitive information is canceled by rendering the original sensitive content in the area. Those skilled in the art should clearly know that a trigger manner for implementing a decrease of the light intensity detected by the light sensor to the second threshold is not limited to only the manner of covering the light sensor with the finger, but may be in other forms in practice, which are not limited in this embodiment of the present application.

In addition, when the finger of the user is moved away from the light sensor, the light intensity increases gradually, and when the light sensor monitors that the light intensity is lower than the first threshold, the sensitive information is continued to be displayed; and when the light sensor monitors that the light intensity increases to the first threshold, step S303 is performed to mask the sensitive information.

It should be further noted that the first threshold mentioned in this embodiment is greater than or equal to the second threshold.

Through the screen sensitive information processing method of this embodiment, after it is monitored that light intensity increases to a first threshold, an area where sensitive information is located can be positioned in a predefined manner, and the sensitive information is masked by performing interface rendering twice, where the sensitive information is rendered at the first time and a covering picture is rendered at the second time, so that leakage of sensitive information of a user can be effectively prevented; moreover, after it is monitored that the light intensity decreases to a second threshold,

original display content is rendered, so that masking of the area where the sensitive information is located can be canceled, thus meeting an information viewing requirement of the user, and security of information viewing is significantly improved for the user compared with the conventional techniques.

Embodiment 3

FIG. 7 is a schematic flowchart of a screen sensitive information processing method according to this embodiment. The screen sensitive information processing method may be applied to any electronic device that can display information, such as a mobile smart phone, a tablet electronic device, a portable computer (such as a notebook computer), a personal digital assistant (PDA), a laptop computer, or other devices that can display information through a screen. Applications corresponding to information displayed on the screen include, but are not limited to, a social platform application (such as Facebook, Twitter, or Weibo), an email application, a short messaging service (SMS) application, a multimedia messaging service (MMS) application, and the like.

As shown in FIG. 7, the screen sensitive information processing method includes the following steps:

Step S401: An electronic device opens an application, and a screen displays information of a current application page.

It is assumed that information displayed on the screen after the electronic device opens the application includes information A, information B, information C, information D, and information E, wherein the information A is sensitive information.

Step S402: It is monitored whether light intensity detected by a light sensor increases to a first threshold.

In practice, the current application may monitor ambient light intensity by invoking a light sensor API of the electronic device. The light sensor API of the electronic device cannot be invoked to monitor the light intensity until the application is started; therefore, when the application is just started in step S401, an initial display state of the screen is a state in which sensitive information is not masked; after the light sensor API of the electronic device is invoked, if the detected light intensity is lower than the first threshold, the current page is continued to be displayed, and if the monitored light intensity is higher than the first threshold, step S403 is performed.

Step S403: When it is monitored that the light intensity increases to the first threshold, an area where predefined sensitive information in display content of a screen is

located is identified, and a background color attribute of the area where the sensitive information is located is set to be a sensitive information color attribute.

In practice, to identify the area where the predefined sensitive information is located, a label may be set for each display area in advance, and the labels are identified when the event that the light intensity increases to the first threshold occurs; the area where the sensitive information is located may be positioned according to a label, and the background color attribute of the area where the sensitive information is located is adjusted to a color attribute for sensitive information, thus masking the sensitive information.

Step S404: It is monitored whether the light intensity detected by the light sensor decreases to a second threshold.

Step S405: When it is monitored that the light intensity decreases to the second threshold, the masked area where the sensitive information is located is identified in the screen, and a background color of the area where the sensitive information is located is set to be an original background color attribute of the area.

In the case where the sensitive information is masked, specifically, an event that the light intensity decreases to the second threshold is triggered by covering the light sensor with a finger, the area where the predefined sensitive information is located is identified, and masking display of the sensitive information is canceled by recovering an original state of the background color attribute of the area where the sensitive information is located. Those skilled in the art should clearly know that a trigger manner for implementing a decrease of the light intensity detected by the light sensor to the second threshold is not limited to only the manner of covering the light sensor with the finger, but may be in other forms in practice, which are not limited in this embodiment of the present application.

In addition, when the finger of the user is moved away from the light sensor, the light intensity increases gradually, and when the light sensor monitors that the light intensity is lower than the first threshold, the sensitive information is continued to be displayed; and when the light sensor monitors that the light intensity increases to the first threshold, step S403 is performed to mask the sensitive information.

It should be further noted that the first threshold mentioned in this embodiment is greater than or equal to the second threshold.

Through the screen sensitive information processing method of this embodiment, after it is monitored that light intensity increases to a first threshold, an area where sensitive information is located can be positioned, and the sensitive information is masked by adjusting a background color attribute of the area where the sensitive information is located, so that leakage of sensitive information of a user can be effectively prevented; moreover, after it is monitored that the light intensity decreases to a second threshold, the background color attribute of the area where the sensitive information is located is recovered, so that masking of the area where the sensitive information is located can be canceled, thus meeting an information viewing requirement of the user, and security of information viewing is significantly improved for the user compared with the conventional techniques.

An embodiment of the present application further provides a corresponding screen sensitive information processing apparatus 800, which, as shown in FIG. 8, includes: a first monitoring unit 801, a first identification unit 802, and a first masking unit 803, wherein the first monitoring unit 801 is configured to monitor whether light intensity detected by a light sensor increases to a first threshold; the first identification unit 802 is configured to identify, when the first monitoring unit 801 monitors that the light intensity increases to the first threshold, an area where predefined sensitive information in display content of a screen is located; and the first masking unit 803 is configured to mask, after the first identification unit 802 identifies the area where the predefined sensitive information is located in the display content of the screen, content displayed in the area where the sensitive information is located.

In addition, the apparatus provided by this embodiment of the present application further includes: a second monitoring unit, a second identification unit, and a second masking unit, wherein the second monitoring unit is configured to monitor whether the light intensity detected by the light sensor decreases to a second threshold; the second identification unit is configured to identify, when the second monitoring unit monitors that the light intensity decreases to the second threshold, the area where the predefined sensitive information is located in the display content of the screen; and the second masking unit is configured to cancel, after the second identification unit identifies the area where the predefined sensitive information is located in the display content of the screen, masking of the area where the sensitive information is located.

As can be seen, a screen sensitive information processing apparatus provided in this embodiment, after monitoring that light intensity increases to a first threshold, can position an area where sensitive information is located, can effectively prevent leakage of sensitive information of a user by masking content displayed in the area where the sensitive information is located, and recovers a background color attribute of the area where the sensitive information is located after monitoring that the light intensity decreases to a second threshold, thus canceling masking of the area where the sensitive information is located, to meet an information viewing requirement of the user; security of information viewing is significantly improved for the user compared with the conventional techniques.

In the 1990s, a technological improvement can be distinctively classified as a hardware improvement (for example, improvement on a circuit structure such as a diode, a transistor, or a switch) or a software improvement (improvement on a method procedure). However, with the development of technology, many improvements on method procedures nowadays can be considered as direct improvements on hardware circuit structures. Almost all designers obtain corresponding hardware circuit structures by programming improved method procedures into hardware circuits. Therefore, an improvement on a method procedure can also be implemented by a physical hardware module. For example, a Programmable Logic Device (PLD) (such as a Field Programmable Gate Array (FPGA)) is such an integrated circuit, and a logic function thereof is determined by a user's programming on the device. The designer "integrates" a digital system on a PLD through programming, without asking a chip manufacturer to design and manufacture a dedicated integrated circuit chip 2. Moreover, nowadays, instead of manually manufacturing integrated circuit chips, such programming is mostly implemented by a "logic compiler", which is similar to a software compiler used in program development and writing; original code before compiling also needs to be written in a particular programming language, which is referred to as Hardware Description Language (HDL), and there are many kinds rather than only one kind of HDL, for example, Advanced Boolean Expression Language (ABEL), Altera Hardware Description Language (AHDL), Confluence, Cornell University Programming Language (CUPL), HDCal, Java Hardware Description Language (JHDL), Lava, Lola, MyHDL, PALASM, Ruby Hardware Description Language (RHDL), and the like; Very-High-Speed Integrated Circuit Hardware Description Language (VHDL) and Verilog2 are most commonly used at present. Those skilled in the art should also clearly

know that, by logically programming a method procedure by using the several hardware description languages described above and programming the method procedure into an integrated circuit, a hardware circuit for implementing the logic method procedure can be easily obtained.

A controller can be implemented in any suitable manner, for example, the controller may employ forms such as a microprocessor or processor as well as a computer readable medium storing computer readable program code (such as software or firmware) executable by the processor (microprocessor), a logic gate, a switch, an Application Specific Integrated Circuit (ASIC), a programmable logic controller, and an embedded microcontroller. Examples of the controller include, but are not limited to, the following microcontrollers: ARC 625D, Atmel AT91SAM, Microchip PIC18F26K20, and Silicone LabsC8051F320, and a memory controller may also be implemented as a part of control logic of a memory.

Those skilled in the art are also aware that, in addition to implementing the controller by means of pure computer readable program code, it is totally possible to logically programming method steps such that the controller implements the same function in the forms of a logic gate, a switch, an ASIC, a programmable logic controller, an embedded microcontroller, and the like. Therefore, such a controller may be regarded as a kind of hardware component, and the apparatus included therein for implementing various functions may also be regarded as a structure inside the hardware component. Alternatively, the apparatus for implementing various functions may even be regarded as not only software modules for implementing the method but also the structure in the hardware component.

The system, apparatus, modules or units illustrated in the foregoing embodiment may be specifically implemented by a computer chip or an entity, or implemented by a product having a particular function.

For ease of description, when the apparatus is described, it is divided into various units based on functions and the units are described respectively. Of course, functions of various units may be implemented in one or more software and/or hardware during implementation of the present application.

Through the foregoing description about the implementations, those skilled in the art can clearly understand that the present application may be implemented by software plus a necessary universal hardware platform. Based on such an understanding, the

technical solutions of the present application essentially, or the part contributing to the conventional techniques may be implemented in the form of a software product. In a typical configuration, a computation device includes one or more central processing units (CPUs), I/O interfaces, network interfaces, and a memory. The computer software product may include several instructions for enabling a computer device (which may be a personal computer, a server, a network device, or the like) to execute the method in each embodiment of the present application or in some parts of the embodiment. The computer software product may be stored in a memory. The memory may include computer readable media such as a volatile memory, a Random Access Memory (RAM), and/or non-volatile memory, e.g., Read-Only Memory (ROM) or flash RAM. The memory is an example of a computer readable medium. Computer readable media include permanent, nonpermanent, mobile and immobile media, which can implement information storage through any method or technology. The information may be computer readable instructions, data structures, program modules or other data. Examples of storage media of computers include, but are not limited to, Phase-change RAMs (PRAMs), Static RAMs (SRAMs), Dynamic RAMs (DRAMs), other types of Random Access Memories (RAMs), Read-Only Memories (ROMs), Electrically Erasable Programmable Read-Only Memories (EEPROMs), flash memories or other memory technologies, Compact Disk Read-Only Memories (CD-ROMs), Digital Versatile Discs (DVDs) or other optical memories, cassettes, cassette and disk memories or other magnetic memory devices or any other non-transmission media, which can be used for storing information accessible to the computation device. According to the definitions herein, the computer readable media exclude non-transitory computer readable medium (transitory media), such as modulated data signals and carriers.

The embodiments in this specification are described in a progressive manner, for same or similar parts in the embodiments, reference may be made to each other, and each embodiment focuses on a difference from other embodiments. Especially, description of the system embodiment is relatively simple because it is substantially similar to the method embodiment, and for related parts, reference may be made to the partial description of the method embodiment.

The present application may be applied to a lot of general-purpose or special-purpose computer system environments or configurations, for example, a personal computer, a server computer, a handheld device or portable device, a tablet device, a

multi-processor system, a microprocessor-based system, a set-top box, a programmable consumer electronic device, a network PC, a minicomputer, a mainframe computer, a distributed computing environment including any foregoing system or device, and the like.

The present application may be described in a general context, such as a program module, of a computer executable instruction executed by a computer. Generally, the program module includes a routine, a program, an object, an element, a data structure, a class, and the like for executing a specific task or implementing a specific abstract data type. The present application may also be practiced in distributed computing environments, and in these distributed computing environments, tasks are executed by a remote processing device that is connected through a communications network. In the distributed computing environments, the program module may be located in local and remote computer storage media including a storage device.

Although the present application has been depicted through embodiments, those of ordinary skill in the art should know that the present application has many variations and modifications without departing from the spirit of the present application, and it is desired that the appended claims include these variations and modifications without departing from the spirit of the present application.

Claims

1. A screen sensitive information processing method, the method comprising:
monitoring whether light intensity detected by a light sensor increases to a first threshold; and
when it is monitored that the light intensity increases to the first threshold, identifying an area where predefined sensitive information in display content of a screen is located and masking content displayed in the area where the sensitive information is located.
2. The method of claim 1, further comprising:
monitoring whether the light intensity detected by the light sensor decreases to a second threshold; and
when it is monitored that the light intensity decreases to the second threshold, identifying the masked area where the sensitive information is located and canceling masking of the area where the sensitive information is located.
3. The method of claim 2, wherein the masking content displayed in the area where the sensitive information is located includes:
displaying a rectangular picture in the area where the sensitive information is located.
4. The method of claim 3, wherein the canceling masking of the area where the sensitive information is located includes:
displaying, in the area where the sensitive information is located, the sensitive information of the area.
5. The method of claim 2, wherein the masking content displayed in the area where the sensitive information is located includes:
rendering a rectangular picture; and
displaying the rendered rectangular picture in the area where the sensitive information is located, the rectangular picture covering original display content in the area where the sensitive information is located.

6. The method of claim 5, wherein the canceling masking of the area where the sensitive information is located includes:

rendering original display content in the display content of the screen.

7. The method of claim 2, wherein the masking content displayed in the area where the sensitive information is located includes:

setting a background color attribute of the area where the sensitive information is located to be a sensitive information color attribute.

8. The method of claim 7, wherein the canceling masking of the area where the sensitive information is located includes:

setting a background color of the area where the sensitive information is located to be an original background color attribute of the area.

9. The method of claim 1, wherein the masking content displayed in the area where the sensitive information is located includes:

displaying a rectangular picture in the area where the sensitive information is located.

10. The method of claim 1, wherein the masking content displayed in the area where the sensitive information is located includes:

rendering the rectangular picture; and

displaying the rendered rectangular picture in the area where the sensitive information is located, the rectangular picture covering original display content in the area where the sensitive information is located.

11. The method of claim 1, wherein the masking content displayed in the area where the sensitive information is located includes:

setting a background color attribute of the area where the sensitive information is located to be a sensitive information color attribute.

12. A screen sensitive information processing apparatus, the apparatus comprising:
a first monitoring unit configured to monitor whether light intensity detected by a light sensor increases to a first threshold;

a first identification unit configured to identify, when the first monitoring unit monitors that the light intensity increases to the first threshold, an area where predefined sensitive information in display content of a screen is located; and

a first masking unit configured to mask, after the first identification unit identifies the area where the predefined sensitive information is located in the display content of the screen, content displayed in the area where the sensitive information is located.

13. The apparatus of claim 12, further comprising:

a second monitoring unit configured to monitor whether the light intensity detected by the light sensor decreases to a second threshold;

a second identification unit configured to identify, when the second monitoring unit monitors that the light intensity decreases to the second threshold, the area where the predefined sensitive information is located in the display content of the screen; and

a second masking unit configured to cancel, after the second identification unit identifies the area where the predefined sensitive information is located in the display content of the screen, masking of the area where the sensitive information is located.