

## Description

The invention relates generally to downhole seismic sources and, more particularly, but not by way of limitation, it relates to an improved type of orbital vibration source for generating both shear wave and compression wave energy for coupling to a bore hole wall.

The prior art has seen a number of different downhole sources as used in different types of transmitter/receiver logging systems. Many different types of source mechanisms have been utilized for inducing acoustic energy into a borehole wall and subsequently analyzing velocity and/or phase of received energy to ascertain certain lithologic information. There are currently on-going efforts by a number of entities to develop suitable downhole sources for generation of shear waves and/or compressional waves which sources are capable of generating significantly greater power of energy input with high signal-to-noise ratios in order to enable certain new approaches to seismic data acquisition. Thus, current efforts take various forms and utilize diverse mechanisms in attempts to impart a clean, concise, seismic energy input through the borehole wall or, in some cases, the well casing, and it is contemplated that development of such sources will indeed open new possibilities of seismic data acquisition and interpretation.

United States Patent US-A-4103756 discloses a downhole seismic source which produces longitudinal and shear waves. United States Patent US-A-4207961 discloses an exciting method for a logging using an S wave source located in a bore hole.

The present invention relates to an improved type of downhole vibration device utilizing a reaction mass and motion generator in order to couple compressional and/or shear wave seismic energy waves into a borehole wall, and energy is generated with sufficient power and definitive wave form to enable much expanded forms of seismic energy detection. Basically, the present invention uses the sonde casing of generally cylindrical shape as the source reaction mass while housing an interactive rotational disk or the like to impart transverse orbital motion through the coupling well bore fluid into the borehole wall. The invention contemplates a number of different types of basic orbital motion generators including motor-driven eccentric disk, piezoelectric displacement, and electromagnetic displacement, as well as the various controls and safeguards.

Therefore, it is an object of the present invention to provide a downhole orbital source effective for usage in obtaining reverse vertical seismic profiles (VSP), borehole logging, cross-hole seis-

mic sections, and related data acquisitions.

Viewed from one aspect the invention provides a downhole seismic source for the simultaneous generation of orbital shear wave seismic energy and compression wave seismic energy into a fluid-filled borehole wall comprising:

an elongated frame means having a central axis and an outer wall supportable at a point along said borehole wall; and

drive means disposed in said frame means and energizable to impart an orbital motion to at least a portion of the frame means outer wall thereby to generate an orbital shear wave in said borehole wall.

The invention may thus provide a downhole vibrator for simultaneous production of both shear waves and compression waves with high signal-to-noise ratios.

At least in preferred forms, the invention provides a downhole vibrator that can be easily operated to couple energy through the well bore fluids into the surrounding formation whether the borehole is cased or uncased.

Elliptically polarized seismic shear waves can be generated into the wall of a fluid-filled borehole for time-displaced orbital propagation.

The preferred downhole vibrator does not require azimuthal orientation; that is its seismic output can be the same in all radial directions.

Some embodiments of the invention will now be described by way of example only and with reference to the drawings, in which:

FIG. 1A is an idealized illustration of a section of borehole containing an orbital source and isolated detector sonde with section parts shown in cutaway;

FIG. 1B is a section taken along lines 1B-1B of FIG. 1A;

FIG. 2 is a depiction of energy propagation from an orbital source uphole toward earth's surface;

FIG. 3A is a vertical cross-section of the upper portion of another form of orbital seismic source;

FIG. 3B is a vertical cross-section of the lower portion of the orbital seismic source of FIG. 3A;

FIG. 3C is a cross-section taken along lines 3C-3C of FIG. 3B;

FIG. 4A is a vertical cross-section of a portion of a downhole source wherein prime force generation is effected by electromagnetics;

FIG. 4B is a section taken along lines 4B-4B of FIG. 4A; and

FIG. 5 is a vertical section taken along a portion of a downhole seismic source wherein the prime energizing force relies upon piezoelectric action.

FIGS. 1A and 1B illustrate one type of orbital seismic source 10 as it is suspended in a borehole 12 containing wellbore fluid 14. The source 10 is suspended by means of a cable 16 and a suitable

isolator (not shown) which, damps any interactive vibration relative to a receiver sonde 18. The entire sonde string of one or more receiver sondes 18, the isolating structure, and the seismic source 10 are then supported downhole in the borehole fluid 14 by means of a surface-controlled logging cable 20.

The detector sonde 18 consists of a tubular frame 22 housing one or more vibrationally isolated seismic energy detectors 24a-24n which are mounted in energy coupling relationship to the borehole fluid 14. Various detector schemes may be utilized depending upon the information sought from the borehole generated energy. In other applications, the receiver sonde 18 may be eliminated and the source 18 positioned downhole for generation of compression waves and orbital shear waves whereupon a surface detector array aligned for selected vertical seismic profiling (VSP) is utilized. In still other applications, the receiver sonde 18 may be eliminated with the source 10 positioned downhole for generation of seismic shear and compression waves whereupon seismic energy detectors are positioned in one or more separate boreholes in the vicinity of borehole 12 for crosshole seismic imaging activities.

The source 10 consists of a frame 26 formed to contain considerable mass in upper section 28 and lower section 30. The frame 26 constitutes the isolation mass for the source reaction and the upper and lower frame mass members 28 and 30 are maintained in rigid alignment by means of structural cages 32 and 33. Inner structural cage 32 may be formed as a plurality of circumferentially arrayed interconnecting bars secured to define a cylindrical chamber 34 between mass members 28 and 30.

An A-C or D-C motor 36 with a built-in feedback encoder is secured within upper frame mass member 28 to provide rotational drive axially through a flexible coupling 38 into a drive shaft 40. Drive shaft 40 has an eccentric disk 42 secured thereon for rotation as shaft 40 rotates within upper and lower bearing members 44 and 46. The disk 42 is eccentrically mounted on the drive shaft 40, as shown also in FIG. 1B, but it is dynamically balanced relative to drive shaft 40 to provide vibration-free rotation if rotated in air. Thus, and referring to FIG. 1B, rotation of eccentric disk 42 sweeps out a circular path defined by dash-line 48 which results in a circular motion of fluid pressure increase at the largest radius point 50 of eccentric disk 42. Thus, the eccentric disk 42 rotates and sweeps out an envelope 48 in orbital manner about the motor shaft 40 center line or axis as a pressure increase is seen at the position of radius point 50 while a pressure decrease is seen 180° around disk 42.

The inner structural cage consisting of bar members 32 rigidly connects the upper and lower reaction mass frames 28 and 30, and a sleeve of elastomer membrane 52 is circumferentially secured to cover the outside of structural cage and enclose the void 34 which is filled with a highly filtered, low viscosity oil. A pressure compensation system, not shown, automatically equalizes pressure across the membrane as the sonde traverses vertically within the borehole. The elastomer membrane 52 may be tightly secured by means of suitable ring clamps or the like in sealed manner about upper and lower frame mass members 28 and 30. The outer structural cage consisting of bar members 33 prevents elastomer membrane 52 from contacting the borehole sidewall and further rigidly connects the upper and lower reaction mass frames 28 and 30. Optional state-of-the-art borehole centralizers, not shown, may be used to keep the source and/or receiver sondes centered within the borehole and to prevent sonde rotation during operation.

As the eccentric disk 42 rotates, the maximum radius point 50 forces oil outward against the membrane 52 thereby to place a localized pressure increase on the interior of the membrane 52. Simultaneously, pressure is reduced in an area 180° displaced as the disk 42 moves to a maximum away from that area. The exterior of the membrane 52 will then displace outward in the area nearest the maximum radius point 50 of disk 42 with simultaneous displacement inward on the opposite side of disk 42. Thus, the exterior of the membrane 52 serves as a rotating dipole shear wave disturbance which is coupled through the borehole fluid into the borehole wall 12 in orbiting manner.

FIG. 2 illustrates in idealized form the manner in which orbital shear wave energy may propagate upward along a borehole from a selected downhole position. Thus, an orbital shear wave as continuously generated at some point down borehole 12 will propagate upward as an elliptically polarized shear wave along the rotational or helical propagation path 54. Thus, energy is propagated along a ray path 56 or the axis of borehole 12. As the particle motion propagates with earth particle movement continually in a plane perpendicular to ray path 56, the representative vector 58 of particle motion rotates thereabout. The displacement vector 58 sweeps out a helix as it progresses upward and the vector may vary between minor and major axes, depending upon the elliptical function of the generation scheme. In most cases of rotational disk source, the elliptical polarization of the shear wave will assume the circular or special case. Handedness of the helix can easily be reversed by reversing the direction of source rotation. Disclosure of such elliptically polarized shear waves is the

particular subject matter of co-pending European Patent application EP-A-0256625, entitled "Method of Seismic Exploration Using Elliptically Polarized Shear Waves". While FIG. 2 illustrates an upward helical propagation path, it should be realized that a downward helical propagation path will also exist and from the center of the source such path will be a mirror image of that illustrated by FIG. 2.

FIG. 2 illustrates only the propagation form about a ray path coaxial with the borehole. If the orbital input from the source is circular, propagation about any ray path inclined from the borehole axis will be along an elliptical helix with the minor axis of the ellipse shrinking to zero as the ray path reaches the plane normal to the borehole axis. That is, only plane polarized shear waves will be generated in a plane passing through the center of the source and normal to the borehole axis.

It should be emphasized that the orbital downhole source is also effective in generating seismic compression waves. It is well known that a horizontal dipole source produces compression waves in two lobes symmetrical about the horizontal axis along which the source motion occurs. As was previously mentioned, the orbital downhole source is in effect a rotating dipole; hence it will produce compression waves in all radial directions about the borehole vertical axis. Such waves are produced by the direct action of rotating pressure against the side wall of the borehole. Furthermore, experimental evidence indicates that the shearing action simultaneously generates compression waves centered about all ray paths inclined 45° with respect to the centerline of the borehole. Thus, the downhole orbital vibrator is an effective universal downhole source.

FIGS. 3A-3C illustrate an alternative form of orbital shear wave vibrator which utilizes the concept of rotation of an unbalanced mass within a reaction mass with seismic energy generation in response to orbital movement of the reaction mass outer wall. In this case, an orbital shear wave vibrator 60 includes a tubular housing 62 which also forms the reaction mass, which in this application is of as low a value as is practical. The tubular housing 62 is formed of sections consisting of a crown sleeve 64 that is threadedly secured in sealed relationship to an upper sleeve 66 which, in turn, is threadedly connected in sealed relationship to a middle sleeve 68. The middle sleeve 68 is also then threadedly received within a bottom sleeve 70 (FIG. 3B) which is threadedly engaged with a bottom cap sleeve 72 and cap 74 which extends a descending bail 76.

A connector collar 78 having a multiple-conductor logging cable 80 is connected into source 60 in a sealed relationship through mating con-

necter 88 by means of a threaded post 82 which is an integral part of connector 88. A mass body of revolution 84 is adapted to be seized upon threaded affixture of collar sleeve 64 to upper sleeve 66 while defining a threaded radial bore 86 for receiving the threaded post 82. Threaded post 82 extends through connector 88 forming a sealed compartment into secure threaded engagement with threaded collar 90 secured by set screws 92 within the upper portion of collar sleeve 64. Thus, the mass body 84 not only provides a rigid connection to the upper cable assembly, but also it provides support structure for at least one geophone 94 which, through selective rotation of mass body 84, is maintained in a selected transverse alignment. Dowell pin 85 prevents rotation of body 84 with respect to upper sleeve 66.

The lower portion of source 60 is similarly constructed as a mass body 96 is secured upon threaded assembly of cap sleeve 72 and lower sleeve 70. A cable connector 98 is threadedly received within a threaded bore 100 of mass body 96 to provide electrical connection through to the lower cable 102. A lower cable assembly 102 may be used in certain configurations but not all, and a suitable plug member would be utilized otherwise. Bail 76 is available for suspension of selected stabilizing weights. The mass body 96 also retains at least one geophone in designated azimuthal direction for use as will be further described below. Orientation is maintained by an index pin not shown.

The middle sleeve 68 is adapted to contain a variable speed A-C or D-C electric motor 106 having a double ended shaft 108 to provide rotational drive power to the eccentric rotors. Motor 106 contains a built-in encoder, not shown, to provide feedback for use in speed and phase control. The underside of motor 106 (FIG. 3B) is rigidly secured to a transverse annular flange 110 as rotary shaft 108 is secured to a flexible coupling 112 having an output shaft 114 that is secured to an eccentric rotor 116. A circular housing member 118 is suitably secured at the juncture of middle sleeve 68 and lower sleeve 62 by spacer 119 to define a cylindrical cavity 120. A pair of axially aligned bearings 122 and 124 secured in housing 118 provide rotational support to the eccentric rotor 116. As shown in FIG. 3C, the eccentric rotor 116 is a circular disk with off-center drive point as at shaft 114. Other forms of eccentric mass rotors could obviously be used. The form shown is a compromise to provide high mass eccentricity and reduced air drag.

A similar structure is employed at the upper end (FIG. 3A) as motor 106 is secured to annular flange 126. A cylindrical spacer 128 is secured in support beneath a suitable cylindrical housing 130

which is further secured by spacer 129 at the threaded juncture of upper sleeve 66 and middle sleeve 68. The upper end of rotary shaft 108 is connected through a flexible coupling 132 which provides output on shaft 134 that is secured to an eccentric rotor 140. Rotor 140 is retained within upper and lower axial bearings 136, 138. The housing 130 defines a cylindrical void 137 and an eccentric disk 140 is keyed on shaft 134 to rotate therein. The eccentric disks 140 and 116 are key connected to respective shafts 134 and 114 in like phase or radial alignment.

In operation, the orbital shear wave source 60 is suspended in a fluid-filled borehole (not shown) at a designated position and the outer cylindrical walls of frame housing 62 are in energy-coupled relationship to the borehole wall. In-phase rotation of the eccentric disks 140 and 116 by the motor 106 bring about a reactive orbital motion of the frame housing mass 62 which results in an orbital shear wave being coupled into the borehole wall for propagation outward and upward in the manner as shown in FIG. 2. Compression seismic waves, as previously described, are also generated. Two geophones 94 and 104 are mounted in identical orientation proximate opposite ends of the frame housing 62, and these provide output control signals for use variously in monitoring the source output signal, indexing rotation of the source, detection of replica signals, etc. Additional pairs of geophones such as a pair orientated 90° with respect to geophones 94 and 104 can easily be added.

FIGS. 4A and 4B illustrate an alternative form of source power generation of the low inertia type, i.e., similar to that disclosed in FIG. 1A wherein the rotor is balanced but energy coupling movement is imparted through an orbiting diaphragm motion. An orbital shear wave source 140 includes a cylindrical frame portion 142 having a quadrature array of wire coils disposed near the periphery. A plurality of wire coils 144, 146, 148 and 150 are wound of selected gauge wire on high magnetic permeability cores to provide desired electromagnetic qualities. The frame housing 142 is formed of non-magnetic metal and the upper pole pieces 152, 154, 156, and 158 and lower pole pieces 160, 162, 164, and 166 are formed of high magnetic permeability material. Thus, each of the pole pieces is secured through the inner wall of frame housing 142 in suitable arcuate grooves 167 and 168 to support the respective wire coils 144-150 adjacent the inner wall of frame housing 142.

A non-magnetic stainless steel ring 170 having upper and lower beveled edges 172, 174 is suitably secured around frame housing 142 and extending between the upper and lower iron pole pieces 152-158 and 160-166. A reaction ring 176

having inside diameter race surfaces 177 and 179 slightly larger than the outside diameter of the stainless steel ring 170 is then disposed to overlay the stainless steel ring 170 in spaced relationship. The iron ring 176 may be formed with heavier upper and lower races 177 and 179 to assure magnetic alignment with the respective upper and lower pole pieces. An elastomer upper sleeve 178 is suitably secured to seal between frame housing 142 and the upper portion of iron ring 176 as a lower elastomer sleeve 180 is similarly secured to seal adjacent the lower edge of iron ring 176. A cavity 182 formed within the elastomer barriers is then filled with a suitable low viscosity oil to provide pressure balance across the elastomer barriers and to ensure smooth contact and reduction of noise and interference.

In operation, a plurality of phase displaced alternating current sources are connected downhole to selected ones of the respective electromagnetic coils 144-150 and, in accordance with the energizing voltage phase relationship, energization of the respective electromagnetic coils takes place in a predetermined sequence progressing around the frame housing 142. Thus, as iron ring 176 is attracted inward adjacent stainless steel ring 170 on one side, the opposite side is maximum outward to provide a localized increase in pressure in the borehole fluid which, in turn, imparts shear wave particle energy to the borehole wall at that point. Depending upon the phase relationship of the energizing voltages, the iron ring 176 can be orbitally rotated variously around the frame housing to generate an elliptically polarized shear wave in the borehole wall.

FIG. 5 illustrates yet another form of low inertia orbital shear wave source for downhole application wherein piezoelectric elements are used. A downhole shear wave source 190 includes a suitable tubular frame housing 192 and a plurality of directionally displaced piezoelectric elements secured centrally therealong. Thus, central most, a pair of reaction masses 194 and 196 are disposed in juxtaposition and in parallel as supported transversely in frame housing 192 by means of respective low friction linear bearings 198 and 200. The linear bearings of selected diameter and length are available from such as Linear Rotary Bearings, Inc. of Westbury, New York. The piezoelectric elements 202 and 204 are suitably bonded on the ends of reaction mass 194, and piezoelectric elements 206 and 208 are similarly bonded on the ends of reaction mass 196. The outer ends of piezoelectric elements 202-208 are suitably bonded in rigid contact with tubular frame housing 192. The electrical connections 210 and 212 then control the alternating piezoelectric energizations. A pair of reaction masses 214 and 216 are then disposed

above and below masses 194 and 196 in equi-spaced position but disposed at right angles. Each of masses 214 and 216 is suspended by a low friction linear bearing 218 and 220 and each of these includes opposite end piezoelectric elements assembled in the same manner as reaction masses 194 and 196. The electrical control connections 19 and 221 apply alternating energization to the piezoelectric elements.

The source 190 is another alternative form of low inertia seismic source capable of relatively good power output. The transverse reaction masses and energizing elements are arranged in pairs so that they can be equally disposed on each side of the frame housing center line 222 thereby to provide balanced transverse force on frame housing 192 and to avoid any torquing motion to the longitudinal axis. While four elements are shown, additional quadratures of such elements could easily be added equally disposed on each side of housing centerline 222, to provide increased power output capability. Thus, application of an energizing voltage on lead 212 with opposite pulsing on lead 210 results in crystal elongation of piezoelectric elements 204 and 208 with attendant contraction of elements 202 and 206 thereby to generate localized increased pressure at the borehole wall adjacent piezoelectric elements 204 and 208. Similar control of the transverse reaction masses 214 and 216 by alternate pulsing of their respective piezoelectric elements, results in similar shear wave forces at the borehole wall. Thus, coordinated control in selected phase relationships of the two 90° displaced pairs of reaction masses is effective to generate an elliptical or circularly polarized shear wave in the adjacent borehole wall. This type of phase adjusted electronic control is more clearly discussed in the aforementioned U.S. patent application EP-A-0256625 entitled "Method of Seismic Exploration Using Elliptically Polarized Shear Waves".

The foregoing discloses a novel form of downhole orbital seismic vibrator of the type wherein seismic shear waves, particularly elliptically polarized seismic shear waves, can be coupled through the borehole fluid into the borehole wall with appreciable power while simultaneously generating seismic compression waves of appreciable power. Generation of such shear waves and compression waves downhole enables a number of new sounding techniques wherein data can be compiled in the form of reverse vertical seismic profiles, (VSP) or seismic profiles can be established from hole to hole across a selected terrain. In addition, such vibrators may still be useful for acoustic sounding along a single borehole for the purpose of establishing velocity relationships of the various stratum.

Changes may be made in combination and arrangement of elements as heretofore set forth in the specification and shown in the drawings; it being understood that changes may be made in the embodiments disclosed without departing from the scope of the invention as defined in the following claims.

#### Claims

1. A downhole seismic source (10;60;140;190) for the simultaneous generation of orbital shear wave seismic energy and compression wave seismic energy into a fluid-filled borehole wall (12) comprising:
  - an elongated frame means (26;62) having a central axis and an outer wall supportable at a point along said borehole wall; and
  - drive means disposed in said frame means and energizable to impart an orbital motion to at least a portion (52;62;176;192) of the frame means outer wall thereby to generate an orbital shear wave in said borehole wall (12).
2. A downhole seismic source (10;60;140;190) as set forth in claim 1 wherein said frame means (26;62) comprises:
  - a cylinder (28,30;62) having continuous outer wall in contact with the borehole fluid; and
  - top and bottom end cap structure (90,74) secured to opposite ends of the cylinder (28,30;62).
3. A downhole seismic source (60) as set forth in claim 1 or 2 wherein said drive means comprises:
  - a drive motor (106) providing rotational output; and
  - first and second eccentric rotors (116,140) receiving said rotational output, said rotors being equi-spaced along the central axis of said frame means (62) and aligned in parallel and radial alignment for synchronous eccentric rotation.
4. A downhole seismic source (60) as set forth in claim 3 wherein said first and second eccentric rotors each comprises:
  - a circular disk (116,140) having an eccentrically displaced shaft hole for receiving input of rotation.
5. A downhole seismic source (60) as set forth in claim 3 or 4 wherein:
  - said drive motor (106) is a variable speed electric motor which includes a feedback encoder.

above and below masses 194 and 196 in equi-spaced position but disposed at right angles. Each of masses 214 and 216 is suspended by a low friction linear bearing 218 and 220 and each of these includes opposite end piezoelectric elements assembled in the same manner as reaction masses 194 and 196. The electrical control connections 19 and 221 apply alternating energization to the piezoelectric elements.

The source 190 is another alternative form of low inertia seismic source capable of relatively good power output. The transverse reaction masses and energizing elements are arranged in pairs so that they can be equally disposed on each side of the frame housing center line 222 thereby to provide balanced transverse force on frame housing 192 and to avoid any torquing motion to the longitudinal axis. While four elements are shown, additional quadratures of such elements could easily be added equally disposed on each side of housing centerline 222, to provide increased power output capability. Thus, application of an energizing voltage on lead 212 with opposite pulsing on lead 210 results in crystal elongation of piezoelectric elements 204 and 208 with attendant contraction of elements 202 and 206 thereby to generate localized increased pressure at the borehole wall adjacent piezoelectric elements 204 and 208. Similar control of the transverse reaction masses 214 and 216 by alternate pulsing of their respective piezoelectric elements, results in similar shear wave forces at the borehole wall. Thus, coordinated control in selected phase relationships of the two 90° displaced pairs of reaction masses is effective to generate an elliptical or circularly polarized shear wave in the adjacent borehole wall. This type of phase adjusted electronic control is more clearly discussed in the aforementioned U.S. patent application EP-A-0256625 entitled "Method of Seismic Exploration Using Elliptically Polarized Shear Waves".

The foregoing discloses a novel form of downhole orbital seismic vibrator of the type wherein seismic shear waves, particularly elliptically polarized seismic shear waves, can be coupled through the borehole fluid into the borehole wall with appreciable power while simultaneously generating seismic compression waves of appreciable power. Generation of such shear waves and compression waves downhole enables a number of new sounding techniques wherein data can be compiled in the form of reverse vertical seismic profiles, (VSP) or seismic profiles can be established from hole to hole across a selected terrain. In addition, such vibrators may still be useful for acoustic sounding along a single borehole for the purpose of establishing velocity relationships of the various stratum.

Changes may be made in combination and arrangement of elements as heretofore set forth in the specification and shown in the drawings; it being understood that changes may be made in the embodiments disclosed without departing from the scope of the invention as defined in the following claims.

#### Claims

1. A downhole seismic source (10;60;140;190) for the simultaneous generation of orbital shear wave seismic energy and compression wave seismic energy into a fluid-filled borehole wall (12) comprising:
  - an elongated frame means (26;62) having a central axis and an outer wall supportable at a point along said borehole wall; and
  - drive means disposed in said frame means and energizable to impart an orbital motion to at least a portion (52;62;176;192) of the frame means outer wall thereby to generate an orbital shear wave in said borehole wall (12).
2. A downhole seismic source (10;60;140;190) as set forth in claim 1 wherein said frame means (26;62) comprises:
  - a cylinder (28;30;62) having continuous outer wall in contact with the borehole fluid; and
  - top and bottom end cap structure (90;74) secured to opposite ends of the cylinder (28;30;62).
3. A downhole seismic source (60) as set forth in claim 1 or 2 wherein said drive means comprises:
  - a drive motor (106) providing rotational output; and
  - first and second eccentric rotors (116;140) receiving said rotational output, said rotors being equi-spaced along the central axis of said frame means (62) and aligned in parallel and radial alignment for synchronous eccentric rotation.
4. A downhole seismic source (60) as set forth in claim 3 wherein said first and second eccentric rotors each comprises:
  - a circular disk (116;140) having an eccentrically displaced shaft hole for receiving input of rotation.
5. A downhole seismic source (60) as set forth in claim 3 or 4 wherein:
  - said drive motor (106) is a variable speed electric motor which includes a feedback encoder.



6. A downhole seismic source (10) as set forth in claim 1 or 2 wherein said frame means (26) comprises:

at least two cylindrical frames (28,30) of relatively heavy mass secured in axial alignment by a largely open peripheral structural cage (32,33) and defining a cylindrical cavity (34) therebetween;

a pliable boot (52) enclosing said cavity outer wall and retaining fluid therein; and

first and second end cap means secured to opposite ends of the secured cylindrical frames.

7. A downhole seismic source (10) as set forth in claim 6 wherein said drive means comprises:

a drive motor (36) providing rotational output along said central axis; and

a rotor disk (42) having selected thickness and being driven eccentrically by said rotational output, said disk being disposed in said cavity to distend said boot (52) in orbital manner relative to the borehole wall (12).

8. A downhole seismic source (10) as set forth in claim 6 or 7 wherein said structural cage (32,33) comprises:

at least two peripherally disposed equispaced struts secured longitudinally between the respective frames (28,30).

9. A downhole seismic source (10) as set forth in claim 6, 7 or 8 wherein said pliable boot comprises:

a generally cylindrical elastomer membrane (52) sealingly secured about the periphery of respective frames (28,30) adjacent said cylindrical cavity (34).

10. A downhole seismic source (10) as set forth in claim 7 wherein:

said drive motor (36) is a variable speed electric motor with at least one built-in feedback encoder.

11. A downhole seismic source (190) as set forth in claim 1 or 2 wherein said drive means comprises:

at least two equal first reaction masses (194,196) having opposite ends and being secured in parallel juxtaposition and transverse alignment generally centrally in said frame means (192);

at least two equal second reaction masses (214,216) having opposite ends and being secured adjacent on each side of said first reaction masses (194,196) but in right angle alignment relative to the first masses;

a plurality of piezoelectric elements (202,204,206,208) each bonded in affixture on respective ends of said first and second reaction masses (194,196,214,216) and to the frame means cylinder (192); and

means for energizing said piezoelectric elements in selected phase relationship to exert predetermined rotational transverse thrust to said cylindrical frame means (192).

12. A downhole seismic source (190) as set forth in claim 11 which further includes:

at least four linear bearings (198,200,218,220) secured to support said first and second reaction masses (194,196,214,216).

13. A downhole seismic source (140) as set forth in claim 1 or 2 wherein said drive means comprises:

at least four electromagnetic coils (144,146,148,150) having upper (152,154,156,158) and lower (160,162,164,166) pole pieces of metal having high magnetic permeability, said coils being held in quadrature array with the upper and lower pole pieces each being circularly aligned and with all pole pieces being secured within the mass of said cylinder (142);

a non-magnetic ring (170) of selected outer diameter bonded around said cylinder in the circular area between the circularly arrayed pole pieces;

an iron ring (176) of selected inside diameter greater than said non-magnetic ring outer diameter and disposed concentrically thereto;

fluid-tight pliable boot means (180) secured to said cylinder means (142) on each side of said non-magnetic ring to retain said iron ring in concentricity;

fluid of selected viscosity and compressibility disposed within said boot means; and

means for energizing said electromagnetic coils (144,146,148,150) in selected quadrature phase relationship to displace said soft iron ring (170) in rotational transverse thrust relative to said cylindrical frame means (142).

#### Patentansprüche

1. Seismischer Bohrlochgenerator (10; 60; 140; 190) zum gleichzeitigen Erzeugen seismischer Umlaufschwerwellenenergie und seismischer Druckwellenenergie in eine Wand (12) eines fluidgefüllten Bohrlochs, umfassend: ein länggestrecktes Rahmenmittel (26; 62) mit einer Mittelachse und einer an einer Stelle längs der Bohrlochwand abstützbaren Außen-



wand; und  
ein in dem Rahmenmittel angeordnetes Antriebsmittel, das zum Anlegen einer Umlaufbewegung an Wenigstens einem Abschnitt (52; 62; 176; 192) der Außenwand des Rahmenmittels erregbar ist, um hierdurch in der Bohrlochwand (12) eine Umlaufschervelle zu erzeugen.

2. Seismischer Bohrlochgenerator (10; 60; 140; 190) nach Anspruch 1, in dem das Rahmenmittel (26, 62) umfaßt:  
einen Zylinder (28, 30; 62) mit einer durchgehenden Außenwand in Kontakt mit dem Bohrlochfluid; und  
an gegenüberliegenden Enden des Zylinders (28, 30; 62) befestigte obere und untere Endkappenstrukturen (90, 74).

Seismischer Bohrlochgenerator (60) nach Anspruch 1 oder 2, in dem das Antriebsmittel umfaßt:  
einen Drehkraft erzeugenden Antriebsmotor (106); und  
die Drehkraft aufnehmende erste und zweite exzentrische Rotoren (116, 140), welche Rotoren mit gleichem Abstand entlang der Mittelachse des Rahmenmittels (62) angeordnet und zu synchroner exzentrischer Drehung zueinander parallel und radial ausgerichtet sind.

4. Seismischer Bohrlochgenerator (60) nach Anspruch 3, in dem jeder der ersten und zweiten exzentrischen Rotoren umfaßt:  
eine kreisförmige Scheibe (116, 140) mit einem exzentrisch versetzten Wellenloch zur Aufnahme eingegebener Drehung.

Seismischer Bohrlochgenerator (60) nach Anspruch 3 oder 4, in dem der Antriebsmotor (106) ein Elektromotor variabler Drehzahl mit einem Rückkopplungscodierer ist.

6. Seismischer Bohrlochgenerator (10) nach Anspruch 1 oder 2, in dem das Rahmenmittel (26) umfaßt:  
wenigstens zwei zylindrische Rahmen (28, 30) relativ schwerer Masse, die in axialer Ausrichtung durch einen weit offenen peripheren Tragkäfig (32, 33) gesichert sind und dazwischen eine zylindrische Kammer (34) festlegen;  
eine biegsame Manschette (52), die die Kammeraußenwand einschließt und Fluid darin hält; und  
erste und zweite Endkappenmittel, die an gegenüberliegenden Enden der gesicherten zylindrischen Rahmen gesichert sind.

7. Seismischer Bohrlochgenerator (10) nach Anspruch 6, worin das Antriebsmittel umfaßt:  
einen Antriebsmotor (36), der entlang der Mittelachse Drehkraft erzeugt; und  
eine Rotorscheibe (42) ausgewählter Dicke, die durch die Drehkraft exzentrisch angetrieben ist, welche Scheibe in der Kammer angeordnet ist, um die Manschette (52) in umlaufender Weise relativ zu der Bohrlochwand (12) zu strecken.

8. Seismischer Bohrlochgenerator (10) nach Anspruch 6 oder 7, in dem der Tragkäfig (32, 33) umfaßt:  
wenigstens zwei in Umfangsrichtung mit gleichem Abstand voneinander angeordnete Streben, die in Längsrichtung zwischen den jeweiligen Rahmen (28, 30) gesichert sind.

9. Seismischer Bohrlochgenerator (10) nach Anspruch 6, 7 oder 8, in dem biegsame Manschette umfaßt:  
eine im wesentlichen zylindrische elastomere Membrane (52), die um den Umfang der jeweiligen Rahmen (28, 30) nahe der zylindrischen Kammer (34) abdichtend befestigt sind.

10. Seismischer Bohrlochgenerator (10) nach Anspruch 7, in dem der Antriebsmotor (36) ein Elektromotor variabler Drehzahl mit wenigstens einem eingebauten Rückkopplungscodierer ist.

11. Seismischer Bohrlochgenerator (190) nach Anspruch 1 oder 2, in dem das Antriebsmittel umfaßt:  
wenigstens zwei gleiche erste Reaktionsmassen (194, 196), die gegenüberliegende Enden aufweisen, und parallel nebeneinanderliegend und quer ausgerichtet im wesentlichen zentral in dem Rahmenmittel (192) befestigt sind;  
wenigstens zwei gleiche zweite Reaktionsmassen (214, 216), die gegenüberliegende Enden aufweisen und nahe jeder Seite der ersten Reaktionsmassen (194, 196), jedoch in rechtwinkliger Ausrichtung relativ zu den ersten Massen befestigt sind;  
eine Mehrzahl piezoelektrischer Elemente (202, 204, 206, 208), die jeweils mit den jeweiligen Enden der ersten und zweiten Reaktionsmassen (194, 196, 214, 216) und mit dem zylindrischen Rahmenmittel (192) fest verbunden sind; und  
ein Mittel zum Erregen der piezoelektrischen Elemente in ausgewählter Phasenbeziehung, um auf das zylindrische Rahmenmittel (192) eine vorbestimmte Drehquerkraft auszuüben.

12. Seismischer Bohrlochgenerator (190) nach Anspruch 11, der weiter umfaßt:



wenigstens vier Linearlager (198, 200, 218, 220), die zum Tragen der ersten und zweiten Reaktionsmassen (194, 196, 214, 216) befestigt sind.

13. Seismischer Bohrlochgenerator (140) nach Anspruch 1 oder 2, in dem das Antriebsmittel umfaßt:

wenigstens vier elektromagnetische Spulen (144, 146, 148, 150) mit oberen (152, 154, 156, 158) und unteren (160, 162, 164, 166) Polstücken aus Metall hoher magnetischer Permeabilität, welche Spulen in quadratischer Anordnung gehalten sind, wobei die oberen und unteren Polstücke jeweils kreisförmig ausgerichtet sind und wobei alle Polstücke in der Masse des Zylinders (142) befestigt sind; einen nicht-magnetischen Ring (170) gewählten Außendurchmessers, der um den Zylinder in dem Kreisbereich zwischen den ringförmig angeordneten Polstücken befestigt ist; einen Eisenring (176) mit einem Innendurchmesser, der größer gewählt ist als der Außendurchmesser des nicht-magnetischen Rings und der dazu konzentrisch angeordnet ist; ein fluiddichtes biegsames Manschettenmittel (180), das an dem Zylindermittel (142) jederseits des nicht-magnetischen Rings gesichert ist, um den Eisenring konzentrisch zu halten; in dem Manschettenmittel angeordnetes Fluid ausgewählter Viskosität und Kompressibilität; und ein Mittel zum Erregen der elektromagnetischen Spulen (144, 146, 148, 150) in ausgewählter quadratischer Phasenbeziehung, um den weichen Eisenring (170) mit Drehquerkraft relativ zu dem zylindrischen Rahmenmittel (142) zu verlagern.

#### Revendications

1. Source sismique (10 ; 60 ; 140 ; 190) pour fond de sondage, destinée à la création simultanée d'énergie sismique sous forme d'ondes orbitales de cisaillement et d'énergie sismique sous forme d'ondes de compression dans la paroi (12) d'un sondage rempli d'un fluide, comprenant :  
un châssis allongé (26 ; 62) ayant un axe central et une paroi externe et destiné à être supporté en un point le long de la paroi du sondage ; et  
un dispositif d'entraînement placé dans le châssis et destiné à être excité afin qu'il donne un mouvement orbital à une partie au moins (52 ; 62 ; 176 ; 192) de la paroi externe du châssis et crée ainsi une onde orbitale de

cisaillement dans la paroi (12) du sondage.

2. Source sismique (10 ; 60 ; 140 ; 190) pour sondage selon la revendication 1, dans laquelle le châssis (26, 62) comporte :  
un cylindre (28, 30 ; 62) ayant une paroi externe continue qui est au contact du fluide du sondage, et  
des structures supérieure et inférieure (90, 74) à capuchon d'extrémité fixées aux extrémités opposées du cylindre (28, 30 ; 62).
3. Source sismique (60) pour sondage selon la revendication 1 ou 2, dans laquelle le dispositif d'entraînement comporte :  
un moteur (106) qui donne un entraînement en rotation, et  
un premier et un second rotor excentrique (116, 140) qui reçoivent la force d'entraînement en rotation, les rotors étant espacés également le long de l'axe central du châssis (62) et étant alignés parallèlement et radialement afin qu'ils présentent une rotation excentrique synchrone.
4. Source sismique (60) pour sondage selon la revendication 3, dans laquelle le premier et le second rotor excentrique comportent chacun :  
un disque circulaire (116, 140) ayant un trou de passage d'arbre décalé excentriquement pour l'entraînement en rotation.
5. Source sismique (60) pour sondage selon la revendication 3 ou 4, dans laquelle :  
le moteur (106) est un moteur électrique à vitesse variable qui comporte un codeur de rétroaction.
6. Source sismique (10) pour sondage selon la revendication 1 ou 2, dans laquelle le châssis (26) comporte :  
au moins deux châssis cylindriques (28, 30) de masse relativement grande, fixés sous forme alignée axialement par une cage périphérique résistante (32, 33) largement ouverte et délimitant une cavité cylindrique (34) entre eux,  
un sabot souple (52) entourant la paroi externe de la cavité et retenant du fluide à l'intérieur, et  
un premier et un second capuchon d'extrémité fixés aux extrémités opposées des châssis cylindriques fixés.
7. Source sismique (10) pour sondage selon la revendication 6, dans laquelle le dispositif d'entraînement comporte :  
un moteur (36) assurant un entraînement



en rotation le long d'un axe central, et  
un disque (42) de rotor ayant une épaisseur choisie et entraîné excentriquement par la rotation du moteur, le disque étant placé dans la cavité afin qu'il provoque un allongement du sabot (52) de manière orbitale par rapport à la paroi (12) du sondage.

8. Source sismique (10) pour sondage selon la revendication 6 ou 7, dans laquelle la cage résistante (32, 33) comporte :

au moins deux montants disposés périphériquement et espacés également, fixés longitudinalement entre les châssis respectifs (28, 30).

9. Source sismique (10) pour sondage selon la revendication 6, 7 ou 8, dans lequel le sabot souple comprend :

une membrane élastomère (52) de forme générale cylindrique, fixée de manière étanche à la périphérie des châssis respectifs (28, 30) près de la cavité cylindrique (34).

10. Source sismique (10) pour sondage selon la revendication 7, dans laquelle :

le moteur (36) est un moteur électrique à vitesse variable ayant au moins un codeur incorporé de rétroaction.

11. Source sismique (190) pour sondage selon la revendication 1 ou 2, dans laquelle le dispositif d'entraînement comporte :

au moins deux premières masses réactives égales (194, 196) ayant des extrémités opposées et fixées afin qu'elles soient juxtaposées parallèlement et alignées transversalement pratiquement au centre dans le châssis (192),

au moins deux secondes masses réactives égales (214, 216) ayant des extrémités opposées et fixées près de chaque côté des premières masses réactives (194, 196) mais avec un alignement perpendiculaire à celui des premières masses,

plusieurs éléments piézoélectriques (202, 204, 206, 208) fixés chacun aux extrémités respectives des premières et secondes masses réactives (194, 196, 214, 216) et au cylindre (192) du châssis, et

un dispositif destiné à exciter les éléments piézoélectriques avec des phases choisies de manière qu'ils exercent une poussée transversale prédéterminée en rotation sur le châssis cylindrique (192).

12. Source sismique (190) pour sondage selon la revendication 11, qui comporte en outre :

au moins quatre glissières (198, 200, 218, 220) fixées afin qu'elles supportent les premières et secondes masses réactives (194, 196, 214 et 216).

13. Source sismique (140) pour sondage selon la revendication 1 ou 2, dans laquelle le dispositif d'entraînement comporte :

au moins quatre enroulements électromagnétiques (144, 146, 148, 150) ayant des pièces polaires supérieures (152, 154, 156, 158) et inférieures (160, 162, 164, 166) formées d'un métal ayant une perméabilité magnétique élevée, les enroulements étant maintenus sous forme d'un ensemble de quatre enroulements d'une manière telle que les pièces polaires supérieures et inférieures sont alignées circulairement, toutes les pièces polaires étant fixées dans la masse du cylindre (142),

un anneau non magnétique (170) ayant un diamètre externe choisi, fixé autour du cylindre dans une zone circulaire comprise entre les pièces polaires disposées circulairement,

un anneau de fer (176) ayant un diamètre interne choisi supérieur au diamètre externe de l'anneau non magnétique et disposé concentriquement par rapport à ce dernier,

un sabot souple (180) qui est étanche au fluide et qui est fixé au cylindre (142) de part et d'autre de l'anneau non magnétique afin qu'il assure la concentricité de l'anneau de fer,

un fluide de viscosité et de compressibilité choisies, placé dans le sabot, et

un dispositif d'excitation des enroulements électromagnétiques (144, 146, 148, 150) avec des déphasages choisis en quadrature afin que l'anneau de fer doux (170) soit déplacé par une force transversale de poussée le faisant tourner par rapport au châssis cylindrique (142).

