

COLLECTION SYSTEM FOR MULTIPLE MONEY-ACTUATED MACHINES

DescriptionField of the Invention

This invention relates to a method and apparatus for the storing of data of a validation system and, more particularly, to a detachable system to reliably download data from an operating machine and display the same in usable form.

Background of the Invention

The present invention is particularly adapted for use with the validator system of a coin or currency operated gaming devices of the type used in gambling casinos or similarly large volume operations. The validator includes mechanical and electronic hardware to keep track of a given machine's operation. That is to say, each machine includes electronic hardware or a mechanism that keeps track of the machine's performance, money intake, output of winnings and the like. The data that is collected and intended to be stored include such operational parameters as down time, maintenance routines, payouts, machine uses (activity), faults, credit card use and the like. The problem is that at present neither the machine builders nor their customers have a simple, systematic and reliable way to retrieve the information that a given machine has compiled in its validator. In the past and in order to access the information, an employee is sent to each machine or selected machines which are then taken out of service for repair or downloading. When more than a few machines are involved (and some casinos have hundreds of machines), such past practice is expensive and error prone. Therefore, a need exists for a method and apparatus for reliably retrieving and utilizing the data compiled in a given machine.

Summary of the Invention

The inventive memory management system handles a wide range of information functions. These functions are deemed necessary enhancements in the industry and provide a competitive edge over existing methods which, heretofore, are used to access data in the machine. More particularly and according to the inventive system, the enhancements are downstacked from the validator to a Dallas Semiconductor DS1990A Touch Memory Device and the

- 2 -

Dallas Semiconductor DS2405 Addressable Switch Device. The DS2250, in combination with the inventive software, gives the inventive system a flexible way to access machine performance. According to the inventive method, touch memory data is stored in a binary format. Memory locations of various lengths are assigned as needed for various purposes.

Full details of the present invention are set forth in the following description of the invention and illustrated in the accompanying drawings.

Objects of the Invention

It is an object of the present invention to provide an automated means for extracting and downloading data accumulated in a machine.

It is a further object of the present invention to provide a memory management system that includes a wide range of storage functions.

It is another object of the present invention to provide a means to read data stored in a machine and then communicate such data to a remote computer or laptop, whereby the data can be displayed and manipulated by this computer.

It is another object of the present invention to provide the hardware and software for an accountability system in currency handling that is applicable to currency validators and currency stacking mechanisms.

It is a further object of the present invention to provide a soft count tracking system of closed loop design.

Description of the Drawings

Other objects and features of the present invention will be apparent from the following detailed description considered in connection with the accompanying drawings. It is to be understood, however, that the drawings are designed for purposes of illustration only and not as a definition of the limits of the invention for which reference should be made to the appended claims.

In the drawings, the same reference numerals denote the same element throughout the figures:

Fig. 1 is a block diagram of the inventive apparatus;

Fig. 2 is a schematic diagram showing how a Dallas Semiconductor DS1994 and a Dallas Semiconductor DS2400 are connected to an 8052 CPU;

- 3 -

Fig. 3 is a flow chart of write function assembly code according to the present invention;

Fig. 4 is an enlarged perspective view of the detachable buss or harness used in the present system; and

Fig. 5 is a perspective view of an LRC containing the DS1994 or DS1993 touch memory clip.

Detailed Description of the Invention

Referring now to Fig. 1, there is shown a block diagram of the inventive apparatus seen generally as reference number 10. An Identification System (IDS), (i.e., currency validator) unit 16 acts as a downstacker for the operating machine receiving all the data generated by an identification adaptor (IDA) 12. The IDS unit contains the conventional currency sensors and detectors as well as the CPU or computer device and display. The IDA reads and analyzes all information including the currency value, unequal amounts, cash receipts and efficiency of the machine. The inventive system is a closed loop design for the automatic accounting of cash in gaming and other markets (machines) using coin or currency validators. In other words, the inventive system provides for an accountability routine for currency handling in currency validators and stacking mechanisms. The IDA 12 is built into a wiring harness as an integral active electronic component and is provided with a unique serial number. The IDA 12 electrically communicates with one end of a harness section 14, the other end of which terminates in a host machine interface connector 14a. During use and operation, described below, connector 14a plugs into a host gaming machine, not shown, for electrical and data communication therewith. The validator or IDS unit 16, a Dallas Semiconductor DS2250, about which more is said below, is placed in electrical or data communication with IDA adapter 12 via a detachable buss or harness 18 shown in detail in Fig. 4. Harness 18 includes a muting or quick disconnect between the IDA 12 and the IDS or validator 16. More particularly, harness 18 comprises harness sections 18b and 18c each, on one end, respectively terminating in associated mating quick disconnect elements 18d and 18e.

- 4 -

The validator or IDS unit 16 is a currency note validator with microcontroller in which the DS2250 interrogates IDA 12 for identification number. IDS 16 validates notes, security papers and bar coded coupons used as money substitutes. A lockable removable cassette (LRC) 20 is placed in electrical or data communication with IDS 16 by means of a harness or harness segment 22. As with harness 18, noted above, harness 22 includes a mating or quick disconnect IDS-LRC connector 22a. More particularly, harness 22 is formed of harness buss sections 22b and 22c each, on one end, respectively terminating in associated mating quick disconnect elements 22d and 22e.

L.C. 20 is a storage mechanism, such as a box or lockable container, for the secure stacking and transportation of notes and coupons. The L.C. 20 is portable and designed with a stacking mechanism 34 to hold the currency and notes securely once they pass through the validator. Integral to L.C. 20 is a nonvolatile storage memory to receive and hold the IDA and IDS information generated by these units. The L.C. is provided with a connector buss 34 for connection to a power source, motor sensors and to provide for the memory output to the CPU.

Additionally, the inventive system includes a soft count supervisor (SCS) 24 which is preferably portable or located at a remote position from the validator or IDS 16. The SCS 24, about which more is said below, is detachably placed in data or electrical communication with L.C. 20 by means of harness or harness segment 26. Similar to harnesses 18 and 22, harness 26 includes a mating or quick disconnect SCS-L.C. connector 26a. More particularly, harness 26 is formed of harness sections 26b and 26c on one end, respectively terminating in associated detachable disconnect elements 26d and 26e. Typically, SCS 24 is a personal computer (PC), laptop computer or handheld data storage device that, with harness 26, can be detachably coupled to L.C. 20 to download data therefrom. SCS 24 interrogates the memory device within L.C. 20 once the L.C. is removed from the host system. The SCS provides spread sheet type accounting of notes and coupons as well as status and performance information of system components. Since the L.C. is removed frequently, maintenance personnel may be directed accurately to systems performing efficiently or

- 5 -

performing only marginally. L.C. 20 may be optionally interrogated through the communication port of validator IDS 16.

Referring now to Fig. 2, there is shown in schematic form how the DS1994 and the DS2400 are electrically connected or placed in data communication with a host CPU 210. A single wire or data lead 212 is, on one end, electrically connected to data port 214 of CPU 210. The other end of wire 212 is electrically connected to Dallas Semiconductor Memory Device DS1994, as shown. Line 212 is "pulled-up" by pull-up resistor 216. A single wire or data lead 218 is, on one end, electrically connected to data port 220 of CPU 210. The other end of wire 218 is electrically connected to a Dallas Semiconductor DS2400, as shown. Wire 218 is electrically pulled-up by resistor 222.

Referring now to Fig. 3, there is shown the Flow Chart for the Write Function Assembly Code according to the present invention.

In operation or in operational sequence, all components are connected via power-on and reset switch (POR). The validator or IDS unit 16 loads the unique serial number of IDA 12 into its local nonvolatile memory and L.C. 20 is interrogated by IDS 16 for identification (ID). If L.C. 20 has no ID, as in the case of cash collection, the L.C. 20 is returned to system and IDS 16 will load the L.C. 20 with serial number and the following information:

time and data stamp	factory ID
validation histogram	manufacture date
malfunction summary	IDS configuration
CPU revision	cash and coupon accounting data

The L.C. 20 will further be strung with the various reasons for rejection of currency (optically and/or magnetically sensed), i.e., a full stack of bills, channel jams and whatever other data is supplied.

Overall, the inventive system will store:

- a) time - stacker was attached;
- b) time - stacker was removed;
- c) date - stacker was attached;
- d) date - stacker was removed;

- 6 -

- e) asset number - a serial identification number for the gaming machine;
- f) registers for note denominations and running totals;
- g) registers for coupon information storage;
- h) registers for fault determination and running totals;
- i) self-determining mode;
- j) providing performance data; and
- k) flexible data conversion format so data can be displayed on any PC with simple programs.

There are two main components to this system feature. The first is the DS1990A, noted earlier, and the second is the DS2405 Addressable Switch, also noted above. In the DS2250, data is transferred serially via a one-wire protocol. This protocol requires only a single data lead and a ground return. The DS2405 is an open drain N-channel field effect transistor that can be turned on and off to follow the standard Dallas one-wire protocol. This protocol is implemented with a single port of an 8052 microcontroller CPU. Data is transferred to the DS2250 via a stacker connector, and data in binary form is written to the touch memory device as described in the flow chart of the Write Function Assembly Code. The DS2405 Addressable Switch is housed in the cabling assembly so each machine has a unique identification and not the stacker. This provides flexibility for putting any given stacker on any given machine.

Since the memory device is housed within the money stacker or containers, it is easy for a user to retrieve the data. When the stacker is removed and emptied of coins or currency, the data can be retrieved by a fixture and downloaded to a PC, laptop, or handheld data storage device.

Time and date stamps are used for accounting purposes. This information will tell the user when the stackers are accessed and provide detailed information on hourly activity, and thus provide the user with a system for scheduling maintenance, stacker removal, and various other needed activity. According to the present invention, an asset number is assigned to a given gaming machine, i.e., it is the "name" of a given machine. This feature

eliminates the need for the user or maintenance personnel to write down which currency stacker or data provider goes to which machine. In the inventive apparatus, since the read/write memory is nonvolatile, the removed stacker does not have to be replaced in the same machine. When a stacker is replaced, the asset number of the machine into which it is placed is written to memory.

The registers set up for bill denominations will keep a running total of how many bills of a particular denomination were inserted. This will give the user an instant tally of the amount of notes in the stacker and the total dollar value contained in the stacker. Other registers are set up to handle bar coded coupons. In this case, the complete encoded bar code number will be stored in memory. This eliminates the need for the user to hand read the coupons into the system because in the inventive technique it can now be downloaded directly from the stacker.

In the inventive implementation, other registers are set up to handle fault counts. More particularly, these registers are set up to handle optical window faults and optical ratio faults, magnetic faults, power faults, stacker faults, unrecognizable bill faults and front-end sensor faults. Such data will give the user insight into how well the machine is performing and which areas need improving. Knowledge of this fault data will also allow the inventive system to warn the user of potential problems. For example, if the machine records an excessive number of faults, it can be programmed to warn the user via network connection or by flashing LED's. The user now has a reliable way systematically to maintain the gaming machine at the highest possible performance level, thus increasing the machine's profit potential.

To ensure the integrity of the data and provide the highest possible level of accuracy, CRC and write verify read procedures are employed in the inventive system.

It is to be understood that in this application use of the terms electrical and data communication are meant to be synonymous--that is, where an element is said to be in electrical communication it can be read as meaning in data communication, and, of course, to those in this art, data communication

- 8 -

also includes wireless communication wherein the link can be RF radio frequency, light and infrared, to name a few.

While only a single embodiment of the present invention has been shown and described, it is to be understood that many changes and modifications can be made hereto without departing from the spirit and scope hereof.

WHAT IS CLAIMED IS:

1. A soft count tracking system for a currency operated host gaming machine comprising:

an identification adapter that includes an integral active electronic component, said component adapted to store a unique serial number, means for placing said identification adapter in data communication with the host machine, a currency note validator with microcontroller, means for placing said currency note validator in data communication with said identification adapter for interrogating the identification adapter for identification number, a storage mechanism that includes integral nonvolatile storage memory means, and means for placing said storage mechanism in data communication with said currency note validator thereby to receive and hold information from said identification adapter, and a soft count supervisor adapted to be placed in detachable data communication with said memory means to interrogate and extract data from the same, said soft count supervisor comprising a computer, including software means to provide spread sheet data manipulation of the data extracted from said memory means.

2. The soft count tracking system according to Claim 1, said means for placing said identification adapter in data communication with the host machine including a wiring harness, said active electronic component being disposed in said harness.

3. The soft count tracking system according to Claim 2, said active electronic component communicating by means of a one-wire protocol.

4. The soft count tracking system according to Claim 3, said wiring harness including means for detachably coupling the same to the host machine.

5. The soft count tracking system according to Claim 4, said storage mechanism adapted to stack and securely transport notes and coupon.

6. The soft count tracking system according to Claim 3, each of said means for placing said identification adapter, currency note validator and storage mechanism in data communication comprising a harness segment.

- 10 -

7. The soft count tracking system according to Claim 6, each of said segments including mating disconnect elements by which a respective segment can be decoupled.

**AMENDED CLAIMS**

[received by the International Bureau on 19 March 1998 (19.03.98);
original claims 1-7 replaced by new claims 8-16 (2 pages)]

WHAT IS CLAIMED IS

8. A soft count tracking system for a currency operated host gaming machine comprising:

an identification adaptor;

a currency note validator;

a storage mechanism having a non-volatile storage memory for receiving and storing information; and

a detachable soft count supervisor including a computer and software to interrogate and extract the information from the non-volatile storage memory and to provide spread sheet data manipulation of the extracted information.

9. The soft count tracking system of claim 8, wherein the identification adaptor comprises an active electronic component having a unique serial number.

10. The soft count tracking system of claim 9, wherein the validator is configured to interrogate the identification adaptor for said serial number.

11. The soft count tracking system of claim 9, wherein the validator is configured to interrogate the identification adaptor for said serial number, and wherein the storage mechanism is configured to receive said serial number from the validator and store said serial number in the storage memory.



12. The soft count tracking system of claim 9, wherein the validator is configured to interrogate the identification adaptor for said serial number, wherein the storage mechanism is configured to receive said serial number from the validator and store said serial number in the storage memory, and wherein the soft count supervisor is configured to interrogate and extract said serial number from the storage memory.

13. The soft count tracking system of claim 8, wherein the identification adapter comprises a wiring harness containing the active electronic component for connecting the host machine to the validator.

14. The soft count tracking system of claim 8, wherein the storage mechanism is portable and configured to stack and securely transport notes and coupons.

15. The soft count tracking system of claim 8, wherein data communication between the identification adapter, the validator, the storage mechanism and the soft count validator is accomplished via wiring harnesses.

16. The soft count tracking system of claim 12, wherein data communication between the storage mechanism and the validator is accomplished via a wiring harness.