Description

FIELD OF THE INVENTION AND RELATED ART

The present invention relates to a process cartridge detachably mountable to an image forming apparatus such as an electrophotographic copying machine, an electrophotographic printer or an electrostatic recording apparatus, more particularly to a process cartridge containing an image bearing drum and at least one process means actable on the image bearing drum.

In a conventional image forming apparatus such as a copying machine, a printer or facsimile machine, plural consumable parts contributable to image formation are constituted as a unit, and the unit as a whole is exchanged to make the maintenance operation easier.

As for such an image forming unit, a process cartridge is known as disclosed in U.S. Patent Nos. 4,470,689 or 4,575,221, for example, wherein a housing contain a photosensitive member, and at least one process means such as a charger, developing device or cleaning device, for example, and the process cartridge as a whole is detachably mountable to the main assembly of the image forming apparatus.

Referring first to Figure 6, the image bearing drum is supported in the manner shown in this Figure. Figure 6 is a sectional view illustrating the supporting structure for the photosensitive drum 103 which is the image bearing member. The photosensitive drum 103 comprises a hollow drum 124 and flanges 125 and 126 press-fitted into, bonded to or clamped into, the insides of the hollow drum 124 at its opposite ends. The photosensitive drum is rotatably supported in the housing 102 by centering shafts 127 and 128 penetrating through the flanges 125 and 126, respectively. A developing sleeve 107 of the developing device is rotatably supported in a developer container 104 through flanges 129 and 130 which also function as centering shafts.

In the conventional supporting structure, the surface of the photosensitive drum 103 and the surface of the developing sleeve 107 wobbles when it is rotated, by the amounts of the eccentricity errors of the inside and outside diameters of the flanges 125, 126, 129 and 130 relative to the rotational axes 131 and 132 plus the eccentricity errors of the inside and outside diameters of the photosensitive drum 103 or the developing sleeve 107. This makes it difficult to maintain the accurate relative positional relation between the photosensitive drum 103 and the process means disposed therearound.

Taking the cleaning blade 120 contacted to the photosensitive drum 103 for example, if the degree A of the press-contact of the edge of the cleaning blade 120 to the surface of the photosensitive drum 103 is too small, the cleaning is not sufficient due to passage of the residual toner on the surface of the photosensitive drum 103. If, on the contrary, the degree A is too large, the photosensitive layer at the surface of the photosensitive drum 103 is scraped significantly with the result of decreased durability of the photosensitive drum 103.

Particularly, when the cleaning blade 120 is fixed on the housing 102 supporting the photosensitive drum 103, the wobbling of the surface of the photosensitive drum 103 directly affects the degree A of the press-contact with the cleaning blade 120, more particularly, causes periodic change. In order to assure the accuracy in the relation between the cleaning blade 120 and the photosensitive drum 103, it is required to maintain the high accuracies in the cleaning edge, the housing 102, the inside and outside diameter of the photosensitive drum 103, the flanges 125 and 126 and others. This results in cost increase, decrease in the yield and increase in the number of inspection steps.

In the developing device 104, the clearance B between the surface of the photosensitive drum 103 and the developing sleeve 107 (S-D gap) is required to be maintained with precision. If the S-D gap B is too small, the developed image has too high density as if character image is collapsed. If the gap B is too large, the character image becomes thin and light.

With the conventional supporting structure for the photosensitive drum 103 and the developing sleeve 107, the wobbling of the surfaces of the photosensitive drum 103 and the developing sleeve 107 causes the periodic change of the S-D gap B during rotation, with the result that the non-uniformity in synchronism therewith appears in the developed image.

The present invention has been made in view of the foregoing problems, and has a principal object to provide a process cartridge wherein the wobbling of the image bearing drum or the developing sleeve is sufficiently suppressed with a simple structure.

The present invention may also provide a process cartridge wherein the process means is easy correctly positioned relative to the image bearing drum, and image defect such as non-uniformity can be prevented.

The invention is defined in claim 1 of the claims.

In the accompanying drawings:-

Figure 1 is a cross-sectional view of a process cartridge according to an embodiment of the present invention (taken along a line C-C' in Figure 2).

Figure 2 is a longitudinal sectional view of the process cartridge.

Figure 3 is a front view of the process cartridge.

Figure 4 is a cross-sectional view of a process cartridge according to another embodiment of the present invention.

Figure 5 is a longitudinal sectional view of a process cartridge according to a further embodiment of the present invention.

Figure 6 is a cross-sectional view of a conventional process cartridge.

Figure 7 is a longitudinal sectional view of the process cartridge of Figure 6.

Referring to Figures 1, 2 and 3, there is shown a process cartridge according to an embodiment of the present invention. Figure 1 is a sectional view taken along a line C-C' of Figure 2.

The process cartridge 1 comprises one housing 2, a photosensitive drum (image bearing drum) 3. It also contains as process means a developing device 4, a charging device 5 and a cleaning device 6 in a compact manner. They are formed into a unit. The process cartridge is detachably mountable to a known image forming apparatus.

As shown in Figure 1, the outer peripheries of the photosensitive drum 3 and the developing sleeve 7 of the developing device 4 are rotatably supported at the opposite ends thereof by supporting members 8 and 9, respectively, fixed in the housing 2. A flange 10 or 11 is bonded to the inside, at one end, of the photosensitive drum 3 or the developing sleeve 7.

The magnet roller 7a in the developing sleeve 7 is supported by the supporting member 9 and the flange 11. In Figure 2, an aperture for the image exposure is indicated by a reference 2a.

To the shafts 13 and 14 projected in a main assembly 12 of the image forming apparatus are rotatably mounted driving gears 15 and 16 having large and small diameters, which are in meshing engagement with each other. When the process cartridge is mounted to the main assembly, the driving gears 15 and 16 are meshed with the flanges 10 and 11, as shown in the Figure. The photosensitive drum 3 and the developing sleeve 7 receive the driving force from the driving gears 15 and 16, respectively to rotate in the directions indicated by arrows in Figure 2.

As shown in Figures 1 and 3, the bearings 8 and 9 are fixed in the housing 2 by screws 17. The bearing or supporting members 8 and 9 are provided with steps 8a, 8b, 9a and 9b. The steps 8a and 9a limit the longitudinal movement of the photosensitive drum 3, and the steps 8b and 9b limit the longitudinal movement of the developing sleeve 7.

Since the photosensitive drum 3 and the developing sleeve 7 are supported by the supporting members 8 and 9 at the outer peripherals at their opposite ends, the wobbling upon rotation is limited to the wobbling error of the opposite outer peripheries only, that is, only one outer periphery at each end. The photosensitive drum 3 and the developing sleeve 7 are produced by extrusion or machining, and therefore, the wobbling error at the outer peripheries at the opposite ends can be limited to not more than 0.05 mm. Therefore, the rotational wobbling of the photosensitive drum 3 and the developing sleeve 7 can be limited to be very small, that is, in the same order. Therefore, the non-uniformity in the image attributable to the rotational wobbling can be prevented.

By supporting the outer periphery of the photosensitive drum, the wobbling of the photosensitive drum surface can be reduced, and therefore, the accuracy of the edge of the cleaning blade 20 may be relatively eased, by which the cost increase of parts can be reduced, the yield can be increased, and the number of inspection steps can be reduced.

As shown in Figure 2, a charging wire 18 of the charging device 5, the developing sleeve 7 and a development blade 19 of the developing device 4, the cleaning blade 20 and the toner receiving member 21 of the cleaning device 6, are fixed in the housing 2 supporting the supporting members 8 and 9, and therefore, the gap or the degree of press-contact with the photosensitive drum 3 are maintained constant. As a result, the image non-uniformity due to improper charging or development can be prevented; and improper cleaning for the residual toner can be prevented.

According to this embodiment, only one flange 10 or 11 may be bonded to the inside of each of the photosensitive drum 3 and the developing sleeve 7, and therefore, the number of parts and number of steps for the bonding or the press-fitting can be reduced.

In this embodiment, portions 8c and 9c of the supporting members 8 and 9 function as spacer means for maintaining a constant clearance between the surfaces of the photosensitive drum 3 and the developing sleeve 7, and therefore the possible image non-uniformity attributable to the variation of the clearance can be prevented.

Another spacer means may be usable. The spacer means may include spacer rollers rotatably engaged to the developing sleeve and contacted to the surface of the photosensitive drum, thus maintaining a predetermined clearance between the photosensitive drum and the developing sleeve. The spacer rollers rotate following the rotational wobbling of the photosensitive drum or the developing sleeve. However, when the wobbling is large or when the rotational speed of the sleeve is high, the spacer rollers can be spaced apart from the photosensitive drum or from the developing sleeve, or the rotation of the spacer rollers becomes irregular, so that the wearing of the spacer roller becomes non-uniform, with the result that the clearance between the photosensitive drum and the developing sleeve is not constant. If this occurs, the non-uniformity of the image can occur. However, according to the present invention, the rotational wobbling can be minimized by supporting the outer peripheries of the photosensitive drum and the developing sleeve, and therefore, it is effective to use the supporting structure and simultaneously to use the spacer rollers to assure the clearance between the photosensitive drum and the developing sleeve by the diameter of the rollers.

Referring to Figure 4, there is shown another em-

bodiment. In this Figure, the same reference numerals as in the foregoing embodiment, particularly Figure 1, are assigned to the elements having the corresponding functions.

In this embodiment, the supporting members 8 and 9 in the foregoing embodiment (Figure 1) are not used, and the outer peripheries at the opposite ends of each of the photosensitive drum 3 and the developing sleeve 7 are directly supported on the housing. The photosensitive drum 3 and the developing sleeve 7 are limited in their longitudinal direction by thrust bearings 22 and 23 fixed on the housing 2. In this embodiment, the housing 2 functions as the supporting member.

This embodiment is advantageous over Figure 1 embodiment in that the wobbling of the photosensitive drum 3 and the developing sleeve 7 can be further reduced because they are supported not through the supporting members 8 and 9. The photosensitive drum 3 and the developing sleeve 7 are mounted in the housing 2 by inserting them in the direction indicated by arrows, or by utilizing the elasticity of the housing 2 and expanding it and inserting the photosensitive drum 3 and the developing sleeve 7.

Figure 5 shows a further embodiment. In this embodiment, the process cartridge contains the photosensitive drum 3, the charger 5 and the cleaning device 6 as a unit, but does not contain the developing device.

In this embodiment, the outer peripheries of the photosensitive drum 3 at the opposite longitudinal ends are supported by supporting members 24 and 24 (only one is shown) fixed in the housing 2 of the process cartridge. The charging wire 18 of the charger is received by a groove 24a formed in a part of the supporting member 24 to maintain a constant clearance between the charging wire 18 and the photosensitive drum 3. A part of the supporting member 24 is used as a fixing portion 24b for the cleaning blade, so that the degree of press-contact of the edge of the cleaning blade to the photosensitive drum is maintained constant.

In this manner, the members such as the charging wire or the cleaning blade, actable on the photosensitive drum are supported by the supporting member for supporting the outer periphery of the photosensitive drum, so that the members can be correctly positioned relative to the photosensitive drum with precision.

In the foregoing embodiments, the outer peripheral portions at the opposite ends where the photosensitive drum is supported by the supporting members, are non-image-forming portion of the photosensitive drum, more particularly, end portions of a cylinder which is a base member of the photosensitive drum, in this embodiment.

Similarly, the outer peripheries at the opposite ends of the developing sleeve where the supporting members support it does not carry the developer.

As described in the foregoing, by supporting the image bearing drum at its outer periphery, the wobbling upon rotation can be reduced as compared with the conventional supporting structure. In addition, by supporting the process means by the supporting members supporting the image bearing drum, the positional accuracy of the process means relative to the image bearing drum can be improved. Therefore, good images without the defects such as non-uniformity can be stably provided.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.

Claims

1. A process cartridge detachably mountable to an image forming apparatus, comprising:
   an image bearing drum (3);
   process means (4, 5, 6) actable on said image bearing drum (3); and
   a housing (2) for accommodating said image bearing drum (3) and said process means (4, 5, 6);
   characterised by supporting means (8, 9, 24) for rotatably supporting said image bearing drum (3) at an outer periphery of said image bearing drum (3).

2. A cartridge as claimed in claim 1, characterised in that said housing (2) functions as said supporting means.

3. A cartridge as claimed in claim 1 or 2, characterised in that said process means includes at least one of charging means (5), developing means (4) and cleaning means (6).

4. A cartridge as claimed in claim 3, characterised in that said supporting means supports at least one of said process means.

5. A cartridge as claimed in claim 4, characterised in that said process means includes a developing roller for carrying a developer to supply the developer to said image bearing drum (3); and
   said supporting means (8, 9) serves to rotatably support an outer periphery of said developing roller (7).

6. A cartridge as claimed in claim 5, characterised in that said supporting means (8, 9) includes a spacer portion (8c, 9c) for maintaining a predeter-

bodiment. In this Figure, the same reference numerals as in the foregoing embodiment, particularly Figure 1, are assigned to the elements having the corresponding functions.

In this embodiment, the supporting members 8 and 9 in the foregoing embodiment (Figure 1) are not used, and the outer peripheries at the opposite ends of each of the photosensitive drum 3 and the developing sleeve 7 are directly supported on the housing. The photosensitive drum 3 and the developing sleeve 7 are limited in their longitudinal direction by thrust bearings 22 and 23 fixed on the housing 2. In this embodiment, the housing 2 functions as the supporting member.

This embodiment is advantageous over Figure 1 embodiment in that the wobbling of the photosensitive drum 3 and the developing sleeve 7 can be further reduced because they are supported not through the supporting members 8 and 9. The photosensitive drum 3 and the developing sleeve 7 are mounted in the housing 2 by inserting them in the direction indicated by arrows, or by utilizing the elasticity of the housing 2 and expanding it and inserting the photosensitive drum 3 and the developing sleeve 7.

Figure 5 shows a further embodiment. In this embodiment, the process cartridge contains the photosensitive drum 3, the charger 5 and the cleaning device 6 as a unit, but does not contain the developing device.

In this embodiment, the outer peripheries of the photosensitive drum 3 at the opposite longitudinal ends are supported by supporting members 24 and 24 (only one is shown) fixed in the housing 2 of the process cartridge. The charging wire 18 of the charger is received by a groove 24a formed in a part of the supporting member 24 to maintain a constant clearance between the charging wire 18 and the photosensitive drum 3. A part of the supporting member 24 is used as a fixing portion 24b for the cleaning blade, so that the degree of press-contact of the edge of the cleaning blade to the photosensitive drum is maintained constant.

In this manner, the members such as the charging wire or the cleaning blade, actable on the photosensitive drum are supported by the supporting member for supporting the outer periphery of the photosensitive drum, so that the members can be correctly positioned relative to the photosensitive drum with precision.

In the foregoing embodiments, the outer peripheral portions at the opposite ends where the photosensitive drum is supported by the supporting members, are non-image-forming portion of the photosensitive drum, more particularly, end portions of a cylinder which is a base member of the photosensitive drum, in this embodiment.

Similarly, the outer peripheries at the opposite ends of the developing sleeve where the supporting members support it does not carry the developer.

As described in the foregoing, by supporting the image bearing drum at its outer periphery, the wobbling upon rotation can be reduced as compared with the conventional supporting structure. In addition, by supporting the process means by the supporting members supporting the image bearing drum, the positional accuracy of the process means relative to the image bearing drum can be improved. Therefore, good images without the defects such as non-uniformity can be stably provided.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.

Claims

1. A process cartridge detachably mountable to an image forming apparatus, comprising:
   an image bearing drum (3);
   process means (4, 5, 6) actable on said image bearing drum (3); and
   a housing (2) for accommodating said image bearing drum (3) and said process means (4, 5, 6);
   characterised by supporting means (8, 9, 24) for rotatably supporting said image bearing drum (3) at an outer periphery of said image bearing drum (3).

2. A cartridge as claimed in claim 1, characterised in that said housing (2) functions as said supporting means.

3. A cartridge as claimed in claim 1 or 2, characterised in that said process means includes at least one of charging means (5), developing means (4) and cleaning means (6).

4. A cartridge as claimed in claim 3, characterised in that said supporting means supports at least one of said process means.

5. A cartridge as claimed in claim 4, characterised in that said process means includes a developing roller for carrying a developer to supply the developer to said image bearing drum (3); and
   said supporting means (8, 9) serves to rotatably support an outer periphery of said developing roller (7).

6. A cartridge as claimed in claim 5, characterised in that said supporting means (8, 9) includes a spacer portion (8c, 9c) for maintaining a predeter-

* C L M S *

mined clearance between said image bearing drum (3) and said developing roller (7).

7. A cartridge as claimed in claim 1, 5 or 6, characterised in that said process means includes a charging wire (18) for charging a surface of said drum (3), and said supporting means (24) supports said charging wire (18).

8. A cartridge as claimed in any one of claims 5-7, characterised in that said process means has a cleaning blade (20) for cleaning said image bearing drum (3), and said supporting means (24) supports said cleaning blade (20).

9. A cartridge as claimed in any one of claims 1-8, characterised in that said supporting means (8, 9, 24) supports non-image portions of said drum.

10. A cartridge as claimed in any one of claims 1-9, characterised in that said supporting member (8, 9) supports developer non-carrying portions of said roller (7).

Patentansprüche

1. Abnehmbar in ein Bilderzeugungsgerät einsetzbare Arbeitseinheit mit
einer Bildträgertrommel (3),
einer Arbeitseinheit (4, 5, 6), die auf das Bildträgerteil (3) einwirken kann, und
einem Gehäuse (2) zum Aufnehmen der Bildträgertrommel (3) und der Arbeitseinheit (4, 5, 6),
gekennzeichnet durch
eine Halteeinrichtung (8, 9, 24) zum drehbaren Tragen der Bildträgertrommel (3) an einem äußeren Umfang der Bildträgertrommel (3).

2. Arbeitseinheit nach Anspruch 1, **dadurch gekennzeichnet, daß** das Gehäuse (2) als die Halteeinrichtung dient.

3. Arbeitseinheit nach Anspruch 1 oder 2, **dadurch gekennzeichnet, daß** die Arbeitseinheit zumindest eine von einer Ladeeinrichtung (5), einer Entwicklungseinrichtung (4) und einer Reinigungseinrichtung (6) enthält.

4. Arbeitseinheit nach Anspruch 3, **dadurch gekennzeichnet, daß** die Halteeinrichtung zumindest eine der Arbeitseinheiten trägt.

5. Arbeitseinheit nach Anspruch 4, **dadurch gekennzeichnet, daß**
die Arbeitseinheit eine Entwicklungswalze zum Tragen eines Entwicklers enthält, damit der Entwickler der Bildträgertrommel (3) zugeführt wird, und daß
die Halteeinrichtung (8, 9) zum drehbaren Tragen eines Außenumfangs der Entwicklungswalze (7) dient.

6. Arbeitseinheit nach Anspruch 5, **dadurch gekennzeichnet, daß** die Halteeinrichtung (8, 9) einen Abstandsabschnitt (8c, 9c) zum Erhalten eines vorbestimmmten Abstands zwischen der Bildträgertrommel (3) und der Entwicklungswalze (7) enthält.

7. Arbeitseinheit nach Anspruch 1, 5 oder 6, **dadurch gekennzeichnet, daß** die Arbeitseinheit einen Ladedraht (18) zum Aufladen einer Oberfläche der Trommel (3) enthält und daß die Halteeinrichtung (24) den Ladedraht (18) trägt.

8. Arbeitseinheit nach einem der Ansprüche 5 bis 7, **dadurch gekennzeichnet, daß** die Arbeitseinheit eine Reinigungsklinge (20) zum Reinigen der Bildträgertrommel (3) aufweist und daß die Halteeinrichtung (24) die Reinigungsklinge (20) trägt.

9. Arbeitseinheit nach einem der Ansprüche 1 bis 8, **dadurch gekennzeichnet, daß** die Halteeinrichtung (8, 9, 24) Nicht-Bildabschnitte der Trommel trägt.

10. Arbeitseinheit nach einem der Ansprüche 1 bis 9, **dadurch gekennzeichnet, daß** das Halteteil (8, 9) nicht-entwicklertragende Abschnitte der Walze (7) trägt.

Revendications

1. Cartouche de traitement pouvant être montée de façon amovible sur un appareil de formation d'images, comportant :
un tambour (3) porteur d'image ;
des moyens de traitement (4, 5, 6) pouvant agir sur ledit tambour (3) porteur d'image ; et
un boîtier (2) destiné à loger ledit tambour (3) porteur d'image et lesdits moyens de traitement (4, 5, 6) ;
caractérisée par des moyens de support (8, 9, 24) destinés à supporter en rotation ledit tambour (3) porteur d'image à une périphérie extérieure dudit tambour (3) porteur d'image.

2. Cartouche selon la revendication 1, caractérisée en ce que ledit boîtier (2) remplit la fonction desdits moyens de support.

3. Cartouche selon la revendication 1 ou 2, carac-

* C L M S *

térisée en ce que lesdits moyens de traitement comprennent au moins l'un d'un moyen (5) de charge, d'un moyen (4) de développement et d'un moyen (6) de nettoyage.

4. Cartouche selon la revendication 3, caractérisée en ce que lesdits moyens de support supportent au moins l'un desdits moyens de traitement.

5. Cartouche selon la revendication 4, caractérisée en ce que lesdits moyens de traitement comprennent un rouleau de développement destiné à transporter un développateur pour amener le développateur audit tambour (3) porteur d'image ; et

lesdits moyens (8, 9) de support servent à supporter en rotation une périphérie extérieure dudit rouleau (7) de développement.

6. Cartouche selon la revendication 5, caractérisée en ce que lesdits moyens (8, 9) de support comprennent une partie à entretoise (8c, 9c) destinée à maintenir un espace prédéterminé entre ledit tambour (3) porteur d'image et ledit rouleau (7) de développement.

7. Cartouche selon la revendication 1, 5 ou 6, caractérisée en ce que lesdits moyens de traitement comprennent un fil métallique (18) de charge destiné à charger une surface dudit tambour (3), et lesdits moyens (24) de support supportent ledit fil métallique (18) de charge.

8. Cartouche selon l'une quelconque des revendications 5-7, caractérisée en ce que lesdits moyens de traitement comprennent une lame (20) de nettoyage destinée à nettoyer ledit tambour (3) porteur d'image, et lesdits moyens de support (24) supportent ladite lame (20) de nettoyage.

9. Cartouche selon l'une quelconque des revendications 1-8, caractérisée en ce que lesdits moyens (8, 9, 24) de support supportent des parties sans image dudit tambour.

10. Cartouche selon l'une quelconque des revendications 1-9, caractérisée en ce que ledit élément (8, 9) de support supporte des parties dudit rouleau (7) ne transportant pas de développateur.