



(51) International Patent Classification:

C10M 141/08 (2006.01) *C10N 40/04* (2006.01)
C10M 141/10 (2006.01) *C10N 30/12* (2006.01)

(21) International Application Number:

PCT/US2015/027996

(22) International Filing Date:

28 April 2015 (28.04.2015)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/989,299 6 May 2014 (06.05.2014) US

(71) Applicant: **THE LUBRIZOL CORPORATION**
[US/US]; 29400, Lakeland Blvd., Wickliffe, OH 44092-2298 (US).

(72) Inventors: **SACCOMANDO, Daniel, J.**; P.O. Box 88, Belper Derbyshire DE56 1QN (GB). **DELBRIDGE, Ewa, E.**; 29400, Lakeland Blvd., Wickliffe, OH 44092 (US). **BARTON, William R., S.**; P.O. Box 88, Belper Derbyshire DE56 1QN (GB).

(74) Agents: **SHOLD, David, M.** et al.; 29400, Lakeland Blvd., Wickliffe, OH 44092-2298 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ANTI-CORROSION ADDITIVES

(57) Abstract: A lubricant composition comprising an oil of lubricating viscosity and an N-hydrocarbyl-substituted aminoester, wherein the N-hydrocarbyl substituent comprises a hydrocarbyl group of at least 3 carbons atoms, with a branch at the 1 or 2 position of the hydrocarbyl chain, provides good iron and copper corrosion performance in driveline or gear applications.



WO 2015/171364 A1