



(51) International Patent Classification:

E04B 9/06 (2006.01) *F21V 33/00* (2006.01)
E04B 9/00 (2006.01)

(21) International Application Number:

PCT/AU2010/001089

(22) International Filing Date:

24 August 2010 (24.08.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2009904006 24 August 2009 (24.08.2009) AU

(72) Inventor; and

(71) Applicant : **WHITFIELD, David** [AU/AU]; 7/66 Whit-
ing Road, Artarmon, NSW 2065 (AU).

(74) Agent: **FRASER OLD & SOHN**; PO Box 560, Milsons
Point, NSW 1565 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,


AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: CEILING FRAME SYSTEM



(57) Abstract: A ceiling frame system (1) comprises a plurality of frame members (1) configured to depend from the ceiling. The frame members (1) include one or more service conduits (11) and are configured to be interconnected to one or more other frame members (1) to interconnect said service conduits (11) between predetermined interconnected frame members (1). The services are accessible at one or more predetermined locations along the length of each frame member (1). A ceiling frame member (1) is also provided.

