

PATENT APPLICATION

TITLE OF THE INVENTION

POSITIVE IDENTIFICATION AND PROTECTION OF DOCUMENTS
USING INKLESS FINGERPRINT METHODOLOGY

5 INVENTOR(S): KENNY HANSMIRE and PETER A. PYHRR

CROSS-REFERENCE TO RELATED APPLICATIONS

Priority of U.S. Patent Application Serial No.
08/914,735, entitled "Positive Identification and
Protection of Documents Using Inkless Fingerprint
10 Methodology", filed 08/19/97, is hereby claimed and
incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR
DEVELOPMENT

Not applicable

15 REFERENCE TO A "MICROFICHE APPENDIX"

Not applicable

BACKGROUND OF THE INVENTION

1. Field of the Invention

The apparatus of the present invention relates to a
20 chemical coating solution that can be placed on any type of
material, such as paper stock, plastic, metals, glass,
cloth or any items that include a surface which will accept
a coating, and a second solution placed on an applicator
pad, so that when a person touches the applicator pad with
25 his finger or stamp and then touches the treated paper, a
fingerprint or stamped image will appear.

More particularly, the present invention relates to
a method whereby any printed document (for example, include
but not limited to airline tickets, labels, checks, bonds,
30 passports, green cards, and any other document with
identification of the user or owner is critical) that has
been treated with a chemical coating would react with other
chemicals in an inkless fingerprint pad to form an inkless
fingerprint.

2. General Background of the Invention

Paper products and security features for paper products have been used extensively for many years. Some paper products, like, for example, checks, have built in security features such as: ink caplets that explode when solvents are used to erase signatures or amounts on the check. These exploding ink caplets show up as little ink dots on the check, these dots alert the bank cashiers that the check might be altered or that it has been forged. To achieve a positive identifier (fingerprint) there are several methods available. However, to obtain a fingerprint utilizing the conventional methods of using black ink results in the messy black inks staining the hands and oftentimes, the clothing of the individuals, which is a great inconvenience and a hinderance toward acceptance in an industry.

The inkless print security fraud feature is a two step process; (1) the paper has to be treated or coated with a chemical solution that impregnates or soaks into the paper; (2) the coated paper must react with the chemical solution application pad. The process of the treated paper with the chemical application pad will allow a person to put a stamped mark, or fingerprint, or both, on a document. There are patented inkless methods, such as Vassiliade's Patent #5,009,919, and other patented or proprietary methods, that can be used to achieve an inkless fingerprint.

There are security features that will allow a person to possibly identify a false or forged documents. But many of these features have to be held in certain lights (U.V.) to be seen. Because of the extra expense involved in coating and/or inspection (equipment such as U.V. lights at numerous inspection locations), some documents cannot be coated at all.

Therefore, there is a need to provide a convenient and inexpensive process of achieving coating and inspection of certain documents to provide security features. In the

process and methodology of the present invention, all types of documents can be coated without utilizing special lights, or other extra features, which can be prohibitively expensive to utilize.

5 An example of the applicability of the need for identifying documents properly is the airline industry. Airline tickets have long been used in the airline industry as a means to allow a passenger to board an airplane. The ticket has general information on such things as name of
10 passenger, flight number, destination, time, date, and bar codes for computer tracking. However, there is a constant problem of assuring that the passenger who is in possession of the airline ticket is in fact the person named on the ticket. In the current state of the art, as far as
15 applicants are aware, there is no means for assuring through some personal identification on the ticket that such is the case. One such method might be the use of fingerprints which could match up between the user and the ticket. However, conventional finger printing has severe
20 drawbacks. One is the perception of guilt from having to place one's finger print in black ink such as the police department's utilize. Additionally, the finger printing usually would result in the staining of the hands and clothing by use of the black intrusive inks. The process
25 which would be used in the present invention would be used in airports and not in a criminal environment, therefore, the process by its very nature must be clean and non-obtrusive to the passengers.

 A possible means for achieving this end is the
30 utilization of the inkless finger printing. The inkless coating can be achieved through methods both patented and unpatented. For example, one patented method is a patent to Vassiliade's, patent No. 5,009,919, referred to earlier. This method could be used as well as many other non-
35 patented methods. However, the inkless process is a two-step process. First, the item to be matched must be coated with a chemical solution. Secondly, the coated chemical

solution must react with the chemical solution in the fingerprint pad. The process with the coated ticket and the inkless pad would then serve as a non-intrusive method of obtaining a fingerprint. The person just stamps the
5 treated document with the chemical pad solution and a black, dark or color image will appear and also will allow a fingerprint to appear on the document if desired.

There are patents which have been cited in the art which address the overall features of security features, or
10 utilizing inkless methodology. These are listed in the prior art statement submitted herewith.

BRIEF SUMMARY OF THE INVENTION

The method and process of the present invention has
15 the ability to be utilized on any printed document, which, for example, include airline tickets, labels, checks, bonds, passports, green cards, and any other document with identification of the user or owner is critical. What is provided is a system for coating a document with a chemical
20 compound, for determining an image thereupon, the system which would include the steps of first providing a document such as an airline ticket; next, applying a clear chemical coating onto the document; applying an image onto the chemical coated portion of the document; allowing the
25 image to appear on the treated portion of the document; providing an activator solution; applying the activator solution to the treated portion of the ticket has received a stamped image; and, then, identifying the stamped image for assuring that the stamped image is not a
30 counterfeit or the like. There may be further included the step of providing a second portion of the document with a coated solution and providing a fingerprint onto the treated portion of the document so that when an activator solution is applied thereto, a fingerprint would appear for
35 matching the fingerprint with the holder of the document.

The system may also incorporate an activation application to combine with the coating to produce an

image. The activation material cannot be readily duplicated because it may contain patented or proprietary information, and the stamps or patterns may be changed periodically.

5 The present invention, therefore may be of various styles, applications, and features. For example, the clear coating printed or applied to the document can take on many styles:

10 Non patterned: stamp or finger print creates the pattern;

Patterned: any pattern, design, word, number, etc.

Furthermore, these patterns may be changed. This coating can be applied on any portion of the document, front and/or back. This coating is clear and cannot be
15 copied or readily detected, nor can it be readily duplicated because of the patented and/or proprietary nature of the coating.

An example of the method or steps of the present invention, as it would apply to, for example, the airline
20 industry may be as follows:

1. A clear chemical coating would be applied on any desired documents (airline tickets).

2. The documents, having the coating, would then be sent out in their desired field (airline company).

25 3. The documents would then be placed into the hand of the purchaser or public (airline passenger) as the public or passenger purchases the tickets.

4. A passenger would then hand his ticket over to the boarding agent.

30 5. The agent would then take a stamp and stamp an image or wording onto the treated portion of the airline ticket.

6. An image will appear on the treated ticket.

35 7. If the boarding agent so desires, he can request that the passenger provide a fingerprint. The passenger would touch the chemical applicator pad and touch the treated ticket.

8. A black, dark or color fingerprint will appear on the treated ticket leaving no ink or color on the finger of the passenger.

9. The ticket would be kept by the airline giving the airline a positive identifier (fingerprint) and a fraud document identifier (stamp) for security purposes in case something illegal happens to the plane (bombing or hijacking).

This invention has several advantages over other counterfeit protection methods:

It is non-visible and/or difficult to detect;

Two different patented and/or proprietary coatings/solutions must be used to duplicate the system;

No special materials/papers are required;

Patterned, non patterned, and/or variable combinations of coatings and activation systems can be used.

Utilizing the method of the present invention, a chemical solution is coated on any type of material, such as paper stock, plastic, metals, glass, cloth or any items that include a surface which will accept a chemical coating. The chemical solution reacts with chemicals in an application pad. The reaction produces a black dark or color image. Although an airline ticket example was used, the present system could be utilized but is not limited, in the following areas for counterfeit protection and if desired positive identification (fingerprint): checks, airline tickets, passports, green cards, legal documents, currency, U.S. postal documents, stamps, bonds, I.D. cards, drivers licenses, shipping invoices, adhesive labels and medical forms.

Furthermore, one embodiment of the method of the present invention would provide a hidden/non-visible security feature to prescription slips so that a pharmacist may verify the prescription slips authenticity, by producing an image and/or a fingerprint through application of an activation solution to the non-visible coating solution on the prescription slip. This embodiment would

combine (a) a positive identification feature (non-obtrusive/positive I.D.); and (b) a prescription slip coated with non-visible or a clean, clear coating in a pattern or non-pattern format which would be only on the original prescription slip. The process would verify the authenticity of the prescription slip by having a pharmacist take a pen or any device that may contain the activation solution. Placing the pen with the activation solution onto the coated portion of the prescription slip an image or color would appear, verifying for the pharmacist that the prescription is authentic and not copied. With the advent of high resolution, multi-colored copier machines, computer generated graphics and sophistication of counterfeiters has created a broad range of anti-counterfeiting measures.

The invention also provides other methods for applying the activation solutions on the paper document. Although there can be many methods of delivering the activation solution to the treated surface, there are four examples which are cited in this application. The first is an applicator pad which the finger would touch, the second is an applicator pad that a stamp would touch, and the third is an atomizer which sprays a mist of the activation solution to the treated surface. The fourth is a pen that contains the activation solution, the pen would be swiped over the treated surface. Although these are four examples, other desired methods for applying the activation solution might be the use of a brush, straw, self stamper, swabs, cloth, and any means possible that can apply the activation solution and deliver it to the treated surface.

Therefore, it is the principal object of the present invention to provide chemically treated documents, such as checks, airline tickets, passports, green cards, legal documents, currency, U.S. postal documents, stamps, bonds, I.D. cards, drivers licenses, shipping invoices, adhesive labels, prescription slips, and medical forms that would be used to help identify their rightful owners and avoid

forgery of same;

It is a further object of the present invention to insure a non-intrusive and inexpensive method of providing positive identification of the owner of a particular document for security reasons;

It is a further object of the present invention to utilize the inkless finger printing method in areas such as baggage labels, bag tags, airline labels, shipping slips, freight orders, baggage tickets, medical organ containers and biohazard shipments which assures that the shipment or document can be positively identified with the sender (passenger, shipper, etc. who provided the fingerprint on the shipping document).

BRIEF DESCRIPTION OF THE DRAWINGS

For a further understanding of the nature, objects, and advantages of the present invention, reference should be had to the following detailed description, read in conjunction with the following drawings, wherein like reference numerals denote like elements and wherein:

Figure 1 is a sample of a document, such as a ticket or label, with a chemical coating that would be utilized in the present invention;

FIGURE 2 illustrates a side view of the document with the chemical coating illustrated in FIGURE 1;

FIGURE 3A illustrates an activation pad;

FIGURE 3B illustrates an activation stamp having a raised image on the stamp utilized in the present invention;

FIGURE 3C illustrates the activation stamp being applied to the chemical coated document in FIGURE 1;

FIGURE 4 illustrates a chemical applicator having a built-in pad and stamp combination;

Figure 5 illustrates a front view of an airline ticket;

FIGURE 6 illustrates a back view of an airline ticket;

FIGURE 7 illustrates a side view of an airline ticket;

FIGURE 8 illustrates an overall view of an activation pad;

FIGURE 9 illustrates an overall view of an activation stamp having ABC raised image thereupon;

5 FIGURE 10 illustrates a front view of airline ticket with finger and stamp placed on treated portion of ticket;

FIGURE 11 illustrates a front view of ticket with image stamp and fingerprint appearing on ticket;

10 FIGURE 12 illustrates a front view of an airline ticket with the atomizer being placed on treated portion of the ticket;

FIGURE 13 illustrates an atomizer with a pattern (such as the word "void", logo, number, illustration, etc.);

15 FIGURE 14 illustrates a front view of the airline ticket with the VOID image of the chemical atomizer appearing on the ticket;

FIGURE 15 illustrates a front view of a prescription slip;

20 FIGURE 16 illustrates a front view of a prescription slip with activation pen and finger being placed on treated portions of a prescription slip;

FIGURE 17 illustrates a front view of a prescription slip with the word original and fingerprint appearing on a prescription slip;

25 FIGURE 18 illustrates a pad with activation solution;

FIGURE 19 illustrates a finger being placed in a pad; and

FIGURE 20 illustrates a pen with activation solution.

30 DETAILED DESCRIPTION OF THE INVENTION

FIGURES 1 through 4 illustrate the method and system of the present invention applied to all documents, with FIGURES 5 through 14 illustrating the method of the present invention applied in particular to airline documents, such as tickets and baggage tags.

35 As illustrated, FIGURE 1 illustrates a view of a generic document, such as a check, airline ticket,

passport, green card, legal document, currency, U.S. postal document, stamp, bond, I.D. card, drivers license, shipping invoice, adhesive label, or medical form, for examples, which has been treated with a chemical coating for utilization in inkless finger printing that could be utilized in various industries. As noted, document 12, identified in FIGURE 1, includes a body portion 14, having a face 16, including an area 18, which has been chemically coated with a chemical 20, so that a person may place one's finger print or the like on the coating whereby the finger print would then appear on the area coated. In FIGURE 2, there is illustrated a side view of the document 12, with the chemical coated area 18, raised off of the face 16 of document 12. If the document material is absorbent, the chemical coating may be absorbed into the top layers of the document material so that the coated area 18 is not raised perceptively. The document 12 as seen in FIGURES 1 and 2, may have one or several layers of material. For example, it may have a liner, an adhesive, and a face sheet. For example, as further seen in FIGURE 3A, there is an activation pad 30, having a certain chemical compound 31, absorbed into pad 30. The pad 30 is housed within a box 32, which has a lid 34, which would maintain again the pad 30 so that when the box 32 is in the closed configuration, the chemical compound 31 within activation pad 30 is free from being contaminated and reduce evaporation of chemical compound. However, when one wishes to utilize the pad 30, for example, when finger printing must be done, one would open the lid 34, place one's finger on the activation pad 30, to obtain the chemical compound 31 upon one's finger. Next, one would then place the finger having the chemical compound 31 thereon, on the chemical coating 20 of area 18 on document 12, as seen in FIGURE 1. At this point, the chemical compound on area 18 would reveal the fingerprint of the person.

As seen in FIGURE 3B, there is illustrated an activation applicator 22, of the common type, having a

handle 24, and applicator portion 26, which could involve several methods of application. For example, as illustrated in FIGURE 3B, a raised image 40 is provided on the face 42 of the applicator 22, and one would place the raised image 40 on the activation pad 30. At this point, one would place the raised image 40, now containing the chemical coating 31 from pad 30, on the chemical coating 20, of the document 12, as seen in FIGURES 1 and 2. The raised image 40 of applicator 22 would then appear on area 18 of document 12, as seen in FIGURE 3C.

Other means of applying the image are illustrated. For example, in FIGURE 4, there is a self-contained applicator 50, having a face portion 52 with a raised image 54, which is quite like the applicator 22 in FIGURE 3B, but for the fact that the self contained applicator 50 would include a built in activation pad 56. Therefore, the raised image 54 rotates to pick up the chemical activation compound 58 on the activation pad 56, and the face 52 would rotate back to the original position where the raised image 54 is in the stamped position. The raised image 54 would then be placed on the chemical coating of area 18 on the document 12, and would appear as image 54 on the document.

In yet another embodiment, there may be a non-patterned applicator 22 applied to a patterned chemical coating 59 as shown in Figure 3C. The image or patterned chemical coating would be placed on the document, such as a ticket or label. The non-patterned activation pad would be stamped over the imaged or pattern chemical coating and the pattern would show up on the ticket or label.

Turning now to FIGURES 5 through 14, there is illustrated the preferred embodiment of the system of the present invention, as it would apply, for example to documents used by the public in the airline industry, such as tickets or baggage tags. As illustrated for example in FIGURE 5, there is a front view of an airline ticket 60, which has been coated with a clear chemical solution 62 in one or several locations by the various methods as

previously indicated in the present invention. It is noteworthy to note that the chemical solution 62 would coat only certain areas 64 of the ticket 60. Airline ticket 60, of course, would also include on its face the general flight information, as noted by numeral 66, for example, the name of the ticket holder, the date of the ticket, destination, and baggage identification information. The airline ticket 60 has two portions: a ticket portion 65 which is normally retained by the airline, and a boarding pass and baggage ID portion 63 which is retained by the passenger to use when boarding the aircraft and may be used to identify and claim baggage. Each portion (65 and 63) or either portion may have an area 64 with a chemical solution 62 applied thereto.

In FIGURE 6 there is illustrated the back surface 68 of airline ticket 60 which could include a magnetic stripe 70, and other notices if applicable. FIGURE 7 illustrates the side view of the airline ticket 60 where the chemical solution 62 of the ticket is illustrated, as the chemical coating would appear on both portions (65 and 63) on the top portion 61 of the ticket 60. In FIGURE 8, there is illustrated the chemical applicator pad 30 which would be the type for placing the chemical solution 31 onto various images, as was discussed in a general manner in FIGURES 1 through 4. For Example, as seen in FIGURE 9, there is an activation activator 22, having a raised image stamp 26, in this case, the letters "ABC". The image, of course, could be changed into whatever image would be desirable in the use of the system. Further, turning to FIGURE 10, there is a front view of the airline ticket 60 where the activator 22, having the ABC image thereupon, has been pressed upon the applicator pad 30 to receive chemical compound 31 on the raised ABC image 26. In turn, the raised image 26, with the chemical compound 31 thereupon, has been placed upon the chemical solution 62 which has been coated on the ticket 60, as described earlier. When this is done, as seen in FIGURE 11, the "ABC" image 26 appears on the chemical

solution portion of the ticket 60 in one or more locations. Likewise, as seen in FIGURE 10, on the ticket portion 65 of the ticket 60, having the chemical solution 31 thereupon, a finger 73 of a user may press his or her finger onto the chemical applicator pad 30, and in turn press his finger on the chemical solution of the ticket portion 65 of the ticket 60, forming a fingerprint 74 on the ticket portion 65. Therefore, there is a positive I.D. both in the fingerprint of the user on the ticket portion 65 which is retained by the airline, and on the raised data that has been placed on the stamp on the airline ticket 60 on the chemical solution 62. In effect, the raised "ABC" image on the chemical solution portion of the ticket protects the document because it demonstrates that the airline ticket 60 is an original document rather than counterfeit since the chemical solution 62 is difficult to duplicate because of its patented or proprietary nature. The fingerprint 74 also demonstrates that this is an original document since it also utilized the chemical solution 62; but in addition, it provides a positive identification of the passenger who boarded the airplane.

An additional embodiment of utilizing the method of the present invention is seen in FIGURE 12, where again the airline ticket 60 has a chemical compound 62 coated upon areas 64 on the ticket portion 65 and area 64 of the boarding pass and baggage I.D. portion 63. In this case, in FIGURE 13 there is seen a dispenser 71, for dispensing the activator compound 20 from dispenser 71 rather than the compound 20 being found on a pad as described earlier. The dispenser may comprise, for example, an atomizer 72, or any type of means for applying the chemical solution 20 onto an applicator portion 75, and then onto the area 64 of the ticket 60 so that the solution would adhere to the face of the ticket 60 for the reasons stated earlier. FIGURE 12 illustrates the atomizer 72, with applicator portion 75 dispensing the solution 20 directly onto the area 64 of ticket 60. As illustrated in FIGURE 14, after the atomizer

72 would dispense the activating solution 20, the word "VOID" 80 would appear on one or several areas 64 of ticket 60, which would then determine whether or not the ticket is original or not. Of course, other words or images may be
5 utilized to convey the various status of the ticket or other type documents in question. For example, the words "security check" would show that the passenger has passed through the security and baggage screening procedures.

Although FIGURES 8 through 14 illustrated the method
10 of the present invention being utilized with airline tickets there are a vast number of uses of the methodology as described. For example, another use of the method of the present invention would be positive identification for letter and/or package security with inkless fingerprint.
15 For example, letters and/or packages mailed or shipped by both public and private carriers, for example, the U.S. Postal Service, Federal Express, UPS, trucking companies, etc., may require additional security by positively identifying each shipper. This particular embodiment of
20 the invention would combine the two products that have never before combined as one. That is, the inkless fingerprinting (non-obtrusive/positive I.D.) and 2, the positive identification of the shipper for letter and/or package security. Although various methods have been
25 proposed for improving security for letters and/or packages shipped by ground and/or air relating to security concerns for explosives and/or illegal contents such as drugs which create a danger to the carrier's employees, third parties that may be injured or killed during transportation (such
30 as airline passengers if a package bomb explodes during flight, or recipients of packages). Shippers such as the U.S. Postal Service also face significant financial liabilities for physical damage, injury or death caused by explosions on packages sent through the U.S. mail.
35 Carriers including the U.S. Postal Service also have taken security steps including dogs sniffing packages for drugs and/or explosives.

In utilizing the positive I.D. of people shipping letters and/or packages, a person may not be required to show any identification or may use false identification when shipping a package. By placing a fingerprint on the ticket, the carrier has positive identification of the person shipping the package. The carrier may require one or more labels. One fingerprint label may be affixed to the package. Another label may be retained by the carrier on a copy of the bill of lading or another shipping document as a secondary reference, should the fingerprint label on the package be destroyed. The fingerprint would have to be taken using the inkless method as described earlier for helping to insure a non-messy/non-intrusive method of positive identification. This positive identification may be accomplished in one or more combination of two methods. In the label method, the label would be coated with the chemical solution as was of the type described earlier. The label could then be removed and placed on a package or letter. Multiple labels may be used with one label placed on the package and the second label placed on a shipping document. In the second method called the direct document coating, the document is coated such as a bill of lading so that the fingerprint can be taken directly on the document. Therefore, in either method when the fingerprint is in place on the solution, the activator solution would be applied to create the fingerprint utilizing the method as was described earlier and for matching up the fingerprint to positively identify the shipper.

An additional embodiment of the present invention would be utilized on any document which may include prescription slips. FIGURES 15 - 20 illustrate this additional embodiment. For example, as illustrated in FIGURE 15, there is a prescription slip 90, having a front face 92, where there is seen the address of the hospital or clinic 94, the patient's name and address data are 96, and the physician data 98. Also included on the face 92 of

prescription slip 90, is the designation RX 100, which includes an area 102, having non-visible ink or the like placed there upon in a particular pattern or word configuration, but which is non-visible to the naked eye.

5 Also, which may be present in the alternative, is a blank area 104, which may include a rectangular of non-visible ink 106, which is shown in phantom view, which again is non-visible to the naked eye. For purposes of explanation, non-visible would include being invisible to casual
10 observation, difficult to detect, difficult to detect with the human eye, and in some applications, black light or other chemicals may be purposefully added so that the non-visible image can be detected by various means as part of a security system design.

15 Turning now to FIGURE 16, again there is illustrated the prescription slip 90, wherein the prescription slip has been turned over to a pharmacist or the like at a pharmacy. At this point in the process, the pharmacist can utilize a pen 110, which is illustrated in partial view in FIGURE 16
20 and in full view in FIGURE 20, which is filled with a particular activation solution. The pharmacist would then move the pen across the area 102, and any pattern or word in the area in non-visible ink would show up to the visible eye, in this case the word "original" 114 is identified in
25 the block and therefore this is an authentic prescription. In the event the prescription had been counterfeit, when the security pen 110 had been moved across the area 102, the word "original" would not have shown up since it would not have been present in non-visible ink.

30 Likewise, if the pharmacist chooses, the person turning over the prescription slip 90 may in fact press his finger 111 on an activator fluid pad 112 as seen in FIGURES 18 and 19, and when he places his finger 111 on the second area 104 of prescription slip 90, as seen in FIGURE 15, his
35 fingerprint 116 would likewise show up on the prescription slip 90 as a positive I.D., since the area 104 has likewise been treated with the non-visible ink, and the person's

finger would have picked up the activation fluid from pad 112. Again, were this a counterfeit slip, when the finger of the user had been pressed against the area 104, no fingerprint would have shown up since there would have been no patch of non-visible ink as seen in FIGURE 15.

FIGURE 17 illustrates clearly where both of the areas 102 and 104 have been identified by the user and therefore the prescription slip 90 is an original.

The clear coating printing or applied to the document could take on many styles:

Non patterned: A pen, stamp or fingerprint creates the pattern;

Patterned: any pattern, design, word, number, etc. These patterns may be changed. This coating can be applied on any portion of the prescription slip front and/or back. This coating is clear and cannot be copied or readily detected, the coating cannot be readily duplicated because of the patented and/or proprietary nature of the coating.

The system also requires the activation solution to be placed on or combined with the coating on the paper. This activates the chemical coating to produce an image or color. The activation solution cannot be readily duplicated because of the patented and/or the proprietary nature of the solution.

The method or steps of carrying out the invention are as follows:

1. The clear chemical coating would be put on the prescription slip 90;
2. The prescription slip 90 would then be sent out to the doctors;
3. The doctor would prescribe a medication to patient and write the prescription on the prescription slip 90;
4. The patient would take the prescription slip 90 to the pharmacy to have a pharmacist fill the prescription;
5. The pharmacist or one of his assistants would take the pen 110 (containing the activation solution) and run the pen 110 over the coated or treated portion of the

prescription slip, area 102;

6. An image or color would appear on the coated or treated prescription slip 90; (identifying the prescription slip as being authentic);

5 7. If an image or color didn't appear this would notify the pharmacist that the prescription slip was counterfeit;

8. The pharmacist would call the doctor for confirmation and if necessary, call local law enforcement;

10 9. As an option, or in addition, if the image or color did appear (see #6 above), the pharmacist could ask the patient for a fingerprint to be placed on area 104. (He may ask for a fingerprint on some prescription slips for drugs that may be on the D.E.A.'s controlled substance
15 lists). Used by itself, the fingerprint would also show that the prescription slip is authentic;

10. The patient would touch his finger 111 to a pad 112 containing the activation solution, then touch the coated (treated) portion 104 of the prescription slip 90
20 and a dark fingerprint would appear;

11. The prescription slip 90 would then be kept by the pharmacy to insure that the prescribed medication was handed out to the proper patient;

12. If a doctor calls and says his prescription
25 slips/pads were stolen, the pharmacist can look back through the filled prescriptions and see if the doctor's batch number or stolen prescription shows up;

13. If the stolen prescriptions are found at the pharmacy, they can be turned over to local law enforcement
30 and if a fingerprint had been taken by the pharmacist and placed on the prescription slip, this would help the police locate and identify the person passing the stolen prescription slips.

35 This invention has several advantages over other counterfeit protection methods;

It is non-visible and/or difficult to detect;

Two different patented and/or proprietary

coatings/solutions must be used to duplicate the system;

Patterned, non patterned, and/or variable combinations of coatings and activation systems can be used.

5 The invention is a method using a chemical solution that is coated on prescription slips. The chemical coating solution reacts with chemicals in an application solution. The reaction produces a black or blue or color image. It can be used in the following areas but is not limited to these areas, for counterfeit protection and if desired
10 positive identification (fingerprint): checks, airline tickets, prescription slips, passports, green cards, legal documents, currency, U.S. postal documents, stamps, bonds, I.D. cards, drivers licenses, shipping invoices, adhesive labels and medical forms.

15 The invention also provides many methods for applying the coating solution. The coating solution can be placed on the desired surface (paper) in many ways: The ways to apply the coating on the paper might be, but are not limited to the following: 1) being sprayed on, 2) brushed
20 on, 3) wiped on by a cloth, 4) being machine pressed on, 5) using a print machine to be printed on, 6) or the coating could be placed in a pen and the pen could deliver the coating on the desired surface (paper).

The invention also provides many methods for applying
25 the activation solutions to the chemical coated documents. The ways to apply the activation solution to the coated paper might be, but are not limited to the following: 1) pen, the activation solution would be put in a pen, the pen would deliver the solution to the coated paper. 2) A pad
30 that would contain the activation solution, (finger or stamp could be placed on the pad as to deliver the solution to the coated paper. 3) An atomizer that would deliver a small amount of spray to the coated paper.

PARTS LIST

35 The following is a list of suitable parts and materials for the various elements of the preferred

embodiment of the present invention.

PARTS LIST

	Part Number	Description
	12	document
5	14	body portion
	16	face
	18	area
	20	chemical activator solution
	22	activation applicator
10	24	handle
	26	applicator portion (with raised image)
	30	activation pad
	31	chemical compound
	32	box
15	34	lid
	40	raised image
	50	self contained applicator
	52	face portion
	54	raised image
20	56	activation pad
	58	activation compound
	59	patterned chemical coating
	60	airline ticket
	61	top portion
25	62	chemical solution
	63	boarding pass & baggage ID portion
	64	area
	65	ticket portion
	66	flight information
30	68	back surface
	70	magnetic stripe
	71	dispenser
	72	atomizer
	73	finger
35	74	fingerprint
	75	applicator portion
	80	"VOID" pattern

	90	prescription slip
	92	front face
	94	address of hospital or clinic
	96	patient data
5	98	physician data
	100	RX designation
	102, 14	areas
	106	rectangular of non-visible ink
	110	pen
10	111	finger
	112	pad
	114	"original" mark
	116	fingerprint

Because many varying and different embodiments may be made
15 within the scope of the inventive concept herein taught,
and because many modifications may be made in the
embodiments herein detailed in accordance with the
descriptive requirement of the law, it is to be understood
that the details herein are to be interpreted as
20 illustrative and not in a limiting sense.

What is claimed as invention is:



CLAIMS

1 1. A method for providing a non-visible security
2 feature for protecting and verifying the authenticity of
3 documents, the method comprising the following steps:

4 a) providing a document to be protected;

5 b) applying a non-visible chemical coating onto at
6 least a portion of the document, which may include a
7 definable non-visible image;

8 c) providing an activator solution apart from the
9 chemical coating;

10 d) applying the activator solution onto the
11 nonvisible chemical coating of the document to reveal a
12 visible color image thereupon for verifying that the
13 document is not a counterfeit.

1 2. The method in claim 1, wherein there may be
2 provided a second portion of the document chemically coated
3 so that a person's finger coated with activator solution
4 may be placed on the second portion to reveal a fingerprint
5 on the document.

1 3. The method in claim 1, wherein the activator
2 solution may be maintained within an absorbent pad, sprayed
3 from an atomizer, or dispensed with a pen.

1 4. The method in claim 1, wherein the document may
2 be any document of the type which would include but are not
3 limited to airline tickets, baggage claim tickets, checks,
4 passports, green cards, legal documents, currency, U.S.
5 postal documents, stamps, bonds, I.D. cards, driver's
6 licenses, shipping invoices, adhesive labels, medical forms
7 and prescriptions.

1 5. The method in claim 1, wherein the non-visible
2 security feature may be applied to any document so that
3 the authenticity of the original document can be verified
4 by producing a fingerprint or image when applying the



5 activator solution to the non-visible chemical coating on
6 the document.

1 6. A method for providing a non-visible security
2 feature for document to positively identify the document,
3 the method comprising the following steps:
4 a) providing a document to be identified;
5 b) applying a non-visible chemical coating onto at
6 least a portion of the document leaving an non-visible
7 image thereupon;
8 c) providing an activator solution apart from the
9 chemical coating that can be transferred onto an
10 applicator;
11 d) contacting the applicator onto the activator
12 solution;
13 e) contacting the applicator containing the
14 activator solution onto the chemical coated portion of the
15 document;
16 f) allowing the chemicals on the coated portion of
17 the document to react with the activator solution so that
18 the nonvisible image becomes a visible color image on the
19 chemically coated portion of the document, and the
20 authenticity of the document can be verified.

1 7. The method in claim 6, wherein the image provided
2 on the chemically coated portion of the document may be a
3 person's fingerprint formed from pressing a finger in the
4 applicator solution, and impressing the fingertip on the
5 coated portion of the document.

1 8. The method in claim 6, wherein the activator
2 solution may be maintained within an absorbent pad, sprayed
3 from an atomizer, or applied with a pen.

1 9. The method in claim 6, wherein the document
2 comprises any document of the type which would include
3 airline tickets, baggage claim tickets, checks, passports,
4 green cards, legal documents, currency, U.S. postal



5 documents, stamps, bonds, I.D. cards, driver's licenses,
6 shipping invoices, adhesive labels, medical forms and
7 prescription slips.

1 10. A method of identifying the authenticity of a
2 document from a fingerprint, comprising the following
3 steps:

4 a) providing a document having at least a portion of
5 the document treated with a chemical compound;

6 b) providing a fingerprint pad treated with an
7 activating solution;

8 c) touching the treated pad with a person's finger;

9 d) applying the finger of the person on the treated
10 portion of the document, for producing an identifiable
11 fingerprint thereon.

1 11. The method in claim 10, wherein the document may
2 be of the type which would include but are not limited to
3 airline tickets, baggage claim tickets, checks, passports,
4 green cards, legal documents, currency, U.S. postal
5 documents, stamps, bonds, I.D. cards, driver's licenses,
6 shipping invoices, adhesive labels, medical forms and
7 prescription slips.

1 12. The method in claim 10, wherein the fingerprint
2 appearing on the chemically treated document may be
3 matched against the known fingerprint of the owner of the
4 document.

1 13. The method in claim 10, wherein the process would
2 ensure a non-intrusive way to have a positive identifier in
3 the form of a fingerprint on the document.

1 14. A method of identifying a passenger on a transit
2 vehicle, such as an airplane, train, or bus, comprising the
3 following steps:

4 a) providing a passenger having a ticket to be



5 aboard the transit vehicle;
6 b) providing a chemical solution on a portion of the
7 ticket; and
8 c) providing an inkless fingerprint pad for applying
9 to the passenger's finger, so that when the passenger's
10 finger is applied to the chemical solution on the portion
11 of the ticket, a fingerprint appears on the label for
12 verifying the identity of the passenger.

1 15. The method in claim 14, wherein after the
2 passenger touches the treated ticket with his finger, no
3 ink would be left on the passengers finger.

1 16. The method in claim 14, wherein there may be
2 provided any identifying mark transferred onto the
3 chemically treated portion of the ticket rather than the
4 fingerprint of the passenger.

1 17. A method for providing a non-visible security
2 feature for protecting and verifying the authenticity of
3 the documents, the method comprising the following steps:
4 a) providing a document to be protected;
5 b) applying a non-visible chemical coating onto at
6 least two portions of the document, one of which may
7 include a definable non-visible image;
8 c) providing an activator solution apart from the
9 chemical coating;
10 d) applying the activator solution onto a first
11 chemically coated portion of the document to reveal the
12 image thereupon for first verifying that the document is
13 not a counterfeit;
14 e) coating a person's fingertip with activator
15 solution;
16 f) pressing the person's fingertip onto the second
17 chemically coated portion of the document, to reveal the
18 person's fingerprint on the document as a second means for
19 verifying the authenticity of the document.



1 18. The method in claim 17, wherein the activator
2 solution may be applied to the first coated portion with a
3 pen.