CLAIMS

1. A method for information determination, comprising:

receiving, by a terminal device, first configuration information from a network device, the first configuration information being used for configuring a set of Channel State Information-Reference Signal (CSI-RS) resources, wherein respective CSI-RS resources of the set are quasi co-located with respect to a first Quasi Co-Location (QCL) parameter,

wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources,

wherein the first indication parameter is a parameter *Tracking Reference Signal-Info (TRS-Info)*.

2. The method of claim 1, wherein the first QCL parameter is a spatial QCL parameter.

~~3. The method of claim 1 or 2, wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources.~~

~~4. The method of claim 3, wherein the first indication parameter is a parameter *Tracking Reference Signal-Info (TRS-Info).*~~

~~5~~3. The method of any one of claims 1 to ~~4~~2,

wherein first reference signals indicated by QCL information corresponding to respective CSI-RS resources of the set are quasi co-located with respect to the first QCL parameter, the first reference signals being reference signals corresponding to the first QCL parameter; and/or,

QCL information corresponding to each of the set of CSI-RS resources indicates a same first reference signal, the first reference signal being a reference signal corresponding to the first QCL parameter; and/or,

QCL information corresponding to each of the set of CSI-RS resources corresponds

to a same Transmission Configuration Indicator State (TCI-State).

~~6~~4. A method for information configuration, comprising:

transmitting, by a network device, first configuration information to a terminal device, the first configuration information being used for configuring a set of Channel State Information-Reference Signal (CSI-RS) resources, wherein respective CSI-RS resources of the set are quasi co-located with respect to a first Quasi Co-Location (QCL) parameter,

wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources,

wherein the first indication parameter is a parameter *Tracking Reference Signal-Info (TRS-Info)*.

~~7~~5. The method of claim ~~6~~4, wherein the first QCL parameter is a spatial QCL parameter.

~~8. The method of claim 6 or 7, wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources.~~

~~9. The method of claim 8, wherein the first indication parameter is a parameter *Tracking Reference Signal-Info (TRS-Info).*~~

~~10~~6. An apparatus for information determination, comprising:

a receiving unit, configured to receive first configuration information from a network device, the first configuration information being used for configuring a set of Channel State Information-Reference Signal (CSI-RS) resources, wherein respective CSI-RS resources of the set are quasi co-located with respect to a first Quasi Co-Location (QCL) parameter,

wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources,

wherein the first indication parameter is a parameter *Tracking Reference Signal-Info (TRS-Info)*.

~~11~~7. The apparatus of claim ~~10~~6, wherein the first QCL parameter is a spatial QCL parameter.

~~12. The apparatus of claim 10 or 11, wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources.~~

~~13. The apparatus of claim 12, wherein the first indication parameter is a parameter *Tracking Reference Signal-Info (TRS-Info).*~~

~~14~~8. The apparatus of any one of claims ~~10 to 13~~ 6 to 7,

wherein first reference signals indicated by QCL information corresponding to respective CSI-RS resources of the set are quasi co-located with respect to the first QCL parameter, the first reference signals being reference signals corresponding to the first QCL parameter; and/or,

QCL information corresponding to each of the set of CSI-RS resources indicates a same first reference signal, the first reference signal being a reference signal corresponding to the first QCL parameter; and/or,

QCL information corresponding to each of the set of CSI-RS resources corresponds to a same Transmission Configuration Indicator State (TCI-State).

~~15~~9. An apparatus for information configuration, comprising:

a transmitting unit, configured to transmit first configuration information to a terminal device, the first configuration information being used for configuring a set of Channel State Information-Reference Signal (CSI-RS) resources, wherein respective CSI-RS resources of the set are quasi co-located with respect to a first Quasi Co-Location (QCL) parameter,

wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources,

wherein the first indication parameter is a parameter *Tracking Reference Signal-Info (TRS-Info)*.

~~16~~10. The apparatus of claim ~~15~~9, wherein the first QCL parameter is a spatial QCL parameter.

~~17. The apparatus of claim 15 or 16, wherein the first configuration information is further used for configuring a first indication parameter corresponding to the set of CSI-RS resources, the first indication parameter being configured to indicate a usage of the set of CSI-RS resources.~~

~~18. The apparatus of claim 17, wherein the first indication parameter is a parameter *Tracking Reference Signal Info (TRS Info).*~~

~~19~~11. The apparatus of any one of claims ~~15 to 18~~ 9 to 10,

wherein first reference signals indicated by QCL information corresponding to respective CSI-RS resources of the set are quasi co-located with respect to the first QCL parameter, the first reference signals being reference signals corresponding to the first QCL parameter; and/or,

QCL information corresponding to each of the set of CSI-RS resources indicates a same first reference signal, the first reference signal being a reference signal corresponding to the first QCL parameter; and/or,

QCL information corresponding to each of the set of CSI-RS resources corresponds to a same Transmission Configuration Indicator State (TCI-State).

~~20~~12. A computer storage medium having stored thereon computer executable instructions that, when executed by a processor, cause operations of the method of any one of claims 1 to ~~5~~ 3 or any one of claims ~~6 to 9~~4 to 5 to be performed.