

## Dispensing Appliance For A Double Syringe

Generally, double syringes or double cartridges with a static mixer are used for mixing and dispensing two-  
5 component materials. A double syringe system generally consists of two parallelly arranged storage cylinders, two pistons, a common closure, and a double plunger. To dispense the content, the pistons are pushed forward by means of the double plunger.

10

Particularly in smaller double syringes for single use, the conventional dispensing by means of the dual plungers may result in handling problems because of the small dimensions, and it is therefore the object of the present invention to  
15 provide a dispensing appliance that allows a comfortable dispensing also of small double syringes. This object is attained by the dispensing appliance according to claim 1.

EP-A2-0 315 222 discloses a dispensing device, wherein two  
20 syringes are held together at its outlet end by a connecting part with common outlet and at the inlet end by a bridge connecting the two plungers. This device does not solve the problem of small syringes, which is not addressed therein.

25 The invention will be explained in more detail hereinafter with reference to drawings of exemplary embodiments.

Fig. 1 shows a perspective view of a double syringe with a mixer and of a dispensing appliance  
30 according to the invention,

Fig. 2 shows the double syringe of Fig. 1 inserted in the dispensing appliance of Fig. 1,

35 Fig. 3 shows the dispensing appliance of Fig. 2,

- Fig. 4 shows a partly sectioned view according to arrow IV in Fig. 3,
- 5 Fig. 5 shows a section according to line V - V in Fig. 4,
- Fig. 6 shows an enlarged detail of the plunger end according to Fig. 4,
- 10 Fig. 7 shows a double syringe in an embodiment variant of a dispensing appliance, and
- 15 Fig. 8 shows the dispensing appliance of Fig. 7 in a perspective view and individually.

Fig. 1 shows double syringe 1 with a mixer 2 as well as a first embodiment of the dispensing appliance 3 of the invention with double plunger 4, connected by thrust plate 5, as well as a flange holder 6 having a finger rest grip 7 with finger rests 7F and a guiding slot 8 for receiving retaining flange 9 of double syringe 1. On the syringe side of the flange holder, a collar 7A is provided that serves for guiding the syringe and comprises a syringe snap-in 25 retainer for the container that is inserted first, which is in the case of container volumes that are different from 1:1 the larger container. Furthermore, in Fig. 1, pistons 10 in the syringe are shown.

30 Fig. 1 shows how the filled and operational syringe 1 can be introduced with its retaining flange 9 into guiding slot 8 of the flange holder of the dispensing appliance. The internal contour of guiding slot 8 is adapted to the coded external contour of retaining flange 9, thereby allowing to 35 prevent that non-system syringes may be used and to ensure,

in syringes having containers whose volumetric ratio respectively diameter ratio is different from 1:1, that the syringe is inserted into the guiding slot in the correct position.

5

In Fig. 2, the syringe is in place on the dispensing appliance and a part of the content of the double syringe has already been dispensed, as follows from the position of the pistons and plungers.

10

In Fig. 3 it is apparent that the forward ends 11 of double plungers 4 have an incision 12 to provide a certain elasticity of these ends. In the enlarged illustration of Fig. 6 of a plunger end it is visible that the end spreads out slightly resiliently and has a circumferential bulge 13 such that the plunger ends have a slightly larger diameter than the remainder of the plungers. This enlargement of the circumference by the circumferential bulge 13 and the slight spreading at ends 11 of double plungers 4 have the effect that when the double plunger is pulled back, it is first held back and can only be withdrawn from plunger guide 14 by applying an increased force. When a normal force is applied, the circumferential bulge provides a sufficient safety against a complete withdrawal of the plunger from the flange holder.

25

In Fig. 4 it is shown that the double plungers are guided by a sufficiently long plunger guide 14 that is arranged on the finger rest grip and extends toward the thrust plate. This allows a precise application, which is important especially in smaller double syringes.

30

Fig. 5 illustrates flange holder 6 with finger rest grip 7 and its finger rests 7A as well as guiding slot 8, the

latter guiding slot being shaped for receiving the coded and curved retaining flange of the double syringe.

Figs. 7 and 8 illustrate an embodiment variant where flange  
5 holder 16 of dispensing appliance 15 has a second finger  
rest grip 17 with finger rests 17F that is arranged on  
plunger guide 18 at some distance from the first finger rest  
grip 7. By this second finger rest grip, the distance to the  
thrust plate is reduced, thereby allowing a comfortable  
10 operation of the syringe also by people having smaller  
hands, especially in the case of longer syringes. The  
remaining parts of the dispensing appliance are the same as  
in the preceding exemplary embodiment.

15 The term double syringe is also meant to include a double  
cartridge. Moreover, instead of a mixer, any other accessory  
such as a spray nozzle or another accessory part may be  
connected to the double syringe.

The invention claimed is:

1. A dispensing apparatus for a double syringe or double cartridge, comprising: two plungers connected by a thrust plate; and a flange holder, comprising: a guiding slot for receiving a retaining flange of the double syringe or double cartridge; at least one finger rest grip; and an elongate plunger guide extending from a side of the flange holder that faces away from the double syringe or double cartridge.
2. The dispensing apparatus according to claim 1, wherein an end of each of the plungers, which opens out elastically, comprises an incision and a circumferential bulge.
3. The dispensing apparatus according to claim 1, wherein the at least one finger rest grip comprises a first and a second finger rest grip, wherein the second finger rest grip is disposed between the first finger rest grip and the thrust plate.
4. The dispensing apparatus according to claim 3, wherein the second finger rest grip is disposed on the plunger guide.
5. The dispensing apparatus according to claim 1, wherein the guiding slot in the flange holder comprises a coded internal contour for receiving a coded contour of the retaining flange of the double syringe or double cartridge in an unequivocal position.